

Standard Operating Procedure for Resolving ALARM_6661 on Cisco-PE-Delhi-NCR-33 Provider Edge Router

Node: Cisco-PE-Delhi-NCR-33 | **Vendor:** Cisco | **Severity:** Critical | **Alarm Code:** ALARM_6661

Description

ALARM_6661 indicates a critical failure on Cisco-PE-Delhi-NCR-33 Provider Edge Router, resulting in service disruption. This SOP outlines steps to identify and resolve the root cause.

Potential Root Causes

Cause	Probability
High CPU usage due to CPU-intensive processes	High
Software bugs in Cisco IOS-XE	Medium
Misconfigured routing protocols	Low

Diagnostic Commands

```
show processes cpu | include CPU
show system resources
show ip bgp summary
show ip ospf neighbor
```

Resolution Steps

- Step 1: {'Step': '1. Check CPU usage', 'Description': 'Run the command to monitor CPU usage', 'Command': 'show processes cpu | include CPU'}
- Step 2: {'Step': '2. Identify CPU-intensive processes', 'Description': 'Analyze output to identify processes consuming excessive CPU resources', 'Command': 'show processes cpu'}
- Step 3: {'Step': '3. Kill CPU-intensive processes', 'Description': 'Use the 'kill' command to terminate processes consuming excessive CPU', 'Command': 'kill process-id'}
- Step 4: {'Step': '4. Verify software version', 'Description': 'Check for any software bugs in Cisco IOS-XE', 'Command': 'show version'}
- Step 5: {'Step': '5. Reconfigure routing protocols', 'Description': 'Verify that routing protocols are optimized for performance', 'Command': 'show ip bgp summary'}

Post-Check Verification

```
show ip bgp summary
show ip ospf neighbor
show system resources
```