

Cisco-PE-Kolkata-WB-112 Alarm Handling SOP for ALARM_7191

Node: Cisco-PE-Kolkata-WB-112 | **Vendor:** Cisco | **Severity:** Warning | **Alarm Code:** ALARM_7191

Description

Handling of ALARM_7191 on Cisco-PE-Kolkata-WB-112 due to High CPU Utilization.

Potential Root Causes

Cause	Probability
High CPU Utilization due to Misconfigured BGP Peers	High
High CPU Utilization due to High Memory Usage	Medium
Software Issues or Bug	Low

Diagnostic Commands

```
show process cpu | include CPU
show memory | include Memory
show ip bgp summary
show ip bgp neighbors | include Established
```

Resolution Steps

- Step 1: {'Step': '1. Check CPU Utilization and adjust CPU-intensive processes', 'Action': 'show process cpu | include CPU'}
- Step 2: {'Step': '2. Check and adjust Memory Usage', 'Action': 'show memory | include Memory'}
- Step 3: {'Step': '3. Verify and adjust BGP Peer Configuration', 'Action': 'show ip bgp summary'}
- Step 4: {'Step': '4. Check for Software Issues or Bugs', 'Action': 'show version | include Software'}
- Step 5: {'Step': '5. Upgrade Software if necessary', 'Action': 'copy tftp:///cisco-ueye-3.15.0.bin flash:'}

Post-Check Verification

```
show process cpu | include CPU
show memory | include Memory
show ip bgp summary
show ip bgp neighbors | include Established
```