

Standard Operating Procedure for Huawei-PE-Delhi-NCR-11 ALARM_5238

Node: Huawei-PE-Delhi-NCR-11 | **Vendor:** Huawei | **Severity:** Minor | **Alarm Code:** ALARM_5238

Description

ALARM_5238 on Huawei-PE-Delhi-NCR-11: Minor BFD session authentication failed due to incorrect username or password.

Potential Root Causes

Cause	Probability
Incorrect username or password in BFD session authentication	High
Authentication protocol misconfiguration	Medium
Authentication key mismatch	Low

Diagnostic Commands

```
display bfd session
display bfd authentication
debug bfd
```

Resolution Steps

- Step 1: {'Step': 'Verify BFD session authentication settings', 'Description': 'Check the username and password used in BFD session authentication.', 'CLI_Command': 'display bfd authentication'}
- Step 2: {'Step': 'Correct BFD session authentication settings', 'Description': 'Verify and correct the username and password used in BFD session authentication.', 'CLI_Command': 'bfd authentication username password '}
- Step 3: {'Step': 'Verify authentication protocol configuration', 'Description': 'Check the authentication protocol configuration.', 'CLI_Command': 'display bfd authentication'}
- Step 4: {'Step': 'Correct authentication protocol configuration', 'Description': 'Verify and correct the authentication protocol configuration.', 'CLI_Command': 'bfd authentication protocol '}

Post-Check Verification

```
display bfd session
display bfd authentication
ping
```