

Juniper Core Router - ALARM_4653: Major Alarm Handling SOP

Node: Juniper-Core-Chennai-TN-1 | **Vendor:** Juniper | **Severity:** Major | **Alarm Code:** ALARM_4653

Description

This Standard Operating Procedure (SOP) outlines the steps to handle a Major Alarm Code ALARM_4653 on a Juniper Core Router.

Potential Root Causes

Cause	Probability
High CPU Utilization	High
Memory Leak	Medium
Routing Protocol Misconfiguration	Low

Diagnostic Commands

```
show system resources
show cpu utilization
show memory statistics
show routing protocol statistics
show configuration | display set
```

Resolution Steps

- Step 1: {'Step': '1. Check CPU Utilization', 'Action': "Verify the CPU utilization levels on the router using the command 'show cpu utilization'. If the CPU utilization is above 80%, proceed to the next step."}
- Step 2: {'Step': '2. Check Memory Leaks', 'Action': "Check for memory leaks using the command 'show memory statistics'. If memory leaks are detected, restart the router and recheck the memory statistics."}
- Step 3: {'Step': '3. Check Routing Protocol Configuration', 'Action': "Verify the routing protocol configuration using the command 'show configuration | display set'. If the configuration is incorrect, correct it and reverify."}
- Step 4: {'Step': '4. Restart the Router (if necessary)', 'Action': "If the previous steps do not resolve the issue, restart the router using the command 'request system restart'. After restarting, verify the issue is resolved."}

Post-Check Verification

```
show system resources
```

```
show cpu utilization
show memory statistics
show routing protocol statistics
show configuration | display set
```