

Juniper Provider Edge Router (PE) Alarm SOP - ALARM_6363

Node: Juniper-PE-Chennai-TN-105 | **Vendor:** Juniper | **Severity:** Major | **Alarm Code:** ALARM_6363

Description

This SOP outlines the procedures for diagnosing and resolving the ALARM_6363 on the Juniper Provider Edge Router (PE) Node ID: Juniper-PE-Chennai-TN-105.

Potential Root Causes

Cause	Probability
High CPU Utilization due to Routing Protocol Flaps	High
Memory Leak due to Software Bug	Medium
Interface Flapping due to Cable or Hardware Issues	Low

Diagnostic Commands

```
show system processes cpu | match %
show system processes memory | match %
show interfaces extensive | match Flaps
show bgp summary | match Flaps
show routing-processes | match Flaps
```

Resolution Steps

- Step 1: {'Step': '1. Check CPU Utilization', 'Action': "Run the command 'show system processes cpu | match %' to check CPU utilization. If CPU utilization is high, proceed to step 2.", 'CLI_Command': 'show system processes cpu | match %'}
- Step 2: {'Step': '2. Check for Routing Protocol Flaps', 'Action': "Run the command 'show bgp summary | match Flaps' to check for BGP flaps. If BGP flaps are present, proceed to step 3.", 'CLI_Command': 'show bgp summary | match Flaps'}
- Step 3: {'Step': '3. Check for Memory Leak', 'Action': "Run the command 'show system processes memory | match %' to check for memory leak. If memory leak is present, proceed to step 4.", 'CLI_Command': 'show system processes memory | match %'}
- Step 4: {'Step': '4. Check Interface Flapping', 'Action': "Run the command 'show interfaces extensive | match Flaps' to check for interface flapping. If interface flapping is present, proceed to step 5.", 'CLI_Command': 'show interfaces extensive | match Flaps'}

Step 5: {'Step': '5. Clear Interface Flaps (if present)', 'Action': "Run the command 'clear interfaces ' to clear interface flaps (if present).", 'CLI_Command': 'clear interfaces '}

Step 6: {'Step': '6. Clear BGP Flaps (if present)', 'Action': "Run the command 'clear bgp ' to clear BGP flaps (if present).", 'CLI_Command': 'clear bgp '}

Step 7: {'Step': '7. Reload the Router (if necessary)', 'Action': "Run the command 'request system reboot' to reload the router (if necessary).", 'CLI_Command': 'request system reboot'}

Post-Check Verification

```
show system processes cpu | match %  
show system processes memory | match %  
show interfaces extensive | match Flaps  
show bgp summary | match Flaps  
show routing-processes | match Flaps
```