



Review on methods used for wildlife species and individual identification

Tinao Petso¹ · Rodrigo S. Jamisola Jr.¹ · Dimane Mpoeleng²

Received: 15 March 2021 / Revised: 3 October 2021 / Accepted: 7 November 2021 / Published online: 13 December 2021
© The Author(s), under exclusive licence to Springer-Verlag GmbH Germany, part of Springer Nature 2021

Abstract

This work presented a literature review on animal species and individual identification tools, as well as animal monitoring capabilities. We gathered the literature to cover different aspects of technologies that are widely in use for animal identification, from the traditional up to the latest methods. This study includes species and individual animal identification attributes namely body patterns, footprints, facial features, and sound for identification purposes. The large volume of data collected could be automatically processed using machine learning and deep learning techniques to achieve both species and individual animal identification more efficiently as compared to the human workforce. It is a much faster and accurate approach considering the large volume of data, than manual processing, which is extremely expensive, time-consuming, tedious, and monotonous. We established that machine learning and advancements in deep learning hold significant promise to high-accuracy identification of both species and individual animal. Methods used for individual identification are mainly implemented in endangered species by the conservation management. The traditional methods such as the use of footprints, drawings of animal biometrics are integrated into the recent growth of technology to eliminate the human skill needed to achieve species and individual identification through the use of machine learning and deep learning algorithms for automatic identification purposes.

Keywords Animal monitoring · Deep learning · Individual identification · Machine learning · Machine vision · Species identification

Introduction

Animal species and individual identification are both critical for monitoring wildlife more efficiently (Goldsworthy and Matam 2021). It is primarily done for population counts, movement tracking, health and disease control, tourism, and anti-poaching (Banga et al. 2010). Species identification relies on the general characteristics such as animal

body pattern, footprint, and sound. Individual identification is normally based on uniqueness an animal biometrics such as facial, visual patterns, footprint, nose prints (Bugge et al. 2011; Kühl and Burghardt 2013). It allows direct monitoring for detailed animal life history, future follow-up, and survivorship (Pollard et al. 2010). It is mostly implemented to endangered species for specific conservation and management practices (Gibbon et al. 2015; Vidya et al. 2014). Over the years, different technologies have been investigated to improve their capability to carry out automatic species and individual identification to yield more reliable results. It aids in activities that have to be repeated several times. Its application does not remove the requirement of a human involvement (Gaston and O'Neill 2004), and thus it complements their traditional methods of monitoring wildlife. The developments of automatic species and individual animal identification are based on statistical and computer vision machine learning techniques. These techniques offer tremendous opportunities by extracting features needed for automatic species and individual identification (Mmereki et al. 2021).

✉ Tinao Petso

Rodrigo S. Jamisola Jr.
jamisolar@biust.ac.bw

Dimane Mpoeleng
mpoelengd@biust.ac.bw

¹ Department of Mechanical, Energy and Industrial Engineering, Botswana International University of Science and Technology, Palapye, Botswana

² Department of Computer Science and Information Systems, Botswana International University of Science and Technology, Palapye, Botswana

Figure 1 shows an automatic aerial zebra (*Equus quaggas*) species identification with a custom computer vision algorithm from a drone footage with the capability to enhance wildlife monitoring techniques.

Accurate individual identification is important in conservation projects for critically endangered species. Some countries in South Asia with one-horned rhinoceros (*Rhinoceros unicornis*) have extreme individual identification monitoring programmes to ensure their survivability as well as to understand the relationship between rhinoceros (Subedi et al. 2013; Talukdar 2009). Other programmes such as assisted reproductive techniques are implemented to ensure optimum animal growth rate. Accurate individual identification is also used to prevent an imbalance of sexes which can create fights among males that can cause male species death (Dunham 2001). Around the 1900's most African countries relocated their black rhinoceros (*Diceros bicornis*) from the wild to sanctuaries to protect them from extinction (Patton et al. 2007) due to the increased poaching. In 2016, it was approximated that for every eight hours, one rhinoceros is killed in South Africa hence the need to implement better monitoring methods for them (Kamminga et al. 2018).

When populations are not monitored, we cannot track changes in abundance over time. In the case of overpopulation, animals are most likely to intrude into human territory leading to human–animal conflict. Due to its increased incidents, wildlife conservation authorities have great interest in improving monitoring methods (Cheteni 2014). An effective monitoring system of wildlife populations can assist in managing their numbers. In the case of extinction, wildlife conservation efforts are increasing. From DeMotts and Hoon (2012), the increase of elephant population by 133% within a period of two decades resulted in a conflict over water, fodder, and space with residents in the northern countryside of Botswana. Additionally, the human–animal

conflict was found to exist when Asian elephants destroy crops in agricultural fields and sometimes kill people when they leave their sanctuaries in southern India (Münster and Münster 2012).

Invasive species management ensures monitoring and balance of species in the ecosystem. The study conducted by (Connally et al. 2021) recommended the wildlife authorities to establish management plans to monitor the wild pig population in Texas. Another study recommended Asian carps for human consumption to address their intrusion to fishermen as well as other fish species in Midwest and the southern USA (Varble and Secchi 2013).

This paper mainly focuses on the methods used to collect data for species and individual identification purposes. It also covers the method techniques based on the unique body shape, footprint characteristics, facial attributes, sound and pattern for both species and individual identification. Other noninvasive techniques such as the use of genetics sampling for species and individual identification from animal waste remains and hair are not covered in this review study.

Methods used of gathering data for species and individual identification

Manual data gathering

The globally practiced method of manual data gathering is primarily dependent on the detailed drawings or memory knowledge of an individual on an animal distinguishing biometrics features such as the ear, face, footprints, and nose prints. Individual endangered species such as one-horned rhino in Nepal with distinguishing features are manually recorded in a sight booklet to enhance the monitoring techniques (AsRSG 2009). The memory knowledge is dominated by local experts who are most likely to be illiterate. Most of this personnel typically lack scientific knowledge, thus a challenge to attain proper detailed data gathering for an orthodox scientific basis (Elbroch et al. 2011). Questionnaires are normally conducted to acquire the information for species and individual identification for wildlife monitoring purposes. A method of identifying animals by their footprints has been one of the oldest methods used by traditional expert trackers in Africa (Blake 2002). The ability to identify species based on their tracks is usually an integral part of hunting (Hewes 1994; Stander et al. 1997). It had been used by the hunter-gatherers for over a hundred thousand years (Liebenberg et al. 1998). Hunting guides, ecologists, military, and search and rescue personnel still use it (Liebenberg et al. 2010). It is based primarily on visual inspection which involves the skills of an expert tracker (Bothma and Le Riche 1993), to look at the footprint, associate it with a particular species and get information about their direction of movement and number.




Fig. 1 Automatic aerial wildlife species identification from a drone footage

Hence, trackers aid researchers to collect data to study animal behavior (Liebenberg et al. 1998, 1999). Local people were used to assist on Amur tiger footprints data collection in China for the development footprint identification technology (FIT) (Gu et al. 2014).

The use of ear patterns for individual African elephant identification in South Africa had been established to be a reliable approach based on human memory as well as the manual matching drawings (Bedetti et al. 2020). Rhinoceros kept in national parks in Africa are ear-notched for individual identification purposes in Zimbabwe (Hall-Martin 1986; Matipano 2004). The use of eye and profile wrinkles is another feature tool that had been established to aid in individual identification of rhinoceros either alive or recently deceased. The acquisition of the eye wrinkles patterns data is through the manual approach during anesthetized for translocation, notching, or treatment in UK (Patton and Campbell 2011). Though this approach can accurately identify individual rhinoceros, it was recommended not to be used alone (Patton and Jones 2010). Figure 2 shows eye wrinkle patterns used for individual rhinoceros identification.

Data gathering by technology with human aid

Different techniques of acquiring data by technology for animal identification with human aid have been used over the years. Some of them include cameras to gather animal footprints and animal images, as well as acoustic recorder to gather animal sounds (Anderson and Hitchins 1971; Dos Santos et al. 2014; Shrader and Beauchamp 2001), to name a few. More advanced technologies are used to assist wildlife monitoring effectively through the use of artificial marks and proximity loggers.

Camera trapping is a method of automatically recording videos and images remotely, by activating a motion sensor without human assistance. Camera trapping for animals with unique markings can be used as a possible method to monitor their populations, as done for black rhinoceros (Stein et al. 2010). Other methods of automatically collecting information about wild animals are the use of satellites and manned or unmanned aircraft. Through these methods, a wealth of information through videos and images of animals are obtained. However, effectively analyzing and identifying animals within this wealth of data are demanding tasks.

The affordability of unmanned aircraft vehicles (UAVs) also commonly known as drones in the market had made them readily available for many applications such as agricultural fields, emergency and rescue, military, wildlife conservation, and different research areas, to name a few (Makgantai et al. 2021; Ramalepa and Jamisola 2021). The current increase of usage of UAVs is vital in further exploring its capabilities for animal monitoring. The use of UAVs is an effective means to monitor wildlife species (Linchant et al. 2015). A UAV was




Fig. 2 Two black rhinoceros left eye wrinkles used for individual identification, top set of images shows left eye wrinkles with the eye nearly closed, middle set of images shows the eye open, and the last set of images are the drawings of the key wrinkles cited with permission from Patton and Jones (2010)

used to conduct a population census for large herbivorous, namely kiangs, Tibetan gazelles, blue sheep, domestic yaks, and domestic sheep and was established to be fast, economical, and reliable compared to the manual method (Guo et al. 2018). In Nepal, government patrolling officers concurrently used UAVs to effectively protect wild animals (Goodyer 2013).

Animals can also be identified by the sound they make. One method is by vocal sound, and another is by seismic vibrations. Vocal sound is a form of communication by animals within the same species and between species. The elephants were fitted with microphones and radio transmitters to allow for individual identification (Soltis et al. 2005). It was established that females did not produce rumbles at random.

The use of artificial marks includes the use of dyes and ear tags can be used to gather individual data in operations such as capture–recapture studies for species population count (Alonso et al. 2015). The use of proximity loggers such as global positioning system (GPS) collars and radio frequency identification (RFID) technology on animals is another method used to gather data about their location and

that can be used to identify each individual for behavioral studies (Cagnacci et al. 2010; Ungar et al. 2005). The individual animal is known as the animal was captured when the logger was placed. Thus, this method can be considered as invasive. A study conducted by Grünewälder et al. (2012) affixed six cheetahs with GPS collars for a period of around one year, to monitor their feeding, mobile and stationary behaviors. Radio frequency transmitters were implanted into the horns of rhinoceros mainly for future individual animal identification (Koschan et al. 2006; Van Nguyen et al. 2018). An application of using a small fixed-wing UAV with radio frequency receiver on-board for individual identification was used to improve the traditional approach of “on foot” (Dos Santos et al. 2014; Van Nguyen et al. 2018; Webber et al. 2017).

Use of camera for data gathering for species and individual identification

On ground

Camera traps in the wild had been used as early as the 1950s in Australia (Meek et al. 2015). Researchers and natural resource managers primarily use them to assist in the acquisition of the ecological data (Meek et al. 2014). These ecological data are used for research studies such as animal behavior, population monitoring and fauna–flora interaction (Mohd-Azlan 2009). The millions of pictures and videos acquired can be a challenging task to efficiently identify the species. Hence the application of machine learning and computer vision had been employed to efficiently analyse the data collected (Carl et al. 2020; Tabak et al. 2019). As the camera motion sensors in the wild are vital tools to acquire images of animals, they can also ‘capture’ humans who might be poachers. The study conducted by Yousif et al. (2017), classified regions with human, animals, and background patches based on data collected from camera traps, while Willi et al. (2019) were interested in developing convolutional neural network (CNN) to differentiate different animal species, images of human, vehicle, and empty images. Attaining accurate and detailed information from the images is essential to study animal behavior also tackle automatic animal identification. Hence, the application of animal identification by computer tools can also be accompanied with human visual animal identification to assist the users to reach an identification agreement, and this approach was attempted Mendoza et al. (2011) on the bobcat identification.

Individual identification is a crucial step for animals subject to close monitoring programmes. The study conducted by Ferreira et al. (2020) yielded positive outcomes for the feasibility of automatic individual bird identification through the application of deep learning algorithms in laboratory and

wild environmental fields through the use of a camera for data collection. Another study used the unique individual biometric natural marking in the chest of the African penguins with a high success rate that yielded false detection occurring at 1 in 10,000 comparisons (Sherley et al. 2010). It was established to be an ideal approach with minimum stress toward the animal.

Despite the significant developments of both species and individual identification from camera traps images, some challenges still exist from environmental conditions. Environmental conditions such as poor illumination, overexposure, occlusion, and rain to name a few, affect the resolution quality in the image for both species and individual capabilities. The distinguishing features or natural marks such as scars, unique spots, or stripe patterns for individual identification, and sometimes, they are not captured in the images and thus remain as a challenge to achieve individual identification (Dorning and Harris 2019). This makes the task to achieve individual identification to have several images taken at different positions and angles, with varying seasonal and environmental conditions to have a detailed profile of the unique characteristics. The study conducted by Johansson et al. (2020) concluded that unique individual identification based from camera trap images attained an overestimation in their population count. The application of a capture–recapture method for animal population estimate requires each animal to be individually recognized, and thus without the unique individual distinguishing feature from the camera trap images, the viability of population estimate by this method is unreliable (Stevenson et al. 2019).

Aerial view

Aerial view refers to the videos and images collected from an aerial camera where the data are collected and then analyzed offline. An increase in UAVs in the research field had opened doors to a complementary approach to animal identification from an aerial view. Computer vision is a method that is proposed to assist in improving precision and accuracy in the aerial surveying approach to wildlife management (Naude and Joubert 2019). Conducting animal population census is an essential aspect for animal monitoring for conservation management (Greene et al. 2017; Sirmacek et al. 2012). A case study of using aerial images to train a classifier that detects the presence of wildebeests for population census is shown in Valletta et al. (2017). The study identified four other classes namely grass, rocks, trees, and zebra. Its predictive performance evaluated on the testing data sets indicated an accuracy ranging from 80% to 100% based on random forest algorithm (RFA). Another study on wildebeest population census at Serengeti National Park used Fourier histogram oriented gradient (HOG) feature for classification that is confirmed to be more accurate than manual count

(Torney et al. 2016). It is a technique that uses the Fourier series for a continuous function to extract constant features even when the object of interest in an image rotates. Population estimates using aerial data for five large herbivores were established from animal density, that is confirmed to be better than ground estimates (Guo et al. 2018). Another study by Ezat et al. (2018) performed crocodile populations census from aerial view with high resolution cameras which, yielded 26% more accurate than ground survey. Wild birds are monitored using UAV aerial images for population estimation as well as habitat identification (Hong et al. 2019).

An approach to tackle an increase in illegal wildlife poaching led to the development of an object detection method to detect large animals from UAV images (Kellenberger et al. 2017), operating in near-real-time. Aerial approach to automatic species identification improved wildlife population census, and in some cases helped to fight poaching. Figure 3 shows automatic animal identification of giraffe and zebra indicated in red and blue boundary boxes, respectively.

The use of very high-resolution satellite imagery had been established to yield positive results for species identification such as whales, polar bears, grey seals, cetaceans, Macaroni penguin and African elephant (Borowicz et al. 2019; Cubaynes 2020; Duporge et al. 2020; Guirado et al. 2018, 2019; LaRue et al. 2017). This approach is cost-effective, less time-consuming logistically as compared to use an aircraft for wildlife researches (Cubaynes et al. 2019; Höschle et al. 2021). The study conducted by Borowicz et al.



Fig. 3 Aerial image containing giraffe and zebra cited with permission from Eikelboom et al. (2019)

(2019) highlighted the efficiency of using convolutional neural networks (CNN) to detect cetaceans from satellite tiled imagery with model accuracy of 100% and 94% for whales and water only, respectively. A combination of whale detection and counting through the application of deep learning algorithms increment the accuracy by 36% against the detection model alone (Guirado et al. 2019).

Some of the challenges associated with aerial species identification includes: animal camouflage with the surrounding environment, animal occlusion due to the vegetation cover in the wild, low detection accuracy due to the low species pixel quality at high altitude and presence of wildlife species that is active at night and rest during the day. High-resolution imagery was established to achieve positive aerial species identification through the use of convolutional neural networks in an open area with the capability to save human time (Delplanque et al. 2021).

Moving camera

Moving camera refers to the collection of images and videos from an aerial camera where the data are analyzed in real or near-real-time. The ability to detect and track a moving object of interest from a moving camera has been a challenging field for researchers (Burt et al. 1989). The use of UAVs in wildlife research field has led to an interest in investigating their capability for both species and individual identification. An approach to detect moving zebra and antelope was investigated by Fang et al. (2016). The optical flow method used proved to be an effective way for species identification and tracking. To protect wild animals from extinction, traditional approaches that had been used over the years needed improvement. Hence Olivares-Mendez et al. (2015) investigated the use of vision sensors on UAVs for detecting and tracking of animals and poachers.

Computer assistance techniques used for both automatic species and individual identification

There are three main categorical domains from computer-based techniques used to aid species and individual animal identification which are artificial intelligence (AI), machine learning (ML), and deep learning (DL). Definitions for the commonly used techniques for automatic species and individual identification are highlighted in Table 1. Some of the machine learning algorithms that are commonly applied for automatic species and individual identification are *k*NN, SVM, random forest, and decision tree, to name a few. DL consists of different types such as artificial neural network (ANN), convolutional neural network (CNN), and recurrent neural network (RNN), to name a few. CNN is mainly

Table 1 Definitions for the commonly used techniques for automatic species and individual identification

AI Domain	Technique or Algorithm	Definition
ML	Support Vector Machine (SVM)	Discriminative classifier with hyperplanes as margins (Chauhan and Singh 2018).
ML	Scale-Invariant Feature Transform (SIFT)	Feature detection algorithm (Hu et al. 2008)
ML	Ensemble of Exemplar Support Vector Machine (EESVM)	Has much more defined discriminative classifier by incorporating inputs from the negative samples (Malisiewicz et al. 2012)
ML	Random Forest Algorithm	Classifier algorithm based on the decision tree model (Chen et al. 2016)
ML	Optical Flow	Apparent distribution of velocities (Shafie et al. 2009)
ML	<i>k</i> -nearest neighbor classifier (<i>k</i> NN)	A distance function that takes into account the difference or similarity between two instances (Xin et al. 2018)
DL	Convolutional Neural Network (CNN)	Main architecture successive layers (Huang et al. 2018)
DL	Recurrent Convolutional Network	ANNs with recurrent connections
DL	VGG-Face Convolutional Neural Network	Facial CNN models developed by Visual Geometry Group (VGG)
DL	Deep segmentation convolutional neural network	Identifying portions of an input image and classifies based on CNN
DL	You Only Look Once (YOLO)	One step approach that detects and classifies (Huang et al. 2018).


implemented for computer vision for species and individual identification. The name originates from convolutional layers. CNN comprises of three layers which are convolution, pooling and fully connected. The illustration of architecture is shown in Fig. 4. It is mainly inverted to process pixel information. Convolution layer extracts and learns feature elements of the input image (Gu et al. 2018). The pooling layer used to reduce the feature map resolution to reduce computation (Zhang et al. 2019). Fully connected layer high-level feature elements are attained that maps features to the classes (Zhang et al. 2019). Application of convolutional neural network includes image classification, object detection, object tracking, post-estimation, text detection and recognition, action recognition, scene labeling, speech and natural language processing. Wild-ID and interactive individual identification

system (I3SPattern) are feature detection and matching algorithms that apply scale-invariant feature transform (SIFT) and speeded up robust features (SUFT) algorithms. They are both used for individual identification. APHIS and AmphIdent are both pixel-based matching algorithm approach.

Identification attributes

Animal body patterns

The large volume of data collected from camera traps and remote sensing systems from UAVs usually apply computer vision techniques to aid animal species or individual identification based on its unique body shape and pattern (Loos et al.

**Fig. 4** The architecture of the original convolutional neural network

2018; Norouzzadeh et al. 2018; Stein et al. 2010). The ability to efficiently identify the species captured by these systems is necessary in animal research for near-real-time monitoring (Kellenberger et al. 2017; Rey et al. 2017; Villa et al. 2017; Yu et al. 2013). Studies conducted in (Kellenberger et al. 2017; Rey et al. 2017) performed automatic animal detection for near-real-time application to aid conservation effort in the war against poaching.

Species identification

Deep neural networks (DNNs) were applied by Norouzzadeh et al. (2018) to automatically extract information for animal identification thereby saving a tremendous amount of time by 99.3% compared to manual labor. Another study by Zeppelzauer (2013) used color model with different backgrounds and lighting conditions to automatically detect and track elephants in wildlife videos. It enabled biologists to effectively conduct behavioral and ecological studies. Object recognition and ensemble of exemplar support vector machine (EESVM) models were used to detect large mammals in semi-arid savanna for wildlife management conservation (Rey et al. 2017). A study by Kellenberger et al. (2017) conducted animal recognition based on pre-trained AlexNet from CNN architecture which was optimized for fast detection based on large animals. An investigation by Yu et al. (2013) used linear support vector machine algorithm to identify wild mammals on sequences of photographs. The technique was used for animal recognition in real, complex scenarios. Deep semantic segmentation CNN was used to recognize and detect kangaroos in a dynamic environment to minimize the number of kangaroo-vehicle collisions (Saleh et al. 2016).

Individual identification

The study conducted by Lahiri et al. (2011) extract simple image features and compare them based on animal coat markings, e.g., stripecoats, and dynamic programming algorithms for individual identification of zebra. A study by Dixon (2003) attained 95% for correct individual badger *Meles meles* based on their tail patterns. Its implementation provided tolerance to scale, exposure, occlusion, and mild perspective skews. It was established by Stein et al. (2010) that both black and white rhinoceros have unique horn sizes, shapes, and scarring, and hence, it was applied to monitor their population. When a rhinoceros possess a unique ear or notch pattern, possibly obtained from being torn by bushes or fighting with predators, it can be used as an individual identification attribute (Patton 2017). This approach was determined to have limitations as no correct

identification was obtained at 30 m in the bush and 65 m in the open area without the use of binoculars (Hussek et al. 2020). Figure 5 shows a female rhinoceros born July 2011 where ear tufts were used to assist for individual identification. The first photograph was from October 2012 to July 2016. Inception V3-based biometric long term recurrent convolutional network was used for individual Holstein Friesian cattle identification based on unique coat pattern (Andrew et al. 2019). An error-free identification was achieved for an online experiment which opens future application in uniquely patterned species in the wild such as zebras and giraffes. The study conducted by Suriyamongkol and Mali (2018) addressed the use of four computer-assisted softwares (wild-ID, APHIS (ITM), APHIS (SPM), and I3S Pattern) for the individual recognition of Rio Grande Cooter. It was established that wild-ID performed better with an accuracy of 83.87% and can be implemented for population count. Hotspotter and wild-ID were investigated for the individual identification of jaguar and ocelots (Nipko et al. 2020). Hotspotter attained an accuracy of 71% to 82% whereas wild-ID 58% to 73% hence these computer-assisted softwares are ideal for wildlife management. Despite these great efforts both the software platforms were applied for individual identification of Wyoming toad but failed to match by 48% and 64% for wild-ID and hotspotter respectively (Morrison et al. 2016).

Footprint identification technology

Footprint identification technology (FIT) was initially developed by WildTrack to improve wildlife monitoring techniques, currently been used several continents in Africa, Asia, and America (Suwal 2015). FIT is a complementary tool that was originally developed to aid in monitoring



Fig. 5 Ear tufts used as an identification feature cited with permission from Patton (2017)

endangered animal species such as Amur tiger, Bengal tiger, polar bear, cougar, Baird's tapir, and lowland tapir (Jewell and Alibhai 2013; Jewell et al. 2016; Raj et al. 2015). It is a radical improvement from the ancient traditional animal identification and tracking techniques to a modern technology that is non-invasive, fast, consistent, and without the need for tracking skills training. Figure 6 shows landmark points and derived measurements that FIT generates automatically. It applies statistical models and needs points with clear outlines.

Species identification

FIT was implemented for species identification between white rhino and black rhino. It was established that FIT was highly accurate for discriminating white rhino from black rhino (Alibhai et al. 2008). Other studies applied FIT for population monitoring of animal species, (Alibhai et al. 2017, 2008; Alli and Viriri 2013; Jewell et al. 2001; Sharma et al. 2005).

Individual identification

The study conducted by Li et al. (2018), successfully identified individual pandas according to sex, as well as classified them according to age. Another study by Laity (2015) implemented individual identification of free-roaming cheetahs based on FIT. It was established that lower quality footprints had lower accuracy as more individuals were predicted.

Facial recognition

Facial recognition is a noninvasive imaging system of recognizing the face of a subject of interest, through technology. Some of its application include animal disease control,

behavior, population, and growth monitoring (Brust et al. 2017; Corkery et al. 2007; Freytag et al. 2016; Hansen et al. 2018; Loos and Ernst 2013; Matkowski et al. 2019). It is highly used on threatened animal species.

Individual identification

Automatic individual facial identification to wild animals is encouraged as it does not rely on analysis by experts which is a tedious, intensive, and term consuming process (Shukla et al. 2019). Log-Euclidean CNN was applied to facial texture information of chimpanzees by predicting attributes such as identity, age, age group, and gender (Freytag et al. 2016). Another study by Crouse et al. (2017) was capable of attaining an accuracy of $98.7\% \pm 1.81\%$ by the application of computer-assisted facial recognition system of lemurs which could aid in the future for long-term monitoring of known individuals. A deep learning approach was used for automatic individual identification from videos and still images with correct identification accuracy of 94.1% with speed of 50 images per second (Guo et al. 2020). As primate species are endangered, an application of a face recognition using CNN architecture was implemented for individual recognition of lemurs, golden monkeys, and chimpanzees. A study by Schofield et al. (2019) applied CNN for chimpanzee face identification and sex recognition mainly for behavior studies. A similar approach was implemented for individual identification of giant pandas with an accuracy of 95% (Hou et al. 2020). It was established that the application of DNN for facial recognition of pandas is an economical approach of monitoring them as compared to the traditional approach (Chen et al. 2020). A study by Brust et al. (2017) achieved an accuracy of 90.8% for individual facial identification of gorillas which was established to be a complementary tool for human manual identification. Haar-like features and Ada-Boost classifiers were utilized for lion face detection and Kanade–Lucas–Tomasi tracker was implemented for tracking behavioral patterns (Burghardt and Čalić 2006).

Sound

Animals can communicate by sound that can be used to assist in identifying and monitoring them (Cakir et al. 2017; Clemins et al. 2005; Ovaskainen et al. 2018; Pabico et al. 2015; Yen and Fu 2001). Automatic identification of animal species from their sound is an important aspect for animal monitoring, research and behavior studying (Frommolt et al. 2008; Lopes et al. 2011; Stowell et al. 2017, 2019).




Fig. 6 FIT generates automatic identification cited with permission from Li et al. (2018)

Species identification

Animal sound identifier (ASI) provided an essential tool for classifying species from field recordings as shown in Fig. 7 (Ovaskainen et al. 2018). It was applied to classify 14 species of Amazonian birds based on their vocalizations. The ability of acoustic monitoring and simultaneous video recordings aided in behavior monitoring for elephants (Payne et al. 2003). As wolves are established to be difficult to be monitored, their capabilities to communicate acoustically to attain clear identification up to a distance of 3 km (Suter et al. 2017). Hidden Markov models (HMMs) were implemented for species identification (birds, frogs, insects, and mammals) based on the sound they produce. The highest and lowest accuracy attained was 99% and 79% respectively highlighting a positive element for ecological monitoring (Aide et al. 2013). Another study by Rai et al. (2016) used feature extraction and SVM classification for automatic identification of four bird species with a maximum accuracy of 89.4%. A comparison between humans and artificial neural networks (ANNs) was implemented for birds automatic species identification, it was established that ANNs performed better about 75% to humans (Jennings et al. 2008). The ability of an African elephant to communicate by sound within the same bond group members was determined to a distance about 2.5 km (McComb et al. 2003; Soltis 2010; Soltis et al. 2005). This skill is also used as an early warning and monitoring system within the elephant family without seeing the potential threat (Mortimer et al. 2018; O'Connell-Rodwell 2007; Zeppelzauer and Stoeger 2015).



Fig. 7 Autonomous audio recorders in 224 sites cited with permission from Ovaskainen et al. (2018)

Use of thermal imaging

Species identification

Thermal images taken by UAVs for species identification improved wildlife management (Oishi et al. 2018; Seymour et al. 2017). A study by Christiansen et al. (2014) used thermal images and discriminated animals from non animals through automatic detection and recognition using k -nearest-neighbor (k -NN) classifier. In a combination of UAV, thermal imagery, and automated detection was used to carry out population census for two grey seal breeding colonies. To reduce manpower hours required to survey wild animals from a large piece of land, (Oishi et al. 2018) automatically identified animals from thermal remote sensing images using moving wild animals algorithm. Thermal camera attached to UAV detected wildlife from heat signatures to obtain animal GPS location (Ward et al. 2016). HOG and SVM were applied for near-real-time deer identification to warn drivers against deer-vehicle collisions (Zhou and Wang 2011; Zhou et al. 2012). As poaching is likely to occur at dawn, thermal camera-enhanced RGB images helped anti-poaching operations to detect animals and poachers near-real-time (Bondi et al. 2018; Karlsson Schmidt 2015; Mulero-Pázmány et al. 2014). A workload reduction of 97% was obtained in Marais (2018) by using infrared images for automatic elephant detection.

Real-time implementation of automatic species and individual identification

The ability for real-time automatic species and individual identification is highly ideal for wildlife protection from poaching (Bondi et al. 2018; Karlsson Schmidt 2015; Wich 2015) as well as animal-vehicle collision (Huijser and McGowen 2003; Schwartz et al. 2020; Zahrani et al. 2011; Zhou and Wang 2011). The capabilities of animal detection and animal warning systems were reviewed by Huijser and McGowen (2003) and the authors concluded that all in all the reviewed systems were found to be effective mitigation tools in animal-vehicle collisions. A combination of YOLO for object detection and joint probabilistic data association (JPDA) for tracking was applied on aerial videos, where the JPDA tracking algorithm affected the YOLO detection capabilities (Xu et al. 2018). Detection of large animals at 72 images per second using CNN was obtained by Kellenberger et al. (2017) allowing near-real-time application. Another study automatically detected poachers and animals in thermal infrared aerial videos in near-real-time (Bondi et al. 2018). It provided aid for new anti-poaching strategies using UAVs. Figure 8 shows a screenshot of automatic detection of poachers in an infrared image.




Fig. 8 Screenshot for near-real-time application cited with permission from Bondi et al. (2018)

Discussion

Different techniques for automatic species and individual identification have been employed over the years, for various reasons such as wildlife research and monitoring. Specifically animal protection, population monitoring, behavior monitoring, and movement tracking to name a few. Table 3 provides an overview of the species and individual identification with different algorithms used by the reviewed studies. The advantages and disadvantages of using different body features for species and individual animal identifications are highlighted in Table 2.

Species identification accommodates animal identification based on general characteristics such as body pattern, footprint, and sound, whereas individual is narrowed to the uniqueness of an animal body pattern, footprint, and facial attributes.

Species identification

From the reviewed studies, the highest accuracy attained was 99.3% using the DNN algorithm in species identification considering animal body patterns. There could be several reasons why the DNN algorithm performs the highest. One possible reason could be the training architecture that goes into iterations of feature extraction and classification. This is one of the strong characteristics of algorithms based on deep learning, where the majority of the algorithms are used for automatic animal identification. Most of the algorithms used in this review study based on deep learning have an accuracy higher than 80%. The other reason for deep learning to perform better is the amount of data that is fed into the algorithm, that is, the bigger the data size, the better the performance. Where in the case of automatic animal identification, a huge amount of data is fed into the algorithm.

One possible reason why the body patterns feature has the highest accuracy is how data are collected, in this case, the image data. For one, camera technology has become very advanced to capture images at a very high resolution and thus is less susceptible to image noise. In the case of sound, it is highly susceptible to environmental noise, and for footprints, it is susceptible to environmental forces like wind that could distort footprint characteristics. This is supported by Priyadarshani et al. (2018) stating the capability of attaining high accuracy is hampered by the unavoidable environmental noise overlapping with the recordings.

Species identification has higher accuracy than individual because of the bigger discrepancy of features among different species compared to the difference in features among individual animals. The other possible reason could be that there is a higher demand in collectively identifying species to study their population, migration, etc., compared to studying individual animal.

Table 2 Advantages and disadvantages of using computer-based species and individual animal identification

Body feature	Application	Advantages	Disadvantages
Body pattern	Species and individual	Non-invasive approach Saves time as compared to human identification	Needs quality images High computational power required for analysis
Footprints	Endangered: species and individual	Non-invasive approach No tracking skilled personnel required Cost effective with respect to digital camera needed	Needs quality footprints
Facial attributes	Mainly individual	Non-invasive approach No skilled personnel required	Needs quality images High computational power required for analysis
Sound	Mainly species	Non-invasive approach No skilled personnel required	Needs quality sound High computational power required for analysis

Table 3 Techniques Used for Species and Individual Identification

Body Feature	Species/Individual	Technique	Accuracy	Study
Body patterns	Wildlife species	CNN	Specific species: 88.7% to 92.7%	Willi et al. (2019)
Body patterns	Wildlife species	DCNN	Average: 94.5%	Yousif et al. (2017)
Body patterns	Wildlife species	CNN	Images from– USA: 98% Canada: 82% Tanzania: 94%	Tabak et al. (2019)
Body patterns	Wildlife species	Linear SVM	Average: 82%	Yu et al. (2013)
Body patterns	Wildlife species	DNN	Deep learning: 99.3% Human count: 96.6%	Norouzzadeh et al. (2018)
Body patterns	Wildlife species	DCNN	Detecting animal: 96.6% Three (3) common species: 90.4%	Nguyen et al. (2017)
Body patterns	Wildlife species	DCNN	Balanced dataset– Top 1: 88.9% Top 5: 98.1%	Villa et al. (2017)
Body patterns	Kangaroo species	Deep semantic segmentation CNN	Overall: 93.0%	Saleh et al. (2016)
Body patterns	Deer species	SVM and HOG	95%	Zhou et al. (2012)
Body patterns	Deer species	SVM and HOG	Overall: 85%	Zhou and Wang (2011)
Body patterns	Wildlife species	Mean shift segmentation	True detection: 90% False alarm: 38.52%	Sirmacek et al. (2012)
Body patterns	Wild birds	RCNN, RFCN, YOLO v2, SSD and RetinaNet	Range: 85.01% to 95.44%	Hong et al. (2019)
Body patterns	Wildlife species (Elephant, giraffe and zebra)	CNN	Elephant: 95% Giraffe: 91% Zebra: 90%	Eikelboom et al. (2019)
Body patterns	Wildlife species	Faster R-CNN YOLO v2.0	Faster R-CNN: 93.0% YOLO v2.0: 76.7%	Schneider et al. (2018)
Body patterns	Elephant species	CNN	98%	Marais (2018)
Body patterns	Wildlife species	CNN	72 images per second	Kellenberger et al. (2017)
Body patterns	Individual rio grande cooter	I3S Pattern, wild.ID and APHIS	I3S Pattern: 61.29% wild.ID: 83.87% APHIS: 68.55%	Suriyamongkol and Mali (2018)
Body patterns	Individual jaguars and ocelots	HotSpotter and wild.ID	HotSpotter: 71 - 82% wild.ID: 58 - 73%	Nipko et al. (2020)
Body patterns	Individual wyoming toad	HotSpotter and wild.ID	HotSpotter: 64% wild.ID: 47%	Morrison et al. (2016)
Footprints	Endangered species	DA	> 90%	Jewell and Alibhai (2013)
Footprints	Individual cheetah	PDA and WCA	> 90%	Jewell et al. (2016)
Footprints	Wildlife species	CERT and CPCT	Population: 91% and 95%	Raj et al. (2015)
	Individual rhinoceros		Monitoring: 97% and 99%	
Footprints	Tiger species	Feature extraction	94.3%	Raj et al. (2015)
Footprints	Individual rhinoceros	CPT and DA	Population: > 94% Monitoring : > 87% - 88%	Jewell et al. (2001)
Footprints	Individual tiger	DFA	-	Sharma et al. (2005)
Footprints	Wildlife species	DA and WCA	Individual: > 90%	Alibhai et al. (2017)
	Individual puma		Sex: > 99%	
Footprints	Individual pandas	DA and WCA	Individual: > 90%	Li et al. (2018)

Table 3 (continued)

Body Feature	Species/Individual	Technique	Accuracy	Study
Facial	Chimpanzee species	Log-Euclidean CNN	Recognition Rate: 92% Gender estimation: 98%	Freytag et al. (2016)
Facial	Individual lemurs	Feature extraction	98.7% \pm 1.81%	Crouse et al. (2017)
Facial	Individual primates	Deep learning	94.1%	Guo et al. (2020)
Facial	Individual chimpanzee	CNN	Individual: > 92.5% Sex: > 96.2%	Schofield et al. (2019)
Facial	Individual giant panda	Deep learning	95%	Hou et al. (2020)
Facial	Individual gorillas	DCNN	90.8%	Brust et al. (2017)
Sound	Bird species	CRNN	88.5%	Cakir et al. (2017)
Sound	Bird species	Feature extraction and SVM	89.4%	Rai et al. (2016)
Sound	Elephant species	HMM	Classification: 94.3% Identification : 82.5%	Clemins et al. (2005)
Sound	Wildlife species (Birds, insects and amphibians)	GMMs and HMMs	91.25%	Potamitis (2014)
Sound	Wildlife species (Birds, dogs and frogs)	ANN	Birds: 71.43% Dogs: 94.44% Frogs: 90.91%	Pabico et al. (2015)
Sound	Bat species	ANN	62%	Jennings et al. (2008)

ANN Artificial Neural Network, CERT Canonical Ellipse Reduction, CNN Convolutional Neural Network, CPCT Canonical Pairwise Comparison Techniques, CPT Centroid Plot Technique, CRNN Convolutional Recurrent Neural Network, DA Discriminant Analysis, DCNN Deep Convolutional Neural Network, DFA Discriminant Function Analysis, DNN Deep Neural Network, GMM Gaussian Mixture Models, HMMs Hidden Markov Models, HOG Histogram of Oriented Gradients, IIS Interactive Individual Identification System, SSD Single Shot Detector, SVM Support Vector Machine, RCNN Region Convolutional Neural Network, YOLO v2.0 You Only Look Once version 2, RFCN Region-based Fully Convolutional Network, PCA Principal Component Analysis, PDA Pairwise Discriminant Analysis, WCA Ward's Clustering Analysis

The future direction in species identification could be to improve identification on other forms of data, e.g. footprints, sound, etc. that can help confirm identification process by data fusion from different inputs. Most likely the algorithm that can be recommended will be based on deep learning. Considering the huge amount of data in this kind of study.

Individual animal identification

From reviewed studies, individual automatic animal identification was implemented in endangered wildlife animals only. Hence the application on non-endangered wildlife animals make individual animal identification to be not yet fully exploited. The reason could be that there is a huge demand for health and population monitoring of endangered wildlife species. The commonly used features for individual identification includes spot pattern, stripe pattern, facial fur pattern and coat pattern, to name a few. Individual identification is prone to be easily attained at close proximity towards the animal by attaining the rich distinguishing detailed characteristics from one another. It is a great challenge to identify a possible individual animal from a large herd as it is time-consuming. The use of fin photographs for individual identification for white sharks was deemed good though its application can be used for a short period

time nearly 5 years (Gubili et al. 2009). Manually tracking them can be manpower demanding and time-consuming considering the vast area that they freely roam. The highest accuracy attained was 99% by the CPCT with the application of statistical algorithms on footprint identification of wild animals of endangered wildlife. We note that the data gathering method that is used here is by camera. Compared to the species identification that achieved the highest accuracy, the data gathering was also by camera. Thus it may be safe to say that the higher accuracy of the machine learning results is highly influenced by the method of data gathering. It is also worth noting that, FIT is highly susceptible to environmental disturbances like wind as well as other animals' movements. But despite these disturbances, FIT was still able to achieve 99%. The algorithm used is CPCT that is not based on neural network. Despite the fact that neural network-based methods, specifically deep learning, showed very high accuracy results in using very large datasets, CPCT, in this case, also showed very high accuracy. The two algorithms, e.g., CPCT and deep learning, have different computational approaches but having superior results in individual and species identification.

In the future, individual identification can be implemented for all wildlife animals, not just for endangered species, in order to track and monitor them, given that all of

them are freely roaming. There could be a need to study footprints identification using deep neural network and compare results against CPCT.

Body patterns

The reviewed studies implemented animal body patterns in various species, which yielded high accuracies compared to individual automatic identification. Body patterns use cameras to gather data. However, the accuracy of results in species identification using body patterns is much more accurate than individual identification. The highest accuracy for species identification is 99.3% while for individual is 83.87%. The difference in accuracy can be attributed to the fact that body patterns between the species are much more distinct than body patterns within the same species.

In the future, body patterns can be more accurately used for individual animal identification in the same way as a person's fingerprint. However, this could be a challenge because it may be necessary to take the 3D image of the whole animal body patterns and transform them into a 2D image to make the analysis. This data gathering method can be tedious such that the current individual animal identification results can be significantly improved.

Footprints

The use of physical footprint characteristics for both endangered species and individual animal identification is a promising application with a minimum accuracy of 87%. Factors such as soil moisture, weather condition, animal gait, and soil type contribute to the footprint's quality for identification purposes. Again, the reason for high accuracy can be the fact that data gathering in footprint identification uses a camera, where such a technology has significantly advanced in the past several decades.

In the future deep neural networks can be implemented for footprint identification which can be compared to the current machine-based algorithms. This can be a good approach considering the fact that footprints are highly susceptible to environmental disturbances such as wind and rain as well from other animals. Deep neural networks are known to be able to handle distortion in the data such as these disturbances to the footprint image.

Facial

Using facial attributes from the reviewed studies is highly applied to individual endangered animals with complex social life dynamics. Applying the advancement of deep learning algorithms to these images aids the critical capabilities of monitoring and understanding the demographic and evolution of individual animals in their natural environments

with high accuracies greater than 90%. The uses of camera aids in achieving these high accuracies.

In the future, facial identification can be fully utilized to individual wildlife animals and not just to the endangered ones. But the difficulty can be on data gathering because it is very tedious to track individual wildlife animal that is freely roaming. Camera traps for sure will not be enough. A flying drone may be used to gather data, but it has a minimum height limitation not to disturb the wildlife from its noise. Taking a high-resolution image from a long distance can be difficult.

Sound

Sound identification is limited to animals that produce sound, mainly bird species. Both deep and machine learning techniques are implemented to extract acoustic features for automatic identification. The highest accuracy attained was 94.44% using ANN. It is most likely that ANN is a more appropriate tool in processing and classifying sound features. The challenge of the presence of noise in the wild can be a challenge in attaining high automatic species identification.

In the future, data collection can be improved by better sensors and data processing that can significantly reduce the unwanted noise from the data. Current approaches can still be used but results can be significantly improved if the unwanted noise can be considerably removed.

Conclusion

In this review, manual animal identification had been established to be time-consuming, monotonous, tedious, and require human skills acquired through experience. Thus the development of automatic identification based on machine learning and deep learning techniques are beneficial for analysing large amount of data for faster and more efficient processing. The capabilities of automatic species and individual identification with very high accuracy as highlighted in Table 3 requires more than one computational method. Despite automatic identification capabilities, quality images, footprints, and sound quality are essential. Real-time animal identification is highly valuable to combat operations like poaching to save wildlife species.

Acknowledgements The authors would like to acknowledge the funding support on this work from the Botswana International University of Science and Technology (BIUST) Drones Project with project number P00015.

Declarations

Ethics approval Not applicable.

Consent to participate Not applicable.

Consent for publication Not applicable.

Conflicts of interest All authors declares that they have no conflict of interest.

References

- Aide TM, Corrada-Bravo C, Campos-Cerqueira M, Milan C, Vega G, Alvarez R (2013) Real-time bioacoustics monitoring and automated species identification. *PeerJ* 1:e103
- Alibhai S, Jewell Z, Evans J (2017) The challenge of monitoring elusive large carnivores: An accurate and cost-effective tool to identify and sex pumas (*puma concolor*) from footprints. *PloS One* 12(3):e0172065
- Alibhai SK, Jewell ZC, Law PR (2008) A footprint technique to identify white rhino *ceratotherium simum* at individual and species levels. *Endanger Species Res* 4(1–2):205–218
- Alli MN, Viriri S (2013) Animal identification based on footprint recognition. In: 2013 International Conference on Adaptive Science and Technology. IEEE, pp 1–4
- Alonso RS, McClintock BT, Lyren LM, Boydston EE, Crooks KR (2015) Mark-recapture and mark-resight methods for estimating abundance with remote cameras: a carnivore case study. *PloS one* 10(3):e0123032
- Anderson F, Hitchins P (1971) A radio tracking system for the black rhinoceros. *S Afr J Wildl Res* 24-month delayed open access 1(1):26–36
- Andrew W, Greatwood C, Burghardt T (2019) Aerial animal biometrics: Individual friesian cattle recovery and visual identification via an autonomous UAV with onboard deep inference. *arXiv preprint arXiv:190705310*
- AsRSG I (2009) The greater one horned rhinoceros monitoring instructors training manual. International Union for Nature Conservation and Asian Rhino Specialist Group. p 108
- Banga C, Besbes B, Balvay B, Chazo L, Jamaa O, Rozstalnyy A, Rovere G, Toto A, Trivedi K et al (2010) Current situation of animal identification and recording systems in developing countries and countries with economies in transition. Farm animal breeding, identification, production recording and management Proceedings of the 37th ICAR Biennial Session. pp 53–59
- Bedetti A, Greyling C, Paul B, Blondeau J, Clark A, Malin H, Horne J, Makukule R, Wilmot J, Eggeling T et al (2020) System for elephant ear-pattern knowledge (SEEK) to identify individual African elephants. *Pachyderm* 61:63–77
- Blake EH (2002) Extended abstract a field computer for animal trackers. In: CHI'02 extended abstracts on Human factors in computing systems. pp 532–533
- Bondi E, Fang F, Hamilton M, Kar D, Dmello D, Choi J, Hannaford R, Iyer A, Joppa L, Tambe M et al (2018) SPOT poachers in action: Augmenting conservation drones with automatic detection in near real-time. In: Thirty-Second AAAI Conference on Artificial Intelligence
- Borowicz A, Le H, Humphries G, Nehls G, Höschle C, Kosarev V, Lynch HJ (2019) Aerial-trained deep learning networks for surveying cetaceans from satellite imagery. *PloS one* 14(10):e0212532
- Bothma JdP, Le Riche E (1993) Disturbance bias when tracking kalahari leopards *panthera pardus* by spoor. *Koedoe* 36(2):109–112
- Brust CA, Burghardt T, Groenenberg M, Kading C, Kuhl HS, Manguette ML, Denzler J (2017) Towards automated visual monitoring of individual gorillas in the wild. In: Proceedings of the IEEE International Conference on Computer Vision Workshops. pp 2820–2830
- Bugge CE, Burkhart J, Dugstad KS, Enger TB, Kasprzycka M, Kleinauskas A, Myhre M, Scheffler K, Ström S, Vetlesen S (2011) Biometric methods of animal identification. Course notes, Laboratory Animal Science at the Norwegian School of Veterinary Science. pp 1–6
- Burghardt T, Čalić J (2006) Analysing animal behaviour in wildlife videos using face detection and tracking. *IEE Proceedings-Vision, Image and Signal Processing* 153(3):305–312
- Burt P, Bergen J, Hingorani R, Kolczynski R, Lee W, Leung A, Lubin J, Shvayster H (1989) Object tracking with a moving camera. [1989] Proceedings. Workshop on Visual Motion. IEEE, pp 2–12
- Cagnacci F, Boitani L, Powell RA, Boyce MS (2010) Animal ecology meets GPS-based radiotelemetry: a perfect storm of opportunities and challenges
- Cakir E, Adavanne S, Parascandolo G, Drossos K, Virtanen T (2017) Convolutional recurrent neural networks for bird audio detection. In: 2017 25th European Signal Processing Conference (EUSIPCO). IEEE, pp 1744–1748
- Carl C, Schönfeld F, Profft I, Klamm A, Landgraf D (2020) Automated detection of European wild mammal species in camera trap images with an existing and pre-trained computer vision model. *Eur J Wildl Res* 66(4):1–7
- Chauhan NK, Singh K (2018) A review on conventional machine learning vs deep learning. 2018 International Conference on Computing, Power and Communication Technologies (GUCON). IEEE, pp 347–352
- Chen J, Li K, Tang Z, Bilal K, Yu S, Weng C, Li K (2016) A parallel random forest algorithm for big data in a spark cloud computing environment. *IEEE Trans Parallel Distrib Syst* 28(4):919–933
- Chen P, Swarup P, Matkowski WM, Kong AWK, Han S, Zhang Z, Rong H (2020) A study on giant panda recognition based on images of a large proportion of captive pandas. *Ecol Evol* 10(7):3561–3573
- Cheteni P (2014) An analysis of anti-poaching techniques in Africa: a case of rhino poaching. *Environ Econ* (5, Iss. 3):63–70
- Christiansen P, Steen K, Jørgensen R, Karstoft H (2014) Automated detection and recognition of wildlife using thermal cameras. *Sensors* 14(8):13778–13793
- Clemins PJ, Johnson MT, Leong KM, Savage A (2005) Automatic classification and speaker identification of African elephant (*Loxodonta africana*) vocalizations. *J Acoust Soc Am* 117(2):956–963
- Connally RL, Frank MG, Briers GE, Silvy NJ, Carlisle KM, Tomeček JM (2021) Hunter motivations and use of wild pigs in Texas, USA. *Human-Wildlife Interactions* 15(1):10
- Corkery G, Gonzales-Barron UA, Butler F, Mc Donnell K, Ward S (2007) A preliminary investigation on face recognition as a biometric identifier of sheep. *Transactions of the ASABE* 50(1):313–320
- Crouse D, Jacobs RL, Richardson Z, Klum S, Jain A, Baden AL, Tecot SR (2017) Lemurfaceid: a face recognition system to facilitate individual identification of lemurs. *BMC Zoology* 2(1):1–14
- Cubaynes HC (2020) Whales from space: Assessing the feasibility of using satellite imagery to monitor whales. PhD thesis, University of Cambridge
- Cubaynes HC, Fretwell PT, Bamford C, Gerrish L, Jackson JA (2019) Whales from space: four mysticete species described using new vhr satellite imagery. *Mar Mamm Sci* 35(2):466–491
- Delplanque A, Foucher S, Lejeune P, Linchant J, Théau J (2021) Multi-species detection and identification of African mammals in aerial imagery using convolutional neural networks. *Remote Sensing in Ecology and Conservation*
- DeMotts R, Hoon P (2012) Whose elephants? Conserving, compensating, and competing in northern Botswana. *Soc Nat Resour* 25(9):837–851

- Dixon DR (2003) A non-invasive technique for identifying individual badgers *meles meles*. *Mammal Rev* 33(1):92–94
- Dorning J, Harris S (2019) The challenges of recognising individuals with few distinguishing features: Identifying red foxes *Vulpes vulpes* from camera-trap photos. *PLoS One* 14(5):e0216531
- Dos Santos GAM, Barnes Z, Lo E, Ritoper B, Nishizaki L, Tejeda X, Ke A, Lin H, Schurgers C, Lin A et al (2014) Small unmanned aerial vehicle system for wildlife radio collar tracking. In: 2014 IEEE 11th International Conference on Mobile Ad Hoc and Sensor Systems. IEEE, pp 761–766
- Dunham K (2001) Reintroduction of black rhino in the Luangwa Valley, Zambia. Evaluation of areas for the reintroduction of rhinos in Zambia SADC Regional Programme for Rhino Conservation
- Duporge I, Isupova O, Reece S, Macdonald DW, Wang T (2020) Using very-high-resolution satellite imagery and deep learning to detect and count african elephants in heterogeneous landscapes. *Remote Sensing in Ecology and Conservation*
- Eikelboom JA, Wind J, van de Ven E, Kenana LM, Schroder B, de Knecht HJ, van Langevelde F, Prins HH (2019) Improving the precision and accuracy of animal population estimates with aerial image object detection. *Methods Ecol Evol* 10(11):1875–1887
- Elbroch M, Mwampamba TH, Santos MJ, Zylberberg M, Liebenberg L, Minye J, Mosser C, Reddy E (2011) The value, limitations, and challenges of employing local experts in conservation research. *Conserv Biol* 25(6):1195–1202
- Ezat MA, Fritsch CJ, Downs CT (2018) Use of an unmanned aerial vehicle (drone) to survey Nile crocodile populations: a case study at Lake Nyamithi, Ndumo game reserve, South Africa. *Biol Conserv* 223:76–81
- Fang Y, Du S, Abdoola R, Djouani K, Richards C (2016) Motion based animal detection in aerial videos. *Procedia Comput Sci* 92:13–17
- Ferreira AC, Silva LR, Renna F, Brandl HB, Renoult JP, Farine DR, Covas R, Doutrelant C (2020) Deep learning-based methods for individual recognition in small birds. *Methods Ecol Evol* 11(9):1072–1085
- Freytag A, Rodner E, Simon M, Loos A, Kühl HS, Denzler J (2016) Chimpanzee faces in the wild: Log-euclidean CNNs for predicting identities and attributes of primates. In: German Conference on Pattern Recognition. Springer, pp 51–63
- Frommolt KH, Bardeli R, Clausen M (2008) Computational bioacoustics for assessing biodiversity. In: Proceedings of the International Expert meeting on IT-based detection of bioacoustical patterns, BfN-Skripten, Citeaser, vol 234
- Gaston KJ, O'Neill MA (2004) Automated species identification: why not? *Philos Trans R Soc Lond Ser B Biol Sci* 359(1444):655–667
- Gibbon GE, Bindemann M, Roberts DL (2015) Factors affecting the identification of individual mountain Bongo antelope. *PeerJ* 3:e1303
- Goldsworthy C, Matam BR (2021) Improved rare species identification using focal loss based deep learning models. *International Journal of Computer and Information Engineering* 15(1):18–22
- Goodyer J (2013) Drone rangers [Africa special sustainability]. *Eng Technol* 8(5):60–61
- Greene K, Bell D, Kioko J, Kiffner C (2017) Performance of ground-based and aerial survey methods for monitoring wildlife assemblages in a conservation area of northern Tanzania. *Eur J Wildl Res* 63(5):77
- Grünewälder S, Broekhuis F, Macdonald DW, Wilson AM, McNutt JW, Shawe-Taylor J, Hailes S (2012) Movement activity based classification of animal behaviour with an application to data from cheetah (*Acinonyx jubatus*). *PloS One* 7(11):e49120
- Gu J, Alibhai SK, Jewell ZC, Jiang G, Ma J (2014) Sex determination of Amur tigers (*Panthera tigris altaica*) from footprints in snow. *Wildl Soc Bull* 38(3):495–502
- Gu J, Wang Z, Kuen J, Ma L, Shahroudy A, Shuai B, Liu T, Wang X, Wang G, Cai J et al (2018) Recent advances in convolutional neural networks. *Pattern Recogn* 77:354–377
- Gubili C, Johnson R, Gennari E, Oosthuizen WH, Kotze D, Meyer M, Sims DW, Jones CS, Noble LR (2009) Concordance of genetic and fin photo identification in the great white shark, *Carcharodon carcharias*, off Mossel Bay, South Africa. *Marine Biology* 156(10):2199–2207
- Guirado E, Tabik S, Rivas ML, Alcaraz-Segura D, Herrera F (2018) Automatic whale counting in satellite images with deep learning. *BioRxiv* p 443671
- Guirado E, Tabik S, Rivas ML, Alcaraz-Segura D, Herrera F (2019) Whale counting in satellite and aerial images with deep learning. *Sci Rep* 9(1):1–12
- Guo S, Xu P, Miao Q, Shao G, Chapman CA, Chen X, He G, Fang D, Zhang H, Sun Y, et al. (2020) Automatic identification of individual primates with deep learning techniques. *Iscience* 23(8):101412
- Guo X, Shao Q, Li Y, Wang Y, Wang D, Liu J, Fan J, Yang F (2018) Application of UAV remote sensing for a population census of large wild herbivores—taking the headwater region of the yellow river as an example. *Remote Sens* 10(7):1041
- Hall-Martin A (1986) Recruitment in a small black rhino population. *Pachyderm* 7:6–8
- Hansen MF, Smith ML, Smith LN, Salter MG, Baxter EM, Farish M, Grieve B (2018) Towards on-farm pig face recognition using convolutional neural networks. *Comput Ind* 98:145–152
- Hewes GW (1994) Evolution of human semiosis and the reading of animal tracks. In: *Origins of Semiosis Sign Evolution in Nature and Culture* pp 139–149
- Hong SJ, Han Y, Kim SY, Lee AY, Kim G (2019) Application of deep-learning methods to bird detection using unmanned aerial vehicle imagery. *Sensors* 19(7):1651
- Höschle C, Cubaynes HC, Clarke PJ, Humphries G, Borowicz A (2021) The potential of satellite imagery for surveying whales. *Sensors* 21(3):963
- Hou J, He Y, Yang H, Connor T, Gao J, Wang Y, Zeng Y, Zhang J, Huang J, Zheng B et al (2020) Identification of animal individuals using deep learning: A case study of giant panda. *Biol Conserv* 242:108414
- Hu X, Tang Y, Zhang Z (2008) Video object matching based on SIFT algorithm. In: 2008 International Conference on Neural Networks and Signal Processing. IEEE, pp 412–415
- Huang R, Pedoeem J, Chen C (2018) Yolo-lite: a real-time object detection algorithm optimized for non-GPU computers. In: 2018 IEEE International Conference on Big Data (Big Data). IEEE, pp 2503–2510
- Huijser MP, McGowen PT (2003) Overview of animal detection and animal warning systems in North America and Europe
- Hussek A, Hackländer K, Graf C (2020) Are ear notches an effective tool for monitoring individual rhino? *Pachyderm* (60):55–66
- Jennings N, Parsons S, Pocock M (2008) Human vs. machine: identification of bat species from their echolocation calls by humans and by artificial neural networks. *Can J Zool* 86(5):371–377
- Jewell Z, Alibhai S (2013) Identifying endangered species from footprints. *International Society for Optics and Photonics (SPIE) Newsroom* 2013:1–3
- Jewell ZC, Alibhai SK, Law PR (2001) Censusing and monitoring black rhino (*Diceros Bicornis*) using an objective spoor (footprint) identification technique. *J Zool* 254(1):1–16
- Jewell ZC, Alibhai SK, Weise F, Munro S, Van Vuuren M, Van Vuuren R (2016) Spotting cheetahs: identifying individuals by their footprints. *JoVE (Journal of Visualized Experiments)* 111:e54034
- Johansson Ö, Samelius G, Wikberg E, Chapron G, Mishra C, Low M (2020) Identification errors in camera-trap studies result in systematic population overestimation. *Sci Rep* 10(1):1–10

- Kamminga J, Ayele E, Meratnia N, Havinga P (2018) Poaching detection technologies—a survey. *Sensors* 18(5):1474
- Karlsson Schmidt C (2015) Rhino and human detection in overlapping RGB and LWIR images
- Kellenberger B, Volpi M, Tuia D (2017) Fast animal detection in UAV images using convolutional neural networks. In: 2017 IEEE International Geoscience and Remote Sensing Symposium (IGARSS). IEEE, pp 866–869
- Koschan A, Li S, Visich JK, Khumawala BM, Zhang C (2006) Radio frequency identification technology: applications, technical challenges and strategies. *Sensor Review*
- Kühl HS, Burghardt T (2013) Animal biometrics: quantifying and detecting phenotypic appearance. *Trends Ecol Evol* 28(7):432–441
- Lahiri M, Tantipathananandh C, Warungu R, Rubenstein DI, Berger-Wolf TY (2011) Biometric animal databases from field photographs: identification of individual zebra in the wild. In: Proceedings of the 1st ACM international conference on multimedia retrieval. pp 1–8
- Laity KM (2015) Field validation of the footprint identification technology on free-roaming cheetahs in Namibia. Duke University
- LaRue MA, Stapleton S, Anderson M (2017) Feasibility of using high-resolution satellite imagery to assess vertebrate wildlife populations. *Conserv Biol* 31(1):213–220
- Li BV, Alibhai S, Jewell Z, Li D, Zhang H (2018) Using footprints to identify and sex giant pandas. *Biol Conserv* 218:83–90
- Liebenberg L, Blake E, Steventon L, Benadie K, Minye J (1998) Integrating traditional knowledge with computer science for the conservation of biodiversity. In: 8th International Conference on Hunting and Gathering Societies Foraging and Post-Foraging Societies: History, Politics, and Future. pp 26–30
- Liebenberg L, Steventon L, Benadie K, Minye J (1999) Rhino tracking with the cybertracker field computer. *Pachyderm* 27:59–61
- Liebenberg L, Louw A, Elbroch M (2010) Practical tracking: a guide to following footprints and finding animals. Stackpole Books
- Linchant J, Lisein J, Semeki J, Lejeune P, Vermeulen C (2015) Are unmanned aircraft systems (UAS) the future of wildlife monitoring? A review of accomplishments and challenges. *Mammal Rev* 45(4):239–252
- Loos A, Ernst A (2013) An automated chimpanzee identification system using face detection and recognition. *EURASIP Journal on Image and Video Processing* 1:49
- Loos A, Weigel C, Koehler M (2018) Towards automatic detection of animals in camera-trap images. In: 2018 26th European Signal Processing Conference (EUSIPCO). IEEE, pp 1805–1809
- Lopes MT, Gioppo LL, Higushi TT, Kaestner CA, Silla Jr CN, Koerich AL (2011) Automatic bird species identification for large number of species. In: 2011 IEEE International Symposium on Multimedia. IEEE, pp 117–122
- Makgantai B, Subaschandar N, Jamisola RS (2021) Design optimization of wingtip devices to reduce induced drag on fixed-wings. In: 2021 International Conference on Unmanned Aircraft Systems (ICUAS). IEEE, pp 1459–1465
- Malisiewicz T, Shrivastava A, Gupta A, Efros AA (2012) Exemplars for visual object detection, label transfer and image retrieval. In: ICML
- Marais JC (2018) Automated elephant detection and classification from aerial infrared and colour images using deep learning. PhD thesis, Stellenbosch: Stellenbosch University
- Matipano G (2004) Black rhinoceros mortality in Matusadona National Park, Zimbabwe: 1992–2003. *IUCN*, p 109
- Matkowski WM, Kong AWK, Su H, Chen P, Hou R, Zhang Z (2019) Giant panda face recognition using small dataset. In: 2019 IEEE International Conference on Image Processing (ICIP). IEEE, pp 1680–1684
- McComb K, Reby D, Baker L, Moss C, Sayialel S (2003) Long-distance communication of acoustic cues to social identity in African elephants. *Anim Behav* 65(2):317–329
- Meek P, Ballard G, Claridge A, Kays R, Moseby K, O'brien T, O'connell A, Sanderson J, Swann D, Tobler M et al (2014) Recommended guiding principles for reporting on camera trapping research. *Biodivers Conserv* 23(9):2321–2343
- Meek PD, Ballard GA, Vernes K, Fleming PJ (2015) The history of wildlife camera trapping as a survey tool in Australia. *Australian Mammalogy* 37(1):1–12
- Mendoza E, Martineau PR, Brenner E, Dirzo R (2011) A novel method to improve individual animal identification based on camera-trapping data. *J Wildl Manag* 75(4):973–979
- Mmerek W, Jamisola RS, Mpoeleng D, Petso T (2021) YOLOv3-based human activity recognition as viewed from a moving high-altitude aerial camera. In: 2021 7th International Conference on Automation, Robotics and Applications (ICARA). IEEE, pp 241–246
- Mohd-Azlan J (2009) The use of camera traps in Malaysian rainforests. *Journal of Tropical Biology and Conservation* 5:81–86
- Morrison TA, Keinath D, Estes-Zumpf W, Crall JP, Stewart CV (2016) Individual identification of the endangered wyoming toad *Anaxyrus baxteri* and implications for monitoring species recovery. *J Hered* 50(1):44–49
- Mortimer B, Rees WL, Koelemeijer P, Nissen-Meyer T (2018) Classifying elephant behaviour through seismic vibrations. *Current Biology* 28(9):R547–R548
- Mulero-Pázmány M, Stolper R, Van Essen L, Negro JJ, Sassen T (2014) Remotely piloted aircraft systems as a rhinoceros anti-poaching tool in Africa. *PloS One* 9(1):e83873
- Münster D, Münster U (2012) Human-animal conflicts in Kerala: Elephants and ecological modernity on the agrarian frontier in South India. *RCC Perspectives* 5:41–50
- Naude J, Joubert D (2019) The aerial elephant dataset: a new public benchmark for aerial object detection. In: Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition Workshops. pp 48–55
- Nguyen H, MacLagan SJ, Nguyen TD, Nguyen T, Flemons P, Andrews K, Ritchie EG, Phung D (2017) Animal recognition and identification with deep convolutional neural networks for automated wildlife monitoring. In: 2017 IEEE international conference on data science and advanced Analytics (DSAA). IEEE, pp 40–49
- Nipko RB, Holcombe BE, Kelly MJ (2020) Identifying individual jaguars and ocelots via pattern-recognition software: Comparing hotspotter and wild-id. *Wildl Soc Bull* 44(2):424–433
- Norouzzadeh MS, Nguyen A, Kosmala M, Swanson A, Palmer MS, Packer C, Clune J (2018) Automatically identifying, counting, and describing wild animals in camera-trap images with deep learning. *Proc Natl Acad Sci* 115(25):E5716–E5725
- O'Connell-Rodwell CE (2007) Keeping an “ear” to the ground: seismic communication in elephants. *Physiology* 22(4):287–294
- Oishi Y, Oguma H, Tamura A, Nakamura R, Matsunaga T (2018) Animal detection using thermal images and its required observation conditions. *Remote Sens* 10(7):1050
- Olivares-Mendez M, Fu C, Ludvig P, Bissyard T, Kannan S, Zurad M, Annaiyan A, Voos H, Campoy P (2015) Towards an autonomous vision-based unmanned aerial system against wildlife poachers. *Sensors* 15(12):31362–31391
- Ovaskainen O, Moliterno de Camargo U, Somervuo P (2018) Animal Sound Identifier (ASI): software for automated identification of vocal animals. *Ecol Lett* 21(8):1244–1254
- Pabico JP, Gonzales AMV, Villanueva MJS, Mendoza AA (2015) Automatic identification of animal breeds and species using bioacoustics and artificial neural networks. *arXiv preprint arXiv:150705546*

- Patton F (2017) The use of ear tufts to assist in the identification of individual black rhinos. *Pachyderm* 58:148–151
- Patton F, Campbell P (2011) Using eye and profile wrinkles to identify individual white rhinos. *Pachyderm J African Elephant, African Rhino Asian Rhino Spec Groups* 84–86
- Patton F, Jones M (2010) Determining the suitability of using eye wrinkle patterns for the accurate identification of individual black rhinos. *Pachyderm* 48:18–23
- Patton F, Campbell P, Parfet E (2007) Establishing a monitoring system for black rhinos in the Solio Game Reserve, central Kenya. *Pachyderm* 43:87–95
- Payne KB, Thompson M, Kramer L (2003) Elephant calling patterns as indicators of group size and composition: the basis for an acoustic monitoring system. *Afr J Ecol* 41(1):99–107
- Pollard KA, Blumstein DT, Griffin SC (2010) Pre-screening acoustic and other natural signatures for use in noninvasive individual identification. *J Appl Ecol* 47(5):1103–1109
- Potamitis I (2014) Automatic classification of a taxon-rich community recorded in the wild. *PloS One* 9(5)
- Priyadarshani N, Marsland S, Castro I (2018) Automated birdsong recognition in complex acoustic environments: a review. *J Avian Biol* 49(5):jav-01447
- Rai P, Golchha V, Srivastava A, Vyas G, Mishra S (2016) An automatic classification of bird species using audio feature extraction and support vector machines. In: 2016 International Conference on Inventive Computation Technologies (ICICT), vol 1. IEEE, pp 1–5
- Raj A, Choudhary P, Suman P (2015) Identification of tigers through their pugmark using pattern recognition. *HCTL Open International Journal of Technology Innovations and Research (IJTIR)* 15
- Ramalepa LP, Jamisola RS (2021) A review on cooperative robotic arms with mobile or drones bases. *Int J Autom Comput* 1–20
- Rey N, Volpi M, Joost S, Tuia D (2017) Detecting animals in African Savanna with UAVs and the crowds. *Remote Sens Environ* 200:341–351
- Saleh K, Hossny M, Nahavandi S (2016) Kangaroo vehicle collision detection using deep semantic segmentation convolutional neural network. In: 2016 International Conference on Digital Image Computing: Techniques and Applications (DICTA). IEEE, pp 1–7
- Schneider S, Taylor GW, Kremer S (2018) Deep learning object detection methods for ecological camera trap data. In: 2018 15th Conference on Computer and Robot Vision (CRV). IEEE, pp 321–328
- Schofield D, Nagrani A, Zisserman A, Hayashi M, Matsuzawa T, Biro D, Carvalho S (2019) Chimpanzee face recognition from videos in the wild using deep learning. *Sci Adv* 5(9):eaaw0736
- Schwartz AL, Shilling FM, Perkins SE (2020) The value of monitoring wildlife roadkill. *Eur J Wildl Res* 66(1):1–12
- Seymour AC, Dale J, Hammill M, Halpin P, Johnston D (2017) Automated detection and enumeration of marine wildlife using unmanned aircraft systems (UAS) and thermal imagery. *Sci Rep* 7:45127. <https://doi.org/10.1038/srep45127>
- Shafie AA, Hafiz F, Ali M et al (2009) Motion detection techniques using optical flow. *World Acad Sci Eng Technol* 56:559–561
- Sharma S, Jhala Y, Sawarkar VB (2005) Identification of individual tigers (*Panthera Tigris*) from their pugmarks. *J Zool* 267(1):9–18
- Sherley RB, Burghardt T, Barham PJ, Campbell N, Cuthill IC (2010) Spotting the difference: towards fully-automated population monitoring of African penguins *Spheniscus Demersus*. *Endanger Species Res* 11(2):101–111
- Shrader AM, Beauchamp B (2001) A new method for implanting radio transmitters into horns of black and white rhinoceroses
- Shukla A, Cheema GS, Anand S, Qureshi Q, Jhala Y (2019) Primate face identification in the wild. In: Pacific Rim International Conference on Artificial Intelligence. Springer, pp 387–401
- Sirmacek B, Wegmann M, Cross A, Hopcraft J, Reinartz P, Dech S (2012) Automatic population counts for improved wildlife management using aerial photography
- Soltis J (2010) Vocal communication in African elephants (*Loxodonta africana*). *Zoo Biol* 29(2):192–209
- Soltis J, Leong K, Savage A (2005) African elephant vocal communication I: antiphonal calling behaviour among affiliated females. *Anim Behav* 70(3):579–587
- Stander P, Ghau I, Tsisaba Do, Oma I, VI (1997) Tracking and the interpretation of spoor: a scientifically sound method in ecology. *J Zool* 242(2):329–341
- Stein A, Erckie B, Fuller TK, Marker L (2010) Camera trapping as a method for monitoring rhino populations within the waterberg plateau park, Namibia. *Pachyderm* 48:67–70
- Stevenson BC, Borchers DL, Fewster RM (2019) Cluster capture-recapture to account for identification uncertainty on aerial surveys of animal populations. *Biometrics* 75(1):326–336
- Stowell D, Benetos E, Gill LF (2017) On-bird sound recordings: automatic acoustic recognition of activities and contexts. *IEEE/ACM Transactions on Audio, Speech, and Language Processing* 25(6):1193–1206
- Stowell D, Petrusková T, Šálek M, Linhart P (2019) Automatic acoustic identification of individuals in multiple species: improving identification across recording conditions. *J R Soc Interface* 16(153):20180940
- Subedi N, Jnawali SR, Dhakal M, Pradhan NM, Lamichhane BR, Malla S, Amin R, Jhala YV (2013) Population status, structure and distribution of the greater one-horned Rhinoceros *Rhinoceros Unicornis* in Nepal. *Oryx* 47(3):352–360
- Suriyamongkol T, Mali I (2018) Feasibility of using computer-assisted software for recognizing individual Rio Grande Cooter (*Pseudemys Gorzugi*). *Copeia* 106(4):646–651
- Suter SM, Giordano M, Nietlisbach S, Apollonio M, Passilongo D (2017) Non-invasive acoustic detection of wolves. *Bioacoustics* 26(3):237–248
- Suwal T (2015) Assessing the use of footprint identification technique to monitor Bengal tigers in Nepal. PhD thesis, Duke University
- Tabak MA, Norouzzadeh MS, Wolfson DW, Sweeney SJ, VerCauteren KC, Snow NP, Halseth JM, Di Salvo PA, Lewis JS, White MD et al (2019) Machine learning to classify animal species in camera trap images: applications in ecology. *Methods Ecol Evol* 10(4):585–590
- Talukdar BK (2009) Asian Rhino Specialist Group report/rapport du groupe de spécialistes du rhinocéros d'Asie. *Pachyderm* 45:16–19
- Torney CJ, Dobson AP, Borner F, Lloyd-Jones DJ, Moyer D, Maliti HT, Mwita M, Fredrick H, Borner M, Hopcraft JGC (2016) Assessing rotation-invariant feature classification for automated wildebeest population counts. *PloS one* 11(5):e0156342
- Ungar ED, Henkin Z, Gutman M, Dolev A, Genizi A, Ganskopp D (2005) Inference of animal activity from GPS collar data on free-ranging cattle. *Rangel Ecol Manag* 58(3):256–266
- Valletta JJ, Torney C, Kings M, Thornton A, Madden J (2017) Applications of machine learning in animal behaviour studies. *Anim Behav* 124:203–220
- Van Nguyen H, Chessier M, Chen F, Rezaatofghi SH, Ranasinghe DC (2018) Autonomous UAV sensor system for searching and locating VHF radio-tagged wildlife. In: Proceedings of the 16th ACM Conference on Embedded Networked Sensor Systems. pp 333–334
- Varble S, Secchi S (2013) Human consumption as an invasive species management strategy: a preliminary assessment of the marketing potential of invasive Asian carp in the US. *Appetite* 65:58–67
- Vidya T, Prasad D, Ghosh A (2014) Individual identification in Asian elephants. *Gajah* 40:3–17
- Villa AG, Salazar A, Vargas F (2017) Towards automatic wild animal monitoring: Identification of animal species in camera-trap images using very deep convolutional neural networks. *Eco Inform* 41:24–32

- Ward S, Hensler J, Alsalam B, Gonzalez LF (2016) Autonomous UAVs wildlife detection using thermal imaging, predictive navigation and computer vision. In: 2016 IEEE Aerospace Conference. IEEE, pp 1–8
- Webber D, Hui N, Kastner R, Schurgers C (2017) Radio receiver design for unmanned aerial wildlife tracking. 2017 International Conference on Computing Networking and Communications (ICNC). IEEE, pp 942–946
- Wich SA (2015) Drones and conservation. Drones and Aerial Observation: New Technologies for Property Rights, Human Rights, and Global Development Washington DC: New America. pp 63–70
- Willi M, Pitman RT, Cardoso AW, Locke C, Swanson A, Boyer A, Veldthuis M, Fortson L (2019) Identifying animal species in camera trap images using deep learning and citizen science. *Methods Ecol Evol* 10(1):80–91
- Xin Y, Kong L, Liu Z, Chen Y, Li Y, Zhu H, Gao M, Hou H, Wang C (2018) Machine learning and deep learning methods for cybersecurity. *IEEE Access* 6:35365–35381
- Xu S, Savvaris A, He S, Shin Hs, Tsourdos A (2018) Real-time implementation of YOLO+ JPDA for small scale UAV multiple object tracking. In: 2018 International Conference on Unmanned Aircraft Systems (ICUAS). IEEE, pp 1336–1341
- Yen GG, Fu Q (2001) Automatic frog calls monitoring system: a machine learning approach. *Int J Comput Intell Appl* 1(02):165–186
- Yousif H, Yuan J, Kays R, He Z (2017) Fast human-animal detection from highly cluttered camera-trap images using joint background modeling and deep learning classification. In: 2017 IEEE international symposium on circuits and systems (ISCAS). IEEE, pp 1–4
- Yu X, Wang J, Kays R, Jansen PA, Wang T, Huang T (2013) Automated identification of animal species in camera trap images. *EURASIP Journal on Image and Video Processing* 2013(1):52
- Zahrani MS, Ragab K, Haque AU (2011) Design of GPS-based system to avoid camel-vehicle collisions: A. *Asian J Appl Sci* 4(4):362–377
- Zeppelzauer M (2013) Automated detection of elephants in wildlife video. *EURASIP Journal on Image and Video Processing* 2013(1):46
- Zeppelzauer M, Stoeger AS (2015) Establishing the fundamentals for an elephant early warning and monitoring system. *BMC Res Notes* 8(1):409
- Zhang Q, Zhang M, Chen T, Sun Z, Ma Y, Yu B (2019) Recent advances in convolutional neural network acceleration. *Neurocomputing* 323:37–51
- Zhou D, Wang J (2011) Identification of deer in thermal images to avoid deer-vehicle crashes. In: Proceedings of 2011 International Conference on Electronics and Optoelectronics, vol 3. IEEE, pp V3–342
- Zhou D, Wang J, Wang S (2012) Countour based HOG deer detection in thermal images for traffic safety. In: Proceedings of the International Conference on Image Processing, Computer Vision, and Pattern Recognition (IPCV), The Steering Committee of The World Congress in Computer Science, Computer. p 1