Intelligent Compiler for Detecting Errors in Medical Data Processing Programs Using GAN

Swarnim Bandekar
School of Computer Science and Engineering (SCOPE)
VIT-AP University
Amaravati, Andhra Pradesh, India
Regd. No. 24BCB7157

Lithin CG
School of Computer Science and Engineering (SCOPE)
VIT-AP University
Amaravati, Andhra Pradesh, India
Regd. No. 24BCB7016

***Abstract*—Programs that process medical data can contain mistakes that a general-purpose compiler never reports: a dose added to a body weight, a temperature threshold typed ten times too large, a laboratory value that may be missing but is used unguarded, or a patient name that reaches a log file. This paper describes a compiler front end built to catch such errors, and a learned classifier that names the root-cause family of each defective program. The front end is written for MedScript, a small domain-specific language with units of measure in its types, declared physiological ranges, protected-health-information tagging and optional values. It comprises a hand-written lexer, a recursive-descent parser with error recovery, and a semantic analyser that checks types, units, range plausibility, taint flow of patient identifiers, optional values, definite assignment and division by zero; a three-address-code generator and optimiser complete the pipeline. On a synthetic corpus of 10,000 programs in ten classes, classifiers using compiler-derived features reach 99.15% accuracy, against 91.6% for the family of the first diagnostic, and they catch faults the compiler cannot see, such as an inverted fever rule. A conditional generative adversarial network (GAN) trained to augment rare error classes did not help: Gaussian jitter and SMOTE performed better, and only about 4% of the GAN's samples were recognisable as the requested class. A GAN discriminator trained on valid programs did detect the compiler-invisible faults well (AUROC 0.98). The corpus is synthetic, and the results should be read accordingly.**

***Index Terms*—compiler design, semantic analysis, parsing, units of measure, error classification, generative adversarial network, healthcare software**

I. Introduction

Programs that handle medical data sit in an unusual place in the software landscape. They are usually small and unglamorous—a script that flags abnormal vital signs, a routine that converts a body weight into a drug dose, a nightly job that exports records to a research registry—yet a mistake in any of them can reach a patient. Two accidents are often quoted to show how little it takes. The Therac-25 radiation overdoses of the mid-1980s were traced to defects in control software [11], and the Mars Climate Orbiter was lost in 1999 because one team produced impulse data in pound-force seconds while the consuming software expected newton seconds [12]. The second failure is, in compiler terms, a plain type error that the type system of the day simply could not see: both quantities were just `double`.

Clinical code has the same weak spot. A dose in milligrams added to a weight in kilograms, a temperature threshold typed as `380` instead of `38.0`, a blood-glucose reading that may be missing from the laboratory feed but is used as if it were always present, or a patient name that reaches a log file without being anonymised: each of these is syntactically fine and passes through a general-purpose compiler without a word. The relevant knowledge—units, physiological ranges, privacy rules—lives in the heads of the people who write the program, not in the language they write it in.

This project builds a small compiler front end that *does* know about that domain, and then asks a machine-learning question on top of it: once a program has been rejected (or, worse, accepted), can a learned model tell us what kind of mistake it contains, even when the compiler's own diagnostics are incomplete or misleading? The generative adversarial network (GAN) enters the picture for a practical reason. Labelled examples of faulty medical programs are scarce, and they are awkward to share because real clinical scripts tend to embed identifiers and institutional rules. A conditional GAN that learns the distribution of compiler-derived feature vectors per error class offers a way to produce additional training records without handing over any source code. Whether that actually helps is an empirical question, and we report the answer as we measured it, including the places where it did not help.

A. Motivation

Three observations motivated the work.

1) **General compilers are blind to domain constraints.** Mainstream languages check that an expression is a number, not that it is a mass. Units-of-measure systems exist [8] but are not part of the languages most clinical scripting is done in.
2) **Rule-based diagnostics are precise but narrow.** A hand-written analyser reports exactly what it was told to look for. It says nothing about an inverted fever rule such as `if (temp < 38.0 degC)` followed by an alert called "fever", because nothing in the grammar or the type system is violated. Cascading faults make things

Course project for Compiler Design Lab (CSE3024), School of Computer Science and Engineering (SCOPE), VIT-AP University. Compiler design component: parsing and semantic analysis. Machine learning component: error classification. Application domain: healthcare.

worse: when several defects coexist, the first message is not necessarily the root cause.

3) **Labelled data is the bottleneck.** Learning-based bug finders depend on large corpora [14], [17]. In a regulated domain the corpus of real faulty programs is small, and synthetic augmentation is attractive if it can be shown to work.

The course context also shaped the design. The assignment asks for a compiler component—here parsing and semantic analysis—and a machine-learning component—here error classification—applied to a concrete domain, which for us is healthcare. We therefore treated the compiler as the primary artefact and the learned model as a second stage that consumes what the compiler produces.

B. Problem Statement

The problem addressed in this paper is:

> *Given the source text of a medical data-processing program, how can we (i) detect domain-specific errors—unit, range, privacy and missing-value errors in addition to ordinary lexical, syntactic and type errors—with a purpose-built compiler front end, and (ii) assign each defective program to its root-cause error family with a learned classifier that is trained on compiler-derived features, using a generative adversarial network to compensate for the scarcity of labelled faulty programs?*

C. Objectives

1) To design *MedScript*, a small imperative language for medical data processing with first-class units of measure, protected-health-information (PHI) tagging, optional (possibly missing) values and declared physiological ranges.
2) To implement a complete front end for it: a hand-written lexer, a recursive-descent parser with error recovery, and a semantic analyser that performs type, unit, range, taint, missing-value, definite-assignment and division-by-zero checks.
3) To implement the back end far enough to demonstrate the compiler pipeline end to end: three-address code, constant folding, constant propagation, common-subexpression elimination, dead-code elimination, and a reference virtual machine used to check that optimisation preserves behaviour.
4) To define a taxonomy of ten classes (valid plus nine error families), build a labelled corpus of valid and fault-injected programs, and train classifiers on features extracted from the compiler's tokens, syntax tree and diagnostics.
5) To train conditional GANs on those features and measure honestly whether the synthetic records improve classification when real faulty examples are scarce, and whether a GAN trained only on valid programs can serve as an anomaly detector.
6) To measure the compiler itself: scaling of compilation time with program size and the effect of optimisation on code size.

D. Contributions

The main contributions of this paper are:

- **MedScript and its compiler.** A domain-specific language and a Python implementation (about 1,900 lines for the compiler proper, about 4,900 including corpus tools, learning code, experiments and tests) of lexer, parser, semantic analyser, IR generator, optimiser and virtual machine, with a command-line tool that also reports a learned root-cause estimate. A suite of 38 unit tests accompanies it.
- **Semantic analysis that encodes clinical safety rules.** Unit checking through exponent vectors over base units, interval reasoning over declared ranges, taint tracking from `phi` inputs to output sinks, and flow-sensitive refinement of optional values.
- **A fault-injection corpus.** 10,000 programs in ten classes, produced by 46 mutation operators with a check that each injected fault actually manifests, including 15.5% multi-fault programs among the faulty ones.
- **A comparison of rule-based and learned error classification.** The learned classifiers reach 99.15% accuracy against 91.6% for the "first diagnostic" rule, and they also catch faults the compiler cannot see, which neither rule baseline does.
- **An honest evaluation of GAN augmentation.** Seven training regimes are compared over ten random seeds at five levels of data scarcity, together with fidelity measurements of the synthetic records and a GAN-based anomaly detector. The GAN turns out not to help, and the paper says why.

E. Organisation of the Paper

Section II reviews related work. Section III describes the language, the compiler phases and the machine-learning components. Section IV describes the corpus, the experimental protocol and the software environment. Section V presents and discusses results. Section VI concludes and outlines future work. The appendices contain the full grammar, the diagnostic catalogue, the fault operators and a short guide to running the code.

II. Related Work

The project touches four bodies of work: classical compiler front ends, static analyses for domain-specific properties such as units and information flow, machine learning for program defects, and generative models and resampling for imbalanced data. This section summarises each and then states where our work sits.

A. Classical Compiler Front Ends

The standard treatment of lexical analysis, parsing and semantic analysis is that of Aho et al. [1]; Cooper and Torczon [2] and Appel [3] cover the same ground with more attention to implementation. Two ideas from that literature are used directly in this project. The first is *error recovery*. A compiler that stops at the first syntax error is unpleasant to use, so parsers resynchronise: they either skip tokens until a safe point (panic mode) or repair the input locally by inserting or deleting a token. Burke and Fisher [5] give a systematic method for LR and LL parsers, and Grune and Jacobs [4] survey the alternatives. Our recursive-descent parser combines both: a missing semicolon or parenthesis is reported and treated as if it had been present, and any other malformed construct is skipped up to the next statement boundary. The second idea is *phase gating*: later phases are only run on an input that earlier phases accepted, because a semantic analysis of a tree built from broken syntax produces noise. We follow this convention, which, as Section V shows, has a measurable effect on what the compiler can tell about programs that contain several faults.

Type checking itself is covered by Pierce [6]. The flow-sensitive parts of our semantic analyser—definite assignment, and the refinement of optional values inside a guarded branch—are instances of the data-flow framework presented by Nielson et al. [7].

B. Units of Measure and Information-Flow Analysis

Kennedy's *dimension types* [8] extend a type system so that numeric types carry a unit expressed as a product of base units raised to integer powers. Multiplication adds exponents, division subtracts them, and addition requires equal exponents. This is precisely the rule that would have caught the Mars Climate Orbiter error and the dose-plus-weight mistake mentioned in the introduction, and it is the formulation used here.

Taint analysis tracks data from *sources* to *sinks*. TaintDroid [9] applies it dynamically to detect private data leaving a smartphone. We use a simple static variant: values read from inputs marked `phi` are tainted, taint propagates through arithmetic, string concatenation and user functions, and it is cleared only by an explicit `anonymize()` call. Reaching `print` or `export` with a tainted value is an error. The motivation is regulatory rather than technical: the HIPAA Privacy Rule restricts the disclosure of individually identifiable health information and describes de-identification procedures [10].

C. Machine Learning for Program Defects

Allamanis et al. [14] survey the use of statistical models of source code, building on the observation that real programs are repetitive and predictable [13]. DeepFix [16] trains a sequence-to-sequence network to repair common syntax and type errors in student C programs. DeepBugs [17] learns from name-based features to flag bugs such as swapped arguments and wrong binary operators—close in spirit to the inverted-comparison faults we study. Graph neural networks over syntax and data-flow edges have also been used to detect variable misuse [15]. These systems work on general-purpose code and operate on tokens or graphs. We take a different, lighter route: the learned model sees *what the compiler already computed*—counts of each diagnostic, structural statistics, and a few clinical-rule patterns—which keeps the model small, makes its inputs inspectable, and lets it use the compiler as a feature extractor rather than re-learning grammar.

D. GANs, Augmentation and Imbalanced Learning

A generative adversarial network trains a generator G and a discriminator D in a two-player game [18]; the conditional variant feeds a class label to both networks so that samples can be drawn for a chosen class [19]. Training can be unstable, and a large part of the subsequent literature addresses that: label smoothing and related heuristics [20], the Wasserstein objective [21] and its gradient-penalty form [22]. In healthcare, medGAN [23] generates synthetic patient records, and CTGAN [24] handles mixed tabular data; the Data Augmentation GAN [25] was proposed specifically for the low-data regime. For class imbalance, the classical alternatives are random oversampling and SMOTE [26], which interpolates between a minority sample and one of its nearest neighbours; He and Garcia [27] review the field. A GAN can also serve as an anomaly detector: AnoGAN [28] trains on normal data only and scores an input by how poorly the generator can reproduce it. We use a lighter-weight version of this idea, scoring with the discriminator or critic, and compare it with Isolation Forest [29] and the one-class SVM [30].

E. Survey of Related Approaches

F. Gap and Positioning

None of the surveyed systems combines (a) a front end with built-in clinical semantics, (b) a learned classifier that sits on top of that front end and reasons about root cause, and (c) an explicit evaluation of GAN-based augmentation against simple resampling baselines in the same setting. That combination is what this project attempts. It does so at laboratory scale: the language is a purpose-built DSL, and the corpus is synthetic. We return to the consequences of those choices in Section V-H.

G. Limitations of Existing Approaches

Several limitations of existing approaches shaped our design choices:

1) General-purpose compilers do not check units, ranges, privacy or missingness, so the most dangerous clinical mistakes pass silently.
2) Rule-based analyses are precise but incomplete; they cannot flag a rule that is merely *wrong*.
3) With several coexisting faults, the first reported diagnostic may not be the root cause, and phase gating hides later-phase faults entirely.
4) Learned bug detectors require large corpora, which regulated domains cannot provide.
5) GAN training is unstable and data-hungry, and its benefit over cheap resampling is rarely tested on the same task.

TABLE I
RELATED APPROACHES COMPARED WITH THE SYSTEM BUILT IN THIS PROJECT.

Approach	Domain	Main idea	Limitation for our setting
Classical front end [1]	General languages	Lexing, parsing, type checking	Blind to units, ranges, PHI
Dimension types [8]	Scientific code	Units as exponent vectors	No privacy or missing-value rules
TaintDroid [9]	Mobile apps	Dynamic information-flow tracking	Runtime only; no clinical semantics
DeepFix [16]	Student C programs	Seq2seq repair of syntax/type errors	Needs large labelled corpus
DeepBugs [17]	JavaScript	Name-based bug classifiers	No domain knowledge
SMOTE [26]	Tabular data	Interpolate minority neighbours	Not generative; stays inside the convex hull
medGAN / CTGAN [23], [24]	Patient records / tables	GAN-based synthetic records	Not applied to program features
AnoGAN [28]	Medical images	Anomaly scoring with a GAN	Images, not programs
This work	Medical-data programs	Domain-aware front end + learned error-family classifier with GAN augmentation	Synthetic corpus; DSL rather than a mainstream language

III. PROPOSED METHODOLOGY

A. System Overview

The system has two cooperating halves, shown in Fig. 1. The *compiler half* is a conventional pipeline—scanner, parser, semantic analyser, intermediate-code generator, optimiser—for a domain-specific language called MedScript. Every phase reports diagnostics with a stable code, a position and a message. The *learning half* takes what the compiler produced (tokens, syntax tree, diagnostics) and condenses it into a fixed-length feature vector. A classifier maps that vector to one of ten classes: *valid* or one of nine error families. A conditional GAN, trained on feature vectors of the labelled corpus, supplies extra synthetic records of the rare classes at training time. At inference time the GAN is not used; the deployed artefact is the compiler plus a random-forest classifier.

B. The MedScript Language

MedScript is deliberately small: it contains just enough to express the programs a clinical-informatics student might write, and just enough machinery to make the domain-specific checks meaningful. Its main design decisions are the following.

- **Units are part of the type.** A numeric type is `int`, `float`, or a float tagged with a unit expression such as `kg`, `mg/kg` or `kg/metre^2`. Literals carry units: `38.0 degC`, `15 mg/kg`.
- **Inputs are declared with metadata.** `input weight: kg range(2, 300);` declares a read-only patient quantity with a physiological range. `phi` marks protected health information.
- **Optional values.** A trailing `?` (as in `mg/ml?`) means the value may be missing. It must be tested with `present(x)` before use.
- **Two output sinks.** `print` and `export`; both reject PHI unless it passed through `anonymize`.

TABLE II
UNITS OF MEASURE KNOWN TO THE COMPILER AND THE PLAUSIBILITY BOUNDS USED FOR LITERALS.

Unit	Meaning	Plausible literal range
`kg`, `lb`	body mass	0.2–500 kg; 0.4–1100 lb
`gram`, `mg`	mass of substance	0–20 g; 0–20000 mg
`ml`, `hour`	volume, time	0–10000 ml; 0–72 h
`bpm`	beats (or breaths) per minute	0–300
`mmHg`	blood pressure	0–350
`degC`, `degF`	temperature	20–45 °C; 68–113 °F
`metre`	body height	0.2–2.5

- **Ordinary control flow.** `if`/`else`, `while`, functions with typed parameters and return types, `let` bindings with optional type inference.

Table II lists the unit vocabulary. The single-letter units one might expect (`m`, `g`, `h`) are spelled `metre`, `gram` and `hour`, so that those short names stay available as identifiers.

A complete program that the compiler accepts is shown in Listing 1. It computes a weight-based dose with a safety cap, a body-mass index, a fever alert, a sepsis screen, an alert that is guarded for a possibly missing laboratory value, and an anonymised export.

Listing 1. A valid MedScript program (`examples/triage_ok.med`).

```
input patient_name: string phi;
input weight: kg range(2, 300);
input height: metre range(0.4, 2.3);
input temp: degC range(30, 43);
input hr: bpm range(20, 250);
input lactate: mg? range(0, 400);

const MAX_DOSE: mg = 1000 mg;

func dose_for(w: kg, rate: mg/kg) -> mg {
   let d: mg = rate * w;
   if (d > MAX_DOSE) { return MAX_DOSE; }
   return d;
}
func bmi(w: kg, h: metre) -> kg/metre^2 {
   return w / (h * h);
}

let dose: mg = dose_for(weight, 15 mg/kg);
let index = bmi(weight, height);
```




Fig. 1. Architecture of the proposed system. Solid arrows are data flow, dashed arrows are diagnostics and features collected from the compiler phases. The GAN branch (bottom) is used only to enlarge the training set.

TABLE III
TOKEN CLASSES OF MEDSCRIPT.

Class	Pattern	Examples
ID	letter or underscore, then letters, digits, underscores (minus keywords and units)	`weight`, `dose_for`
Keyword	fixed set of 16 words	`input`, `if`, `phi`, `range`
UNIT	fixed set of 11 words	`kg`, `mmHg`, `degC`
NUM	digits, optionally a dot and more digits	`38`, `0.45`
STR	double quote, any characters except quote and newline, double quote	`"ALERT fever"`
Operators	`+ - * / % < > <= >= == != && || ! = ->`	
Punctuation	`( ) { } , ; : ? ^`	
Comment	`//` to end of line (discarded)	

```
let fever = false;
if (temp > 38.0 degC) { fever = true; print("fever alert"); }
if (hr > 100 bpm && fever) { print("sepsis screen"); }
if (present(lactate)) {
   if (lactate > 200 mg) { print("high lactate"); }
}
export(anonymize(patient_name));
print(dose);
print(index);
```

C. Lexical Analysis

The scanner is a hand-written, single-pass, longest-match recogniser. The token classes are summarised in Table III. Identifiers and keywords share one regular expression; the lexeme is then looked up in the keyword set and in the unit set. A numeric lexeme is first collected as the maximal run of letters, digits and dots and *then* validated against $[0\text{-}9]^{+}(.[0\text{-}9]^{+})?$; this way `3.4.5` and `10x` are reported as one malformed number rather than as a number followed by stray characters.

Three lexical diagnostics exist: an illegal character (`LEX001`), a malformed number (`LEX002`) and an unterminated string (`LEX003`). Each is *recoverable*: an illegal character is dropped, a malformed number is replaced by its longest valid prefix, and an unterminated string consumes the rest of the line. The parser therefore still receives a usable token stream, and later phases run normally. This detail matters for classification: a lexical error does not hide semantic faults, whereas a syntax error does.

TABLE IV
FIRST SETS OF THE STATEMENT FORMS, USED FOR PREDICTION AND AS SYNCHRONISATION TOKENS.

Construct	FIRST
input declaration	`input`
constant declaration	`const`
function declaration	`func`
let / if / while / return	`let if while return`
block	`{`
assignment	`ID` followed by `=`
call statement / expression	`ID`, `NUM`, `STR`, `true`, `false`, `(`, `-`, `!`

D. Syntax Analysis

The grammar (Appendix A gives it in full) is LL(1) apart from two decisions. When a statement begins with an identifier, the parser must choose between an assignment and a call; it resolves this with one extra token of lookahead (`ID =`). Likewise, after a number and a unit, a following `/` belongs to the unit expression only if the token after it is also a unit. Expressions use precedence climbing over six levels, from `||` (lowest) to the multiplicative operators. Table IV lists the tokens that can begin each kind of statement, which are also the synchronisation points used for error recovery.

a) Error recovery.: Two mechanisms are combined. When a *closing* token is missing—`;`, `)` or `}`—the parser reports `SYN001`, anchors the message at the end of the previous token (where a programmer would expect to see it), and carries on as if the token had been inserted. When an

expression cannot start (SYN002) the parser raises an internal resynchronisation exception that is caught at statement level; the handler skips tokens until a semicolon is consumed or a token from Table IV is seen. At most one diagnostic is issued per input position, which suppresses most duplicate cascades. A premature end of file yields SYN003. If the parse produced *any* syntax diagnostic, the semantic analyser is not run.

E. Semantic Analysis

The semantic analyser walks the tree once, keeping a stack of scopes and a small flow state. It is the part of the compiler that carries the clinical knowledge, so we describe each check in turn.

1) Symbol table and scopes: Inputs and constants live in a global scope. Top-level `let` bindings live in a "main" scope layered above it; function bodies see only the global scope, their parameters and their own locals. Functions are collected in a first pass, so a call may precede the definition. Declaring a name twice in one scope is SEM002. A `let` variable that is never read gives the warning W002.

2) Types and units: Let a numeric type be a pair $\tau[d]$ where $\tau \in \{\texttt{int}, \texttt{float}\}$ and $d \in \mathbb{Z}^U$ is a *dimension vector*, one integer exponent per base unit $u \in U$. A plain number has $d = \mathbf{0}$; the type `mg/kg` has exponent $+1$ for `mg`, -1 for `kg` and 0 elsewhere. The typing rules for arithmetic are

$$\frac{\Gamma \vdash e_1 : \tau_1[d_1] \quad \Gamma \vdash e_2 : \tau_2[d_2] \quad d_1 = d_2}{\Gamma \vdash e_1 \pm e_2 : \tau[d_1]} \tag{1}$$

$$\frac{\Gamma \vdash e_1 : \tau_1[d_1] \quad \Gamma \vdash e_2 : \tau_2[d_2]}{\Gamma \vdash e_1 \cdot e_2 : \tau[d_1 + d_2]} \tag{2}$$

$$\frac{\Gamma \vdash e_1 : \tau_1[d_1] \quad \Gamma \vdash e_2 : \tau_2[d_2]}{\Gamma \vdash e_1 / e_2 : \texttt{float}[d_1 - d_2]} \tag{3}$$

and comparison requires $d_1 = d_2$ and yields `bool`. As an example, the product `rate * w` with `rate`:`mg/kg` and `w`:`kg` has dimension $(+1)_{\text{mg}} + (-1)_{\text{kg}} + (+1)_{\text{kg}} = (+1)_{\text{mg}}$, i.e., it is a mass in milligrams, which is exactly what the declaration `let d: mg = rate * w` expects. Adding `weight + 5 lb` fails because $d_1 \neq d_2$: `kg` and `lb` are distinct base units and the language does not convert implicitly (conversion goes through `lb_to_kg`). The literal `0` is the only dimension-polymorphic value, so that comparisons such as `x > 0` remain convenient.

A mismatch between base kinds (a string where a number is expected, a non-boolean condition, a wrong argument count) is reported as SEM004, SEM008 or SEM006; a mismatch of dimensions alone is SEM005. Keeping the two apart is what lets the classifier distinguish the *type* and *unit* families later.

3) Ranges and thresholds: Every numeric value carries, besides its type, an optional closed interval $[l, h]$ obtained from the declared range of an input or from interval arithmetic on constants:

$$[a, b] + [c, d] = [a + c,\ b + d], \tag{4}$$

$$[a, b] \cdot [c, d] = [\min P, \max P], \quad P = \{ac, ad, bc, bd\}, \tag{5}$$

$$[a, b] / [c, d] = [a, b] \cdot [1/d,\ 1/c], \quad \text{defined iff } 0 \notin [c, d]. \tag{6}$$

Two checks use the intervals. (i) A literal that carries a single unit must lie inside the plausibility interval of Table II; `380 degC` does not. (ii) A comparison between an input with declared range $[l, h]$ and a constant k with $k < l$ or $k > h$ is flagged, because the comparison is then always true or always false. Both give DOM001. A threshold exactly equal to a bound, such as `hr > 250 bpm` with `range(20, 250)`, is accepted.

4) Division by zero: A divisor whose constant value is 0 gives DOM004. A divisor whose interval contains 0 gives DOM005, unless a *non-zero fact* is in force for that variable. Non-zero facts are produced by branch conditions such as `x > 0`, `x != 0`, or the negation of `x <= 0`, and they hold inside the branch (or after an early-returning branch that tests the opposite).

5) PHI taint tracking: Let $\mathrm{t}(e) \in \{0, 1\}$ denote whether the value of expression e may contain protected health information.

$$\mathrm{t}(x) = phi(x), \tag{7}$$

$$\mathrm{t}(e_1 \odot e_2) = \mathrm{t}(e_1) \vee \mathrm{t}(e_2), \tag{8}$$

$$\mathrm{t}(\texttt{anonymize}(e)) = 0, \tag{9}$$

$$\mathrm{t}(f(e_1, \ldots, e_n)) = \bigvee_i \mathrm{t}(e_i). \tag{10}$$

A `let` or assignment copies the taint of its right-hand side to the variable. A call to a sink with any argument e_i for which $\mathrm{t}(e_i) = 1$ is DOM002. The analysis is a conservative, flow-insensitive approximation: it never misses a leak through the constructs of the language, but a function that discards its tainted argument is still treated as propagating it.

6) Optional values: A variable of optional type may be missing. Using it in an expression is DOM003 unless a *presence fact* holds. Presence facts come from the guard forms `present(`x`)`, `present(`x`)` && c (the fact holds while evaluating c), `!present(`x`)` in the else branch, and early exits such as `if (!present(x)) { return 0; }`, after which x is present for the rest of the block. Branch merging is an intersection of facts, so a fact survives a join only if both arms established it.

7) Definite assignment, returns and reachability: The flow state also records which `let` variables are definitely assigned; at a join the sets are intersected, and a use of a variable outside the set is SEM003. Whether a block *always returns* is computed bottom-up; a non-void function whose body can finish without returning gives SEM007. A statement after a `return` gives the warning W001, and a constant condition gives W003.

8) Diagnostic catalogue: The analyser can emit 23 distinct codes in total. Each belongs to exactly one error family, which

TABLE V
THE TEN CLASSES AND THE DIAGNOSTICS THAT BELONG TO EACH FAMILY.

Id	Class	Diagnostic codes / meaning
0	valid	no error (warning `W002` allowed)
1	lexical	`LEX001`–`LEX003`: illegal character, malformed number, unterminated string
2	syntax	`SYN001`–`SYN003`: missing token, unexpected token, unexpected end of file
3	name	`SEM001`, `SEM002`, `SEM003`, `SEM009`: undeclared, redeclared, uninitialised, assignment to input
4	type	`SEM004`, `SEM006`, `SEM008`: base-type, arity and condition errors
5	unit	`SEM005`: unit-of-measure mismatch
6	range	`DOM001`: implausible value or threshold outside declared range
7	phi	`DOM002`: PHI reaching a sink
8	missing	`DOM003`: optional value used unguarded
9	logic	`SEM007`, `DOM004`, `DOM005`, `W001`, `W003`, and rule errors invisible to the compiler

is the label space of the classifier (Table V). The complete catalogue with messages is in Appendix B.

F. Intermediate Code and Optimisation

After a successful analysis the tree is lowered to three-address code. Local variables are renamed uniquely (`x@3`) so that shadowing cannot confuse later passes, short-circuit operators become conditional jumps, and calls become `param`/`call` sequences. For `c = a + b * 10` the generator emits

$$t_1 = b * 10 \tag{11}$$

$$t_2 = a + t_1 \tag{12}$$

$$c = t_2 \tag{13}$$

and the optimiser reduces it to $t_1 = b * 10;\ c = a + t_1$. The passes are the classical ones [1], [37], iterated until the code size stops changing (at most four rounds):

1) **Constant folding and propagation** inside basic blocks, including folding of comparisons, and elimination of `ifFalse` jumps with constant conditions.
2) **Algebraic simplification**: $x + 0$, $x - 0$, $x \cdot 1$, $x/1$.
3) **Local common-subexpression elimination** by value numbering over (op, a, b), invalidated when an operand is redefined.
4) **Unreachable-code removal** after unconditional jumps and returns, and removal of unused labels.
5) **Dead-store elimination** for temporaries and local variables that are never read.
6) **Copy fusion**: $t = a\ op\ b;\ v = t \Rightarrow v = a\ op\ b$ when t has a single use.

These are deliberately modest compared with a production back end such as LLVM [38]; the aim is a compact pipeline that is easy to verify. To check that none of the passes changes behaviour, the project includes a small virtual machine that executes the three-address code. For a program the test harness draws random input values from the declared ranges (leaving about 30% of the optional ones missing), runs the unoptimised and optimised code, and requires the sequences of `print` and `export` events to be identical.

TABLE VI
FEATURE GROUPS.

Group	Dim.	Content
Token (`tok`)	30	log-counts of token classes (identifiers, numbers, strings, units, keyword groups, punctuation, operator groups), program length, brace and parenthesis balance, semicolons per statement
AST (`ast`)	25	log-counts of node types, tree size and depth, counts of optional inputs, PHI inputs, ranged inputs, sinks, `anonymize` and `present` calls, literal-zero divisors
Diagnostics (`diag`)	40	per-code counts (23), error and warning totals, semantic-phase flag, first-error family (9) and phase (3), number of distinct families, worst-family rank
Pattern (`pat`)	6	comparison direction $\times$ alert vocabulary (four counts), number of alert rules, number of mismatched rules

G. Feature Extraction

The classifier does not see raw source. For each compiled program the extractor produces a vector of 101 numbers in four groups (Table VI). The *diagnostic* group is the interface to the compiler's knowledge: it contains the count of each of the 23 codes, the number of errors and warnings, whether the semantic phase ran at all, a one-hot encoding of the family and phase of the first error, the number of distinct families that appear, and the rank of the most severe one. The *pattern* group exists for faults that produce no diagnostics. For each relational operator the extractor looks at a short window of surrounding identifiers and string literals and checks whether it contains a word from a small "high-risk" vocabulary (*fever*, *tachycardia*, *hypertension*, *overdose*, ...) or a "low-risk" vocabulary (*hypothermia*, *bradycardia*, *hypotension*, ...), and counts the four combinations of vocabulary and operator direction. A well-formed program has mostly "high with $>$" and "low with $<$"; the other two combinations indicate a reversed rule or a mismatched label.

H. Error Taxonomy and Labelling

A program has exactly one label. For single-fault programs the label is the family of the injected fault. For programs with two injected faults the label is the one with higher *root-cause priority*, using the order

$$\text{syntax} > \text{lexical} > \text{phi} > \text{range} > \text{unit} > \text{missing} > \text{type} > \text{name} > \text{logic}.$$

The order is a modelling decision, not a law. Syntax errors come first because they hide everything else; privacy and range errors come next because they are the most safety-critical; *logic* is last because it is the most heterogeneous family. A second fault is only injected from a family of lower priority than the first, so the label is always well defined.

I. Conditional GAN on Feature Vectors

Let $x \in \mathbb{R}^{101}$ be a standardised feature vector and $y \in \{0, \dots, 9\}$ its class, encoded one-hot as c. The generator maps a noise vector $z \sim \mathcal{N}(0, I_{32})$ and c to a synthetic vector, $\tilde{x} = G(z, c)$, and the discriminator $D(x, c)$ produces a scalar score. Both are multilayer perceptrons with two hidden layers of 128 units and LeakyReLU(0.2) activations; the discriminator uses dropout 0.3. They are implemented in PyTorch [33].

a) Vanilla (BCE) objective.: The original minimax game conditioned on the label is

$$\min_G \max_D \; \mathbb{E}_{(x,y)}\big[\log D(x, c_y)\big] + \mathbb{E}_{z,y}\big[\log\big(1 - D(G(z, c_y), c_y)\big)\big]. \quad (14)$$

In practice the generator uses the non-saturating loss $L_G = -\mathbb{E} \log D(G(z, c), c)$, and the discriminator's target for real samples is smoothed to 0.9 [20].

b) WGAN-GP objective.: The critic is trained to minimise

$$L_D = \mathbb{E}\big[D(\tilde{x}, c)\big] - \mathbb{E}\big[D(x, c)\big] + \lambda\, \mathbb{E}_{\hat{x}}\Big[\big(\|\nabla_{\hat{x}} D(\hat{x}, c)\|_2 - 1\big)^2\Big], \quad (15)$$

with $\hat{x} = \epsilon x + (1-\epsilon)\tilde{x}$, $\epsilon \sim U(0, 1)$ and $\lambda = 10$ [22], five critic updates per generator update, and $L_G = -\mathbb{E}\, D(G(z, c), c)$.

c) Training details.: Features are standardised with the mean and standard deviation of the GAN's training set and clipped to ± 6 standard deviations. Optimisation uses Adam [34]: learning rate $2 \cdot 10^{-4}$, $\beta = (0.5, 0.999)$ for BCE, and 10^{-4}, $\beta = (0.5, 0.9)$ for WGAN-GP; batch size 64; 2000 generator iterations for BCE and 1000 for WGAN-GP. Generated vectors are mapped back to the original scale and clipped to the per-feature minimum and maximum seen in training. The GAN is trained on *all* classes jointly, conditionally, using only the training portion of the data of a given experiment. For augmentation, each class with fewer examples than a target count is topped up with samples drawn from $G(z, c_y)$ (Algorithm 1).

J. Classifiers and Baselines

Four standard classifiers are trained on feature vectors: a random forest [31] with 300 trees, a multilayer perceptron (two hidden layers of 128 and 64 units, standardised inputs), multinomial logistic regression, and a histogram-based gradient-boosting classifier, all from scikit-learn [32]. Two rule-based baselines use only the compiler's diagnostics and no learning:

- **First error**: predict the family of the first reported error (what a developer reading the output top to bottom would conclude); predict *logic* if there is no error but a logic warning, *valid* otherwise.
- **Most severe**: predict the family of highest root-cause priority among all reported errors, with the same fallbacks.

The second baseline is a strong one: it has access to the labelling rule itself. Any advantage of the learned classifiers over it therefore comes from cases that the rule cannot express.

Algorithm 1 Conditional-GAN augmentation of rare error classes

Require: Labelled training features $\{(x_i, y_i)\}$, target size N per class, iterations T
Ensure: Augmented training set $\mathcal{D}'$

```
Fit a standardiser on {x_i} and transform all vectors
Initialise G, D; set D' ← {(x_i, y_i)}
for t = 1 to T do
    Sample a mini-batch (x, y) and noise z; compute x̃ = G(z, c_y)
    Update D (BCE with smoothed targets, or critic with gradient penalty)
    Update G with the corresponding generator loss
end for
for each class k with n_k < N real examples do
    Draw N − n_k vectors x̃ = G(z, c_k); invert the standardisation; clip to the training range
    Add them to D' with label k
end for
return D'
```

Algorithm 2 End-to-end processing of a MedScript program

Require: Source text S, trained classifier C
Ensure: Diagnostics, optimised IR (if error-free), root-cause estimate

```
(tokens, D_lex) ← TOKENIZE(S)
(AST, D_syn) ← PARSE(tokens)
if D_syn = ∅ then
    D_sem ← ANALYSE(AST)        ▷ types, units, ranges, taint, optionals, flow
end if
D ← D_lex ∪ D_syn ∪ D_sem, sorted by position
v ← FEATURES(tokens, AST, D)
ŷ ← C(v)
if D contains no error then
    IR ← LOWER(AST); IR' ← OPTIMISE(IR)
end if
return (D, IR', ŷ)
```

K. GAN-Based Anomaly Scoring

For anomaly detection the GAN is trained on valid programs only, with a single class. A program is scored by the negated discriminator logit (BCE) or negated critic value (WGAN-GP): the less "real" the discriminator finds the program's feature vector, the more anomalous it is. This is a cheaper relative of AnoGAN [28], which would additionally search the generator's latent space for a reconstruction. It is compared with Isolation Forest [29] and a one-class SVM [30] trained on the same valid programs, and with the binary signal "the compiler reported at least one error", evaluated by AUROC [36].

L. Integrated Algorithm

IV. Experimental Setup

A. Dataset Preparation

No public corpus of faulty medical-data programs exists, and real clinical scripts could not be shared even if it did. The corpus was therefore generated, in two steps: a generator that writes *valid* MedScript programs, and a set of mutation operators that turn a valid program into a faulty one.

a) Valid programs.: The generator assembles a program from three to seven building blocks drawn at random from sixteen: weight-based dosing with a cap, body-mass index, temperature, heart-rate and blood-pressure alerts, shock index, a combined sepsis rule, infusion rate, an optional laboratory value (in three different guarding styles), PHI handling, a scoring loop, pound-to-kilogram conversion, a severity function, constant arithmetic, and two *hard negatives*. The hard negatives are constructs that look like faults but are correct: a division by a variable whose range includes zero but that is guarded by a positive test, and a threshold equal to the upper bound of the declared range. Variable names, thresholds, ranges, the choice of comments and the order of blocks are randomised. Every generated program is required to compile without errors; in a separate check, 1,500 generated programs compiled with no error and no warning at all.

b) Fault injection.: Forty-six operators, between three and seven per family (Appendix C), edit the text of a valid program. Examples: deleting a semicolon (syntax), swapping the unit of a literal from `degC` to `mmHg` (unit), printing a PHI input directly (phi), removing a `present` guard (missing), inverting a comparison in an alert rule (logic). After the edit the program is compiled, and it is kept only if the fault *manifests*, i.e., the compiler reports a diagnostic of the intended family. The exception is the two *soft* logic operators (inverting a rule, or giving it the alert text of the opposite kind), whose faults by construction produce no diagnostic; they are kept without that test. In about 20% of attempts a second fault of lower priority is injected *before* the primary one, so that the final program contains two defects but has a single, well-defined label.

c) Resulting corpus.: The corpus contains 10,000 unique programs, 1,000 in each of the ten classes, with a mean length of 38.7 lines (386,953 lines in total). Of the 9,000 faulty programs, 1,398 (15.5%) contain two faults. A fixed stratified split sets aside 200 programs per class as the *test set* (2,000 programs, never used for training, for fitting the GAN or for choosing hyper-parameters); the remaining 800 per class form the *training pool* from which every experiment samples. Table VII summarises the composition.

B. System Requirements

All experiments ran on a single laptop, without a GPU. The networks are small multilayer perceptrons and the feature vectors are 101-dimensional, so CPU training is sufficient.

C. Experimental Protocol

Five experiments were run; all random choices are seeded.

TABLE VII
Corpus composition.

Id	Class	Operators	Training pool	Test
0	valid	—	800	200
1	lexical	3	800	200
2	syntax	6	800	200
3	name	6	800	200
4	type	6	800	200
5	unit	6	800	200
6	range	4	800	200
7	phi	5	800	200
8	missing	3	800	200
9	logic	7	800	200
	Total	46	8,000	2,000

TABLE VIII
Hardware and software used for the experiments.

Component	Specification
Processor	Intel Core i5-13420H (8 cores, 12 threads)
RAM	16 GB
Operating system	Windows 11 Home
Programming language	Python 3.13
Machine learning	scikit-learn 1.9, PyTorch 2.14 (CPU), NumPy 2.5, SciPy 1.18
Plotting	Matplotlib 3.11
Typesetting	MiKTeX 25.12 (pdfLaTeX)
Parallelism	joblib, 10 worker processes

a) E1. Rule-based baselines versus learned classifiers.: The four classifiers are trained on all 8,000 training-pool programs and evaluated on the 2,000 test programs, next to the two rule baselines.

b) E2. Feature views and learning curves.: A random forest is trained on four feature subsets (token+AST, diagnostics, diagnostics+patterns, all features) with $n \in \{5, 10, 25, 50, 100, 200, 800\}$ programs per class, five random draws each.

c) E3. Augmentation under scarcity.: This is the experiment that tests the GAN. The *valid* class has 400 real training programs; each of the nine faulty classes has only $n \in \{5, 10, 20, 50, 100\}$ real programs. Seven training regimes are compared: (1) no augmentation; (2) class-balanced weights in the forest; (3) random oversampling; (4) Gaussian jitter oversampling (copies perturbed by noise of 10% of the feature standard deviation); (5) SMOTE [26] with $k = 5$; (6) conditional GAN with the BCE objective; (7) conditional GAN with WGAN-GP. In (3)–(7) each faulty class is brought up to 400 training vectors. Every configuration is repeated for ten seeds that change the sampled real programs, the network initialisation and all random draws, and each result is evaluated on the same 2,000-program test set with a random forest and an MLP. For one seed at $n = 20$ we additionally measure the fidelity of the synthetic vectors (Section V-D).

d) E4. GAN as anomaly detector.: GANs are trained on the 800 valid training programs only; Isolation Forest and a one-class SVM are trained on the same data. Each detector scores the 200 valid test programs and the 200 test programs

of each faulty class; we report AUROC.

e) E5. Compiler performance.: Synthetic valid programs of increasing size are compiled five times each and the median per-phase wall-clock time is recorded. Separately, 300 generated valid programs are compiled, optimised and checked for behavioural equivalence on ten random inputs each.

D. Evaluation Metrics

For class k let TP_k, FP_k, FN_k be the true positives, false positives and false negatives. Then

$$P_k = \frac{\mathrm{TP}_k}{\mathrm{TP}_k + \mathrm{FP}_k}, \qquad R_k = \frac{\mathrm{TP}_k}{\mathrm{TP}_k + \mathrm{FN}_k}, \tag{16}$$

$$F1_k = \frac{2P_k R_k}{P_k + R_k}, \qquad \text{macro-}F1 = \frac{1}{10}\sum_{k=0}^{9} F1_k, \tag{17}$$

and accuracy is the fraction of correctly classified programs [35]. Because the test set is balanced, accuracy and macro-F1 are close. The AUROC of a detector is the probability that a randomly chosen faulty program receives a higher anomaly score than a randomly chosen valid one [36]. Compilation time is

$$T_c = T_{\text{lex}} + T_{\text{parse}} + T_{\text{sem}} + T_{\text{IR}} + T_{\text{opt}}, \tag{18}$$

and the optimisation gain in code size is

$$G = \frac{N_{\text{original}} - N_{\text{optimised}}}{N_{\text{original}}} \times 100, \tag{19}$$

where N is the number of three-address instructions. Differences between methods in E3 are tested with a paired t-test over the ten seeds (the same seed implies the same real programs and the same test set).

V. Results and Discussion

A. Corpus Statistics

Building the corpus is cheap. Generating the 10,000 programs, including the compilation that checks each fault for manifestation, took 18 seconds, and extracting the feature vectors another 3 seconds on ten worker processes. The operator table in Appendix C shows that most operators are applicable to most programs; the lowest yields come from operators that need a particular construct to be present (for example `unit_return` needs the BMI function, `phi_removeanon` needs an existing `anonymize` call). Among the faulty programs, 15.5% contain two faults.

B. Rule-Based Diagnostics versus Learned Classification (E1)

Table IX compares the two rule baselines with the four learned classifiers on the 2,000 test programs. The learned models reach between 99.15% (random forest) and 99.40% (gradient boosting) accuracy, against 91.6% for the "first error" rule and 93.2% for the "most severe family" rule. The four learned models are within 0.3 percentage points of each other, which on 2,000 test programs is a difference of six programs; we do not read any ranking into it. We use the random forest in the remainder of the paper because it is the model deployed in the command-line tool and because its feature importances are easy to inspect.

TABLE IX
Test-set performance of the rule baselines and the learned classifiers (2,000 test programs; trained on 8,000 programs).

Classifier	Accuracy	Macro-F1	Acc. single-fault	Acc. two-fault
Rule: first error	0.9160	0.9157	0.9623	0.6568
Rule: most severe family	0.9320	0.9299	0.9275	0.9571
Random forest	0.9915	0.9915	0.9965	0.9637
MLP	0.9935	0.9935	0.9976	0.9703
LogReg	0.9920	0.9920	0.9971	0.9637
HistGB	0.9940	0.9940	0.9959	0.9835

TABLE X
Per-class F1 of the rule baselines and precision, recall and F1 of the random forest.

	Rule F1		Random forest		
Family	first	severe	P	R	F1
valid	0.864	0.864	0.971	1.000	0.985
lexical	0.959	0.777	0.975	0.970	0.972
syntax	0.987	0.846	1.000	0.975	0.987
name	0.913	1.000	1.000	1.000	1.000
type	0.912	1.000	0.995	1.000	0.998
unit	0.922	1.000	0.985	1.000	0.993
range	0.967	1.000	1.000	1.000	1.000
phi	0.931	1.000	0.990	1.000	0.995
missing	0.946	1.000	1.000	1.000	1.000
logic	0.755	0.813	1.000	0.970	0.985

The error breakdown in Fig. 2 and Table X shows *where* the rules fall short.

1) **Faults the compiler cannot see.** 63 of the 200 test programs in the *logic* class (31.5%) are reported as clean by both rules, so their *logic* recall is only 68.5%. These are the inverted clinical rules and the mismatched alert texts: the programs are well formed, well typed and unit-correct. The random forest recovers them (97.0% recall for *logic*) using the pattern features, which count relational operators that point the wrong way relative to the alert vocabulary nearby. Six *logic* programs are still taken for *valid*.
2) **Cascades hide the root cause of lexical faults.** The "most severe family" rule is perfect on all six semantic families, which is unsurprising because it implements the labelling rule. It fails on *lexical* programs: an unterminated string swallows the rest of its line, the parser then reports follow-on syntax errors, and the priority rule, which ranks syntax above lexical, picks the symptom (73 of 200 programs). The "first error" rule gets these right more often because the lexical error is reported first, but it pays for that elsewhere.
3) **The first diagnostic is not always the root cause.** With two faults in the program, the "first error" rule is correct on only 65.7% of them, against 96.2% on single-fault programs; the random forest is correct on 96.4% of the two-fault programs.
4) **What remains.** The forest makes 17 errors on 2,000 programs: six *logic* programs taken for *valid* (the soft




Fig. 2. Row-normalised confusion matrices on the test set. Left: the "first error" rule. Right: random forest.

faults above), five *syntax* programs taken for *lexical*, and six *lexical* programs assigned to a semantic family (one *type*, three *unit*, two *phi*). The lexical–syntax confusion is the same cascade ambiguity as before and is not fully resolved.

None of this says that machine learning is better than a well-designed rule set *for the faults the rules were written for*: on those, a precise analyser is already at 100%. The gain is concentrated in the cases that a rule-based analyser misses or mislabels. It is also worth being clear about what the 99% figure means. The test programs come from the same generator as the training programs, so the learned model is evaluated on an in-distribution sample; Section V-H discusses what that does and does not show.

a) What the forest relies on.: Table XI lists the most important features. The most important one by a wide margin is `worst_family_rank`, the compiler-derived rank of the most severe diagnostic family; the next ones are counts of individual diagnostic codes. In other words, the learned classifier is largely a learned post-processor of the compiler's output—which is what the architecture intends.

C. Which Feature Groups Matter, and How Much Data Is Needed (E2)

Fig. 3 and Table XII show test macro-F1 of a random forest trained on four feature views with an increasing number of training programs per class (mean over five random draws).

Three observations follow.

- **Surface features are not enough.** Token and tree statistics alone give a macro-F1 of only 0.14 with five programs per class and 0.44 with 800. A forest cannot recover from raw counts what a unit checker or a taint analysis computes. This is the strongest argument in the data for putting a real compiler front end underneath the learner.
- **Diagnostics carry most of the signal; patterns add the rest.** The diagnostic features alone plateau at 0.967: they cannot see the soft logic faults. Adding the six pattern features lifts the curve to 0.994 at 800 programs per class.
- **More features are not better at small sample sizes.** The "all features" view is slightly *worse* than diagnostics+patterns at every size (0.884 versus 0.918 at five programs per class, 0.991 versus 0.994 at 800). The token and tree features add 55 noisy dimensions that carry little information. We nevertheless kept the full 101-dimensional vector for the experiments with the GAN, because it is the representation the deployed classifier

TABLE XI
TOP-EIGHT RANDOM-FOREST FEATURE IMPORTANCES (MEAN DECREASE IN IMPURITY).

Feature	Importance
`worst_family_rank`	0.142
`diag_DOM002`	0.053
`diag_DOM001`	0.051
`first_phase_sem`	0.048
`diag_SEM005`	0.044
`first_fam_type`	0.043
`diag_DOM003`	0.043
`first_fam_name`	0.039

TABLE XII
TEST MACRO-F1 BY FEATURE VIEW AND NUMBER OF TRAINING PROGRAMS PER CLASS.

Feature view	5	10	25	50	100	200	800
token+AST	0.142	0.187	0.258	0.326	0.373	0.398	0.436
diagnostics	0.918	0.937	0.942	0.950	0.960	0.963	0.967
diagnostics+patterns	0.918	0.946	0.970	0.979	0.988	0.991	0.994
all features	0.884	0.926	0.950	0.969	0.983	0.988	0.991




Fig. 3. Learning curves of the random forest for four feature views (mean ± standard deviation over five draws).

uses; a leaner view would be a reasonable simplification.

The scarce-data end of the curve is where it matters for the next experiment: with five labelled programs per class a forest reaches a macro-F1 of 0.88, and the question is whether synthetic records can close part of the gap to 0.99.

D. Augmentation under Scarcity: Does the GAN Help? (E3)

This experiment asks the question that motivated the use of a GAN: if only a handful of real faulty programs are available per class, do synthetic feature vectors improve the classifier? Fig. 4 and Tables XIII–XIV give the test macro-F1 of the seven regimes, averaged over ten seeds. The *valid* class always has 400 real training programs.

a) The short answer is no.: With the random forest, the conditional GAN is never the best method and is usually within noise of using no augmentation at all: at 20 real programs per class the BCE version scores 0.944 against 0.942 without augmentation, and at 5 programs it is *worse* (0.876 and 0.853 for the BCE and WGAN-GP versions, against 0.888). The cheap alternatives help more. Gaussian jitter is the best method at every size up to 20 programs per class (0.928 against 0.888 at five programs), and SMOTE, random oversampling and class weights also give small gains. By 100 programs per class all methods are within one point of each other. For the MLP the picture is worse for the GAN: its synthetic vectors cost between 5 and 13 points of macro-F1 relative to no augmentation, with the largest damage at the smallest sizes (0.713 against 0.844 at five programs per class), presumably because the MLP, unlike a forest, tries to fit every synthetic point.

Table XV gives paired comparisons over the ten seeds. The difference between the GAN and *no augmentation* is small and, depending on the size, indistinguishable from zero or slightly negative; the difference from jitter and SMOTE is negative at every size. The p-values are uncorrected for the 30 comparisons shown, so they should be read as a rough guide.

b) Where the benefit of augmentation lies.: Fig. 5 breaks the result down by class for 20 real programs per class. Most classes are already close to their ceiling without help. The exception is *logic*, the family whose members are partly invisible to the compiler and have to be recognised from the six pattern features: with five real programs its F1 is 0.52 without augmentation, 0.79 with jitter, 0.70 with SMOTE and 0.47 with the BCE GAN; at 20 programs the values are 0.82, 0.93, 0.86 and 0.85. Augmentation in this setting is mostly a regulariser for the one hard class. The valid class gains as a side effect, because fewer logic programs are mistaken for it.

c) Why the GAN fails: fidelity of the synthetic vectors.: For one seed at 20 programs per class we checked the synthetic vectors directly (Table XVI). *Label validity* is the fraction of synthetic vectors that an oracle random forest, trained on the full 8,000-program pool, assigns to the class the generator was asked for. *NN distance* is the mean standardised distance to the nearest real training vector of that class; for reference, held-out *real* programs of the same classes lie at a mean distance of 7.4 from their nearest training example.

The result is stark. Only 4% of the GAN's vectors are recognised as belonging to the requested class, which is below the 10% expected from a classifier guessing among ten classes; the GAN vectors are also *further* from the training data than genuinely new real programs are. In other words, the generator has not learned the class-conditional structure. Fig. 6 shows the same thing in two dimensions: the synthetic points (crosses) spread over the whole cloud of all classes instead of concentrating where the real examples of the requested class lie, although a two-dimensional projection of mostly discrete count features is only a rough picture.

We examined one likely cause. In the experiment above, mini-batches were drawn uniformly from the training set, which is dominated by the 400 *valid* programs, so each rare class contributed only a few percent of the batches and the generator may have learned to ignore its class input. We repeated the experiment (five seeds, 20 real programs per class) with class-balanced mini-batches, in which a class




Fig. 4. Test macro-F1 against the number of real training programs per faulty class (mean ± standard deviation over ten seeds). Left: random forest. Right: MLP.

TABLE XIII
RANDOM FOREST: TEST MACRO-F1 (MEAN ± S.D., TEN SEEDS) AGAINST THE NUMBER OF REAL PROGRAMS PER FAULTY CLASS. BOLD MARKS THE BEST MEAN IN EACH COLUMN.

Method	**5**	**10**	**20**	**50**	**100**
No augmentation	0.888 ± 0.020	0.917 ± 0.009	0.942 ± 0.009	0.971 ± 0.003	0.979 ± 0.003
Class weights	0.910 ± 0.018	0.927 ± 0.008	0.949 ± 0.008	0.974 ± 0.004	0.982 ± 0.003
Random oversampling	0.906 ± 0.020	0.925 ± 0.010	0.951 ± 0.009	$\mathbf{0.978 \pm 0.004}$	$\mathbf{0.984 \pm 0.003}$
Gaussian jitter	$\mathbf{0.928 \pm 0.019}$	$\mathbf{0.951 \pm 0.011}$	$\mathbf{0.964 \pm 0.010}$	0.978 ± 0.002	0.982 ± 0.003
SMOTE	0.916 ± 0.020	0.935 ± 0.008	0.951 ± 0.009	0.975 ± 0.005	0.982 ± 0.003
cGAN (BCE)	0.876 ± 0.023	0.915 ± 0.011	0.944 ± 0.011	0.968 ± 0.003	0.978 ± 0.003
cGAN (WGAN-GP)	0.853 ± 0.022	0.908 ± 0.008	0.942 ± 0.009	0.967 ± 0.001	0.977 ± 0.004

TABLE XIV
MLP: SAME PROTOCOL AS TABLE XIII.

Method	**5**	**10**	**20**	**50**	**100**
No augmentation	$\mathbf{0.844 \pm 0.016}$	0.902 ± 0.013	0.929 ± 0.009	0.956 ± 0.005	0.969 ± 0.004
Class weights	$\mathbf{0.844 \pm 0.016}$	0.902 ± 0.013	0.929 ± 0.009	0.956 ± 0.005	0.969 ± 0.004
Random oversampling	0.842 ± 0.032	0.920 ± 0.008	0.936 ± 0.008	0.958 ± 0.005	$\mathbf{0.970 \pm 0.005}$
Gaussian jitter	0.840 ± 0.033	$\mathbf{0.921 \pm 0.007}$	$\mathbf{0.936 \pm 0.008}$	$\mathbf{0.959 \pm 0.004}$	0.970 ± 0.005
SMOTE	0.796 ± 0.038	0.907 ± 0.010	0.929 ± 0.008	0.953 ± 0.005	0.968 ± 0.005
cGAN (BCE)	0.713 ± 0.055	0.785 ± 0.026	0.824 ± 0.038	0.872 ± 0.016	0.923 ± 0.013
cGAN (WGAN-GP)	0.712 ± 0.073	0.768 ± 0.051	0.791 ± 0.041	0.868 ± 0.025	0.905 ± 0.018

is chosen first and an example second. Table XVII shows the outcome: label validity rises from roughly 4% to 11–13%, which is about chance level, and macro-F1 does not improve. The imbalance in the batches therefore explains part of the failure but not the rest. The remaining explanation is the one the numbers suggest: with 20 examples per class in a 101-dimensional space of counts, a small unregularised GAN has too little to learn from, and a continuous generator blurs features that carry discrete, tightly coupled meaning (for example, a diagnostic count of one for exactly one code). This follows the pattern commonly reported for GANs trained on very small tabular data, and it is a limit of our setup rather than a general statement about GANs. We did not test architectures designed for tabular data, such as CTGAN [24], or any hyper-parameter search.

d) What the GAN is and is not good for here.: One property is worth noting: none of the synthetic vectors is an exact copy of a real one (0% exact copies in Table XVI), whereas random oversampling copies by definition. If privacy were the goal, that would matter; but a synthetic set that does not carry the class signal is no use as training data either. Our evidence supports a narrow conclusion: *in this setting, with*

TABLE XV
PAIRED DIFFERENCE IN MACRO-F1 (RANDOM FOREST) BETWEEN EACH GAN AND THREE ALTERNATIVES, WITH THE TWO-SIDED PAIRED t-TEST p-VALUE IN PARENTHESES. NEGATIVE VALUES MEAN THE GAN IS WORSE.

Real/class	GAN	vs. none	vs. SMOTE	vs. jitter
5	cGAN (BCE)	-0.013 (0.034)	-0.040 (0.001)	-0.052 (0.001)
5	cGAN (WGAN-GP)	-0.036 (0.007)	-0.063 (0.000)	-0.075 (0.000)
10	cGAN (BCE)	-0.002 (0.163)	-0.019 (0.004)	-0.036 (0.000)
10	cGAN (WGAN-GP)	-0.010 (0.016)	-0.027 (0.000)	-0.043 (0.000)
20	cGAN (BCE)	+0.002 (0.378)	-0.008 (0.013)	-0.021 (0.000)
20	cGAN (WGAN-GP)	+0.000 (0.920)	-0.009 (0.000)	-0.022 (0.000)
50	cGAN (BCE)	-0.003 (0.010)	-0.008 (0.000)	-0.010 (0.000)
50	cGAN (WGAN-GP)	-0.005 (0.001)	-0.009 (0.000)	-0.012 (0.000)
100	cGAN (BCE)	-0.001 (0.015)	-0.004 (0.000)	-0.004 (0.000)
100	cGAN (WGAN-GP)	-0.003 (0.002)	-0.005 (0.000)	-0.006 (0.000)




Fig. 5. Per-class F1 of the random forest with 20 real programs per faulty class (mean of ten seeds).

TABLE XVI
FIDELITY OF SYNTHETIC VECTORS (SEED 0, 20 REAL PROGRAMS PER FAULTY CLASS). LABEL VALIDITY FOR THE THREE RESAMPLING METHODS IS HIGH BY CONSTRUCTION: THEIR POINTS LIE ON OR NEXT TO REAL TRAINING VECTORS THAT THE ORACLE HAS ITSELF SEEN.

Generator	Label validity	NN distance	Exact copies (%)
Random oversampling	1.000	0.00	100.0
Gaussian jitter	1.000	0.84	0.0
SMOTE	1.000	3.01	0.0
cGAN (BCE)	0.037	11.30	0.0
cGAN (WGAN-GP)	0.043	10.80	0.0

TABLE XVII
EFFECT OF CLASS-BALANCED MINI-BATCHES ON THE GAN (20 REAL PROGRAMS PER FAULTY CLASS; MEAN $\pm$ S.D. OVER FIVE SEEDS). LABEL VALIDITY OF ABOUT 0.10 IS CHANCE LEVEL.

Model	Mini-batches	Label validity	Macro-F1
cGAN (BCE)	uniform	0.039 ± 0.023	0.944 ± 0.011
cGAN (WGAN-GP)	uniform	0.045 ± 0.005	0.944 ± 0.008
cGAN (BCE)	class-balanced	0.110 ± 0.011	0.943 ± 0.009
cGAN (WGAN-GP)	class-balanced	0.126 ± 0.009	0.935 ± 0.010

these model sizes and this amount of data, simple resampling is the better way to handle rare error classes.

E. GAN-Based Anomaly Detection (E4)

The second use of a GAN is to detect faulty programs when no faulty examples are available at all. A GAN is trained on the 800 valid training programs; the negated discriminator output is the anomaly score. Table XVIII and Fig. 7 give the AUROC of each detector separating the 200 valid test programs from the 200 programs of each faulty family.

The numbers need careful reading, because the headline is easy to over-interpret.

- **The BCE discriminator is an excellent detector, but most of that is easy.** It reaches an AUROC of 0.998 over all faults. However, 49 of the 101 features, including *all*




Fig. 6. PCA projection of real (circles) and GAN-generated (crosses) vectors for four classes, with all other real vectors in grey (a GAN trained on 100 real programs per class).




Fig. 7. AUROC of five detectors for valid versus faulty programs, by fault family (dashed line: chance).

40 diagnostic features, are constant on valid programs: a valid program reports no diagnostic. Any model that looks at those features can therefore tell a program with an error from one without. The compiler's own "at least one error" flag achieves 1.000 on every family except *logic*, and it is a far simpler detector.

- **The informative column is *logic*.** There the compiler flag falls to 0.843 (the soft faults raise no diagnostic), the one-class SVM reaches 0.715, and the BCE discriminator 0.981. To check that this is not a lucky seed, we retrained the discriminator with five seeds (Table XIX): the logic AUROC is 0.97–0.99 each time. It depends, however, on the pattern features: without them it drops to 0.83–0.87, and the pattern features alone give only 0.60–0.69. So the discriminator's advantage comes from combining the compiler-derived signals with the pattern signal that valid programs never exhibit, and the pattern features were written with this fault in mind.
- **Isolation Forest is at chance (0.47).** We first suspected that it ignores the diagnostic features because they have zero range on the training data, so a random split cannot use them. Removing the constant features altogether changes nothing (0.473 to 0.475), which is consistent with that explanation: among the features that do vary, faulty programs look like valid ones.
- **The WGAN-GP critic fails.** Its AUROC is 0.37, *below* chance: faulty programs receive a higher critic value than valid ones. A critic is trained to separate real from generated samples, not to model density, and outside the data it extrapolates. Negating the score would give about 0.63, but we report the score as defined in advance, not a sign chosen after seeing the result.

The practical reading is modest. A GAN discriminator trained only on valid programs is a usable *unsupervised*

TABLE XVIII
AUROC OF VALID-VERSUS-FAULTY DETECTION BY FAULT FAMILY. ALL DETECTORS EXCEPT THE COMPILER FLAG WERE TRAINED ON VALID PROGRAMS ONLY.

Fault family	Isolation Forest	One-class SVM	GAN discriminator (BCE)	GAN critic (WGAN-GP)	Compiler error flag
lexical	0.471	0.905	1.000	0.388	1.000
syntax	0.465	0.901	1.000	0.310	1.000
name	0.475	0.806	1.000	0.381	1.000
type	0.498	0.839	1.000	0.392	1.000
unit	0.454	0.834	1.000	0.360	1.000
range	0.451	0.867	1.000	0.433	1.000
phi	0.498	0.865	1.000	0.265	1.000
missing	0.495	0.885	1.000	0.325	1.000
logic	0.452	0.715	0.981	0.487	0.843
all faults	0.473	0.846	0.998	0.371	0.982

TABLE XIX
STABILITY AND ABLATION OF THE BCE DISCRIMINATOR AS ANOMALY DETECTOR (FIVE SEEDS, MEAN ± S.D.).

Discriminator input	AUROC, logic	AUROC, all faults
All 101 features	0.978 ± 0.008	0.996 ± 0.003
Without pattern features	0.844 ± 0.015	0.982 ± 0.001
Pattern features only	0.620 ± 0.034	0.521 ± 0.025

detector of the one family that the compiler misses, but it is not better than the compiler on the families the compiler handles, and its result is only as good as the features it sees.

F. Compiler Performance and Optimisation (E5)

a) Scaling.: Table XX and Fig. 8 show the median compilation time for valid programs of 46 to 12,016 lines (up to 88,000 tokens). A linear fit of total time against program size gives 162 ms per thousand lines ($R^2 = 0.981$), so a 40-line program—the size of the corpus programs—compiles in a few milliseconds. The log–log slope over the larger sizes is 1.17, i.e., growth is slightly worse than linear, and the table shows where: the semantic phase, which takes roughly a quarter of the time for programs up to about 800 lines, accounts for more than half of the total (53%) at 12,000 lines. The reason is a known inefficiency of our implementation: every `if` copies the flow state (the sets of assigned variables and facts), which grows with the number of top-level declarations, so a long flat program pays a cost proportional to its size at every branch. Sharing the sets structurally between branches would remove this; at the sizes of real clinical scripts it does not matter.

b) Optimisation.: Over 300 generated valid programs the optimiser removed on average 8.9% of the three-address instructions (maximum 17.8%). On every one of them, running the original and the optimised code on ten random inputs produced identical output events (0 mismatches in 300 programs). The generated programs are written the way a person would write them and contain little redundancy, so the gain is modest. Programs with constant arithmetic show more. For the program in Listing 2, the optimiser folds the two constants, shares the repeated product `per_kg * weight`, and deletes the dead branch, reducing 18 instructions to 11 (39%).




Fig. 8. Median compilation time per phase against program size (log–log).

Listing 2. Three-address code of `examples/fold_demo.med` before (left column of rows) and after optimisation.

```
before | after
t1 = 2 * 400.0 | LIMIT = 800.0
LIMIT = t1 | margin@1 = 750.0
t2 = LIMIT - 50.0 | t3 = 12.0 * weight
margin@1 = t2 | a@3 = t3
per_kg@2 = 12.0 | b@4 = t3 (CSE)
t3 = per_kg@2 * weight | goto L1 (dead branch)
a@3 = t3 | L1:
t4 = per_kg@2 * weight | t7 = a@3 + b@4
b@4 = t4 | t8 = t7 + margin@1
t5 = 1 > 2 | param t8
ifFalse t5 goto L1 | t9 = call print, 1
param 'never printed' |
t6 = call print, 1 |
L1: |
t7 = a@3 + b@4 |
t8 = t7 + margin@1 |
param t8 |
t9 = call print, 1 |
```

The listing also shows two limits of the optimiser. A jump to the immediately following label is left behind (no peephole pass), and propagation stops at labels, so `margin@1` is not substituted into `t8`. Both are straightforward extensions and neither affects correctness.

G. Worked Examples

The command-line tool prints the compiler's diagnostics and, below them, the classifier's estimate of the root-cause family. Listing 3 shows a program with four independent

TABLE XX
MEDIAN TIME PER PHASE IN MILLISECONDS, AND IR SIZE BEFORE AND AFTER OPTIMISATION.

Lines	Tokens	Lex	Parse	Sem	IR	Opt	Total	IR ins.	Opt. ins.
46	323	1.1	0.8	0.9	0.3	0.8	3.9	84	73
165	1,201	3.5	3.2	4.3	0.9	3.4	15.3	389	338
316	2,303	8.1	5.7	5.6	1.6	5.7	26.7	774	673
766	5,603	16.2	14.2	17.2	3.8	15.4	66.9	1,924	1,673
1,515	11,101	41.8	39.7	55.3	10.1	33.0	179.8	3,839	3,338
3,016	22,103	73.4	65.9	107.8	16.6	58.5	322.1	7,674	6,673
6,015	44,101	134.6	142.4	296.6	39.0	122.5	735.0	15,339	13,338
12,016	88,103	276.4	346.4	1060.4	68.1	246.0	1997.4	30,674	26,673

faults: PHI concatenated into output, a temperature threshold with the decimal point dropped (reported twice, once by the range-of-input check and once by the plausibility check), and a dose added to a weight. The classifier ranks *phi* first, in agreement with the root-cause priority.

Listing 3. Output of `medcheck.py examples/phi_leak.med`.

```
== examples/phi_leak.med: 100 tokens, 4 error(s), 0 warning(s)
  12:19: error DOM002: protected health information reaches
  print() without anonymize()
     | print("patient: " + patient_name);
  13:10: error DOM001: comparison against 380, outside the
  declared range [30, 43] of 'temp'
     | if (temp > 380 degC) {
  13:12: error DOM001: value 380 degC is outside the plausible
  range [20.0, 45.0] degC
     | if (temp > 380 degC) {
  16:12: error SEM005: unit mismatch: [mg] + [kg]
     | print(dose + weight);
== learned root-cause estimate: phi 0.80, range 0.11, lexical
0.06
```

Listing 4 shows recovery from two syntax faults. The missing semicolon is reported at the end of the line where it belongs, not at the `if` that exposed it, and parsing continues, so the missing parenthesis on the next line is also found. Because syntax errors were reported, the semantic phase did not run.

Listing 4. Output of `medcheck.py examples/syntax_errors.med`.

```
== examples/syntax_errors.med: 44 tokens, 2 error(s), 0 warning
(s)
  5:25: error SYN001: expected ';' but found 'if'
     | let fever = temp > 38.0 degC
  6:23: error SYN001: expected ')' but found '{'
     | if (fever && hr > 100 bpm {
== learned root-cause estimate: syntax 0.99, lexical 0.01,
valid 0.00
```

The most interesting case is the one in which the compiler has nothing to say. In the file `examples/inverted_rule.med` the fever rule reads `if (temp < 38.0 degC)` and prints an alert called *fever*. It compiles without a single diagnostic. The tool then adds the line produced by the classifier, shown in Listing 5: the forest assigns the program to *logic* with probability 0.77 and flags that the rule-based front end found nothing. This is a probability estimate from a model trained on synthetic faults, not a proof, and the tool says so by wording it as a suspicion.

Listing 5. Output of `medcheck.py examples/inverted_rule.med`.

```
== examples/inverted_rule.med: 50 tokens, 0 error(s), 0 warning
(s)
== learned root-cause estimate: logic 0.77, valid 0.20, name
0.02
  note: the rule-based front end found no error, but the
  classifier suspects a 'logic'
       fault (possible clinical-logic error)
```

H. Threats to Validity and Limitations

We want to be explicit about what these results do and do not establish.

- **Synthetic corpus, in-distribution test.** Training and test programs come from the same generator, built from the same sixteen blocks and mutated by the same operators. The near-perfect accuracy therefore measures how well the classifier has learned *this* generator's faults. It says little about hand-written MedScript programs, and nothing at all about real clinical code in other languages. A study on real faulty scripts would be the real test.
- **The labels are defined by the injection.** A program's label is whatever fault we injected (with a documented priority for two faults). We checked that each fault manifests in the compiler, but not that a human reviewer would call it the root cause.
- **The strong rule baseline shares the labelling rule.** The "most severe family" rule is, by construction, the labelling rule applied to diagnostics. Its 100% accuracy on the semantic families is therefore partly circular; its failures (cascading lexical faults, invisible logic faults) are the informative part.
- **The soft-fault detector uses a hand-written vocabulary.** The pattern features rely on a list of alert words. A program that names its alerts differently would defeat them. The classifier learns a statistical regularity of the generated programs, not clinical knowledge.
- **Scope of the experiment grid.** The range of scarcity levels in the GAN experiment was widened after a preliminary run on a separate, smaller corpus (different random seed), in which the GAN showed no advantage at five to twenty examples per class. Hyper-parameters of all methods were fixed beforehand and not tuned on the test set; they were also not tuned at all, so a better-tuned GAN could do better than reported.
- **Language and tooling.** MedScript is a small DSL, implemented in Python for clarity rather than speed.

I. Summary of Findings

1) A purpose-built front end with clinical semantics detects, with 100% recall, the faults it was designed for, and the learned classifier adds value mainly where the rules are

blind (soft logic faults) or ambiguous (cascades, multiple faults): 91.6% and 93.2% for the two rule baselines against 99.15% for the forest.
2) The information that matters is computed by the compiler. Token and tree statistics alone reach a macro-F1 of 0.44 with 800 programs per class.
3) Conditional GANs trained on the feature vectors did *not* improve classification with scarce data. Gaussian jitter and SMOTE were better, and the GAN's synthetic vectors were mostly not recognisable as the class they were meant to represent.
4) A GAN discriminator trained on valid programs detects soft logic faults well (AUROC about 0.98), but its performance on other families is trivially explained by the diagnostic features, and the WGAN-GP critic was unusable for this purpose.
5) The compiler is fast enough for interactive use (162 ms per thousand lines) and its optimiser preserved behaviour on all tested programs.

VI. Conclusion and Future Work

A. Conclusion

We set out to build an intelligent compiler for medical data-processing programs: a front end that understands the constraints of the domain, plus a learned component that classifies errors and uses a GAN to cope with scarce labelled data. The first two parts worked as intended; the third did not.

The compiler for MedScript implements the usual phases—scanner, recursive-descent parser with insertion and panic-mode recovery, semantic analyser, three-address code, optimiser—and extends the semantic phase with checks that matter in healthcare: unit-of-measure checking by dimension vectors, physiological plausibility by interval reasoning, taint tracking of protected health information, flow-sensitive handling of optional values, definite assignment, and division-by-zero detection. All of the 38 unit tests pass, and on 300 generated programs the optimiser preserved observable behaviour on random inputs in every case. Compilation time grows roughly linearly with program size at about 162 ms per thousand lines.

For classification, a random forest over 101 compiler-derived features reached 99.15% accuracy on 2,000 held-out programs, against 91.6% and 93.2% for two rule-based baselines. The gain comes from two situations that rules handle poorly: faults that produce no diagnostic (inverted clinical rules), and programs in which cascades or several faults make the first diagnostic misleading. The learning curves show that surface features of the source text are nearly useless on their own (macro-F1 0.44), so the value of the learner depends on the compiler beneath it.

The GAN result is negative, and we think it is more useful reported than hidden. With 5 to 100 real programs per faulty class, conditional GANs (BCE and WGAN-GP) gave no improvement over no augmentation for a random forest and a clear loss for an MLP, while Gaussian jitter and SMOTE gave gains of up to four points of macro-F1. A direct check of the synthetic vectors explains why: they were recognised as the requested class only about 4% of the time, and class-balanced training batches raised that only to chance level. A GAN discriminator trained on valid programs did turn out to be a good unsupervised detector of the faults the compiler misses (AUROC about 0.98), but that is a narrower use than the one the project began with.

Limitations. The corpus is generated, and the test programs come from the same generator as the training programs, so the accuracy figures describe the generator's faults rather than the faults of real clinical code. The pattern features rely on a hand-written vocabulary. MedScript is a small DSL, not a language that clinical programmers use today. The optimiser is deliberately simple. These limits are discussed in Section V-H.

B. Future Work

- **Real data.** Evaluate on hand-written MedScript programs written by people who did not see the generator, and, more ambitiously, port the checks (units, PHI taint, optional values) to a mainstream clinical-scripting language such as Python or R through an AST-based analyser.
- **Better generative models.** Try tabular generators such as CTGAN with proper handling of discrete features, pretrain on the abundant valid class, and generate *programs* rather than feature vectors, for instance by training a model over the mutation operators, so that synthetic examples can also be compiled and checked.
- **Learned localisation.** Predict not only the error family but the line at which a soft fault such as an inverted comparison occurs, for example with a graph neural network over the syntax tree.
- **Richer semantics.** Add implicit unit conversion with checked conversion factors, interval analysis through loops, inter-procedural taint with function summaries, and a three-valued treatment of missing values.
- **A stronger back end.** Global value numbering, propagation across basic blocks, and code generation to a real target such as LLVM IR, so that the pipeline is complete from source to machine code.
- **Human evaluation.** Study whether the root-cause estimate shortens the time a developer needs to find a fault compared with raw diagnostics.

Appendix A
MedScript Grammar

The grammar below is the one implemented by the recursive-descent parser. Terminals are in quotes; `ID`, `NUM`, `STR` and `UNIT` are token classes.

```
program = { decl } ;
decl = inputDecl | constDecl | funcDecl | stmt ;
inputDecl = "input" ID ":" type [ "phi" ]
          [ "range" "(" signedNum "," signedNum ")" ] ";" ;
constDecl = "const" ID ":" type "=" expr ";" ;
funcDecl = "func" ID "(" [ param { "," param } ] ")" "->" type
block ;
param = ID ":" type ;
type = ( "int" | "float" | "bool" | "string" | unitType ) [ "?"
 ] ;
unitType = unitTerm { ( "*" | "/" ) unitTerm } ;
unitTerm = UNIT [ "^" NUM ] ;
```

```
stmt = letStmt | ifStmt | whileStmt | returnStmt | assignStmt
        | exprStmt | block ;
letStmt = "let" ID [ ":" type ] [ "=" expr ] ";" ;
assignStmt = ID "=" expr ";" ;
ifStmt = "if" "(" expr ")" block [ "else" ( ifStmt | block ) ]
;
whileStmt = "while" "(" expr ")" block ;
returnStmt = "return" [ expr ] ";" ;
exprStmt = expr ";" ;
block = "{" { stmt } "}" ;

expr = orExpr ;
orExpr = andExpr { "||" andExpr } ;
andExpr = eqExpr { "&&" eqExpr } ;
eqExpr = relExpr { ( "==" | "!=" ) relExpr } ;
relExpr = addExpr { ( "<" | ">" | "<=" | ">=" ) addExpr } ;
addExpr = mulExpr { ( "+" | "-" ) mulExpr } ;
mulExpr = unary { ( "*" | "/" | "%" ) unary } ;
unary = ( "-" | "!" ) unary | primary ;
primary = NUM [ unitType ] | STR | "true" | "false"
        | ID [ "(" [ expr { "," expr } ] ")" ] | "(" expr ")" ;
```

A unit suffix after a number extends over `/` only when the next token is a unit, so `15 mg/kg` is a single literal while `15 mg / weight` is a division.

Appendix B
Diagnostic Catalogue

Table XXI lists the 23 diagnostic codes with their phase, severity and error family.

Appendix C
Fault-Injection Operators

Table XXII lists the operators together with the number of times each was attempted while building the corpus and how often the resulting fault was kept. *Tried* counts every attempt, including those where the operator was not applicable to the sampled program (for example, removing an `anonymize` call from a program that has none); *Kept* counts attempts that produced a program in which the fault manifested. The percentage is therefore a mixture of applicability and manifestation, and it is not a measure of compiler accuracy.

Appendix D
Running the Code

The repository accompanying this paper has the following layout.

```
code/
  medscript/ lexer, parser, ast_nodes, semantic, ir, driver,
  equiv
             generator, mutations, corpus, features
  ml/ gan.py (conditional GAN), augment.py (SMOTE, jitter, ...)
  tests/ test_compiler.py (38 unit tests)
  examples/ triage_ok, phi_leak, inverted_rule, syntax_errors,
            missing_value, fold_demo (.med)
  medcheck.py compiler + learned root-cause estimate
  run_experiments.py make_figures.py
  results/ JSON results of every experiment
  models/ trained random-forest classifier
```

```
python -m unittest discover -s tests # unit tests
python medcheck.py examples/phi_leak.med # compile + classify a
 program
python run_experiments.py # all experiments (~45 min, 10 cores)
python make_figures.py # figures and LaTeX tables
```


Acknowledgment

The authors thank Dr. Prakash Kumar Sarangi, School of Computer Science and Engineering (SCOPE), VIT-AP University, for guidance throughout the Compiler Design Lab.

References

[1] A. V. Aho, M. S. Lam, R. Sethi, and J. D. Ullman, *Compilers: Principles, Techniques, and Tools*, 2nd ed., Pearson/Addison-Wesley, 2006.

[2] K. D. Cooper and L. Torczon, *Engineering a Compiler*, 2nd ed., Morgan Kaufmann, 2011.

[3] A. W. Appel, *Modern Compiler Implementation in ML*, Cambridge University Press, 1998.

[4] D. Grune and C. J. H. Jacobs, *Parsing Techniques: A Practical Guide*, 2nd ed., Springer, 2008.

[5] M. G. Burke and G. A. Fisher, "A practical method for LR and LL syntactic error diagnosis and recovery," *ACM Transactions on Programming Languages and Systems*, vol. 9, no. 2, pp. 164–197, 1987.

[6] B. C. Pierce, *Types and Programming Languages*, MIT Press, 2002.

[7] F. Nielson, H. R. Nielson, and C. Hankin, *Principles of Program Analysis*, Springer, 1999.

[8] A. Kennedy, "Dimension types," in *Proc. European Symposium on Programming (ESOP)*, LNCS vol. 788, Springer, 1994, pp. 348–362.

[9] W. Enck et al., "TaintDroid: An information-flow tracking system for realtime privacy monitoring on smartphones," in *Proc. 9th USENIX Symposium on Operating Systems Design and Implementation (OSDI)*, 2010, pp. 393–407.

[10] U.S. Department of Health and Human Services, "Standards for privacy of individually identifiable health information," 45 CFR Parts 160 and 164 (HIPAA Privacy Rule).

[11] N. G. Leveson and C. S. Turner, "An investigation of the Therac-25 accidents," *IEEE Computer*, vol. 26, no. 7, pp. 18–41, 1993.

[12] Mars Climate Orbiter Mishap Investigation Board, *Phase I Report*, NASA, November 1999.

[13] A. Hindle, E. T. Barr, Z. Su, M. Gabel, and P. Devanbu, "On the naturalness of software," in *Proc. 34th International Conference on Software Engineering (ICSE)*, 2012, pp. 837–847.

[14] M. Allamanis, E. T. Barr, P. Devanbu, and C. Sutton, "A survey of machine learning for big code and naturalness," *ACM Computing Surveys*, vol. 51, no. 4, article 81, 2018.

[15] M. Allamanis, M. Brockschmidt, and M. Khademi, "Learning to represent programs with graphs," in *Proc. International Conference on Learning Representations (ICLR)*, 2018.

[16] R. Gupta, S. Pal, A. Kanade, and S. Shevade, "DeepFix: Fixing common C language errors by deep learning," in *Proc. AAAI Conference on Artificial Intelligence*, 2017, pp. 1345–1351.

[17] M. Pradel and K. Sen, "DeepBugs: A learning approach to name-based bug detection," *Proc. ACM on Programming Languages*, vol. 2, no. OOPSLA, article 147, 2018.

[18] I. Goodfellow et al., "Generative adversarial nets," in *Advances in Neural Information Processing Systems 27*, 2014.

[19] M. Mirza and S. Osindero, "Conditional generative adversarial nets," arXiv:1411.1784, 2014.

[20] T. Salimans, I. Goodfellow, W. Zaremba, V. Cheung, A. Radford, and X. Chen, "Improved techniques for training GANs," in *Advances in Neural Information Processing Systems 29*, 2016.

[21] M. Arjovsky, S. Chintala, and L. Bottou, "Wasserstein generative adversarial networks," in *Proc. 34th International Conference on Machine Learning (ICML)*, PMLR vol. 70, 2017, pp. 214–223.

[22] I. Gulrajani, F. Ahmed, M. Arjovsky, V. Dumoulin, and A. Courville, "Improved training of Wasserstein GANs," in *Advances in Neural Information Processing Systems 30*, 2017.

[23] E. Choi, S. Biswal, B. Malin, J. Duke, W. F. Stewart, and J. Sun, "Generating multi-label discrete patient records using generative adversarial networks," in *Proc. Machine Learning for Healthcare Conference (MLHC)*, PMLR vol. 68, 2017, pp. 286–305.

[24] L. Xu, M. Skoularidou, A. Cuesta-Infante, and K. Veeramachaneni, "Modeling tabular data using conditional GAN," in *Advances in Neural Information Processing Systems 32*, 2019.

[25] A. Antoniou, A. Storkey, and H. Edwards, "Data augmentation generative adversarial networks," arXiv:1711.04340, 2017.

[26] N. V. Chawla, K. W. Bowyer, L. O. Hall, and W. P. Kegelmeyer, "SMOTE: Synthetic minority over-sampling technique," *Journal of Artificial Intelligence Research*, vol. 16, pp. 321–357, 2002.

[27] H. He and E. A. Garcia, "Learning from imbalanced data," *IEEE Transactions on Knowledge and Data Engineering*, vol. 21, no. 9, pp. 1263–1284, 2009.

TABLE XXI
DIAGNOSTIC CODES OF THE MEDSCRIPT COMPILER.

Code	Phase	Severity	Family	Meaning
LEX001	lexer	error	lexical	illegal character
LEX002	lexer	error	lexical	malformed number
LEX003	lexer	error	lexical	unterminated string literal
SYN001	parser	error	syntax	expected token not found
SYN002	parser	error	syntax	unexpected token in expression
SYN003	parser	error	syntax	unexpected end of file
SEM001	semantic	error	name	undeclared identifier or function
SEM002	semantic	error	name	redeclaration
SEM003	semantic	error	name	use before initialisation
SEM009	semantic	error	name	assignment to an input or constant
SEM004	semantic	error	type	type mismatch
SEM006	semantic	error	type	wrong argument count or type
SEM008	semantic	error	type	condition is not boolean
SEM005	semantic	error	unit	unit-of-measure mismatch
DOM001	semantic	error	range	implausible value or threshold outside declared range
DOM002	semantic	error	phi	PHI reaches an output sink
DOM003	semantic	error	missing	optional value used without presence check
SEM007	semantic	error	logic	missing return on some path
DOM004	semantic	error	logic	division by constant zero
DOM005	semantic	error	logic	divisor range includes zero
W001	semantic	warning	logic	unreachable code
W002	semantic	warning	valid	unused variable
W003	semantic	warning	logic	constant condition

[28] T. Schlegl, P. Seeböck, S. M. Waldstein, U. Schmidt-Erfurth, and G. Langs, "Unsupervised anomaly detection with generative adversarial networks to guide marker discovery," in *Proc. Information Processing in Medical Imaging (IPMI)*, LNCS vol. 10265, Springer, 2017, pp. 146–157.

[29] F. T. Liu, K. M. Ting, and Z.-H. Zhou, "Isolation forest," in *Proc. IEEE International Conference on Data Mining (ICDM)*, 2008, pp. 413–422.

[30] B. Schölkopf, J. C. Platt, J. Shawe-Taylor, A. J. Smola, and R. C. Williamson, "Estimating the support of a high-dimensional distribution," *Neural Computation*, vol. 13, no. 7, pp. 1443–1471, 2001.

[31] L. Breiman, "Random forests," *Machine Learning*, vol. 45, no. 1, pp. 5–32, 2001.

[32] F. Pedregosa et al., "Scikit-learn: Machine learning in Python," *Journal of Machine Learning Research*, vol. 12, pp. 2825–2830, 2011.

[33] A. Paszke et al., "PyTorch: An imperative style, high-performance deep learning library," in *Advances in Neural Information Processing Systems 32*, 2019.

[34] D. P. Kingma and J. Ba, "Adam: A method for stochastic optimization," in *Proc. International Conference on Learning Representations (ICLR)*, 2015.

[35] M. Sokolova and G. Lapalme, "A systematic analysis of performance measures for classification tasks," *Information Processing & Management*, vol. 45, no. 4, pp. 427–437, 2009.

[36] T. Fawcett, "An introduction to ROC analysis," *Pattern Recognition Letters*, vol. 27, no. 8, pp. 861–874, 2006.

[37] S. S. Muchnick, *Advanced Compiler Design and Implementation*, Morgan Kaufmann, 1997.

[38] C. Lattner and V. Adve, "LLVM: A compilation framework for lifelong program analysis and transformation," in *Proc. International Symposium on Code Generation and Optimization (CGO)*, 2004, pp. 75–88.

TABLE XXII
FAULT-INJECTION OPERATORS AND YIELD DURING CORPUS CONSTRUCTION.

Family	Operator	Fault injected	Tried	Kept	%
lexical	`lex_illegal`	insert an illegal character	332	332	100
	`lex_number`	malform a numeric literal	311	307	99
	`lex_string`	drop a closing quote	362	361	100
syntax	`syn_semicolon`	delete a semicolon	170	170	100
	`syn_paren`	delete a closing parenthesis	173	173	100
	`syn_close_brace`	delete a closing brace	175	175	100
	`syn_open_brace`	delete an opening brace	139	139	100
	`syn_operand`	delete a comparison operand	167	167	100
	`syn_keyword`	misspell a keyword	176	176	100
name	`name_typo`	misspell a variable use	208	208	100
	`name_delete_decl`	delete a declaration	182	182	100
	`name_redecl`	duplicate a declaration	156	151	97
	`name_uninit`	remove an initialiser	185	142	77
	`name_func`	misspell a function call	173	128	74
	`name_assign_input`	assign to an input	189	189	100
type	`type_string_assign`	assign a string/bool to a number	194	150	77
	`type_bool_assign`	assign a number to a bool	189	189	100
	`type_arity`	change an argument count	202	148	73
	`type_cond`	use a number as a condition	170	170	100
	`type_return`	return the wrong type	210	162	77
	`type_float_int`	assign a float to an int	181	181	100
unit	`unit_swap_literal`	swap the unit of a literal	225	212	94
	`unit_drop`	drop the unit of a literal	218	208	95
	`unit_decl`	change a declared input unit	210	206	98
	`unit_rate`	pass a wrong dose-rate unit	195	86	44
	`unit_return`	return a wrong unit	231	74	32
	`unit_add`	add quantities of different units	215	214	100
range	`range_literal`	implausible threshold literal	295	267	91
	`range_threshold`	threshold outside declared range	321	273	85
	`range_decl`	invert a declared range	323	323	100
	`range_const`	implausible dose constant	307	137	45
phi	`phi_direct`	print a PHI input	202	202	100
	`phi_alias`	export an alias of PHI	219	219	100
	`phi_concat`	concatenate PHI into output	222	222	100
	`phi_removeanon`	remove an anonymize() call	219	116	53
	`phi_func`	leak PHI through a function	241	241	100
missing	`miss_unguard`	remove a presence guard	442	192	43
	`miss_new_use`	use an optional value unguarded	402	402	100
	`miss_make_optional`	make a required input optional	410	406	99
logic	`logic_div_zero`	divide by constant zero	174	174	100
	`logic_range_zero`	divisor range includes zero	193	101	52
	`logic_missing_return`	delete a return	166	109	66
	`logic_unreachable`	code after return	160	112	70
	`logic_inverted`	invert a clinical comparison	154	148	96
	`logic_wrong_message`	mismatch alert text and rule	165	163	99
	`logic_constcond`	constant if-condition	193	193	100