

Today Route Test Document + Wiring Feasibility Addendum (Granular Component Parts)

Scope: /payout-command-view/today | Generated: 2026-05-31 23:11

What is covered: Each frontend part (hero cards, chart lines, table rows, action buttons, and summary tiles) has its own row with API source, exact fields, and compute rule.

Mode tags used inline: Wired, Hybrid, Mock are included inside API/source column for each row.

1) Component-Part API Mapping Table (Detailed)

Frontend element	What it shows	API and backend source	Exact fields used	How frontend computes final value
Home > Hero intended value	Total intended payment value.	[Mode: Hybrid] /api/prod/intelligence/leakage (zord-intelligence) + fallback /api/prod/home/disbursement-trend.	leakage.total_intended_amount_minor trend.buckets[].total_amount.	Primary: parseMinorField(total_intended_amount_minor). Fallback: sum(trend.total_amount). Rendered as INR.
Home > Hero observed/bank-confirmed value	Observed settled (bank-confirmed) value.	[Mode: Hybrid] /api/prod/intelligence/leakage + trend fallback.	leakage.total_observed_settled_amount_minor trend.buckets[].confirmed_amount.	Uses leakage observed amount first. If unavailable, chart confirmed series still shows from trend endpoint.
Home > Hero review exposure	Value needing review (ambiguity risk).	[Mode: Wired] /api/prod/intelligence/ambiguity.	ambiguity.value_at_risk_minor.	INR formatting from minor units; if missing, shows dash/empty-state copy.
Home > Trend bars (intended)	Bar series for intended value over time.	[Mode: Wired] /api/prod/home/disbursement-trend (BFF over intent-engine).	buckets[].label buckets[].total_amount.	barValue = total_amount/1000 for chart scale; axis labels from bucket label.
Home > Trend line (confirmed)	Confirmed value line over time.	[Mode: Wired] /api/prod/home/disbursement-trend.	buckets[].confirmed_amount.	lineValue = confirmed_amount/1000; tooltip shows full INR via fmtInrFull.
Home > Trend line (review)	Review-needed value line.	[Mode: Wired] /api/prod/home/disbursement-trend.	buckets[].review_amount.	reviewLineValue = review_amount/1000; shown as dashed line.
Home > Trend tooltip totals	Tooltip intended/confirmed/review values for selected point.	[Mode: Wired] /api/prod/home/disbursement-trend.	selected bucket total_amount confirmed_amount review_amount.	Uses selected bucket index; values formatted with fmtInrFull.
Home > Match confidence chip	Average attachment confidence percent.	[Mode: Wired] /api/prod/intelligence/ambiguity.	avg_attachment_confidence.	Displayed as Math.round(confidence*100) + "%".
Home > Proof coverage chip	Evidence coverage percent.	[Mode: Wired] /api/prod/intelligence/defensibility.	evidence_pack_rate.	Displayed as Math.round(evidence_pack_rate*100) + "%".
Home > Next action: upload settlement prompt	Prompt to upload settlement/bank file when source missing.	[Mode: Hybrid] /api/prod/ingest-status (or fallback probes).	ingest.sources["settlement_file"].status fallback settlement batch existence.	If settlementStatus == missing, action is emphasized with upload guidance.

Home > Command cards: Success rate	KPI success percentage.	[Mode: Wired] /api/prod/zord/metrics/overview.	kpis.success_rate_pct.	Mapped into outcome card with one-decimal percent.
Home > Command cards: Value at risk	Money-at-risk KPI in compact INR.	[Mode: Wired] /api/prod/zord/metrics/overview.	kpis.money_at_risk_inr.	inrCompact formatter (L/Cr thresholds).
Home > Command cards: In-flight value	Pending/dispatched value.	[Mode: Wired] /api/prod/zord/metrics/overview.	kpis.amount_in_flight_inr.	Mapped to in-flight card with compact INR formatting.
Home > Connectivity graph nodes/edges	Illustrative topology graph in command-center section.	[Mode: Mock] mockOpsCommandCenter payload (not from overview API).	payload.nodes payload.edges.	Rendered as-is from mock payload; no live topology API mapping yet.
Workspace > In-scope summary tile	Total instructions in current scope.	[Mode: Wired] /api/prod/intelligence/patterns.	patterns.total_count patterns.success_count.	Formats count with thousands separators; subtext uses success_count.
Workspace > Value observed tile	Observed/known value from instructions or settlement.	[Mode: Wired] /api/prod/intelligence/leakage.	total_intended_amount_minor total_observed_settled_amount_minor.	Prefers intended amount when >0, else settled amount; formatted INR.
Workspace > Needing review tile	Ambiguity value-at-risk.	[Mode: Wired] /api/prod/intelligence/ambiguity.	value_at_risk_minor.	Minor->INR conversion; zero shows specific reviewZeroHint copy.
Workspace > Proof readiness tile	Proof/evidence readiness % and governance/replay hints.	[Mode: Wired] /api/prod/intelligence/defensibility.	evidence_pack_rate governance_coverage_pct replayability_pct.	proofReadiness = evidence_pack_rate*100%; subtext includes rounded governance/replay percentages.
Workspace > Lifecycle state	intent_only / settlement_only / full_lifecycle state.	[Mode: Wired] leakage + ambiguity + patterns from intelligence APIs.	intendedMinor confirmedMinor reviewMinor ambiguity/pattern flags.	derivePaymentCommandDataState computes lifecycle from value and signal availability.
Workspace > Ask Zord latest answer	Tenant-scoped natural-language answer.	[Mode: Wired] POST /api/prompt-layer/query.	request query/top_k response.answer response.confidence response.citations.	mapPromptLayerAnswer extracts answer text; message stream updates thread state.
Leakage > Intended amount KPI	Tenant/batch intended total.	[Mode: Wired] /api/prod/intelligence/leakage.	total_intended_amount_minor.	coerceMinor -> PortfolioLeakageViewModel.intendedMinor -> INR label.
Leakage > Settled amount KPI	Observed settled total.	[Mode: Wired] /api/prod/intelligence/leakage.	total_observed_settled_amount_minor.	coerceMinor -> totalSettledMinor -> formatted INR.
Leakage > Unmatched / short-settled / orphan / reversal KPIs	Breakdown of leakage components.	[Mode: Wired] /api/prod/intelligence/leakage.	unmatched_amount_minor under_settlement_amount_minor orphan_amount_minor reversal_exposure_minor.	Each field coerced to number and displayed as individual component cards.
Leakage > Value needing review override	Review value aligned to ambiguity engine.	[Mode: Hybrid] leakage + /api/prod/intelligence/ambiguity.	leakage.ambiguous_value_at_risk_minor + ambiguity.value_at_risk_minor.	If ambiguity value_at_risk_minor available, it overrides leakage-derived review value.

Leakage > Current leakage series	Observed leakage series in trend chart.	[Mode: Wired] /api/prod/intelligence/timeseries/leakage.	series[].date current_leakage_minor granularity.	mapLeakageComparisonSeries builds dateKey/period/label for chart x-axis.
Leakage > Predicted leakage series	Predicted leakage line/area.	[Mode: Wired] /api/prod/intelligence/timeseries/leakage.	series[].predicted_leakage_minor project_start_at is_future.	Predicted values plotted with reference line at project_start period.
Leakage > Export gap report button	Export trigger status message.	[Mode: Hybrid] POST /api/prod/exports/gap-report (stub).	response.reason response.message response.job_id.	Button posts empty payload; UI prints returned message.
Ambiguity > Ambiguous count KPI	Count of ambiguous intents.	[Mode: Hybrid] /api/prod/intelligence/ambiguity + batch-health merge when batch selected.	ambiguous_intent_count (and batch_health projected counts).	effectiveAmb overlays batch-health projection over tenant snapshot.
Ambiguity > Ambiguity rate KPI	Ambiguity percentage.	[Mode: Hybrid] /api/prod/intelligence/ambiguity + batch-health merge.	ambiguity_rate.	Displayed as percent with one-decimal formatting.
Ambiguity > Missing ref rate KPI	Provider reference missing rate.	[Mode: Hybrid] /api/prod/intelligence/ambiguity + batch-health merge.	provider_ref_missing_rate.	Direct percent formatting; used in reason charts and summary cards.
Ambiguity > Value-at-risk KPI	Total value at risk.	[Mode: Wired] /api/prod/intelligence/ambiguity.	value_at_risk_minor.	formatAmbiguityInr(value_at_risk_minor).
Ambiguity > Velocity scatter bubble size	Bubble area by ambiguous amount.	[Mode: Hybrid] /api/prod/ambiguity/velocity (fallback when upstream missing).	points[].ambiguous_amount_minor total_amount_minor ambiguity_level_pct.	z-axis uses ambiguous_amount_minor; y uses ambiguity_level_pct (or derived ambiguous/total ratio).
Ambiguity > Velocity scatter color	Red/high ambiguity, amber/medium, green/low.	[Mode: Hybrid] /api/prod/ambiguity/velocity.	ambiguity_level_pct per point.	bubbleColorForAmbiguity thresholds: >=35 red, <=18 green, else amber.
Ambiguity > Batches needing review table	Batch list with finality/review context.	[Mode: Wired] /api/prod/intelligence/batches?status=&limit=80.	batch_id total_count pending_count finality_status status_label match_confidence_pct value_at_risk_minor.	Client applies finality filter, sort, and pagination over returned rows.
Ambiguity > Export review list button	Export initiation message.	[Mode: Hybrid] POST /api/prod/exports/review-list (stub).	response.reason message job_id.	Shows API message until export worker is connected.
Intent Journal > Sidebar batch rows	Batch ID, txn counts, confirmed/mismatch/unresolved hints.	[Mode: Hybrid] /api/prod/intents/batches; fallback /api/prod/intelligence/batches.	intent items batchId/type/totalValue/transactions/ confirmedCount/highConfidenceCount/ mismatchCount/unresolvedCount fallback batch_id + counts.	mapSidebarItemToBatchRecord or mapIntelligenceRowToBatchRecord normalizes into sidebar model.
Intent Journal > Transaction status	Ready/Pending/In Progress/Needs Review state per intent.	[Mode: Wired] /api/prod/intents/batches? batch_id=&page=&page_size=.	paymentIntents.items[].status governance_state business_state.	mapPaymentIntentToIntentRow applies status classification rules from status strings.

Intent Journal > Transaction match label	Matched/Likely Matched/Awaiting/ Mismatch/Not Found.	[Mode: Wired] same paymentIntents payload.	aggregate_confidence_score + derived status.	Confidence and status thresholds map to match label.
Intent Journal > Zord ID display	Short Zord ID per row.	[Mode: Wired] same paymentIntents payload.	intent_id batchId.	buildZordId from normalized requestId/ batchId tail.
Intent Journal > Failures (DLQ) stage and action	Validation/Dispatch/ Processing/ Settlement stage and Retry/ Investigate action.	[Mode: Wired] dlqItems from /api/prod/intents/batches?batch_id=.	dlq row stage reason_code error_detail replayable created_at intent_context.	mapDlqToFailureRow infers stage/action and parses context fields.
Settlement Journal > Client batch sidebar IDs	Available client_batch_id list.	[Mode: Wired] /api/prod/settlement/observations/batches.	items[].client_batch_id.	extractClientBatchIdsFromListResponse normalizes list and de-duplicates.
Settlement Journal > Observation amount fields	Amount, settled amount, fee, deductions per row.	[Mode: Wired] /api/prod/settlement/observations/batches? client_batch_id=.	amount settled_amount fee_amount deduction_amount currency_code.	mapObservationToTableRow parses numerics and formats row model.
Settlement Journal > Observation status fields	Settlement status and reason/provider codes.	[Mode: Wired] same settlement observations endpoint.	settlement_status provider_status_code failure_reason_code retry_flag reversal_flag return_flag.	Status displayed directly; filters applied client-side by status/date/source/amount.
Settlement Journal > Parse errors panel	Parser/mapping errors for selected batch.	[Mode: Wired] /api/prod/settlement/errors?batch_id=.	source_row_ref error_stage reason_code severity.	Rows rendered directly; empty list shows no-error state.
Evidence > Defensibility KPI card	Defensibility score/ tier and readiness metrics.	[Mode: Wired] /api/prod/intelligence/defensibility.	defensibility_score defensibility_tier evidence_pack_rate governance_coverage_pct replayability_pct audit_ready_pct dispute_ready_pct.	deriveEvidenceKpis maps fields to cards; rates converted to percentages.
Evidence > Leakage/ Ambiguity context cards	Evidence context from leakage and ambiguity for selected batch.	[Mode: Hybrid] /api/prod/intelligence/leakage?batch_id= and /api/prod/intelligence/ambiguity?batch_id=.	leakage risk fields + ambiguity risk fields.	Combined with defensibility cards via deriveEvidenceKpis.

Evidence > Pack Browser rows	Pack id, refs, intent/ batch scope, proof root, status, score, counts.	[Mode: Wired] /api/prod/evidence/packs?batch_id= + /api/prod/evidence/batch/{batchId}/intents.	evidence_pack_id batch_id intent_id client_reference/client_payout_ref merkle_root mode pack_status proof_status proof_score leaf_count required_leaf_count pack_completeness_score created_at.	mergePackSummaries + mapPackTableRow + mapProofStatusFromPack derive final row view model.
Evidence > Proof status label	proofReady/verified/ exported/partial/ missing states.	[Mode: Wired] evidence pack summary rows.	pack_status proof_status leaf_count artifact_count required_leaf_count intent_id.	mapProofStatusFromPack applies rule ladder to choose status key/label.
Evidence > Breakdown segments	Mix of proof status categories.	[Mode: Hybrid] derived from mapped pack rows; mock segments when empty.	row.proofStatusKey row.generatedAt.	deriveEvidenceAnalytics buckets statuses and computes percentages; uses mock template if row count is zero.
Evidence > 30-day trend chart	Evidence volume over last 30 calendar days.	[Mode: Hybrid] derived from pack rows; mock waveform when empty.	generatedAt timestamps from table rows.	buildVolumeHistogram creates daily skeleton and counts row dates within window.
Evidence > Export center buttons	Download finance/ audit/bank-pack/ raw-json export files.	[Mode: Hybrid] POST /api/v1/ dispute/export.	request: payment_reference dispute_reason export_type response headers content-disposition + blob body.	Creates blob URL and downloads file; fallback message on HTTP error.
Live Sync > Connector cards	Connector name, status, and last sync timestamp.	[Mode: Hybrid] /api/prod/systems/ sync-status (proxy to connectors service, fallback reason).	data_available connectors[].id/name/status/last_sync_at reason.	live=true only when data_available==true and connectors length>0; else shows no-telemetry guidance.
Connector Intelligence (live dock) KPI panels	Network health, leakage composition, route ranking.	[Mode: Mock] seededRoutingData through getRoutingIntelligenceAdapter().	snapshot.connectors routeCandidates networkHealthTrend leakageComposition actionRecommendations.	buildKpis and rankRoutes compute summary metrics and top-route ordering.
Sandbox Connectors list	Connected provider cards and available provider catalog.	[Mode: Mock] local connected-providers-store (localStorage).	providers[] local state + provider catalog constants.	Hydrates local state and renders connect/disconnect mutations immediately.
Borrower Verification > Summary buckets	Safe/blocked/ exposure prevented/ KYC pass/proof coverage.	[Mode: Mock] BORROWER_VERIFICATION_MOCK.	summary queueCounts totals checkBreakdown.	Reads precomputed mock summary and applies local UI formatting.

Borrower Verification > Queue table row	Borrower signals (KYC/bank/fraud/AML), amount, status, source.	[Mode: Mock] BORROWER_VERIFICATION_MOCK.K.queueRows.	borrowerId borrowerName loanAmountInr kyc bank fraud aml status source.	Client-side sort/filter/page; compact INR label for loan amount.
Post-Disbursal Monitoring > Summary cards	Total disbursed, confirmed received, at risk, recovered, repayment rate.	[Mode: Mock] POST_DISBURSAL_MONITORING_MOCK.summaryCards.	summaryCards[].label/value/sub/tone.	Direct render from mock card list with tone styling.
Post-Disbursal Monitoring > Queue row status	Confirmed/Pending/At-risk loan status and risk signal.	[Mode: Mock] POST_DISBURSAL_MONITORING_MOCK.queueRows.	loanId amountInr confirmed repayment riskSignal evidence status.	Client-side filtering/sorting; status tone and signal tone derived from label mappings.
Billing > Processing in Zord count	Count of intents currently in processing-like states.	[Mode: Wired] /api/prod/intents/batches list + per-batch detail calls.	batch list batchId paymentIntents[].status business_state governance_state.	isZordProcessingPaymentIntent predicate over scanned intents (first 15 batches).
Billing > Sandbox cap progress bar	Processing count against daily sandbox cap (10).	[Mode: Hybrid] processing count from live calls + local SANDBOX_DAILY_INTENT_LIMIT constant.	processingCount SANDBOX_DAILY_INTENT_LIMIT.	usagePct = min(100, round((processing/limit)*100)).
Billing > Plan and invoices section	Plan options and invoice placeholders.	[Mode: Mock] local PLANS constant and static placeholders.	PLANS[] fields static copy.	Direct static render with environment-based badge behavior.
Support > Processing overview totals	Total intents, completed, failed, processing, unresolved, with percentages.	[Mode: Hybrid] /api/prod/intents/batches + /api/prod/intelligence/patterns + /api/prod/intelligence/ambiguity/heatmap + /api/prod/settlement/observations/batches.	batch items transactions/confirmedCount/mismatchCount/unresolvedCount patterns.pending_count.	currentlyProcessing = total - completed - failed; pct values derived from totalIntents.
Support > Failure reasons panel	Reason buckets (TOKENIZATION_FAILURE, WEBHOOK_TIMEOUT, etc.).	[Mode: Hybrid] derived in client from pattern pending/failed counts.	patterns.pending_count or failed count from batch totals.	Synthetic split percentages are computed in client (not direct backend reason distribution).
Support > Recent processing activity rows	Recent observation-linked activity with intent and batch references.	[Mode: Hybrid] /api/prod/settlement/observations/batches (+ first selected batch details).	created_at/observation_timestamp matched_intent_id settlement_status client_batch_id.	Takes first 8 rows and maps relative time + display defaults.

Support > Heatmap matrix	Compact weekly heat bands from ambiguity/failure ratios.	[Mode: Hybrid] /api/prod/intelligence/ambiguity/heatmap.	batches[].total_count unresolved_count conflicted_count ambiguous_count.	Client computes failRatio/procRatio and assigns discrete heat levels per row.
Support > Ticket inbox and thread	Open/closed tickets, message thread, unread markers.	[Mode: Hybrid] localStorage supportTickets store (seed data) + user profile via /api/auth/me.	ticket/message objects + profile user/session fields.	Hydrates per-tenant key, persists local mutations, and derives relative-time labels.
Header > API keys popover context row	Tenant/workspace context and publishable key.	[Mode: Hybrid] /api/sandbox/workspace-api-keys (backed by edge /v1/auth/me).	tenant_id tenant_name workspace_code publishable_key secret_key_prefix.	Combines server payload with localStorage secret when available for masked display/copy behavior.

2) Wiring Feasibility Matrix (for non-fully-live parts)

Component	Current source	Current mode	Can be wired now?	Target API (existing or to create)	Service/backing calc	Why this wiring is correct in current system	Blocker/gap	Owner (frontend/ BFF/ upstream)
Home trend chart	BFF aggregate over intents	Hybrid	Partially	Dedicated disbursement timeseries API	Move bucketing to upstream analytics	Current route itself marks aggregate as temporary	No dedicated upstream contract	Upstream+BFF
Ambiguity velocity chart	Route exists with fallback data_available:false	Hybrid	Yes (when upstream live)	/v1/intelligence/timeseries/ambiguity-velocity (existing target)	Upstream point timeseries	Frontend mapper/chart already built	Upstream empty/unavailable for tenant	Upstream
Command-center connectivity graph	Illustrative mock graph	Mock	Not yet	Create topology/flow API	Route graph builder in analytics service	Cards already live; graph isolated for swap	No graph API payload yet	Upstream+BFF
Leakage/Review exports	Endpoints return export_service_pending	Hybrid	Not fully	Keep endpoints + add export job status endpoint	Export worker + job queue	UI action wiring complete already	No export worker/job lifecycle	BFF+Upstream
Live sync	Proxy route with unreachable fallback	Hybrid	Yes	/v1/connectors/sync-status (already proxied)	Connector telemetry feed	Tenant-scoped proxy already working	Connector service readiness	Upstream
Borrower verification	Local mock module	Mock	No	New BFF verification routes	Intent+KYC+fraud aggregations	UI already expects queue + signal model	No backend contract	BFF+Upstream
Post-disbursal monitoring	Local mock module	Mock	No	New BFF monitoring routes	Settlement+repayment+risk aggregation	UI separated into cards/queue/charts	No monitoring APIs in /api/prod	BFF+Upstream
Connector intelligence live dock	seededRoutingData adapter	Mock	Partially	Create /api/prod/intelligence/routing-*	Routing ranking + health calc service	Adapter boundary already present	Missing live routing endpoints	Upstream+BFF
Support processing overview	Mixed live + synthetic derivations	Hybrid	Yes	Single aggregated processing-overview endpoint	Backend canonical metric aggregation	Reduces frontend drift and test burden	No single canonical endpoint	BFF
Billing plans/invoices	Static constants and placeholders	Mock	No	Billing plan/invoice/payment-method APIs	Billing provider integration	UI cards align to resource boundaries	Billing backend not integrated	BFF+Upstream

3) QA Testing Instructions (exact execution order)

Step 1: From frontend, capture API context first.

- Open API keys panel/settings and note tenant/workspace/API-key context used by UI.
- In DevTools Network tab, capture actual request URL, method, payload/query, and response for each component-part row under test.

Step 2: Re-run same APIs in Postman.

- Use same auth and tenant context.
- Use collection link referenced in app docs: <https://www.postman.com/zord/zord-public/collection/sandbox>
- Replay exact same endpoint + params/body captured from frontend.

Step 3: Compare frontend vs Postman response.

- Compare status code, schema keys, and value parity for exact consumed fields.
- Validate frontend-derived values (INR formatting, percentages, totals, derived KPIs) against raw API fields.

Step 4: Record mismatch classification.

- Classify as: Frontend compute issue, BFF mapping issue, Upstream API issue, or Intentional fallback/mock.
- Log component part, API, field, expected vs actual, and owner.

4) QA Test Plan

1. Coverage test: every Today component-part is represented in table rows.
2. Accuracy test: every row cites real endpoint path and consumed fields from code.
3. Live-readiness test: every non-live part has explicit wiring path and owner.
4. Flow test: frontend context first, then Postman replay, then parity, then mismatch class.

5) Assumptions

- Scope remains /payout-command-view/today.
- Table is component-part granularity (not only page/surface level).
- Postman collection is referenced by SANDBOX_DOCS_LINKS, not stored as file in repo.

- Session-tenant context must match between frontend and Postman for valid comparisons.