

Httpd --> Hyper Text Transfer Protocol daemon
Systemctl --> system control of linux.

VPC COMPONENTS:

1. VPC (Virtual Private Cloud):

It is our own private space in AWS.

It is larger network in AWS.

We can create all the resources in this VPC.

WHY?

For security of our resources & application.

For isolated environment(own space for applications)

We can able to create 5 VPC's per region.

Before CIDR: 5 classes - A, B, C, D, E - 255 IP's

Class A: 1.0.0.0 to 127.255.255.255

Very large networks, for very large organizations like Google, Microsoft

Default mask: /8 (2 (power(32-8)))

VPC: 125.0.0.0/8

1.0.0.0, 1.0.0.1 or 1.1.0.0 --> 254 subIP's

Class B: 128.0.0.0 to 191.255.255.255

Medium size organizations like Wipro

Default mask: /16 --> 65,536 IP's

Class C: 192.0.0.0 to 223.255.255.255

Small organizations

Default mask: /24

Class D: 224.0.0.0 to 239.255.255.255

Multicasting purpose.

Class E: 240.0.0.0 to 255.0.0.0

Research & experiment(reserved)

CIDR(Class-less Inter Domain Routing): Assigning IP address of our desired without any restrictions. No classes.

16 to 28

2. Subnet:

It is the smaller group of networks inside VPC

or

VPC can be divided into smaller group of network called Subnets.

These will be inside Availability zone.

3. Route Table: route traffic to correct path.

Decides where traffic should go.

Traffic --> user requests.

4. IGW (Internet Gateway): communication between Internet & VPC.

1 IGW will be attached to 'n' no. of public subnets under route table.

1. NAT Gateway: one component to pass internet to private subnets or private resources.

While creating, consider all public(public subnet, public connectivity)

After creating NAT, it should be attached to private subnets.

1 nat can be attached to 'n' no. of private subnets under route table.

