Java script Execution Context

{} → Global & c
Execute under thread
Java Script is single threaded
→ Global execution context
→ function " "
→ Eval execution "

{} → memory → Creation Phase
→ Execution Phase → operation

Only memory allocation

Ex:

```
let val1 = 10
let val2 = 5
function addNum(num1, num2){
    let total = num1 +num2
    return total
}
let result1 = addNum(val1, val2)
let result2 = addNum(10, 5)
```

How it is going to execute?

1→ Global execution / environment
this

2→ Memory phase
val 1 → undefined
val 2 → undefined
add num → definition
result 1 → undefined
result 2 → undefined

3→ Execution Phase
val 1 → 10
val 2 → 5
add num → [illegible]
result 1 = 15
result 2 =

It will delete

Execution context
num1 → 10
num2 → 5
total → 15

memory phase
val1 → undefined
val2 → undefined
total → undefined

After this

New variable environment + thread

memory phase

Execution Phase

Total

Call stack

three()
two()
one()
method

while executing

three()
two()
one()
Global Execution

after execution

three()
two()
one()

when one(), two(), three() are called 3 function

LIFO → last in 1st out

concept appears

So three() will execute and go outside
1st, then two() and
at last one()





look at this

:- Function leaving has nothing to do with output only when console.log is placed before inner calls.