

```
`www_project`
```

```
---
```

```
-----
```

```
---
```

```
-- Table structure for table `admin`
```

```
---
```

```
CREATE TABLE IF NOT EXISTS `admin` (
  `name` varchar(20) COLLATE latin1_general_ci NOT NULL,
  `pass` varchar(40) COLLATE latin1_general_ci NOT NULL
) ENGINE=InnoDB DEFAULT CHARSET=latin1 COLLATE=latin1_general_ci;
```

```
---
```

```
-- Dumping data for table `admin`
```

```
---
```

```
INSERT INTO `admin` (`name`, `pass`) VALUES
('admin', 'd033e22ae348aeb5660fc2140aec35850c4da99');
```

```
-----
```

```
---
```

```
-- Table structure for table `books`
```

```
---
```

```
CREATE TABLE IF NOT EXISTS `books` (
  `book_isbn` varchar(20) COLLATE latin1_general_ci NOT NULL,
  `book_title` varchar(60) COLLATE latin1_general_ci DEFAULT NULL,
  `book_author` varchar(60) COLLATE latin1_general_ci DEFAULT NULL,
  `book_image` varchar(40) COLLATE latin1_general_ci DEFAULT NULL,
  `book_descr` text COLLATE latin1_general_ci,
  `book_price` decimal(6,2) NOT NULL,
  `publisherid` int(10) unsigned NOT NULL
) ENGINE=InnoDB DEFAULT CHARSET=latin1 COLLATE=latin1_general_ci;
```

```
---
```

```
-- Dumping data for table `books`
```

```
---
```

```
INSERT INTO `books` (`book_isbn`, `book_title`, `book_author`, `book_image`,
`book_descr`, `book_price`, `publisherid`) VALUES
('978-0-321-94786-4', 'Learning Mobile App Development', 'Jakob Iversen, Michael
Eierman', 'mobile_app.jpg');
```

```
-----
```

```
---
```

```
-- Table structure for table `customers`
```

```
---
```

```
CREATE TABLE IF NOT EXISTS `customers` (
  `customerid` int(10) unsigned NOT NULL,
  `name` varchar(60) COLLATE latin1_general_ci NOT NULL,
  `address` varchar(80) COLLATE latin1_general_ci NOT NULL,
  `city` varchar(30) COLLATE latin1_general_ci NOT NULL,
```

0000-f0eb-169a-af2e-0f9.txt

```
`zip_code` varchar(10) COLLATE latin1_general_ci NOT NULL,  
`country` varchar(60) COLLATE latin1_general_ci NOT NULL  
) ENGINE=InnoDB AUTO_INCREMENT=4 DEFAULT CHARSET=latin1  
COLLATE=latin1_general_ci;
```

```
--  
-- Dumping data for table `customers`  
--
```

```
INSERT INTO `customers` (`customerid`, `name`, `address`, `city`, `zip_code`,  
`country`) VALUES  
(1, 'Anil', 'banashankari', 'bangalore', '560084', 'india'),  
(2, 'Gokul', 'kr puram', 'mysore', '560100', 'usa'),  
(3, 'swathi', 'yamalokha', 'yamapura', '000', 'sky');
```

```
--  
-- Table structure for table `orders`  
--
```

```
CREATE TABLE IF NOT EXISTS `orders` (  
`orderid` int(10) unsigned NOT NULL,  
`customerid` int(10) unsigned NOT NULL,  
`amount` decimal(6,2) DEFAULT NULL,  
`date` timestamp NOT NULL DEFAULT CURRENT_TIMESTAMP,  
`ship_name` char(60) COLLATE latin1_general_ci NOT NULL,  
`ship_address` char(80) COLLATE latin1_general_ci NOT NULL,  
`ship_city` char(30) COLLATE latin1_general_ci NOT NULL,  
`ship_zip_code` char(10) COLLATE latin1_general_ci NOT NULL,  
`ship_country` char(20) COLLATE latin1_general_ci NOT NULL  
) ENGINE=InnoDB AUTO_INCREMENT=5 DEFAULT CHARSET=latin1  
COLLATE=latin1_general_ci;
```

```
--  
-- Dumping data for table `orders`  
--
```

```
INSERT INTO `orders` (`orderid`, `customerid`, `amount`, `date`, `ship_name`,  
`ship_address`, `ship_city`, `ship_zip_code`, `ship_country`) VALUES  
(1, 1, '60.00', '2015-12-03 13:30:12', 'Anil', 'banashankari', 'bangalore',  
'560084', 'india'),  
(2, 2, '60.00', '2015-12-03 13:31:12', 'Gokul', 'kr puram', 'mysore', '560100',  
'usa'),  
(3, 3, '20.00', '2015-12-03 19:34:21', 'swathi', 'yamalokha', 'yamapura', '000',  
'sky'),  
(4, 1, '20.00', '2015-12-04 10:19:14', 'a', 'a', 'a', 'a', 'a');
```

```
--  
-- Table structure for table `order_items`  
--
```

```
CREATE TABLE IF NOT EXISTS `order_items` (  
`orderid` int(10) unsigned NOT NULL,
```

```

                                0000-f0eb-169a-af2e-0f9.txt
`book_isbn` varchar(20) COLLATE latin1_general_ci NOT NULL,
`item_price` decimal(6,2) NOT NULL,
`quantity` tinyint(3) unsigned NOT NULL
) ENGINE=InnoDB DEFAULT CHARSET=latin1 COLLATE=latin1_general_ci;

--
-- Dumping data for table `order_items`
--

INSERT INTO `order_items` (`orderid`, `book_isbn`, `item_price`, `quantity`)
VALUES
(1, '978-1-118-94924-5', '20.00', 1),
(1, '978-1-44937-019-0', '20.00', 1),
(1, '978-1-49192-706-9', '20.00', 1),
(2, '978-1-118-94924-5', '20.00', 1),
(2, '978-1-44937-019-0', '20.00', 1),
(2, '978-1-49192-706-9', '20.00', 1),
(3, '978-0-321-94786-4', '20.00', 1),
(1, '978-1-49192-706-9', '20.00', 1);

-----

--
-- Table structure for table `publisher`
--

CREATE TABLE IF NOT EXISTS `publisher` (
  `publisherid` int(10) unsigned NOT NULL,
  `publisher_name` varchar(60) COLLATE latin1_general_ci NOT NULL
) ENGINE=InnoDB AUTO_INCREMENT=7 DEFAULT CHARSET=latin1
COLLATE=latin1_general_ci;

--
-- Dumping data for table `publisher`
--

INSERT INTO `publisher` (`publisherid`, `publisher_name`) VALUES
(1, 'Wrox'),
(2, 'Wiley'),
(3, 'O'Reilly Media'),
(4, 'Apress'),
(5, 'Packt Publishing'),
(6, 'Addison-Wesley');

--
-- Indexes for dumped tables
--

--
-- Indexes for table `admin`
--
ALTER TABLE `admin`
  ADD PRIMARY KEY (`name`,`pass`);

--
-- Indexes for table `books`

```

```
---
ALTER TABLE `books`
  ADD PRIMARY KEY (`book_isbn`);

---
-- Indexes for table `customers`
---
ALTER TABLE `customers`
  ADD PRIMARY KEY (`customerid`);

---
-- Indexes for table `orders`
---
ALTER TABLE `orders`
  ADD PRIMARY KEY (`orderid`);

---
-- Indexes for table `publisher`
---
ALTER TABLE `publisher`
  ADD PRIMARY KEY (`publisherid`);

---
-- AUTO_INCREMENT for dumped tables
---

---
-- AUTO_INCREMENT for table `customers`
---
ALTER TABLE `customers`
  MODIFY `customerid` int(10) unsigned NOT NULL AUTO_INCREMENT,AUTO_INCREMENT=4;
---
-- AUTO_INCREMENT for table `orders`
---
ALTER TABLE `orders`
  MODIFY `orderid` int(10) unsigned NOT NULL AUTO_INCREMENT,AUTO_INCREMENT=5;
---
-- AUTO_INCREMENT for table `publisher`
---
ALTER TABLE `publisher`
  MODIFY `publisherid` int(10) unsigned NOT NULL
  AUTO_INCREMENT,AUTO_INCREMENT=7;
```