DBMS LAB ASSIGNMENT

Labs 4 to 6

Functions | Operators | Special and Set Operations

Name: Swayam

USN: AS 1RUA25BCA0109

Course: BCA, R.V. University

Database used: MySQL / MariaDB 10.11

Lab 4	Implement SQL Functions (Conversion and Date Functions)
Lab 5	Implement SQL Operators (Arithmetic, Comparison and Logical)
Lab 6	Implement SQL Operators (Special Operators and Set Operations)

LAB 4: Implement SQL Functions (Conversion and Date Functions)

Aim: To implement SQL functions: conversion functions and date functions.

1. Create database, table and insert data

INPUT (SQL)

```
DROP DATABASE IF EXISTS lab4;
CREATE DATABASE lab4;
USE lab4;
CREATE TABLE orders (
  order_id   INT PRIMARY KEY,
  customer   VARCHAR(20),
  amount     VARCHAR(10),
  order_date DATE
);
INSERT INTO orders VALUES
 (1,'Asha','1250.75','2026-01-15'),
 (2,'Ravi','890.50','2026-03-02'),
 (3,'Meera','2300.00','2026-07-28'),
 (4,'Karan','450.25','2026-10-05');
SELECT * FROM orders;
```

OUTPUT

```
+----------+----------+---------+------------+
| order_id | customer | amount  | order_date |
+----------+----------+---------+------------+
|        1 | Asha     | 1250.75 | 2026-01-15 |
|        2 | Ravi     | 890.50  | 2026-03-02 |
|        3 | Meera    | 2300.00 | 2026-07-28 |
|        4 | Karan    | 450.25  | 2026-10-05 |
+----------+----------+---------+------------+
```

2. CONVERSION: CAST - string to number and number to string

INPUT (SQL)

```
SELECT order_id,
       amount,
       CAST(amount AS DECIMAL(10,2)) AS amount_decimal,
       CAST(amount AS SIGNED)        AS amount_int,
       CAST(order_id AS CHAR)        AS id_as_text
FROM orders;
```

OUTPUT

```
+----------+---------+----------------+------------+------------+
| order_id | amount  | amount_decimal | amount_int | id_as_text |
+----------+---------+----------------+------------+------------+
|        1 | 1250.75 |        1250.75 |       1250 | 1          |
|        2 | 890.50  |         890.50 |        890 | 2          |
|        3 | 2300.00 |        2300.00 |       2300 | 3          |
|        4 | 450.25  |         450.25 |        450 | 4          |
+----------+---------+----------------+------------+------------+
```

3. CONVERSION: CONVERT - number and date conversion

INPUT (SQL)

```
SELECT CONVERT('123', UNSIGNED) AS text_to_number,
       CONVERT(98.76, CHAR)     AS number_to_text,
       CONVERT('2026-12-25', DATE) AS text_to_date;
```

OUTPUT

```
+----------------+----------------+--------------+
| text_to_number | number_to_text | text_to_date |
+----------------+----------------+--------------+
|            123 | 98.76          | 2026-12-25   |
+----------------+----------------+--------------+
```

4. CONVERSION: STR_TO_DATE - text in any format to a date

INPUT (SQL)

```
SELECT STR_TO_DATE('25-12-2026', '%d-%m-%Y') AS d1,
       STR_TO_DATE('March 5, 2026', '%M %d, %Y') AS d2;
```

OUTPUT

```
+------------+------------+
| d1         | d2         |
+------------+------------+
| 2026-12-25 | 2026-03-05 |
+------------+------------+
```

5. CONVERSION: DATE_FORMAT and FORMAT - date/number to formatted text

INPUT (SQL)

```
SELECT order_id,
       DATE_FORMAT(order_date, '%d-%b-%Y') AS short_date,
       DATE_FORMAT(order_date, '%W, %M %e, %Y') AS long_date,
       FORMAT(CAST(amount AS DECIMAL(10,2)) * 1000, 2) AS amount_formatted
FROM orders;
```

OUTPUT

```
+----------+-------------+---------------------------+------------------+
| order_id | short_date  | long_date                 | amount_formatted |
+----------+-------------+---------------------------+------------------+
|        1 | 15-Jan-2026 | Thursday, January 15, 2026 | 1,250,750.00     |
|        2 | 02-Mar-2026 | Monday, March 2, 2026      | 890,500.00       |
|        3 | 28-Jul-2026 | Tuesday, July 28, 2026     | 2,300,000.00     |
|        4 | 05-Oct-2026 | Monday, October 5, 2026    | 450,250.00       |
+----------+-------------+---------------------------+------------------+
```

6. CONVERSION: implicit conversion (string used in arithmetic)

INPUT (SQL)

```
SELECT '10' + 5 AS implicit_add, '3.5' * 2 AS implicit_mul;
```

OUTPUT

```
+--------------+--------------+
| implicit_add | implicit_mul |
+--------------+--------------+
|           15 |            7 |
+--------------+--------------+
```

7. DATE: current date and time functions

INPUT (SQL)

```
SELECT CURDATE() AS today, CURTIME() AS time_now, NOW() AS date_time_now;
```

OUTPUT

```
+------------+----------+---------------------+
| today      | time_now | date_time_now       |
+------------+----------+---------------------+
| 2026-10-09 | 16:18:20 | 2026-10-09 16:18:20 |
+------------+----------+---------------------+
```

8. DATE: extract parts of a date

INPUT (SQL)

```
SELECT order_id, order_date,
       YEAR(order_date)      AS yr,
       MONTH(order_date)     AS mon,
       DAY(order_date)       AS dy,
       MONTHNAME(order_date) AS month_name,
       DAYNAME(order_date)   AS day_name,
       QUARTER(order_date)   AS qtr
FROM orders;
```

OUTPUT

```
+----------+------------+------+------+------+------------+----------+------+
| order_id | order_date | yr   | mon  | dy   | month_name | day_name | qtr  |
+----------+------------+------+------+------+------------+----------+------+
|        1 | 2026-01-15 | 2026 |    1 |   15 | January    | Thursday |    1 |
|        2 | 2026-03-02 | 2026 |    3 |    2 | March      | Monday   |    1 |
|        3 | 2026-07-28 | 2026 |    7 |   28 | July       | Tuesday  |    3 |
|        4 | 2026-10-05 | 2026 |   10 |    5 | October    | Monday   |    4 |
+----------+------------+------+------+------+------------+----------+------+
```

9. DATE: EXTRACT, WEEK and DAYOFYEAR

INPUT (SQL)

```
SELECT order_date,
       EXTRACT(YEAR FROM order_date) AS yr,
       WEEK(order_date)      AS week_no,
       DAYOFYEAR(order_date) AS day_of_year
FROM orders;
```

OUTPUT

```
+------------+------+---------+-------------+
| order_date | yr   | week_no | day_of_year |
+------------+------+---------+-------------+
| 2026-01-15 | 2026 |       2 |          15 |
| 2026-03-02 | 2026 |       9 |          61 |
| 2026-07-28 | 2026 |      30 |         209 |
| 2026-10-05 | 2026 |      40 |         278 |
+------------+------+---------+-------------+
```

10. DATE: DATE_ADD, DATE_SUB and LAST_DAY

INPUT (SQL)

```
SELECT order_date,
       DATE_ADD(order_date, INTERVAL 10 DAY)   AS plus_10_days,
       DATE_ADD(order_date, INTERVAL 2 MONTH)  AS plus_2_months,
       DATE_SUB(order_date, INTERVAL 1 YEAR)   AS minus_1_year,
       LAST_DAY(order_date)                    AS month_end
FROM orders;
```

OUTPUT

```
+------------+--------------+---------------+--------------+------------+
| order_date | plus_10_days | plus_2_months | minus_1_year | month_end  |
+------------+--------------+---------------+--------------+------------+
| 2026-01-15 | 2026-01-25   | 2026-03-15    | 2025-01-15   | 2026-01-31 |
| 2026-03-02 | 2026-03-12   | 2026-05-02    | 2025-03-02   | 2026-03-31 |
| 2026-07-28 | 2026-08-07   | 2026-09-28    | 2025-07-28   | 2026-07-31 |
| 2026-10-05 | 2026-10-15   | 2026-12-05    | 2025-10-05   | 2026-10-31 |
+------------+--------------+---------------+--------------+------------+
```

11. DATE: DATEDIFF and TIMESTAMPDIFF - difference between dates

INPUT (SQL)

```
SELECT order_id, order_date,
       DATEDIFF('2026-12-31', order_date)               AS days_to_year_end,
       TIMESTAMPDIFF(MONTH, order_date, '2026-12-31')   AS months_to_year_end
FROM orders;
```

OUTPUT

```
+----------+------------+------------------+--------------------+
| order_id | order_date | days_to_year_end | months_to_year_end |
+----------+------------+------------------+--------------------+
|        1 | 2026-01-15 |              350 |                 11 |
|        2 | 2026-03-02 |              304 |                  9 |
|        3 | 2026-07-28 |              156 |                  5 |
|        4 | 2026-10-05 |               87 |                  2 |
+----------+------------+------------------+--------------------+
```

12. DATE: age calculation and filtering by date

INPUT (SQL)

```
SELECT TIMESTAMPDIFF(YEAR, '2005-06-20', '2026-10-09') AS age_in_years;
SELECT * FROM orders WHERE YEAR(order_date) = 2026 AND MONTH(order_date) >= 7;
```

OUTPUT

```
+--------------+
| age_in_years |
+--------------+
|           21 |
+--------------+
+----------+----------+---------+------------+
| order_id | customer | amount  | order_date |
+----------+----------+---------+------------+
|        3 | Meera    | 2300.00 | 2026-07-28 |
|        4 | Karan    | 450.25  | 2026-10-05 |
+----------+----------+---------+------------+
```

LAB 5: Implement SQL Operators (Arithmetic, Comparison and Logical)

Aim: To demonstrate arithmetic, comparison and logical operators in SQL with examples.

1. Create database, table and insert data

INPUT (SQL)

```
DROP DATABASE IF EXISTS lab5;
CREATE DATABASE lab5;
USE lab5;
CREATE TABLE products (
  pid      INT PRIMARY KEY,
  pname    VARCHAR(20),
  category VARCHAR(20),
  price    INT,
  qty      INT
);
INSERT INTO products VALUES
 (1,'Keyboard','Accessories',800,25),
 (2,'Mouse','Accessories',450,40),
 (3,'Monitor','Display',9500,10),
 (4,'Laptop','Computer',55000,5),
 (5,'Webcam','Accessories',2200,0),
 (6,'Printer','Office',7200,8);
SELECT * FROM products;
```

OUTPUT

```
+-----+----------+-------------+-------+------+
| pid | pname    | category    | price | qty  |
+-----+----------+-------------+-------+------+
|   1 | Keyboard | Accessories |   800 |   25 |
|   2 | Mouse    | Accessories |   450 |   40 |
|   3 | Monitor  | Display     |  9500 |   10 |
|   4 | Laptop   | Computer    | 55000 |    5 |
|   5 | Webcam   | Accessories |  2200 |    0 |
|   6 | Printer  | Office      |  7200 |    8 |
+-----+----------+-------------+-------+------+
```

*2. ARITHMETIC operators: + - * / % and DIV*

INPUT (SQL)

```
SELECT 20 + 6 AS addition, 20 - 6 AS subtraction, 20 * 6 AS multiplication,
       20 / 6 AS division, 20 DIV 6 AS integer_division, 20 % 6 AS modulus;
```

OUTPUT

```
+----------+-------------+----------------+----------+------------------+---------+
| addition | subtraction | multiplication | division | integer_division | modulus |
+----------+-------------+----------------+----------+------------------+---------+
|       26 |          14 |            120 |   3.3333 |                3 |       2 |
+----------+-------------+----------------+----------+------------------+---------+
```

3. ARITHMETIC operators applied on table columns

INPUT (SQL)

```
SELECT pname, price, qty,
       price * qty        AS stock_value,
       price + 100        AS price_plus_100,
       price - price*0.10 AS after_10pct_discount,
       price % 1000       AS remainder
FROM products;
```

OUTPUT

```
+----------+-------+------+-------------+----------------+----------------------+-----------+
| pname    | price | qty  | stock_value | price_plus_100 | after_10pct_discount | remainder |
+----------+-------+------+-------------+----------------+----------------------+-----------+
| Keyboard |   800 |   25 |       20000 |            900 |               720.00 |       800 |
| Mouse    |   450 |   40 |       18000 |            550 |               405.00 |       450 |
| Monitor  |  9500 |   10 |       95000 |           9600 |              8550.00 |       500 |
| Laptop   | 55000 |    5 |      275000 |          55100 |             49500.00 |         0 |
| Webcam   |  2200 |    0 |           0 |           2300 |              1980.00 |       200 |
| Printer  |  7200 |    8 |       57600 |           7300 |              6480.00 |       200 |
+----------+-------+------+-------------+----------------+----------------------+-----------+
```

4. COMPARISON operators: = > <

INPUT (SQL)

```
SELECT pname, price FROM products WHERE category = 'Accessories';
SELECT pname, price FROM products WHERE price > 5000;
SELECT pname, qty   FROM products WHERE qty < 10;
```

OUTPUT

```
+----------+-------+
| pname    | price |
+----------+-------+
| Keyboard |   800 |
| Mouse    |   450 |
| Webcam   |  2200 |
+----------+-------+
+---------+-------+
| pname   | price |
+---------+-------+
| Monitor |  9500 |
| Laptop  | 55000 |
| Printer |  7200 |
+---------+-------+
+---------+------+
| pname   | qty  |
+---------+------+
| Laptop  |    5 |
| Webcam  |    0 |
| Printer |    8 |
+---------+------+
```

5. COMPARISON operators: >= <= != (<>)

INPUT (SQL)

```
SELECT pname, price FROM products WHERE price >= 7200;
SELECT pname, price FROM products WHERE price <= 800;
SELECT pname, category FROM products WHERE category <> 'Accessories';
```

OUTPUT

```
+---------+-------+
| pname   | price |
+---------+-------+
| Monitor |  9500 |
| Laptop  | 55000 |
| Printer |  7200 |
+---------+-------+
+----------+-------+
| pname    | price |
+----------+-------+
| Keyboard |   800 |
| Mouse    |   450 |
+----------+-------+
+---------+----------+
| pname   | category |
+---------+----------+
| Monitor | Display  |
| Laptop  | Computer |
| Printer | Office   |
+---------+----------+
```

6. COMPARISON result as 1 (true) / 0 (false) and NULL-safe equal <=>

INPUT (SQL)

```
SELECT 10 > 5 AS gt, 10 = 5 AS eq, 10 != 5 AS ne, NULL = NULL AS null_eq, NULL <=> NULL AS null_safe_eq;
```

OUTPUT

```
+----+----+----+---------+--------------+
| gt | eq | ne | null_eq | null_safe_eq |
+----+----+----+---------+--------------+
|  1 |  0 |  1 |    NULL |            1 |
+----+----+----+---------+--------------+
```

7. LOGICAL operator: AND

INPUT (SQL)

```
SELECT pname, category, price FROM products
WHERE category = 'Accessories' AND price > 500;
```

OUTPUT

```
+----------+-------------+-------+
| pname    | category    | price |
+----------+-------------+-------+
| Keyboard | Accessories |   800 |
| Webcam   | Accessories |  2200 |
+----------+-------------+-------+
```

8. LOGICAL operator: OR

INPUT (SQL)

```
SELECT pname, category, price FROM products
WHERE category = 'Display' OR category = 'Office';
```

OUTPUT

```
+---------+----------+-------+
| pname   | category | price |
+---------+----------+-------+
| Monitor | Display  |  9500 |
| Printer | Office   |  7200 |
+---------+----------+-------+
```

9. LOGICAL operator: NOT

INPUT (SQL)

```
SELECT pname, category FROM products
WHERE NOT category = 'Accessories';
```

OUTPUT

```
+---------+----------+
| pname   | category |
+---------+----------+
| Monitor | Display  |
| Laptop  | Computer |
| Printer | Office   |
+---------+----------+
```

10. LOGICAL operators combined with brackets and XOR

INPUT (SQL)

```
SELECT pname, category, price, qty FROM products
WHERE (category = 'Accessories' OR category = 'Office') AND qty > 0;
SELECT pname, price, qty FROM products
WHERE (price > 5000) XOR (qty > 8);
```

OUTPUT

```
+----------+-------------+-------+------+
| pname    | category    | price | qty  |
+----------+-------------+-------+------+
| Keyboard | Accessories |   800 |   25 |
| Mouse    | Accessories |   450 |   40 |
| Printer  | Office      |  7200 |    8 |
+----------+-------------+-------+------+
+----------+-------+------+
| pname    | price | qty  |
+----------+-------+------+
| Keyboard |   800 |   25 |
| Mouse    |   450 |   40 |
| Laptop   | 55000 |    5 |
| Printer  |  7200 |    8 |
+----------+-------+------+
```

LAB 6: Implement SQL Operators (Special Operators and Set Operations)

Aim: To demonstrate special operators (BETWEEN, IN, LIKE, IS NULL, EXISTS, ANY/ALL) and the UNION set operation.

1. Create database, tables and insert data

INPUT (SQL)

```
DROP DATABASE IF EXISTS lab6;
CREATE DATABASE lab6;
USE lab6;
CREATE TABLE students (
  roll_no INT PRIMARY KEY,
  name    VARCHAR(20),
  city    VARCHAR(20),
  marks   INT,
  email   VARCHAR(30)
);
INSERT INTO students VALUES
 (1,'Swayam','Bangalore',82,'Swayam@mail.com'),
 (2,'Aman','Udaipur',74,NULL),
 (3,'Riya','Delhi',91,'riya@mail.com'),
 (4,'Neha','Bangalore',68,NULL),
 (5,'Karan','Mumbai',55,'karan@mail.com');
CREATE TABLE sports (name VARCHAR(20), sport VARCHAR(20));
INSERT INTO sports VALUES ('Swayam','Chess'),('Riya','Cricket'),('Zoya','Tennis'),('Aman','Chess');
SELECT * FROM students;
SELECT * FROM sports;
```

OUTPUT

```
+---------+--------+-----------+-------+-----------------+
| roll_no | name   | city      | marks | email           |
+---------+--------+-----------+-------+-----------------+
|       1 | Swayam | Bangalore |    82 | Swayam@mail.com |
|       2 | Aman   | Udaipur   |    74 | NULL            |
|       3 | Riya   | Delhi     |    91 | riya@mail.com   |
|       4 | Neha   | Bangalore |    68 | NULL            |
|       5 | Karan  | Mumbai    |    55 | karan@mail.com  |
+---------+--------+-----------+-------+-----------------+
+--------+---------+
| name   | sport   |
+--------+---------+
| Swayam | Chess   |
| Riya   | Cricket |
| Zoya   | Tennis  |
| Aman   | Chess   |
+--------+---------+
```

2. SPECIAL operator: BETWEEN

INPUT (SQL)

```
SELECT name, marks FROM students WHERE marks BETWEEN 70 AND 90;
SELECT name, marks FROM students WHERE marks NOT BETWEEN 70 AND 90;
```

OUTPUT

```
+--------+-------+
| name   | marks |
+--------+-------+
| Swayam |    82 |
| Aman   |    74 |
+--------+-------+
+-------+-------+
| name  | marks |
+-------+-------+
| Riya  |    91 |
| Neha  |    68 |
| Karan |    55 |
+-------+-------+
```

3. SPECIAL operator: IN / NOT IN

INPUT (SQL)

```
SELECT name, city FROM students WHERE city IN ('Bangalore','Delhi');
SELECT name, city FROM students WHERE city NOT IN ('Bangalore','Delhi');
```

OUTPUT

```
+--------+-----------+
| name   | city      |
+--------+-----------+
| Swayam| Bangalore |
| Riya   | Delhi     |
| Neha   | Bangalore |
+--------+-----------+
+-------+---------+
| name  | city    |
+-------+---------+
| Aman  | Udaipur |
| Karan | Mumbai  |
+-------+---------+
```

4. SPECIAL operator: LIKE with % and _ wildcards

INPUT (SQL)

```
SELECT name FROM students WHERE name LIKE 'S%';
SELECT name FROM students WHERE name LIKE '%a';
SELECT name FROM students WHERE name LIKE '_i%';
```

OUTPUT

```
+--------+
| name   |
+--------+
| Swayam|
+--------+
+------+
| name |
+------+
| Riya |
| Neha |
+------+
+------+
| name |
+------+
| Riya |
+------+
```

5. SPECIAL operator: IS NULL / IS NOT NULL

INPUT (SQL)

```
SELECT name, email FROM students WHERE email IS NULL;
SELECT name, email FROM students WHERE email IS NOT NULL;
```

OUTPUT

```
+------+-------+
| name | email |
+------+-------+
| Aman | NULL  |
| Neha | NULL  |
+------+-------+
+--------+-----------------+
| name   | email           |
+--------+-----------------+
| Swayam| Swayam@mail.com |
| Riya   | riya@mail.com   |
| Karan  | karan@mail.com  |
+--------+-----------------+
```

6. SPECIAL operator: EXISTS

INPUT (SQL)

```
SELECT name FROM students s
WHERE EXISTS (SELECT 1 FROM sports p WHERE p.name = s.name);
```

OUTPUT

```
+--------+
| name   |
+--------+
| Swayam|
| Aman   |
| Riya   |
+--------+
```

7. SPECIAL operators: ANY and ALL

INPUT (SQL)

```
SELECT name, marks FROM students
WHERE marks > ALL (SELECT marks FROM students WHERE city = 'Bangalore');
SELECT name, marks FROM students
WHERE marks > ANY (SELECT marks FROM students WHERE city = 'Bangalore');
```

OUTPUT

```
+------+-------+
| name | marks |
+------+-------+
| Riya |    91 |
+------+-------+
+--------+-------+
| name   | marks |
+--------+-------+
| Swayam|    82 |
| Aman   |    74 |
| Riya   |    91 |
+--------+-------+
```

8. SET operation: UNION (removes duplicates)

INPUT (SQL)

```
SELECT name FROM students
UNION
SELECT name FROM sports;
```

OUTPUT

```
+--------+
| name   |
+--------+
| Swayam|
| Aman   |
| Riya   |
| Neha   |
| Karan  |
| Zoya   |
+--------+
```

9. SET operation: UNION ALL (keeps duplicates)

INPUT (SQL)

```
SELECT name FROM students
UNION ALL
SELECT name FROM sports;
```

OUTPUT

```
+--------+
| name   |
+--------+
| Swayam|
| Aman   |
| Riya   |
| Neha   |
| Karan  |
| Swayam|
| Riya   |
| Zoya   |
| Aman   |
+--------+
```

10. SET operation: UNION with different columns and ORDER BY

INPUT (SQL)

```
SELECT name, 'Student' AS source FROM students WHERE marks >= 80
UNION
SELECT name, sport FROM sports
ORDER BY name;
```

OUTPUT

```
+--------+---------+
| name   | source  |
+--------+---------+
| Aman   | Chess   |
| Riya   | Student |
| Riya   | Cricket |
| Swayam| Student |
| Swayam| Chess   |
| Zoya   | Tennis  |
+--------+---------+
```

11. SET operations: INTERSECT and EXCEPT (extra)

INPUT (SQL)

```
SELECT name FROM students
INTERSECT
SELECT name FROM sports;
SELECT name FROM students
EXCEPT
SELECT name FROM sports;
```

OUTPUT

```
+--------+
| name   |
+--------+
| Swayam|
| Aman   |
| Riya   |
+--------+
+-------+
| name  |
+-------+
| Neha  |
| Karan |
+-------+
```