

# INSPECTION CERTIFICATE

발급일자 : 2024.04.20

DATE OF ISSUE : 2024.04.20

재품명 : 강재 맞대기 용접식 관이음쇠

COMMODITY :

61-7 Gimhae-daero 1031beonan-gil, Haeilim-myeon, Gimhae-si,  
Gyeongsangnam-do, Korea  
Tel : 055-902-6453 / Fax : 055-902-6452

증명서번호 : MSQ240420001  
CERTIFICATE NO :  
수요자 :  
CUSTOMER :  
주문자 :  
SHIPPER :

| Spec. for Material                  | Spec. for Inspection | Test Piece Size | Visual Inspection        | Dimension Inspection | Heat Treatment    |       |       |    |    |    |    |   |                       |           |         |                  |                     |                   |     |
|-------------------------------------|----------------------|-----------------|--------------------------|----------------------|-------------------|-------|-------|----|----|----|----|---|-----------------------|-----------|---------|------------------|---------------------|-------------------|-----|
| KS D 3507                           | KS B 1543            | KS B 0801       | GOOD                     | GOOD                 | 850°C Time ( min) |       |       |    |    |    |    |   |                       |           |         |                  |                     |                   |     |
| DESCRIPTION                         | Q/V (EA)             | HEAT No.        | CHEMICAL COMPOSITION (%) |                      |                   |       |       |    |    |    |    |   | MECHANICAL PROPERTIES |           |         | Flat tening Test | Hardn ess Test (HB) | Hydrost atic Test | NDT |
|                                     |                      |                 | C                        | Si                   | Mn                | P     | S     | Ni | Cr | Mo | Cu | V | Y.S (Mpa)             | T.S (Mpa) | E.L (%) |                  |                     |                   |     |
|                                     |                      |                 |                          |                      |                   |       |       |    |    |    |    |   |                       |           |         |                  |                     |                   |     |
| 90D ELBOW (L) 50A SPP<br>B.W BLACK  | 37                   | SB01928         | 0.05                     | 0.05                 | 0.397             | 0.008 | 0.002 |    |    |    |    |   | 279.1                 | 418.6     | 40      |                  |                     | G                 |     |
| 90D ELBOW (L) 65A SPP<br>B.W BLACK  | 1                    | SP01928         | 0.14                     | 0.01                 | 0.435             | 0.01  | 0.004 |    |    |    |    |   | 306.1                 | 431.4     | 38      |                  |                     | G                 |     |
| 90D ELBOW (L) 50A SPP<br>B.W BLACK  | 129                  | SB01928         | 0.05                     | 0.05                 | 0.397             | 0.008 | 0.002 |    |    |    |    |   | 279.1                 | 418.6     | 40      |                  |                     | G                 |     |
| 90D ELBOW (L) 80A SPP<br>B.W BLACK  | 34                   | SP69453         | 0.07                     | 0.01                 | 0.32              | 0.01  | 0.007 |    |    |    |    |   | 288.1                 | 393.5     | 40      |                  |                     | G                 |     |
| 90D ELBOW (L) 65A SPP<br>B.W BLACK  | 48                   | SP01928         | 0.14                     | 0.01                 | 0.435             | 0.01  | 0.004 |    |    |    |    |   | 306.1                 | 431.4     | 38      |                  |                     | G                 |     |
| 90D ELBOW (L) 125A SPP<br>B.W BLACK | 6                    | SQ69157         | 0.07                     | 0.01                 | 0.3               | 0.011 | 0.004 |    |    |    |    |   | 277.2                 | 395.6     | 41      |                  |                     | G                 |     |
| 90D ELBOW (L) 100A SPP<br>B.W BLACK | 27                   | SF70696         | 0.07                     | 0.01                 | 0.3               | 0.012 | 0.008 |    |    |    |    |   | 262.3                 | 388.9     | 40      |                  |                     | G                 |     |
| 90D ELBOW (L) 125A SPP<br>B.W BLACK | 17                   | SQ69157         | 0.07                     | 0.01                 | 0.31              | 0.011 | 0.004 |    |    |    |    |   | 277.2                 | 395.6     | 41      |                  |                     | G                 |     |
| 90D ELBOW (L) 200A SPP<br>B.W BLACK | 2                    | S83824          | 0.07                     | 0.01                 | 0.77              | 0.01  | 0.006 |    |    |    |    |   | 280.2                 | 416.0     | 37      |                  |                     | G                 |     |
| 90D ELBOW (L) 150A SPP<br>B.W BLACK | 48                   | SB23186         | 0.03                     | 0.01                 | 0.31              | 0.011 | 0.004 |    |    |    |    |   | 274.9                 | 362.6     | 41.0    |                  |                     | G                 |     |

\* We hereby certify, that the products described herein has been manufactured and tested in accordance with the specification.  
\* Repair welding has not performed on the material

Approved By :

QA Dept. Manager