Open a pull request

Create a new pull request by comparing changes across two branches. If you need to, you can also compare across forks. Learn more about diff comparisons here.

base repository: Governikus/eidas-middleware ▾   base: master ▾   ←   head repository: swedenconnect/eidas-middle... ▾   compare: 3.4.0-swedenconnect-hsm ▾

✓ **Able to merge.** These branches can be automatically merged.

Add a title

3.4.0 swedenconnect hsm

Add a description

Write   Preview

Add your description here...

Markdown is supported   Paste, drop, or click to add files

Create pull request ▾

Helpful resources

Contributing

GitHub Community Guidelines

Remember, contributions to this repository should follow its contributing guidelines.

16 commits   **8** files changed   **1** contributor

Commits on Dec 4, 2020

- **Revert " Release eumw-2.0.1"** … — **Razumain** committed on Dec 4, 2020 — f18e1a5
- **Revert "Revert " Release eumw-2.0.1""** … — **Razumain** committed on Dec 4, 2020 — 1b0d5b3

Commits on Jan 14, 2021

- **Merge remote-tracking branch 'upstream/master'** — **Razumain** committed on Jan 14, 2021 — 1c256fe

Commits on Nov 19, 2021

- **Merge remote-tracking branch 'upstream/master'** — **Razumain** committed on Nov 19, 2021 — 816617b

Commits on Dec 19, 2021

- **Merge remote-tracking branch 'upstream/master'** — **Razumain** committed on Dec 19, 2021 — 9ac833b

Commits on Mar 13, 2022

- **Merge remote-tracking branch 'upstream/master'** — **Razumain** committed on Mar 13, 2022 — 7dfc39e

Commits on May 26, 2022

- **Merge remote-tracking branch 'upstream/master'** — **Razumain** committed on May 26, 2022 — c6cbaed

Commits on Jul 11, 2022

- **Merge remote-tracking branch 'upstream/master'** — **Razumain** committed on Jul 11, 2022 — 9c8e695

Commits on Apr 18, 2023

- **Merge remote-tracking branch 'upstream/master'** — **Razumain** committed on Apr 18, 2023 — 9c580a3

Commits on Dec 4, 2023

- **Merge remote-tracking branch 'upstream/master'** — **Razumain** committed on Dec 4, 2023 — 0ab7d2e

Commits on Jan 11, 2024

- **Merge remote-tracking branch 'upstream/master'** — **Razumain** committed on Jan 11, 2024 — 1d96c0a

Commits on Jun 17, 2024

- **Merge remote-tracking branch 'upstream/master'** — **Razumain** committed on Jun 17, 2024 — aea932d

Commits on Mar 19, 2025

- **Merge remote-tracking branch 'upstream/master'** — **Razumain** committed 3 weeks ago — 0f8c4e7

Commits on Mar 20, 2025

- **SC Updates to 3.4.0** — **Razumain** committed 3 weeks ago — 1c32f22
- **Update documentation** — **Razumain** committed 3 weeks ago — 1a65818

Commits on Apr 10, 2025

- **Making the RestrictedHSMProvider a non @component** … — **Razumain** committed 3 minutes ago — 10cf797

Showing 8 changed files with **121 additions** and **6 deletions**.   Split   Unified

4 .gitignore

```diff
@@ -1,9 +1,13 @@
 target/
 packer/
+out/
 *Jenkinsfile*
 .hg/
 /helm/
 
+# Mac
+.DS_Store
+
 # IntelliJ project files
 *.iml
 *.iws
```

BIN +595 KB ...vernikus:master...swedenconnect:3.4.0-swedenconnect-hsm · Governikus:eidas-middleware.pdf

Binary file not shown.

23 Dockerfile

```diff
@@ -0,0 +1,23 @@
+FROM openjdk:17-jdk-slim
+#FROM docker.sunet.se/openjdk-jre-luna:luna7.4-jre11
+#FROM docker.sunet.se/openjdk-jre-luna:ubuntu-luna7.4-jre11
+
+# Define the spring boot configuration directory
+ENV CONFIG_DIR=/opt/eidas-middleware/configuration
+
+# Define the location of the configuration directory inside of the container
+ENV SPRING_CONFIG_ADDITIONAL_LOCATION=file:${CONFIG_DIR}/
+
+# Expose the ports we're interested in
+EXPOSE 8443
+EXPOSE 10000
+
+RUN mkdir -p /opt/eidas-middleware
+WORKDIR /opt/eidas-middleware
+
+# Add built eidas middleware application
+ADD eidas-middleware/target/eidas-middleware.jar eidas-middleware.jar
+RUN mkdir -p ${CONFIG_DIR}
+
+#ENTRYPOINT ["java", "-jar", "./eidas-middleware.jar"]
+ENTRYPOINT ["java","-agentlib:jdwp=transport=dt_socket,server=y,suspend=n,address=*:8218","-jar","eidas-middleware.jar"]
```

2 ...-middleware/src/test/java/de/governikus/eumw/eidasmiddleware/MetadataServiceImplTest.java

```diff
@@ -92,7 +92,7 @@ public void setUp() throws Exception
     configuration.setXmlConfigBlob(createConfiguration());

 Mockito.when(configurationRepository.findById(1L)).thenReturn(java.util.Optional.of(configuration));
     metadataService = new MetadataServiceImpl(buildProperties, hsmServiceHolder,
-                                              new ConfigurationService(configurationRepository));
+                                              new ConfigurationService(configurationRepository, null, null, null));
   }


```

56 poseidas/src/main/java/de/governikus/eumw/pkcs11/RestrictedHSMProvider.java

```diff
@@ -0,0 +1,56 @@
+package de.governikus.eumw.pkcs11;
+
+import java.security.KeyStore;
+import java.security.Provider;
+import java.security.Security;
+
+import org.springframework.beans.factory.annotation.Value;
+import org.springframework.core.io.Resource;
+import org.springframework.stereotype.Component;
+
+import de.governikus.eumw.poseidas.server.idprovider.config.KeyPair;
+import lombok.extern.slf4j.Slf4j;
+
+/**
+ * Provides a Restricted HSM bean component for a HSM that is restricted
+ * to providing a SAML signing key.
+ *
+ */
+@Slf4j
+public class RestrictedHSMProvider {
+
+  private KeyPair signingKeyPair = null;
+
+  public RestrictedHSMProvider(
+    @Value("${sc-hsm.p11-config-file:#{null}}") String p11ConfigFile,
+    @Value("${sc-hsm.p11-pin:#{null}}") String p11Pin,
+    @Value("${sc-hsm.p11-alias:#{null}}") String p11Alias
+  ) throws Exception {
+    if (p11ConfigFile != null) {
+      log.info("Initializing Restricted HSM provider ...");
+      initHSMKey(p11ConfigFile, p11Pin, p11Alias);
+    } else {
+      log.info("No restricted HSM provider configured");
+    }
+  }
+
+  private void initHSMKey(final String pkcs11ConfigFilePath, String password,
+    String alias) throws Exception {
+    Provider createdPkcs11Provider = null;
+    if (pkcs11ConfigFilePath != null) {
+      createdPkcs11Provider = Security.getProvider("SunPKCS11");
+      createdPkcs11Provider = createdPkcs11Provider.configure(pkcs11ConfigFilePath);
+      Security.addProvider(createdPkcs11Provider);
+    }
+
+    KeyStore keyStore = KeyStore.getInstance("PKCS11", createdPkcs11Provider);
+    keyStore.load(null, password.toCharArray());
+    signingKeyPair = new KeyPair(keyStore, alias, password);
+
+  }
+
+  public KeyPair getHSMSigningKeyPair() {
+    return signingKeyPair;
+  }
+
+}
```

35 .../main/java/de/governikus/eumw/poseidas/server/idprovider/config/ConfigurationService.java

```diff
@@ -24,6 +24,7 @@
 import org.apache.commons.lang3.StringUtils;
 import org.opensaml.core.config.InitializationException;
 import org.opensaml.core.xml.io.UnmarshallingException;
+import org.springframework.beans.factory.annotation.Value;
 import org.springframework.stereotype.Service;
 import org.springframework.web.util.UriComponentsBuilder;
 
@@ -39,6 +40,7 @@
 import de.governikus.eumw.eidasmiddleware.eid.RequestingServiceProvider;
 import de.governikus.eumw.eidasstarterkit.EidasMetadataNode;
 import de.governikus.eumw.eidasstarterkit.EidasSaml;
+import de.governikus.eumw.pkcs11.RestrictedHSMProvider;
 import de.governikus.eumw.utils.key.KeyReader;
 import de.governikus.eumw.utils.key.KeyStoreSupporter;
 import de.governikus.eumw.utils.xml.XmlException;
@@ -53,7 +55,6 @@
  * This class is a service providing methods to load and save the {@link EidasMiddlewareConfig}
  */
 @Service
-@RequiredArgsConstructor
 @Slf4j
 public class ConfigurationService
 {
@@ -62,6 +63,17 @@ public class ConfigurationService
 
   private final ConfigurationRepository configurationRepository;
 
+  private final RestrictedHSMProvider restrictedHSMProvider;
+
+  public ConfigurationService(final ConfigurationRepository configurationRepository,
+      @Value("${sc-hsm.p11-config-file:#{null}}") String p11ConfigFile,
+      @Value("${sc-hsm.p11-pin:#{null}}") String p11Pin,
+      @Value("${sc-hsm.p11-alias:#{null}}") String p11Alias
+  ) throws Exception {
+    this.configurationRepository = configurationRepository;
+    this.restrictedHSMProvider = new RestrictedHSMProvider(p11ConfigFile, p11Pin, p11Alias);
+  }
+
   /**
    * Get the current configuration from the database
    *
@@ -183,6 +195,27 @@ public String getServerURLWithEidasContextPath()
   public KeyPair getKeyPair(String keyPairName)
   {
     var configuration = getConfiguration();
+
+    /*
+     * Sweden Connect addition for extracting an HSM signing key
+     */
+    String signatureKeyPairName = configuration.get()
+      .getEidasConfiguration()
+      .getSignatureKeyPairName();
+
+    if (signatureKeyPairName.equals(keyPairName)){
+      // Get a configured HSM signing key
+      KeyPair hsmSigningKeyPair = restrictedHSMProvider.getHSMSigningKeyPair();
+      if (hsmSigningKeyPair != null) {
+        // return HSM signing key
+        log.debug("Using restricted HSM provider signing key");
+        return hsmSigningKeyPair;
+      }
+    }
+    /*
+     * End Sweden Connect extension
+     */
     if (configuration.isEmpty())
     {
       throw new ConfigurationException("No configuration present");
```

5 ...t/java/de/governikus/eumw/poseidas/server/idprovider/config/ConfigurationServiceTest.java

```diff
@@ -60,9 +60,8 @@ class ConfigurationServiceTest
   private ConfigurationRepository configurationRepository;

   @BeforeEach
-  void setUp()
-  {
-    configurationService = new ConfigurationService(configurationRepository);
+  void setUp() throws Exception {
+    configurationService = new ConfigurationService(configurationRepository, null, null, null);
   }

   @AfterEach
```

2 ...s/src/test/java/de/governikus/eumw/poseidas/server/pki/TlsClientRenewalDbServiceTest.java

```diff
@@ -133,7 +133,7 @@ void testStoreCertificateSuccess() throws Exception
     certificates.add(csrCertificateAsByteArray);

     TimerHistoryService timerHistoryServiceMock = Mockito.mock(TimerHistoryService.class);
-    ConfigurationService configurationService = new ConfigurationService(configurationRepository);
+    ConfigurationService configurationService = new ConfigurationService(configurationRepository, null, null, null);

     tlsClientRenewalDbService = new TlsClientRenewalDbService(configurationService, requestSignerCertificateService,
                                                               pendingCsrRepository, termAuthServiceBean,
```