1. System requirements

Software	Version
Java 2 SDK, Standard Edition (J2SE)	1.4.1 or higher
Java 2 SDK, Enterprise Edition (J2EE)	1.3.1, includes the Cloudscape database

Set `JAVA_HOME` to the J2SE SDK and `J2EE_HOME` to the J2EE SDK, and add `$JAVA_HOME/bin` to `PATH`.

Java™ Pet Store 1.3.2

Administration Guide

Document	PS-AG-01
Version	1.3.2
Audience	System administrators and build engineers
Based on	Sun Microsystems, "Installing", "Configuring" and "Building the Demo", Java Pet Store Demo 1.3.2

2. Installing

1. Unzip `petstore-1_3_2.zip`. The folder `petstore1.3.2` is created (`<petstore.home>`).
2. Install and configure the message services and database resources: `cd <petstore.home>; sh setup.sh` (Windows: `setup.bat`).
3. Start Cloudscape: `cd $J2EE_HOME/bin; cloudscape -start`.
4. Start the J2EE server: `cd $J2EE_HOME/bin; j2ee -verbose`.
5. Deploy the applications: `cd <petstore.home>; sh setup.sh deploy`.

The four applications are deployed from `petstore.ear`, `opc.ear`, `supplier.ear` and `petstoreadmin.ear`. The context roots are `/petstore`, `/opc`, `/supplier` and `/admin` on port 8000.

3. Configuring

3.1 E-mail notifications

Notifications about order status are disabled by default. Enable them in `src/apps/opc/src/ejb-jar.xml` by setting these env-entries to `true`:

Env-entry	Notification	Bean
`param/SendApprovalMail`	Order approval	MailOrderApprovalMDB
`param/SendConfirmationMail`	Order confirmation	MailInvoiceMDB
`param/SendCompletedOrderMail`	Order completion	MailCompletedOrderMDB

Then set the mail service in `src/apps/opc/src/sun-j2ee-ri.xml`: `mail-from` (From: address), `mail-host` (mail server) and `name` (user name on the mail server). Rebuild the OPC EAR and redeploy. To test, create a user with your e-mail address and complete an order.

3.2 Adding a localization

The Storefront is internationalised and comes with the English (en) and Japanese (ja) localizations. To add another:

1. Add JSP pages for the locale in `src/apps/petstore/src/docroot/<locale.code>/`.
2. Add `screendefinitions_<locale.code>.xml` to `docroot/WEB-INF`.
3. Add data for the locale to `docroot/populate/Populate-UTF8.xml`. `CategoryDetails`, `ProductDetails` and `ItemDetails` take an `xml:lang` attribute.

3.3 Using another database

The Storefront and Supplier use Cloudscape by default. For another database:

1. Copy the `cloudscape` entry of `populate/PopulateSQL.xml` (create, insert, drop and check statements per table) and give it a new `database` identifier.
2. Copy the `cloudscape` entry of `CatalogDAOSQL.xml` (the select statements) and give it the same identifier.
3. Set the identifier in `WEB-INF/web.xml` of the Storefront (`param/CatalogDAODatabase` and the populate `Database` parameter).

> Tables of the OPC and Supplier entity beans are created by the J2EE server at deployment. They are not part of PopulateSQL.xml.

4. Building

Ant 1.4.1 is bundled. The bundle also holds pre-built EAR files, so building is optional.

Set these properties in `src/build.properties`:

Property	Meaning	Example
j2ee.server.name	Host of the J2EE SDK	localhost
j2ee.server.port	HTTP port of the J2EE SDK	8000
j2ee.home	J2EE SDK folder	~/j2sdkee1.3.1
j2ee-script-suffix	Suffix of J2EE scripts	none (Unix), .bat (Windows)
jwsdp-script-suffix	Suffix of JWSDP scripts	.sh (Unix), .bat (Windows)

Run `build.sh [target]` in `<petstore.home>/src`. Targets: `core` (default, builds everything), `clean`, `deploy`, `undeploy`, `verify` (J2EE verifier), `docs` (Javadoc). To build one application run the script in `src/apps/<app>/src`, where app is petstore, opc, supplier or admin. EAR files are written to `src/apps/<app>/build`.