

MICROSAR ComStackLib

Document Information

History

Author	Date	Version	Remarks
	- -		
	- -		
	- -		- -
	- -		
	- -		

Reference Documents

No.	Source	Title	Version
[1]		-	



Caution

Contents

1	Component History	6
2	Introduction.....	7
3	Functional Description	9
4	Integration.....	19
5	Configuration	33
6	Glossary and Abbreviations	40
7	Contact.....	42

Illustrations


[illegible]

1 Component History


Component Version	New Features
	- - - -
	- - - - -
	- -

2 Introduction

Supported AUTOSAR Release*:	
Supported Configuration Variants:	- - -



2.1 Architecture Overview



¹ Extensions for AUTOSAR
XTADC, EEPTEXT, FLSEXT, ETHSWTEXT and WDGEXT
Library represented in ETHTSYN and STBM


Vector Standard Software

3rd Party Software

¹ Available
² Includes E
³ Functiona

3 Functional Description

-




-


3.1 CONFIG-CLASS of Data

3.2 CONFIG-CLASS PRE-COMPILE Optimizations


3.2.1 Optimize Const Data to Defines




3.2.2 Optimize Data Types




3.2.3 Optimize Bool Data in Structs






3.2.4 Data Deduplication and Reduction


3.2.4.1 Equal Data



3.2.4.2 Unary and Binary Operations




3.2.5 Data Streaming



3.3 CONFIG-CLASS Independent Optimizations

3.3.1 Sort Struct Elements



3.4 SELECTABLE Optimizations

3.4.1 Merge of VAR and CONST Based Data



Example

3.5 Freedom from Interference

> Index checking:

> Index saturation:

4 Integration


4.1 Dynamic Files

File Name	Description
	<div data-bbox="480 707 504 913"><div>></div><div>></div><div>></div><div>></div><div>></div></div> <div data-bbox="632 927 644 945">-</div> <div data-bbox="807 927 820 945">-</div>
	<div data-bbox="480 1048 504 1299"><div>></div><div>></div><div>></div><div>></div><div>></div><div>></div></div> <div data-bbox="632 1317 644 1335">-</div> <div data-bbox="807 1317 820 1335">-</div>
	<div data-bbox="480 1404 504 1610"><div>></div><div>></div><div>></div><div>></div><div>></div></div> <div data-bbox="632 1624 644 1641">-</div>
	<div data-bbox="480 1711 504 1962"><div>></div><div>></div><div>></div><div>></div><div>></div><div>></div></div> <div data-bbox="632 1975 644 1993">-</div> <div data-bbox="938 1975 951 1993">-</div>

File Name	Description
	<div data-bbox="481 360 502 562"><div>></div><div>></div><div>></div><div>></div><div>></div></div> <div data-bbox="632 580 643 591">-</div> <div data-bbox="826 580 837 591">-</div>
	<div data-bbox="481 667 502 909"><div>></div><div>></div><div>></div><div>></div><div>></div><div>></div></div> <div data-bbox="632 929 643 940">-</div> <div data-bbox="826 929 837 940">-</div>

4.2 IMPLEMENTATION-CONFIG-VARIANT dependent Data

- - - - -




Expert Knowledge

IMPLEMENTATION- CONFIG-VARIANT	Description
- -	> - - > - -
- -	> - - > - - > - -
- -	> - - > - - > - -

4.3 Optimization Levels

Optimization	Description



Optimization Level				
Parameter				
	TRUE	TRUE	TRUE	TRUE
	DEDUPLICATE_CONST_DATA_WITH_CAST	DEDUPLICATE_CONST_DATA_WITH_CAST	DEDUPLICATE_CONST_DATA_WITH_CAST	DEDUPLICATE_CONST_DATA_WITH_CAST
	TRUE	TRUE	TRUE	TRUE
	TRUE	TRUE	TRUE	TRUE
	BITMASKING	BOOLEAN	BOOLEAN	BITMASKING
	TRUE	TRUE	TRUE	TRUE
	2	0	0	2
	2	0	0	2
	2	0	0	2
	2	0	0	2
	2	0	0	2
	FALSE	FALSE	FALSE	FALSE
	FALSE	FALSE	TRUE	TRUE

4.4 MISRA, PRQA and Compiler Warnings

4.4.1 General



Note

Deviation ID	MD_CSL_3199
	<pre>#define MSN_PROCESS_DATA STD_OFF #define MSN_USE_DUMMY_STATEMENT STD_ON void Msn_foo(uint8 a) { #if (MSN_PROCESS_DATA == STD_ON) /* some code which uses the parameter a */ #endif #if (MSN_USE_DUMMY_STATEMENT == STD_ON) # if (MSN_PROCESS_DATA == STD_OFF) a=a; # endif #endif }</pre>

Deviation ID	MD_CSL_750_759
	<pre>/* symbolic data access for A2L */ typedef struct sMsn_FooDataStructType { boolean indexA; boolean indexB; } Msn_FooDataStructType; /* union data type to have array and symbolic data access */ typedef union uMsn_FooDataType { boolean raw[2]; /**< this element is used for array based data access from the embedded code */ Msn_FooDataStructType str; /**< this element is used for symbolic based data access from A2L */ } Msn_FooDataUType; /* this variable array uses the union data type */ Msn_FooDataUType msn_FooData;</pre>

Deviation ID	MD_CSL_0779
	<pre>#if (MSN_DEFRXSIGGRPINFOENDIDXOFDEFRXPDUINFO == STD_ON) { Msn_DefRxSigGrpInfoEndIdxOfDefRxPduInfoType idxRxSigGrpInfo = Msn_GetDefRxSigGrpInfoStartIdxOfDefRxPduInfo(idxRxPduInfo); /* some code */ } #endif</pre>

-

Deviation ID	MD_CSL_2018
	<pre> #define MSN_PROCESS_DATA STD_ON #define MSN_CASE_SMALL 5 #define MSN_CASE_MEDIUM 8 #define MSN_CASE_LARGE 12 #define MSN_CASE_SMALL_USED FALSE #define MSN_CASE_MEDIUM_USED TRUE #define MSN_CASE_LARGE FALSE /* this array is reduced to a constant define const uint8 msn_FooData [2] = { MSN_CASE_MEDIUM, MSN_CASE_MEDIUM }; */ #define Msn_GetFooData (Index) MSN_CASE_MEDIUM void Msn_foo(uint8 a) { #if (MSN_PROCESS_DATA == STD_ON) switch(Msn_GetFooData(a)) { #if (MSN_CASE_SMALL_USED == STD_ON) case MSN_CASE_SMALL: /* some MSN_CASE_SMALL code */ break; #endif #if (MSN_CASE_MEDIUM_USED == STD_ON) case MSN_CASE_MEDIUM: /* some MSN_CASE_MEDIUM code */ break; #endif #if (MSN_CASE_LARGE_USED == STD_ON) case MSN_CASE_LARGE: /* some MSN_CASE_LARGE code */ break; #endif default: /* some default handling like calling Det */ } #endif } </pre>

Deviation ID	MD_CSL_3355_3356_3358_3359
	<pre>#define MSN_PROCESS_DATA STD_ON /* this array is reduced to a define const boolean msn_FooData [2] = { TRUE, TRUE }; */ #define Msn_IsFooData (Index) TRUE void Msn_foo(uint8 a) { #if (MSN_PROCESS_DATA == STD_ON) if (Msn_IsFooData(a)) { /* some code */ } #endif }</pre>

Deviation ID	MD_CSL_3453
	-
	<pre>#define MSN_PROCESS_DATA STD_ON /* this array is accessed by a generated data access macro */ const boolean msn_FooData [2] = { TRUE, TRUE }; #define Msn_IsFooData (Index) msn_FooData[Index] void Msn_foo(uint8 a) { #if (MSN_PROCESS_DATA == STD_ON) if (Msn_IsFooData(a)) { /* some code */ } #endif }</pre>

Deviation ID	MD_CSL_310
	- - -
	<pre>#define Msn_GetFoo(Index) 1U #define Msn_HasFoo () (Msn_ConfigDataPtr->FooPtrOfPCConfig != NULL_PTR) #define Msn_Foo ((Msn_FooPtrType) (&(Msn_PCConfig))) CONST(Msn_PCConfigsType, MSN_CONST) Msn_PCConfig = { { /* Index: 0 Keys: [Config_LeftFront] */ Msn_Foo /**< the pointer to Msn_Foo */ /* PRQA S 0310 */ /* MD_CSL_310 */ , 5U /**< the number of elements in Msn_Foo */ }, { /* Index: 1 Keys: [Config_RightFront] */ NULL_PTR /**< the pointer to Msn_Foo */ , 0U /**< the number of elements in Msn_Foo */ } };</pre>

4.4.2 Bitfields

BitFieldDataType Literal	Description
	<ul style="list-style-type: none">••
	<ul style="list-style-type: none">••
	<ul style="list-style-type: none">••
	<ul style="list-style-type: none">••

4.4.3 <MSN>_Has Macros in the SELECTABLE Use Case



Example

```
Msn_GetFooData()  
Msn_HasFooData()  
  
#define MSN_USE_INIT_POINTER      STD_ON  
  
#define Msn_HasFooData()          TRUE  
  
void Msn_foo(uint8 a)  
{  
    #if (MSN_USE_INIT_POINTER == STD_ON)  
        if (Msn_HasFooData())  
    #endif  
    {  
        /* some code and process Msn_GetFooData() */  
    }  
}
```


5 Configuration

5.1 Configuration Variants

5.2 Configuration with a GCE



Note

Container Name	
Path	
Multiplicity	
Description	

Attribute Name	Value Type	Description

Attribute Name	Value Type	Description

Attribute Name

Attribute Name	Value Type	Description
		-
		- -
		- -

Attribute Name	Value Type	Description
		- -
		- -
		- -
		- -

Attribute Name	Value Type	Description
		- -

Attribute Name	Value Type	Description

6 Glossary and Abbreviations

6.1 Glossary

Term	Description
-	- -

-

6.2 Abbreviations

Abbreviation	Description
	-

7 Contact

>

>

>

>

>

>
