## FIREWALL IPTABLES OUESTIONS

1.	How many predefined chains are in "raw" table?  a) 3  b) 5  c) 4  d) 2
	ANS: d)
2.	<ul><li>"mangle" table is used for?</li><li>a) Packet Forwarding</li><li>b) To alter QOS bits in TCP Header</li><li>c) Masquerading</li><li>d) None of the above</li></ul>
3.	ANS: b) What is the default policy of a user defined chain in any table? a) DROP b) ACCEPT c) Reject d) No default policy
	ANS: d)
4.	How to rename a user defined chain?  a) Iptables –E <old_name> <new_name> b) Iptables –R <old_name> <new_name> c) Iptables –S <old_name> <new_name> d) It's not possible to rename a user defined chain</new_name></old_name></new_name></old_name></new_name></old_name>
	ANS: a)
5.	How the MAC module is used in iptables?  a) -m mac -mac-address xx : xx : xx : xx : xx  b) -m mac -mac-addr xx : xx : xx : xx : xx  c) -m mac -mac-destination xx : xx : xx : xx : xx  d) -m mac -mac-source xx : xx : xx : xx : xx
	ANS: d)
6.	Packet filter firewall work up to which layer?  a) Transport layer ( Layer 4)  b) Network layer (Layer 3)  c) Application layer (Layer 5)  d) Data Link layer (Layer 2)
	ANS: b)
7.	Iptables is a

a) Host based firewall

## FIREWALL IPTABLES QUESTIONS

- b) Network firewall
- c) Both a) and b)
- d) None of the a) and b)

ANS: c)

- 8. Which type of firewall can restrict spread of computer worms and Trojans?
  - a) Application layer firewall
  - b) Packet filter firewall
  - c) Stateful firewall
  - d) NAT firewall

ANS: a)

- 9. Which of the following rule is syntactically incorrect?
  - a) Iptables -A INPUT -j LOG
  - b) Iptables -A INPUT -sport 80 -j DROP
  - c) Iptables –A INPUT –p tcp –sport 80 –j DROP
  - d) Iptables -A OUTPUT -p tcp -sport 70 -j DROP

ANS: b)

- 10. "Iptables –F" What does this command will do? Choose the most appropriate answer.
  - a) Flush all the rules in all chains of all tables
  - b) Flush all the rules of all INPUT chains of all tables
  - c) Flush all the rules of all OUTPUT chains of all tables
  - d) Flush all the rules of all chains of filter table

ANS: d)

- 11. If one wants to block all the traffic routed through his system, in which table he should put the rule?
  - a) PREROUTING
  - b) POSTROUTING
  - c) INPUT
  - d) FORWARD

ANS: d)

- 12. What tells a firewall how to reassemble a data stream that has been divided into packets?
  - a) The header checksum field in the packet header
  - b) The destination IP address
  - c) The number in header's identification field
  - d) None of the above

ANS: c)

- 13. What is the most effective security approach for a stateless packet filter?
  - a) Deny all except specified hosts
  - b) Allow all except specified hosts

## FIREWALL IPTABLES QUESTIONS

- c) Allow access to only specified destination servers
- d) Deny access to all destination except specified servers

ANS: a)

The practice of designing operational aspects of a system to work with a minimal amount of system privilege is called

- 14. The practice of designing operational aspects of a system to work with a minimal amount of system privilege is called?
  - a) Access denied
  - b) Least privilege
  - c) Failover firewall
  - d) IP Forwarding

ANS: b)

- 15. A stateful firewall maintains a \_\_\_\_\_, which is a list of active connections.
  - a) Routing table
  - b) State table
  - c) Connection table
  - d) Bridging table

ANS: b)