

# Лабораторная работа №5

---

Назирова М.Т.

16 марта 2023

Российский университет дружбы народов, Москва, Россия

## Информация

---

- Назирова Малика Темржоновна
- студентка группы НКабд-04-22
- Факультет физико-математических и естественных наук
- Российский университет дружбы народов
- 1032225197@pfur.ru
- [https://github.com/sweetliiikk/study\\_2022-2023\\_os-intro.git](https://github.com/sweetliiikk/study_2022-2023_os-intro.git)



Ознакомление с инструментами поиска файлов и фильтрации текстовых данных.  
Приобретение практических навыков: по управлению процессами (и заданиями), по проверке использования диска и обслуживанию файловых систем.

## Выполнение лабораторной работы

---

```
[nazirovamt@nazirovamt ~]$ sudo su  
[sudo] пароль для nazirovamt:  
[root@nazirovamt nazirovamt]#
```

## Создаём файл и записываем туда названия файлов из каталога /etc и из домашнего каталога

```
[root@nazirovamt nazirovamt]# touch file.txt
[root@nazirovamt nazirovamt]# ls /etc > file.txt
[root@nazirovamt nazirovamt]# ls /home >> file.txt
[root@nazirovamt nazirovamt]# cat file.txt
abrt
adjtime
aliases
alsa
alternatives
anaconda
anthy-unicode.conf
appstream.conf
asound.conf
audit
authselect
avahi
bash_completion.d
bashrc
bindresvport.blacklist
binfmt.d
bluetooth
brlapi.key
brltty
brltty.conf
ceph
chkconfig.d
chromium
```

## Записываем в файл conf.txt имена всех файлов с расширением .conf из file.txt

```
[root@nazirovamt nazirovamt]# grep .conf file.txt > conf.txt
[root@nazirovamt nazirovamt]# cat conf
cat: conf: Нет такого файла или каталога
[root@nazirovamt nazirovamt]# cat conf.
cat: conf.: Нет такого файла или каталога
[root@nazirovamt nazirovamt]# cat conf.txt
anthy-unicode.conf
appstream.conf
asound.conf
brltty.conf
chkconfig.d
chrony.conf
dconf
dleyna-renderer-service.conf
dleyna-server-service.conf
dnsmasq.conf
dracut.conf
dracut.conf.d
extlinux.conf
fprintd.conf
fuse.conf
host.conf
idmapd.conf
jwhois.conf
kdump.conf
krb5.conf
krb5.conf.d
ld.so.conf
```



## Используя команду find определяем имена, начинавшиеся с символа c

```
[root@nazirovamt nazirovamt]# find ~ -name "c*" -print
/root/.cache/pip/http/4/c
/root/.cache/pip/http/1/2/8/c
/root/.cache/pip/http/c
/root/.cache/pip/http/c/1/4/2/c
/root/.cache/pip/http/c/1/4/2/c/c142c005888845cbebed2978119a034310bc68a893cf35461eb22589
/root/.cache/pip/http/c/b/c
/root/.cache/pip/http/c/b/c/9/4/cbc9492d2a4616aad83530ad74970874936540fe00b6ed22d96d3e13
/root/.cache/pip/http/2/0/a/e/c
/root/.cache/keyring-KD1811/control
/root/.local/lib/python3.10/site-packages/pandocxnos/core.py
/root/.local/lib/python3.10/site-packages/pandocxnos/__pycache__/core.cpython-310.pyc
/root/.texlive2021/texmf-var/luatex-cache/context
/root/.config/gh/config.yml
/root/work/study/2022-2023/Операционные системы/os-intro/.git/hooks/commit-msg.sample
/root/work/study/2022-2023/Операционные системы/os-intro/.git/config
/root/work/study/2022-2023/Операционные системы/os-intro/.git/modules/template/presentation/hooks/commit-
sg.sample
/root/work/study/2022-2023/Операционные системы/os-intro/.git/modules/template/presentation/config
/root/work/study/2022-2023/Операционные системы/os-intro/.git/modules/template/report/hooks/commit-msg.sam
ple
/root/work/study/2022-2023/Операционные системы/os-intro/.git/modules/template/report/config
/root/work/study/2022-2023/Операционные системы/os-intro/config
/root/work/study/2022-2023/Операционные системы/os-intro/config/course
/root/work/study/2022-2023/Операционные системы/os-intro/labs/lab01/report/bib/cite.bib
/root/work/study/2022-2023/Операционные системы/os-intro/labs/lab01/report/pandoc/csl
/root/work/study/2022-2023/Операционные системы/os-intro/labs/lab01/report/pandoc/filters/pandocxnos/core.
py
/root/work/study/2022-2023/Операционные системы/os-intro/labs/lab02/report/bib/cite.bib
/root/work/study/2022-2023/Операционные системы/os-intro/labs/lab02/report/pandoc/csl
/root/work/study/2022-2023/Операционные системы/os-intro/labs/lab02/report/pandoc/filters/pandocxnos/core.
py
/root/work/study/2022-2023/Операционные системы/os-intro/labs/lab03/report/bib/cite.bib
```

Используя команду `find` выводим на экран файлы, начинающиеся с символа `h`, из каталога `/etc`

```
[root@nazirovamt nazirovamt]# find /etc -name "h*" -print
/etc/avahi/hosts
/etc/brltty/Contraction/ha.ctb
/etc/brltty/Input/bm/horizontal.kti
/etc/brltty/Input/hd
/etc/brltty/Input/hm
/etc/brltty/Input/ht
/etc/brltty/Input/hw
/etc/brltty/Text/he.ttb
/etc/brltty/Text/hi.ttb
/etc/brltty/Text/hr.ttb
/etc/brltty/Text/hu.ttb
/etc/brltty/Text/hy.ttb
/etc/containers/oci/hooks.d
/etc/firewalld/helpers
/etc/hp
/etc/hp/hplip.conf
/etc/httpd
/etc/httpd/conf/httpd.conf
/etc/libibverbs.d/hfiverbs.driver
/etc/libibverbs.d/hns.driver
/etc/logrotate.d/httpd
/etc/sane.d/dll.d/hpaio
/etc/sane.d/hp.conf
/etc/sane.d/hp3900.conf
/etc/sane.d/hp4200.conf
/etc/sane.d/hp5400.conf
/etc/sane.d/hpsj5s.conf
/etc/sane.d/hs2p.conf
```

Используя команду `find` запускаем процесс в фоновом режиме, которые будет записывать имена, начинающиеся с `log` в файл `~/logfile`

```
[root@nazirovamt nazirovamt]# find ~ -name "log*" -print > logfile &  
[1] 4319
```

```
[root@nazirovamt nazirovamt]# rm logfile  
rm: удалить обычный файл 'logfile'? y  
[1]+  Завершён      find ~ -name "log*" -print > logfile
```

## Запускаем gedit в фоновом режиме

```
[root@nazirovamt nazirovamt]# gedit &  
[1] 4352
```



## Используем команду ps для определения идентификатора процесса

```
[root@nazirovamt nazirovamt]# ps aux | grep gedit
root      4405  0.0  0.0 222192 2320 pts/0    S+   11:26   0:00 grep --color=auto gedit
```

# Открываем справку о команде kill

```
KILL(1)                                User Commands                                KILL(1)

NAME
    kill - terminate a process

SYNOPSIS
    kill [-signal|-s signal|-p] [-q value] [-a] [--timeout milliseconds signal] [--] pid|name...

    kill -l [number] | -L

DESCRIPTION
    The command kill sends the specified signal to the specified processes or process groups.

    If no signal is specified, the TERM signal is sent. The default action for this signal is to terminate the process. This signal should be used in preference to the KILL signal (number 9), since a process may install a handler for the TERM signal in order to perform clean-up steps before terminating in an orderly fashion. If a process does not terminate after a TERM signal has been sent, then the KILL signal may be used; be aware that the latter signal cannot be caught, and so does not give the target process the opportunity to perform any clean-up before terminating.

    Most modern shells have a builtin kill command, with a usage rather similar to that of the command described here. The --all, --pid, and --queue options, and the possibility to specify processes by command name, are local extensions.

    If signal is 0, then no actual signal is sent, but error checking is still performed.
```

Используем её для завершения процесса gedit

```
[root@nazirovamt nazirovamt]# man kill  
[root@nazirovamt nazirovamt]# kill 4352  
bash: kill: (4352) - Нет такого процесса
```



# Получаем подробную информацию о команде df

```
DF(1)                                     User Commands                               DF(1)

NAME
    df - report file system space usage

SYNOPSIS
    df [OPTION]... [FILE]...

DESCRIPTION
    This manual page documents the GNU version of df. df displays the amount of space available on the file system containing each file name argument. If no file name is given, the space available on all currently mounted file systems is shown. Space is shown in 1K blocks by default, unless the environment variable POSIXLY_CORRECT is set, in which case 512-byte blocks are used.

    If an argument is the absolute file name of a device node containing a mounted file system, df shows the space available on that file system rather than on the file system containing the device node. This version of df cannot show the space available on unmounted file systems, because on most kinds of systems doing so requires very nonportable intimate knowledge of file system structures.

OPTIONS
    Show information about the file system on which each FILE resides, or all file systems by default.

    Mandatory arguments to long options are mandatory for short options too.

    -a, --all
        include pseudo, duplicate, inaccessible file systems

    -B, --block-size=SIZE
        scale sizes by SIZE before printing them; e.g., '-BM' prints sizes in units of 1,048,576 bytes; see SIZE format below
```

## Выполняем команду df

```
[root@nazirovamt ~]# df -vi
```

Файловая система	Инодов	ИИспользовано	ИСвободно	ИИспользовано%	Смонтировано в
devtmpfs	1048576	444	1048132	1%	/dev
tmpfs	501464	1	501463	1%	/dev/shm
tmpfs	819200	873	818327	1%	/run
/dev/sda2	0	0	0	-	/
tmpfs	1048576	46	1048530	1%	/tmp
/dev/sda2	0	0	0	-	/home
/dev/sda1	65536	456	65080	1%	/boot
tmpfs	100292	169	100123	1%	/run/user/1000

# Получаем подробную информацию о команде du

```
DU(1)                                     User Commands                               DU(1)
```

**NAME**

du - estimate file space usage

**SYNOPSIS**

du [OPTION]... [FILE]...

du [OPTION]... --files0-from=F

**DESCRIPTION**

Summarize device usage of the set of FILES, recursively for directories.

Mandatory arguments to long options are mandatory for short options too.

**-0, --null**  
end each output line with NUL, not newline

**-a, --all**  
write counts for all files, not just directories

**--apparent-size**  
print apparent sizes rather than device usage; although the apparent size is usually smaller, it may be larger due to holes in ('sparse') files, internal fragmentation, indirect blocks, and the like

**-B, --block-size=SIZE**  
scale sizes by SIZE before printing them; e.g., '-BM' prints sizes in units of 1,048,576 bytes; see SIZE format below

**-b, --bytes**  
equivalent to '--apparent-size --block-size=1'

```
[nazirovamt@nazirovamt ~]$ du -a ~/file.txt  
4      /home/nazirovamt/file.txt
```

```
-type c  
File is of type c:  
  
b      block (buffered) special  
  
c      character (unbuffered) special  
  
d      directory  
  
p      named pipe (FIFO)  
  
f      regular file
```

## Выводим имена всех директорий, которые есть в домашнем каталоге

```
[nazirovamt@nazirovamt ~]$ find -type d
.
./.mozilla
./.mozilla/extensions
./.mozilla/extensions/{ec8030f7-c20a-464f-9b0e-13a3a9e97384}
./.mozilla/plugins
./.mozilla/firefox
./.mozilla/firefox/fslydgl.default-release
./.mozilla/firefox/fslydgl.default-release/security_state
./.mozilla/firefox/fslydgl.default-release/storage
./.mozilla/firefox/fslydgl.default-release/storage/permanent
./.mozilla/firefox/fslydgl.default-release/storage/permanent/chrome
./.mozilla/firefox/fslydgl.default-release/storage/permanent/chrome/idb
./.mozilla/firefox/fslydgl.default-release/storage/permanent/chrome/idb/3870112724rsegmnoittet-es.files
./.mozilla/firefox/fslydgl.default-release/storage/permanent/chrome/idb/356128849sdhlie.files
./.mozilla/firefox/fslydgl.default-release/storage/permanent/chrome/idb/1451318868ntouromlalnodry--epcr.files
./.mozilla/firefox/fslydgl.default-release/storage/permanent/chrome/idb/1657114595AmcateirvtiSty.files
./.mozilla/firefox/fslydgl.default-release/storage/permanent/chrome/idb/2823318777ntouromlalnodry--naod.files
./.mozilla/firefox/fslydgl.default-release/storage/permanent/chrome/idb/2918063365piupsah.files
./.mozilla/firefox/fslydgl.default-release/storage/temporary
./.mozilla/firefox/fslydgl.default-release/storage/default
./.mozilla/firefox/fslydgl.default-release/storage/default/https+++github.com
./.mozilla/firefox/fslydgl.default-release/storage/default/https+++github.com/ls
./.mozilla/firefox/fslydgl.default-release/storage/default/https+++www.google.com
./.mozilla/firefox/fslydgl.default-release/storage/default/https+++www.google.com/ls
./.mozilla/firefox/fslydgl.default-release/storage/default/https+++web.telegram.org
./.mozilla/firefox/fslydgl.default-release/storage/default/https+++web.telegram.org/idb
./.mozilla/firefox/fslydgl.default-release/storage/default/https+++web.telegram.org/idb/3318935238tbwe.files
./.mozilla/firefox/fslydgl.default-release/storage/default/https+++web.telegram.org/idb/3318935238tbwe.files/journals
```

Спасибо за внимание

---