ITA14 - ETHICAL HACKING
EX - 9

i) Execute and display the results for the following Nmap Timing and performance commands in Kali Linux operating Systems: (i) polite IDS evasion (ii) normal IDS evasion

Aim

To execute and display the results for the following Nmap Timing and performance commands in Kali Linux operating Systems: (i) polite IDS evasion (ii) normal IDS evasion

Procedure

- Open (Cloud Shell Editor)
- (i) Polite IDS evasion
    1. sudo apt update -- press Enter
    2. sudo apt install nmap -y -- press Enter
    3. nmap --version -- press Enter

```
┌──(kali㉿kali)-[~]
└─$ sudo apt update
Hit:1 http://http.kali.org/kali kali-rolling InRelease
1554 packages can be upgraded. Run 'apt list --upgradable' to see them.

┌──(kali㉿kali)-[~]
└─$ sudo apt install nmap -y
nmap is already the newest version (7.991+dfsg-1kali1).
Summary:
  Upgrading: 0, Installing: 0, Removing: 0, Not Upgrading: 1554

┌──(kali㉿kali)-[~]
└─$ nmap --version
Nmap version 7.991 ( https://nmap.org )
Platform: x86_64-pc-linux-gnu
Compiled with: liblua-5.4.9 openssl-3.6.2 libssh2-1.11.1 libz-1.3.2 libpcre2-10.48 libpcap-1.10.6 nmap-libdnet-1.18
.0 ipv6
Compiled without:
Available nsock engines: epoll poll select
```

    4. nmap -T2 scanme.nmap.org -- press Enter
- (ii) Normal IDS evasion
    1. nmap -T3 scanme.nmap.org -- press Enter

```
┌──(kali㉿kali)-[~]
└─$ nmap -T3 scanme.nmap.org
Starting Nmap 7.991 ( https://nmap.org ) at 2026-10-27 11:10 -0400
Warning: Hostname scanme.nmap.org resolves to 2 IPs. Using 45.33.32.156.
Nmap scan report for scanme.nmap.org (45.33.32.156)
Host is up (0.023s latency).
Other addresses for scanme.nmap.org (not scanned): 2600:3c01::f03c:91ff:fe18:bb2f
Not shown: 971 filtered tcp ports (no-response), 26 closed tcp ports (reset)
PORT     STATE SERVICE
22/tcp   open  ssh
80/tcp   open  http
9929/tcp open  nping-echo

Nmap done: 1 IP address (1 host up) scanned in 22.30 seconds
```

Result:

Thus, the Nmap timing and performance commands nmap -T2 scanme.nmap.org for polite timing and nmap -T3 scanme.nmap.org for normal timing were executed in Kali Linux. The commands demonstrate different scan timing profiles. The scan results depend on network conditions and target responses.