Ostbayerische Technische Hochschule Amberg-Weiden
Fakultät Elektrotechnik, Medien und Informatik

Studiengang Elektro- und Informationstechnik

**Bachelorarbeit**

von

Thomas **Mustermann**

# LaTeX im Griff

LaTeX under control

Ostbayerische Technische Hochschule Amberg-Weiden
Fakultät Elektrotechnik, Medien und Informatik

Studiengang Elektro- und Informationstechnik

**Bachelorarbeit**

von

Thomas **Mustermann**

# LaTeX im Griff

LaTeX under control

| | | |
|---|---|---|
| Bearbeitungszeitraum: | von | 1. Oktober 2013 |
| | bis | 31. Januar 2014 |

1. Prüfer: Prof. Dr. Axel Maier

2. Prüfer: Prof. Dr. Bruno Müller

OTH Amberg-Weiden

Elektrotechnik, Medien und Informatik

Eigenständigkeitserklärung gemäß § 27 (8) ASPO

---

Name und Vorname
der Studentin/des Studenten: **Mustermann, Thomas**

Studiengang: **Elektro- und Informationstechnik**

---

Ich bestätige, dass ich die Bachelorarbeit mit dem Titel:

**LaTeX im Griff**

selbständig verfasst, noch nicht anderweitig für Prüfungszwecke vorgelegt, keine anderen als die angegebenen Quellen oder Hilfsmittel benutzt sowie wörtliche und sinngemäße Zitate als solche gekennzeichnet habe.

---

Datum: May 11, 2026

Unterschrift:

---

OTH Amberg-Weiden

Elektrotechnik, Medien und Informatik

Bachelorarbeit Zusammenfassung

---

| | |
|---|---|
| Studentin/Student (Name, Vorname): | **Mustermann, Thomas** |
| Studiengang: | Elektro- und Informationstechnik |
| Aufgabensteller, Professor: | Prof. Dr. Axel Maier |
| Durchgeführt in (Firma/Behörde/Hochschule): | Renner-Verlag, Musterstadt |
| Betreuer in Firma/Behörde: | Dr. Karl Schulze |
| Ausgabedatum: 1. Oktober 2013 | Abgabedatum: 31. Januar 2014 |

---

Titel:

**LaTeX im Griff**

---

Zusammenfassung:

Lorem ipsum dolor sit amet, consetetur sadipscing elitr, sed diam nonumy eirmod tempor invidunt ut labore et dolore magna aliquyam erat, sed diam voluptua. At vero eos et accusam et justo duo dolores et ea rebum. Stet clita kasd gubergren, no sea takimata sanctus est Lorem ipsum dolor sit amet. Lorem ipsum dolor sit amet, consetetur sadipscing elitr, sed diam nonumy eirmod tempor invidunt ut labore et dolore magna aliquyam erat, sed diam voluptua. At vero eos et accusam et justo duo dolores et ea rebum. Stet clita kasd gubergren, no sea takimata sanctus est Lorem ipsum dolor sit amet.

Schlüsselwörter: LaTeX, Textsatz, Formeln, Graphiken

# Contents

**1 Introduction** **1**
1.1 Motivation . . . 1
1.2 Project Goal . . . 2
1.3 Research Focus – Imitation Learning . . . 3

**2 Basics Classical Robotics** **4**
2.1 Erster Abschnitt von Kapitel 2 . . . 4
2.1.1 Ein Unterabschnitt . . . 4
2.1.1.1 Ein Unterabschnitt . . . 4

**3 Basics Intelligent Robotics** **5**
3.1 Machine Learning Basics . . . 5
3.1.1 Mathematical Notation of formulas . . . 5
3.1.2 Glossary . . . 5
3.1.3 Core Machine Learning Categories . . . 6
3.2 Intelligent robots with Deep Learning (RL) . . . 7
3.2.1 Reinforcement Learning . . . 8
3.2.1.1 Mathematical description of the RL problem: . . . 9
3.2.1.2 Knowledge Modality . . . 11
3.2.2 Imitation Learning . . . 12
3.2.2.1 Behavior Cloning (BC) . . . 13
3.2.2.2 Learning from Videos / Observation . . . 13
3.2.3 Summary IL & RL . . . 14

**4 Imitation Learning fundamentals** **16**
4.1 Why Imitation Learning? . . . 16
4.1.1 Idea behind Imitation Learning: . . . 16
4.1.2 Ways to instruct robots . . . 17
4.2 Generalist Robots . . . 20
4.2.1 Data Bottleneck in Robotics . . . 21
4.2.2 Relevant Data Categories for Robotics . . . 22
4.2.3 How to Address the Data Bottleneck . . . 22
4.2.4 Reduce the amount of robot data . . . 25
4.2.5 Challenges of Video Data . . . 30
4.2.6 Other Paths to Generalist Robots. . . . 32

**5 Learning from Video Techniques** **33**
5.1 Extracting Foundational Knowledge from Internet Video . . . . . 33
5.1.1 Video Encoders . . . . . 33
5.1.2 Video Prediction Models . . . . . 33
5.1.3 Video-to-Text Models. . . . . 33
5.2 Video-to-Robot Transfer: Addressing Missing Action Labels and Distribution Shift . . . . . 33
5.3 LfV and Reinforcement Learning . . . . . 33

**Literaturverzeichnis** **34**

**Abbildungsverzeichnis** **37**

**Tabellenverzeichnis** **38**

# Symbole, Formelzeichen und Einheiten

# Chapter 1

# Introduction

## 1.1 Motivation

Roboter werden zukünftig eine Schlüsselrolle in zahlreichen Anwendungsfeldern einnehmen. Be-reits heute steigt der Einsatz von Robotersystemen in der industriellen Produktion kontinuierlich an, da diese insbesondere monotone, einfache und repetitive Aufgaben effizient und zuverlässig übernehmen können. Trotz der teilweisen sehr hohen Anschaffungskosten, investieren immer mehr Unternehmen in die Integration von Roboter in Ihre Produktionslinien. Die Vorteile liegen dabei vor allem in der hohen Verfügbarkeit und Planbarkeit: Nach der Inbe-triebnahme fallen nur noch geringe laufende Betriebskosten an, die sich primär auf Energiever-brauch in From von Strom- und Wartungskosten beschränken. Darüber hinaus können Roboter unabhängig von der Arbeitszeit 24h, 7 Tage die Woche betrieben werden und liefern eine gleich-bleibende Qualität. Dies ermöglicht eine hohe Prozessstabilität sowie eine signifikante Steigerung der Produktivität. Im Gegensatz zu menschlichen Arbeitskräften, werden Roboter nicht krank, nehmen nicht an einen Gewerkschaftsstreik teil und es müssen auch keine Sonderzahlungen in Form von Nacht-, Wochenend- und Feiertagszuschlägen geleistet werden. Grundsätzlich lassen sich Robotersysteme hinsichtlich ihrer Programmierung in zwei Kategorien einteilen. In der industriellen Praxis dominieren derzeit statisch programmierte Roboter, die für klar definierte Aufgaben in strukturierten Umgebungen eingesetzt werden. Sie haben feste Bewe-gungsabläufe und können sich nur in geringem Maße mithilfe integrierter intelligenter Sensoren an ihre Umgebung bzw. an die jeweilige Aufgabe anpassen. Solche Systeme sind besonders effi-zient in standardisierten Produktionsprozessen, stoßen jedoch an ihre Grenzen, sobald sich die Umgebung oder die Anforderungen ändern. Im Gegensatz dazu gewinnen intelligente Robotersysteme zunehmend an Bedeutung. Diese sind in der Lage, auf Veränderungen in ihrer Umgebung zu reagieren und ihr Verhalten adaptiv anzu-passen. Insbesondere durch den Einsatz von Künstlicher Intelligenz eröffnen sich neue Möglich-keiten, komplexe und unstrukturierte Aufgaben zu bewältigen. Zentrale Herausforderungen bestehen jedoch hierdabei in der robusten Ausführung vielfältiger Szenarien sowie in der Fähigkeit, auf neue Objekte, Umgebungen und Aufgaben zu generalisieren. Die heute eingesetzten intelligenten Robotersysteme, bzw.

deren zugrunde liegenden KI-Modelle sind oftmals stark auf ihre jeweilige Aufgabe und die Zielumgebung spezialisiert, bzw. trainiert worden. Aufgaben, die nicht im Trainingsdatensatz enthalten sind, können häufig nicht zuverlässig ausge-führt werden. Ebenso treten Probleme auf, wenn gelernte Aufgaben in grundlegend verschiedenen Umgebungen ausgeführt werden sollen. Der Grund hierfür liegt in der Art und Weise, wie die zugrunde liegenden KI-Modelle trainiert werden: Die Trainingsdaten sind in der Regel stark auf eine spezifische Aufgabe und Umgebung zugeschnitten. Eine Erhöhung der Datenvielfalt führt dabei häufig zu einem Zielkonflikt, da sie mit einer geringeren Genauigkeit bei der Ausführung einzelner Aufgaben einhergehen kann. Selbst wenn man ein großes generalisierendes Roboter KI-Modell entwickeln möchte, stellt der Mangel an geeigneten und vielfältigen Roboter-Trainingsdaten ein gravierendes Problem dar. Klassische, aufgabenspezifische Trainingsansätze stoßen hierbei aufgrund mangelnder Skalierbar-keit und Flexibilität an ihre Grenzen. Aktuelle Forschungsansätze verfolgen daher das Ziel, Robo-tern ein visuelles und semantisches Aufgabenverständnis zu vermitteln, sodass sie Handlungen aus hochdimensionalen Eingaben wie Videos oder Bildern ableiten können. Dadurch können neue Datenquellen für das Training des Roboters herangezogen werden. Mit einem visuellen und se-mantischen Verständnis können beispielsweise (menschliche) Videos von YouTube im Training verwendet werden. Diese beinhalten viele verschiedene Handlungen und Ausführungsformen ver-schiedenster Aufgaben, die ein generalisierendes Roboter KI-Modell brauchen würde. Imitation Learning ist ein vielversprechender Ansatz in diesem Kontext, der in dieser Arbeit genauer unter-sucht wird. Beim Imitation Learning geht es darum, den Roboter seine Aufgabe mithilfe eines (menschlichen) Demonstrationsvideos beizubringen (z.B. das Stapeln von Würfeln, oder das Greifen von Objek-ten). Beim traditionellen Ansatz muss ein Roboter auf die jeweilige Aufgabe mit viel Aufwand bzw. mit vielen Roboter trajectory Datensätzen trainiert werden.

## 1.2 Project Goal

Ziel dieser Arbeit ist es eine Einführung in das Thema Robotic mit Imitation Learning zu liefern. Die Arbeit gliedert sich in zwei Teile. Dabei werden zuerst die Grundlagen der Robotik erläutert und anschließend technisch in das Thema Intelligente Robotik mit dem Fokus Imitation Learning eingeführt. Abgerundet wird der erste Teil mit einem Literaturüberblick, über ausgewählte Imitation Learning Ansätze, die dort näher untersucht werden. Im zweiten Teil dieser Arbeit wird ein Open-Source Imitation Learning Modell experimentell auf einen realen Roboterarm implementiert. Die Erstmalige Inbetriebnahme des Roboters und das Setup, wie ein KI-Modell zur Ausführung auf den Roboter gebracht werden kann, gehört auch dazu. Ziel ist es, den Roboter zu befähigen, einfache Manipulationsaufgaben, beispielsweise das Stapeln von Würfeln, allein auf Basis menschlicher Demonstrationsvideos zu erlernen und auszu-führen. Die Leistungsfähigkeit des vorgeschlagenen Ansatzes wird anschließend experimentell auf dem realen Robotersystem untersucht und evaluiert.

Beim Imitation Learning geht es darum, den Roboter seine Aufgabe mithilfe eines (menschlichen) Demonstrationsvideos beizubringen (z.B. das Stapeln von Würfeln,

oder das Greifen von Objek-ten). Beim traditionellen Ansatz muss ein Roboter auf die jeweilige Aufgabe mit viel Aufwand bzw. mit vielen Roboter trajectory Datensätzen trainiert werden. Beim Imitation Learning geht es darum, den Roboter seine Aufgabe mithilfe eines (menschlichen) Demonstrationsvideos beizubringen. Dabei nimmt eine Kamera ein Video von der jeweiligen Person auf, die eine bestimmte Aufgabe ausübt. Anschließend wird dem Roboter-KI-Modell das Demonstrationsvideo der Aufgabe gezeigt, welches wiederum den Roboter entsprechend steuert, um die jeweilige Aufgabe in seiner Umgebung auszuführen.

## 1.3 Research Focus – Imitation Learning

# Chapter 2

# Basics Classical Robotics

## 2.1 Erster Abschnitt von Kapitel 2

test test test test

### 2.1.1 Ein Unterabschnitt

#### 2.1.1.1 Ein Unterabschnitt

jetzt gehts

# Chapter 3

# Basics Intelligent Robotics

## 3.1 Machine Learning Basics

### 3.1.1 Mathematical Notation of formulas

**Capital letters** are used for random variables, e.g. $S$ represents the set of all states in which the robot can be and $A$ represents the set of all possible actions it can perform.

**Lowercase letters** are used for specific values of these random variables, e.g. $s$ stands for a specific robot state and $a$ for a specific action that the robot performs. A lowercase letter is usually followed by a time index $_t$, representing the specific action taken by the robot at time step $t$. In some cases the time index is omitted for simplicity, e.g. $a$ instead of $a_t$ and the next state or action is then denoted as $s'$ or $a'$ instead of $s_{t+1}$ or $a_{t+1}$.

**Capital letters in bold** represents Matrices, e.g. the matrix $\mathbf{X}$.

**Lowercase letters in bold** are used for specific values of (random) variables that are vectors, e.g. $\mathbf{x}$ represents a specific vector.

### 3.1.2 Glossary

**Agent & Policy:**

An agent is an entity that learns to perform a specific behavior through interaction with its environment. In the context of this work, the agent corresponds to the robot, which has to execute a given action or task. The policy can be interpreted as the brain of the agent, determining which action to take next in a given situation in order to achieve the task objective. In our example, the policy controls the robot's motion and actions.

Formally, a policy can be represented as

$$\pi_\theta(a \mid s) \tag{3.1}$$

which defines a probability distribution over actions $a$, conditioned on the current state $s$. In other words, the policy specifies how likely the agent is to select a particular action given its current observation of the environment.

In the classical meaning, the action $a$ corresponds for example to a robot command, such as moving the gripper to a target position $(x, y, z)$ or setting a joint angle to a specific value with a defined velocity. The state $s$ represents the agent's observation, which may include, for example, a sequence of recent camera images (e.g., the last four frames) as well as additional sensor inputs such as proprioceptive signals.

**Robot Trajectory:**

A robot trajectory describes how the robot moves from a starting state to a target state, including position, orientation and, if applicable, speeds, accelerations, and forces acting on the robot. A robot tracetory is a temporal sequence of actions and the resulting robot states.

**Annotation:**

Annotation refers to the process of labeling data. Data is provided with additional information. For example, class affiliations can be determined, target objects can be marked in images, or states and actions can be marked in robot trajectories. Annotated data, or labeled data, form the basis for supervised learning approaches.

Annotating refers to the process of labeling data, in which data is enriched with additional information. For example, this may include assigning class labels, marking target objects in images, or labeling states and actions within robot trajectories. Annotated, or labeled, data forms the foundation for supervised learning approaches.

**Foundation Model vs. Multi-Model Model**

### 3.1.3 Core Machine Learning Categories

There are various approaches to training an AI model for a robot. These involve methods from the four core machine learning categories, which can also be combined with one another:

**Supervised Learning:**

In supervised learning, a model is trained using labeled training data. This means that, for the input data, the output data to be predicted are known. The goal is to train a model that correctly predicts the output data and makes reliable predictions on unseen data.

**Unsupervised Learning:**

In contrast to supervised learning, unsupervised learning uses unlabeled data for model training. The model tries to recognize structures, patterns or relationships in

the data on its own.

**Semi Supervised Learning:**

Semi-supervised learning is a combination of supervised and unsupervised learning. In this approach, a model is trained using a small amount of labeled data and a large amount of unlabeled data. The goal is to leverage the advantages of both approaches, particularly when annotating data is time-consuming or costl-intensive. This is relevant in robotics, as the data used in that field is often difficult to label.

**Reinforcement Learning:**

Reinforcement learning (RL) differs fundamentally from the previously mentioned approaches. Instead of learning from fixed datasets, an agent actively interacts with its environment and tries to find out an optimal strategy to reach a defined goal. Through its actions, it influences the state of the environment and subsequently receives feedback in the form of rewards or penalties, see Figure 3.1 for a short overview. In the context of robotics, the robot is the agent. The objective is to learn a strategy (= policy) that maximizes the cumulative reward over time for the given task.




**Figure 3.1:** Base concept of Reinforcement Learning

The agent proceeds in its environment according to the trial-and-error principle to learn an optimal policy. Safety is a critical concern during training, as the agent may execute unpredictable actions while exploring the state space. For this reason, simulation environments are a central component of training and are frequently used for pre-training the policy. The policy is then subsequently often fine-tuned in the real-world environment. Because the agent learns through trial and error, more efficient, unknown, and creative solutions can be found that a human might not have come up with. See section 3.2.1 for more details.

## 3.2 Intelligent robots with Deep Learning (RL)

In general, modern robot training distinguishes between two main approaches: imitation learning and reinforcement learning. Each approach uses a different strategy for training the robot model. In Figure 3.2 an overview of the two approaches is given. The following sections explain the two approaches in more detail and provide a mathematical description of the underlying problem.




**Figure 3.2:** Overview Robotic Learning

### 3.2.1 Reinforcement Learning

Reinforcement learning (RL) is both a fundamental discipline of machine learning and a distinct approach within Robot Learning. The robot learns a policy through trial and error using rewards provided from the given task and the environment. The actions performed by the agent are evaluated with a reward score, and this score is then used to gradually optimize the policy.

Key components of the RL problem The following section explains the key concepts in RL related to robotics, see also figure 3.1 for a general graphical overview.

- **Agent:** The agent is the entity that learns to perform a specific behavior through interaction with its environment. In the context of this work, the agent corresponds to the robot, which has to execute a given action or task.
- **Environment:** The environment is the setting in which the agent (the robot) operates. Simply put, the environment is the robot's workplace, where it is deployed. In addition to the robot itself, it includes all relevant objects with which the robot interacts. The environment can be either the real world or a simulated environment in which the robot is trained.
- **Robot Actions:** The Robot actions are simply the control commands the robot can send to its actuators, e.g. open or close the gripper, move the arm to position $X, Y, Z$, or the joint angles of the individual robot axes, etc.
- **Reward:** The reward is a numerical value that indicates how well the robot is performing in relation to the task objective. For example, if the robot successfully picks up an object, it might receive a positive reward, while if it fails or drops the object, it might receive a negative reward. The goal of Reinforcement Learning is to learn a policy that maximizes the cumulative reward over time.
- **Robot State:** state is a complete description of the situation in the environment

at a particular point in time. The robot state represents the current situation of the robot and its environment. It can include various types of information, such as the robot's position, orientation, joint angles, sensor readings, and even visual input from cameras [35]. The state is crucial for the robot to make informed decisions about which actions to take.

- **Observation:** An observation is the information that the robot receives from its sensors at a given time step. It may not provide a complete picture of the environment, and thus may not fully represent the true robot state. In our case, the observation is mostly equivalent to the state [35].
- **Policy:** The policy can be interpreted as the brain of the agent. The policy determines which action should be taken next when the agent is in a particular state in order to achieve the task objective. The Policy controls the robot's motion and actions.

#### 3.2.1.1 Mathematical description of the RL problem:

Die RL Modularitäten werden wie folgt dargestellt:

- Action: $a$
- Reward: $r$
- State: $s$
- Observation: $o$
- Policy: $\pi$
- Time step: $t$, e.g. $a_t$ is the action taken at time step $t$, $a_{t+1}$ is the action taken at the next time step, etc.
- $s'$: The next state after taking action $a$ in state $s$, i.e. $s' = s_{t+1}$, $s = s_t$.

<u>Markov Decision Process</u>

Reinforcement Learning is based on the Markov decision process (MDP). A MDP is a stochastic decision-making process that formally models the transition probabilities from a state $s$ to a subsequent state $s'$ provided that action $a$ is performed, expressed mathematically as $P(s'|s,a)$ [30, 19].

The objective is to learn a policy $\pi(a|s)$ that maximizes the expected long-term cumulative reward, defined as $\mathbb{E}\left[\sum_{t=0}^{\infty} \gamma^t r_t\right]$. The discount factor $\gamma \in [0,1]$ determines the importance of future rewards compared to immediate rewards. A value of $\gamma$ close to 0 makes the agent focus more on immediate rewards, while a value close to 1 encourages the agent to consider long-term rewards more heavily [30, 10].

An MDP also defines a reward function that specifies the reward $r$ an agent receives when taking action $a$ in state $s$ and transitioning to a subsequent state $s'$. This is commonly expressed as $R_a(s,s')$ [30, 19].

The **Markov property** says that all information from the past is contained in the current state, mathematically expressed as $P(S_{t+1}|S_t) = P(S_{t+1}|S_1, S_2, ...S_t)$. In other words, the transition probabilities depend only on the current state and not on the history of previous states [10].

In practice, the Markov property is often not strictly satisfied. For example, a single image captured by a camera does not provide sufficient information to infer the dynamics of the environment. From one image alone, it is not possible to determine whether a car is moving forward at 100 km/h or 10 km/h, reversing, or remaining stationary. However, such information is crucial for making correct decisions in applications like autonomous driving [29]. Therefore, in practice, only sufficiently informative state representations are often used because the ideal Markov property is not strictly fulfilled. This is often achieved by incorporating a history of observations, such as a sequence of the last five camera frames, to better capture the underlying dynamics of the environment [19].

Training process:

Zu Beginn des Trainingsprozesses ist die Policy in der Regel zufällig, was bedeutet, dass der Roboter zunächst zufällige Bewegungen ausführt. Durch Ausprobieren versucht der Roboter nun Aktionen zu finden, die mit einer hohen Belohnung einhergehen. Diese Aktionen werden anschließend von der Policy höher gewichtet, was bedeutet, dass der Roboter in Zukunft eher dazu neigt, diese Aktionen auszuführen. Für eine erfolgreiche Lernphase ist es wichtig, dass der Roboter eine gute Balance zwischen Exploration (Ausprobieren neuer Aktionen im jeweiligen Zustand) und Exploitation (Nutzung bereits bekannter, erfolgreicher Aktionen im jeweiligen Zustand) findet. Auf die Exploration wird zu Beginn des Trainingsprozesses mehr Wert gelegt, um die Umgebung besser kennenzulernen und die effizientesten Aktionen im jeweiligen Roboter State für den Erfolg der Aufgabe zu finden. Im Laufe der Zeit, wenn der Roboter mehr über die Umgebung und die Belohnungsstruktur gelernt hat, wird die Exploitation wichtiger, um die bereits gefundenen erfolgreichen Aktionen häufiger auszuführen und so die Gesamtleistung, die am Aufgabenerfolg gemessen wird zu verbessern. Es existieren zahlreiche Methoden und Algorithmen, wie die Exploration und Exploitation Phasen effektiv gesteuert werden können. Beispielalgorithmen sind $\epsilon$-greedy, Upper Confidence Bound (UCB), Thompson Sampling. Im Rahmen der Arbeit wird aber nicht näher darauf eingegangen.

Durch die Explorationsphase wird erst spät der Erfolg des gewählten RL-Ansatzes sichtbar, anders als beim Klassischen Deep Learning, siehe Abbildung 3.3.




**Figure 3.3:** Training Progress in Deep Learning and Reinforcement Learning

#### 3.2.1.2 Knowledge Modality

An RL Knowledge Modality (KM) is some function learned from data that represents specific types of RL-related knowledge. KMs can be learned through trial-and-error principles or from various data sources, like video datasets, and can capture different aspects of the RL problem.

**Knowledge Modalities (KMs) from Video**

- `Policy:` A Policy $\pi(a_t|s_t)$ is a mapping from states to actions and defines the behavior of the agent that is in a particular state. $\pi(a_t|s_t)$ is the probability of taking action $a_t$ given that the agent is in state $s_t$. $_t$ denotes the time step. In other words, the policy specifies how likely the agent is to select a particular action given its current observation of the environment. It can be learned from video data by observing the actions taken in different states and learning to predict those actions based on the visual input.
- `Value functions:` Value functions estimate the expected future return (cumulative reward) for a given state or state-action pair. They can be learned from video data by observing the outcomes of actions and learning to predict the expected future rewards based on the visual input.
  - `State-value function (V-function):` A V-function $V_\pi(s_t)$ is a mapping from states to the expected future return when acting under a particular policy $\pi$.

    **Intuition:** "How good is it to be a certain state, if I follow my policy $\pi$?"




**Figure 3.4:** State-Value Function

  - `State-action value function (Q-function):`

    A Q-function $Q_\pi(s_t, a_t)$ is a mapping from state-action pairs to the expected future return when acting under a particular policy $\pi$.

    **Intuition:** "How good is this specific action here, if I continue behaving like my policy $\pi$?"

  - `V-function vs. Q-function:` Bei der V-function weiß ich nur, wie gut es ist, in einem bestimmten Zustand zu sein, wenn ich nach meiner Policy $\pi$ agiere, aber nicht, wie gut eine konkrete Aktion in diesem Zustand ist. Bei




**Figure 3.5:** State-Action Value Function

der Q-function hingegen weiß ich bereits, wie gut die konkrete Aktion $a_t$ im Zustand $s_t$ ist, wenn ich weiterhin nach meiner Policy $\pi$ agiere. Siehe dazu die Abbildung 3.4 und 3.5.

- `Dynamics model:` A Dynamic model $p(s_{t+1}|s_t, a_t)$ predicts the next state $s_{t+1}$ given the current state $s_t$ and action $a_t$. Video prediction models can be used as robot dynamics models. By learning to predict future video frames based on current observations and actions, the model can capture the underlying dynamics of the environment. This allows the robot to anticipate the consequences of its actions and make informed decisions based on predicted future states.
- `Reward model:` A reward function $r(s_t, a_t)$ defines the reward received by the agent for taking action $a_t$ in state $s_t$. It can be learned from video data by observing the outcomes of actions and inferring the underlying reward structure that motivates those actions. For example, if a video shows a robot successfully picking up an object, the reward function can learn to assign a positive reward to that action in similar states.

### 3.2.2 Imitation Learning

Imitation Learning (IL) or Learning from Demonstration is a general term for methods in which the agent derives or learns its behavior from expert demonstrations.

Imitation learning makes it possible to use "in the wild" videos—such as those found in great variety on the internet, for example on platforms like YouTube — to train AI models.

The demonstration videos can show a robot, a human, or even a loose sequence of actions, both in the real world or in a simulation environment, performing a specific task. However, videos without a clearly defined objective or with unknown activity can also be used.

This allows models to be trained to capture the visual and semantic relationships, as well as the physical dynamics of the real world. This, in turn, is a key prerequisite for the development of a generalist policy. Imitation learning can be divided into Behavior Cloning and Learning from Videos/Observation.

#### 3.2.2.1 Behavior Cloning (BC)

Behavior Cloning (BC) is a fundamental approach within imitation learning, where a policy is learned directly from **annotated expert demonstrations**. The training data consists of state–action pairs $(s_t, a_t)$, and the problem is formulated as a standard supervised learning task.

Conceptually, Behavior Cloning can be understood as a form of direct imitation ("direct copying") of expert behavior, without explicitly modeling the underlying system dynamics or task objectives. Due to its simplicity and scalability, BC is one of the most widely used methods in robot learning from datasets.

BC is used to train Vision Language Action models and for pre-training models used in Reinforcement Learning, see Section **XXX**

**Definition:**

Behavior Cloning (BC) learns a policy by supervised learning on expert demonstrations:

$$\pi_\theta(a_t \mid s_t) \tag{3.2}$$

where:

- $s_t$: State / Observation (images, proprioception, etc.) at time $t$
- $a_t$: Expert action at time $t$

The Policy $\pi_\theta(a \mid s)$ is optimized by minimizing the prediction error between the actions generated by the model and the corresponding expert actions.

$$\min_\theta \mathbb{E}_{(s,a)\sim\mathcal{D}} \left[\mathcal{L}(\pi_\theta(s), a)\right] \tag{3.3}$$

where:

- $\pi_\theta(s)$: The action your robot's policy predicts given state $s$.
- $a$: The actual action the expert took in that same state.
- $\mathcal{L}$: Usually Mean Squared Error (MSE) for continuous control or Cross-Entropy for discrete actions.
- $\mathbb{E}_{(s,a)\sim\mathcal{D}}[\cdot]$: Take all the state-action pairs $(s, a)$ inside the expert dataset $\mathcal{D}$, and calculate the average value of the expression inside the brackets.

#### 3.2.2.2 Learning from Videos / Observation

Learning from Videos (LfV), also referred to as Learning from Observation (LfO), is an Imitation Learning approach that relies solely on **video demonstrations without explicit action annotations**. In contrast to Behavior Cloning, where state–action pairs are directly available, LfV aims to infer the underlying actions or high-level intent purely from perceptual data, i.e., mapping observations to actions $(s \to a)$. It often uses *Representation Learning*, to learn and discover the most important (unknown)

underlying data characteristics (features) by transforming and reducing input in a fully data-driven and automatic manner.

A central challenge in LfV is the **inference problem**: determining which actions correspond to the observed behavior in the video. Since no action labels are provided, additional methods and techniques are required to recover or approximate the missing action information. See chapter **XXX** for more information.

Due to this property, LfV is typically categorized as a **weakly supervised or self-supervised imitation learning** approach. Its main advantage lies in scalability, as it enables leveraging large amounts of unannotated video data, including internet videos or human demonstrations, without the need for costly data annotation. Furthermore, additional actions can be derived from annotated video data too.

In robotics, Learning from Videos is commonly used as a **pretraining step**. The learned representations capture visual, semantic, and dynamical aspects of the environment, which can later be refined using methods such as Behavior Cloning with annotated data or in Reinforcement Learning. This combination allows models to first learn the real worlds dynamics from large-scale video data and subsequently specialize on task-specific robot demonstrations.

**Definition:**

Learning from Videos (LfV) learns to infer actions from observations in a weakly supervised or self-supervised manner.

$$\hat{a}_t = f(s_t, s_{t+1}) \tag{3.4}$$

where:

- $\hat{a}_t$: The "latent" or predicted action.
- $s_t$: The current state/video frame.
- $s_{t+1}$: The next state/video frame.
- $f$: The inverse dynamics function (often a neural network) that maps state transitions to actions.

### 3.2.3 Summary IL & RL

Reinforcement learning is a powerful approach for learning complex tasks, as it enables agents to improve their behavior through interaction with the environment. However, it can be sample inefficient and may require a large number of interactions to learn an effective policy, especially in high-dimensional state and action spaces. Therefore, it is often combined with other learning paradigms, such as supervised learning or imitation learning, in order to leverage their complementary strengths and improve overall performance.

Imitation Learning generally refers to a family of methods and techniques that enable learning from demonstrations. Two important approaches in this context are Behavior

Cloning (BC) and Learning from Videos (LfV), which differ primarily in the type of data they utilize. BC relies on annotated demonstrations, where state-action pairs are available, and learns a policy directly via supervised learning. In contrast, LfV aims to infer actions from unannotated video observations, where only visual information is provided.

Methods from the LfV paradigm can be used for Action Recovery, making unannotated video data applicable for Behavior Cloning by recovering or estimating the underlying actions. Furthermore, such methods can be employed to pretrain models for BC or Reinforcement Learning, for example by learning expressive state and action representations through Representation Learning.

Behavior Cloning is also widely used for training Vision-Language-Action (VLA) models and for pretraining Reinforcement Learning Knowledge Modalities, for instance by learning components like value functions or reward models. In practice, BC and LfV are often combined to exploit the advantages of both approaches, enabling the use of large-scale unannotated data while maintaining the efficiency of supervised policy learning.

# Chapter 4

# Imitation Learning fundamentals

Was sollte noch erklärt werden?

Online Learning / Offline Learning

Multi-Modal und Foundation Models

## 4.1 Why Imitation Learning?

### 4.1.1 Idea behind Imitation Learning:

When we want to learn a new skill, we often turn to How-To videos. We learn the new skill through speech instructions and visual observations in the video.

`Advantages of Imitation Learning:`

Visual IL ...

- is ideal for teaching tasks that are difficult or impossible to describe in words.
- allows robots to infer tasks from expert demonstrations in different environments than the robot.
- can be more data efficient than reinforcement learning, especially in high-dimensional state spaces, like a complex robot environment.
- can leverage large datasets of human demonstrations, which are often easier to collect than expert demonstrations in the specific domain.

`Problems in RL:` A Task in RL is commonly defined through a reward function, which assigns a high reward to desirable behavior and a low reward to undesirable behavior. However, designing good reward functions is challenging for every task, and many methods based on computer vision rely on annotated demonstrations in every new environment.

IL allows us to learn complex behaviors that are difficult to specify through a reward function, or it can help us to define a good adaptive reward function for RL.

Robotic specific problems: Gap between videos of humans and robots performing similar tasks Gap between simulation and Real-World Simulations & Trial and Error in real World possible Limitations: time and computational consuming, Safety?

### 4.1.2 Ways to instruct robots

This section discusses the various ways in which the robot can be taught its task and how the interaction between humans and robots can be designed.

Scene Understanding / Intent Inference

The robot derives its task solely from the environment and the objects present in it [12].

`One Policy, Multiple Tasks:` In this setting, a single policy is typically specialized on a finite set of task instances, as they must be explicitly trained for those tasks. Tasks that are not represented or underrepresented in the training dataset, can therefore often not be executed reliably [4, 16]. For example, if the policy has been trained on multiple manipulation tasks and one of them involves pouring liquid from a teapot into a cup, the policy will execute this behavior when a matching scene is observed during inference [12]. However, generalization to other objects or situations is often limited. Using different teapots or cups may not be problematic as long as the relevant visual features are recognized. In contrast, performance typically decreases under substantial domain shift (significantly different objects or scenes) [12]. If a corresponding pouring behavior from a pot was not included during training, the policy may fail to transfer the action to that new object category [4, 12]. A major limitation of this approach is task ambiguity caused by overlapping object context across different behaviors. If the same object types, such as a teapot and a cup, appear in both a pick-and-place task and a pouring task, the policy may not be able to disambiguate the correct action target based on scene context alone [31].

`One Policy, One Task:` An alternative approach is to train a separate policy for each individual task, which is then selected explicitly during inference. The task-specific policy selection can be performed either manually by a human or automatically by a separate AI classification model that analyzes the scene and determines the appropriate task-specific policy [8]. For example, one policy could be trained for "pouring", another for "opening a drawer", and another for "setting up an overturned object". This modular design is closely related to task-aware expert routing and decoupled planning-and-execution frameworks in robotic manipulation [8].

This decoupling enables training each policy on significantly larger and more diverse datasets containing varied object appearances and environmental conditions, while keeping the core task semantics fixed [28]. Consequently, these specialized policies often support more robust generalization across novel object instances and environmental variations compared to the `One Policy, Multiple Tasks` paradigm. [2, 22, 31]

Language instructions:

For humans is the most comfortable and natural way to instruct the robot with voice commands. This is very useful for simple tasks that are easy to describe. But complex tasks, where execution must follow exact instructions, are sometimes difficult to describe in words. For example, how would you teach a humanoid robot to decorate tables exactly like a sample table, especially when various decorations need to be assembled in a complex arrangement? Furthermore, ambiguities may arise, and the same instruction may be interpreted differently in different linguistic contexts. For example, the word "open" is used for: open drawer, open cabinet, open container with lid or open jar with screw cap. Although the same verb is used here, each interaction requires a completely different motor control.

A big advantage to command the robot with voice commands is that it enables an interactive dialogue between humans and the robot. If the robot does not understand the instructions, it can ask follow-up questions to clarify any misunderstandings. This helps minimize the problems associated with voice commands.

Image instructions:

Robots can also be instructed using visual inputs such as images. Compared to language, image-based instructions provide a more concrete and unambiguous specification of spatial arrangements, object relations, and desired outcomes.

A common approach is the use of *goal images*, where the robot is given a visual representation of the desired final state. In this setting, the task is formulated as a goal-conditioned problem: the robot observes the current state and acts such that it minimizes the difference to the goal image. This is often referred to as goal-conditioned behavior. However, this approach does not explicitly specify *how* the task should be executed, only *what* the final configuration should look like. But some works have addressed this issue with the usage of annotations in the image of the initial state to specify the task execution. For example [2] highlights the relevant objects and regions with circles and arrows to visualize the task execution in the image.



(a) Task: Rotate cup and place it on table

(b) Task: Put fruit into bowl

(c) Task: Fold T-shirt

**Figure 4.1:** Image-based instructions for task execution [2].

Another way to address this limitation, *subgoal images* or intermediate states can be provided [25]. These guide the robot through a sequence of visually defined steps, effectively decomposing complex tasks into simpler stages. This is particularly useful for long-horizon or multi-step manipulation tasks.

A key advantage of image instructions is their ability to capture fine-grained spatial details that are difficult to describe in language, such as precise object placement, orientation or symmetry alignments. However, they also introduce challenges related to perception, such as viewpoint variation, occlusions of objects in the real environment, or the use of in-the-wild goal-images with varying lighting and background conditions.

Video-Based Instructions:

Demonstration videos are a powerful way to instruct robots, as they contain rich visual and temporal information. In contrast to single images, videos provide not only the desired goal state of a task but also the sequence of intermediate steps required to reach that goal.

In this setting, the task is typically formulated as an imitation learning problem, where the robot learns a policy that maps visual observations to actions by imitating the demonstrated trajectory. The temporal structure of the video enables the robot to infer *how* a task should be executed, rather than only *what* the final outcome should look like. Depending on the setup, this may also require inferring latent actions from visual observations alone.

Ideally, the robot model should be able to understand it's task from in-the-wild demonstration videos of both robots and humans. In-the-wild videos refer to video data collected in unconstrained, real-world environments, without controlled settings, standardized viewpoints, or curated conditions. Such data exhibits large variability in lighting, backgrounds, and camera motion, making it significantly more challenging for perception and learning compared to controlled laboratory data.

`Human Video Demonstrations:`

- **Data abundance:** In this paradigm, the robot learns from videos of humans performing a task. This is particularly appealing, as large amounts of human demonstration data are readily available (e.g. online videos).
- **Embodiment gap:** A core challenge is the mismatch between human and robot bodies. Human motions and kinematics differ significantly from those of robots. Therefore, the robot must learn to map observed human actions to its own action space.
- **Suboptimal demonstrations:** Another key challenge of human video demonstrations is that they do not necessarily represent optimal task executions. Demonstrations often reflect individual preferences, inefficiencies, or context-specific behaviors, resulting in suboptimal trajectories. In many cases, a video captures only a single possible way of solving the task, without providing information about alternative or more efficient strategies. However, the objective for the robot is typically to perform tasks efficiently and robustly. Therefore, the learned policy must be able to generalize beyond the demonstrated behavior and, if necessary, improve upon it, rather than directly imitating potentially suboptimal actions.

`Robot Video Demonstrations:`

- **No embodiment gap:** The demonstrations are performed by the robot itself or by another robot with similar embodiment. This avoids the human-robot embodiment gap and provides more directly transferable data.
- **Cost and effort:** However, collecting such demonstrations is often expensive and time-consuming, as it requires access to robotic systems and typically controlled environments. In addition, purely visual robot demonstrations may still lack explicit action labels. This means that the robot must still infer the underlying actions and intentions from the visual data.
- **Value of robot demos:** Despite these challenges, robot video demonstrations can provide valuable data for learning, as they are more closely aligned with the robot's own capabilities and constraints compared to human demonstrations.

`Teleoperation:`

- **Direct data collection:** A common method to generate high-quality robot demonstrations is teleoperation, where a human operator directly controls the robot, e.g., via a joystick or a dedicated control interface.
- **Precision and safety:** In contrast to passive video demonstrations, teleoperation provides access to both the visual observations and the corresponding action and trajectory data. As a result, the demonstrated actions are already expressed in the robot's action space, which significantly simplifies reproducing the expected behavior. Such demonstrations are particularly important for fine-grained manipulation tasks that require precise control and accurate timing.
- **Scalability issues:** However, teleoperation may require specialized hardware (controllers, sometimes motion-capture or VR setups) and does not scale as easily as collecting passive video data. Thus, collecting large teleoperation datasets can be time-consuming and is typically done in lab settings only.

## 4.2 Generalist Robots

The ultimate goal of robotics is to develop a `generalist robot`. According to McCarthy et al. [17], such a robot should be able to perform a wide variety of physical tasks in unstructured, unseen real-world environments. It must combine high-level reasoning and planning abilities with low-level physical skills, such as dexterous manipulation. Furthermore, it should be capable of adapting to unforeseen situations and operate under imperfect and partial observations, for example through visual and tactile sensing. In summary, a general-purpose robot is capable of adapting to different situations and learning new skills just like humans [33].

Such a robot would be highly useful across a wide range of real-world applications. In `industrial settings`, this would enable robots to be deployed flexibly across different environments and tasks, without the need for task-specific or environment-specific programming or retraining. As a result, robots could also be utilized for spontaneous small, short-term tasks, where automation is currently not economically viable due to

high setup costs and effort. This increased flexibility would lead to higher utilization rates and, consequently, reduced long-term operational costs [33].

In addition, general-purpose robots could play an important role in `household` settings. They could assist with everyday tasks such as tidy up rooms, (un)loading dishwashers, setting tables, or acting as general assistants for example helping to carry objects.

In `healthcare and assistive contexts`, such robots could support individuals with limited mobility by helping them perform daily activities, such as standing up, sitting down, opening a door, or transporting objects. This highlights the potential of generalizing robotic systems to improve both efficiency in industry and quality of life in everyday and care settings [33].

**Ethical concerns:** Ethical concerns regarding the development of generalist robots should not be underestimated and must not be ignored. In the future, robots are likely to take over many tasks, particularly those that are repetitive and monotonous, which may lead to the displacement of certain jobs. Whether this will result in large-scale unemployment due to automation remains a subject of ongoing debate.

Furthermore, once the technology has sufficiently matured, such robots could also be used for `military purposes`. While this could reduce the risks to human soldiers, it also raises serious ethical concerns, as it makes forms of automated or autonomous warfare increasingly conceivable.

It is therefore essential that the development and deployment of generalist robots are carried out responsibly and in accordance with ethical guidelines, in order to minimize potential negative impacts on society.

### 4.2.1 Data Bottleneck in Robotics

A central question in robotics is how to train a generalist robot capable of performing a wide range of tasks in unstructured and previously unseen real-world environments?

`Usage of large-scale datasets.` Progress in related machine learning domains—such as Natural Language Processing [1], Computer Vision [3], and video generation [7]—suggests that large-scale datasets and model capacity are key drivers of performance and generalization capabilities. Training high-capacity models with expressive architectures on diverse, extensive internet-scale datasets has led to the emergence of robust representations and improved out-of-distribution performance [34]. Empirically, these improvements often follow predictable scaling laws, where performance improves as more data, model size, and compute are used [13]. Recent work suggests that similar scaling behavior may also apply to robotics and imitation learning. For example, studies show that robots generalize better wehn they are trained on more diverse training data, including variations in environments, objects, and tasks [15, 9]. Moreover, large-scale imitation learning approaches based on behavioral cloning have demonstrated that training a single policy across many tasks can yield substantial gains in robustness and generalization. For example, transformer-based robot policies such as RT-1 and RT-2 leverage large, heterogeneous datasets to achieve zero-shot generalization to novel tasks and instructions [5, 6].

`Data bottleneck.` In contrast to vision and language domains, robotics is fundamentally constrained by the cost and complexity of data collection, limiting the availability of large, diverse, and high-quality datasets. High-quality demonstrations require physical real world interaction, making them time-consuming to acquire, and are often limited in diversity due to hardware and safety constraints [33]. As a result, available datasets are usually smaller and less diverse. Consequently, this data scarcity represents a major bottleneck for achieving similar levels of scalability and generalization in robot learning, and remains a central challenge in the development of general-purpose robotic systems [33].

### 4.2.2 Relevant Data Categories for Robotics

### 4.2.3 How to Address the Data Bottleneck

How can we address this data bottleneck in robotics? Before discussing specific approaches, it is important to clarify which data sources are relevant for robot learning and how such data can be acquired.

- `Real world data` Real-world robot data is obtained through physical interaction between the robot and its environment and represents a high-quality source for robot learning. Through direct interaction, trajectories and sensor measurements can be recorded under real operating conditions, capturing effects such as sensor noise and environment variability that are difficult to model accurately in simulation.

  `Teleoperation.` A common approach to collecting such data is human teleoperation, where an operator controls the robot to perform tasks and generate demonstration trajectories [36, 129, 195]. This type of data has been widely used in imitation learning and has contributed to the development of early robot foundation models [36, 264]. Teleoperation can be realized through various control interfaces, including joysticks, motion-capture systems, or virtual reality setups. Teleoperation enables precise control and is particularly suitable for collecting demonstrations of complex manipulation tasks that require fine-grained movements and accurate timing. However, it is time-consuming and often requires specialized hardware, which limits scalability. To mitigate this, datasets are increasingly aggregated across multiple research institutions, improving both scale and diversity [195].

  `Data collection improvements.` To further address the limitations of manual data collection, recent work has explored automated or semi-automated data acquisition methods, where robots collect data with reduced human intervention [35, 5, 304]. In parallel, advances in robotic infrastructure, particularly in industrial settings, indicate that large-scale data collection in real-world environments is becoming increasingly feasible [251, 115].

  Despite these developments, real-world datasets remain significantly smaller and less diverse compared to internet-scale datasets used in vision and language

domains. This limitation continues to pose a challenge for scaling robot learning methods and achieving robust generalization.

- `Simulated data`

  `Simulatedly Generated Demonstration Data.` Simulation enables the generation of robot trajectories in virtual environments without the cost, safety risks, and hardware limitations associated with real-world experiments. As a result, simulated demonstrations can be used in scenarios where collecting physical robot data would be impractical, expensive, or unsafe [336, 127, 190]. These generated trajectories are commonly used in imitation learning especially in Behavior Cloning, where policies are trained on demonstration.

  Expert demonstrations in simulation are typically generated by executing a high-performing controller or policy in the simulated environment, such as a hand-crafted controller, a planning-based system, or a policy obtained via reinforcement learning.

  - **hand-crafted controllers:** Hand-crafted controllers are based on classical control methods such as PD/PID controllers, Linear Quadratic Regulators (LQR), or Model Predictive Control (MPC) [27, 20]. These methods are particularly effective for low-dimensional tasks, including balancing, set-point tracking, or waypoint following, where they can generate stable and accurate trajectories. However, they often struggle in complex or high-dimensional environments.

  - **rule-based and planning-based systems:** For manipulation and navigation tasks, motion planning algorithms such as A*, PRM, or RRT* can be used to compute collision-free trajectories. Frameworks such as MoveIt [21] integrate these planning methods with low-level robot controllers and are widely used in robotics applications [14]. These approaches can generate high-quality demonstrations but often require accurate environment models and can become computationally expensive in complex scenarios.

  - **policies obtained via reinforcement learning:** Another approach is to train a reinforcement learning policy, froze it and use it to generate expert demonstration trajectories for downstream imitation learning. Compared to hand-crafted or planning-based approaches, reinforcement learning policies can better adapt to high-dimensional and complex tasks, although training them typically requires large amounts of interaction data and computational resources.

    In simulation, these policies can additionally be trained using *privileged simulation information*, which would not be accessible in real-world settings. Examples include exact object positions, velocities, segmentation masks, or the full environment state. Access to this additional information can simplify the learning process and improve the quality of the generated trajectories.

    Another opportunity is to simplify the problem by training separate expert

policies for each subtask. For example, train one policy for grasping, one for navigation, and one for the pulling motion for opening drawers and coordinate them to form a complete task.

`Online Learning in Simulation.` In addition to generating demonstration datasets, simulation is widely used for online learning in robotics, particularly in reinforcement learning. In online learning, the robot continuously interacts with the environment and improves its policy based on newly collected experience during training. Simulation is especially suitable for this process because it enables safe exploration and automatic resetting of environments, parallelized data collection, and faster-than-real-time execution without risking damage to physical hardware. Consequently, simulation has become an essential component for scalable robot learning systems that require large amounts of interaction data, particularly in RL [336, 127, 190].

`Sim-to-Real Gap.` Despite its advantages, simulation-based robot learning faces several important challenges [25]. One major issue is the sim-to-real gap, which arises from inaccuracies between simulated and real-world physics. Effects such as friction, contact dynamics, deformable objects, latency, and sensor noise are often difficult to model accurately. This gap can lead to poor performance when transferring policies trained in simulation to real robots [329]. A common strategy to mitigate this problem is domain randomization, where environmental properties such as textures, lighting conditions, physical parameters, and sensor characteristics are randomized during training to improve robustness and transferability [266].

`Task Diversity.` Another limitation is the difficulty of creating sufficiently diverse simulated tasks and environments for general-purpose robot learning. Manually designing large numbers of environments is labor-intensive and does not scale efficiently. Recent work therefore explores procedural environment generation, where environments and task configurations are generated automatically to increase diversity and improve policy generalization [62, 262, 292, 76, 286].

Despite these challenges, simulated demonstrations remain a valuable source of training data for imitation learning, as they enable scalable trajectory generation and rapid experimentation in controlled environments.

- `Internet data.` Internet data is a promising source for robot learning and includes various types of freely available data, such as text, images, videos, and structured information. Its main advantage lies in its scale and diversity, which can improve the robustness, adaptability, and generalization capabilities of learned robot policies. In analogy to recent advances in natural language processing and computer vision, robotics can similarly benefit from leveraging vast, weakly labeled data from the web.

  In particular, these data sources can support robot learning in several complementary ways. For example, image and video datasets have been used to pretrain vision models that provide robust visual representations for robotic perception

systems. In addition, Vision-Language Models (VLMs) and Large Language Models (LLMs) have been employed to define reward functions and task objectives for robot learning. LLMs have also been used as high-level planners for long-horizon tasks by decomposing complex goals into smaller executable actions. Furthermore, several recent works adapt internet-pretrained foundation models for robotics through fine-tuning on robot-specific datasets, while others jointly train on both internet data and action-labeled robot trajectories to improve generalization and cross-domain transfer capabilities.

In this work, the focus lies on internet video data, which is discussed in more detail in the following sections.

`Combination of data sources.` In modern robot learning systems, simulation data, real-world data, and internet data are rarely used in isolation. Instead, these data sources are commonly combined, as each category provides complementary strengths and addresses different limitations. Simulation enables scalable and cost-efficient data generation and provides a safe environment for online robot interaction and reinforcement learning [26, 36, 26, 23]. Internet data offers large-scale and diverse semantic information [9, 6], while real-world data captures accurate physical interactions, sensor characteristics, and real-world dynamics that are difficult to model in simulation [23].

Typical robot learning pipelines therefore combine these data sources hierarchically [6, 24]. In many approaches, perception and policy models are first pretrained on large-scale simulation and/or internet datasets in order to learn robust and generalizable representations. Subsequently, the models are fine-tuned on smaller but high-quality real-world robot datasets to adapt them to specific robotic platforms, sensors, and target environments [9]. Some works additionally employ hybrid training strategies that combine simulated and real-world data using techniques such as domain randomization or domain adaptation to further reduce the gap between simulated and real-world observations [32, 11].

### 4.2.4 Reduce the amount of robot data

To train a generalist robot, large amounts of diverse data are required in order to capture the variability of real-world environments and tasks. In particular, robot interaction data, also known as robot data, is highly valuable because it contains both observations of the environment, such from RGB-D cameras or other sensors, and the corresponding robot trajectories and actions. This enables the robot to learn the relationship between observations, actions, and their resulting outcomes.

However, the currently available amount of robot data is still insufficient in both scale and diversity to train highly generalizable robotic systems. Collecting robot data, whether in real-world environments or in simulation, is expensive and time-consuming. Real-world data collection requires physical hardware, human supervision, and extensive interaction time, while simulation environments often suffer from the sim-to-real gap and still require significant engineering effort. As a result, data scarcity remains one of the central challenges in the development of general-purpose robotic systems.

**Large-scale internet video data.** To adress this data bottleneck, one promising approach is to leverage large-scale internet video data. Internet videos provide a rich source of information about human behaviors, object interactions, and task execution in diverse environments that are relevant for robotics. They contain fundamental information about physical dynamics, a wide variety of scenarios and interactions (motion patterns), and semantic task structure that can be useful for robotic learning. In contrast to robot datasets, internet-scale video data is abundant, inexpensive to obtain, and covers a much broader range of scenarios and activities as robot datasets.

Although such videos typically do not contain direct robot actions, recent work has shown that they can still provide strong supervisory signals for representation learning, action understanding, and policy pretraining. By augmenting traditional robot datasets with large-scale video data, robotic systems can learn more robust and transferable representations, improving their ability to generalize to unseen tasks and environments [15].




**Figure 4.2:** Problem: Data Bottleneck in Robotics. Source: [18].

`Formalsim.`

- $D$: The complete training dataset used for learning the robotic policy. This dataset is a combination of the categories real-world data, simulated data, and internet data. $D$ can be subdivided into two subsets: $D = \{D_{robot}, D_{video}\}$.
- $D_{robot}$: Subset of dataset $D$ containing robot interaction data collected from physical robots in real-world or simulation environments, including observations and the robots corresponding actions obtained during interaction. Each sample in $D_{robot}$ consists of transition tuples of the form $(o_t, a_t, r_t, o_{t+1})$, where $o_t$ is the observation at time $t$, $a_t$ is the action taken by the robot, $r_t$ is the reward received after taking action $a_t$, and $o_{t+1}$ is the resulting observation after executing action $a_t$. The reward $r_t$ may be missing, and each $o$ contains an image observation and can additionally contain other information, such as depth or tactile data.

- $D_{video}$: Subset of the dataset $D$ that consists the video (demonstration) data. $D_{video}$ can be obtained from external sources such as internet videos. A video clip is represented as $\tau = (o_0, o_1, ..., o_T)$, where $\tau$ denotes the full video clip and each observation $o_t$ corresponds to an RGB image. Depending on the dataset, videos may additionally be paired with language descriptions, action annotations, or other auxiliary modalities.

Figure 4.2 illustrates the data bottleneck in robotics. The x-axis represents the spectrum of behaviors that a generalist robot is expected to perform, while the y-axis reflects the different levels of information present in various data sources. The figure highlights that, although internet data encompasses a broader range of behaviors in diverse real-world scenarios compared to specialized robot datasets, it often lacks the detailed, low-level information that is critical for robotic applications. Ideally, for every relevant behavior, both low-level robot data and internet data would be available, allowing a model to establish connections across different information levels. However, as illustrated in Figure 4.2, there is a significant lack of low-level robot data for many behaviors that are well represented in internet data (see "Missing Info" area). This absence of fine-grained information poses a significant challenge for generalizing robot learning beyond the limitations of available robot datasets. Overcoming this gap and effectively leveraging both broad internet data and precise robot data is a central objective in advancing LfV approaches [18].

`Goal of Learning from Video (LfV).` LfV aims to exploit this abundance of video data to improve robotic learning. [18] says, the goal of LfV is to leverage our combined LfV dataset, $D = \{D_{robot}, D_{video}\}$, to obtain an improved policy $\pi(a_t|s_t)$ versus when learning from $D_{robot}$ alone.

`Improvements of LfV.` What can we expect from combining both data sources, $D_{\text{robot}}$ and $D_{\text{video}}$, instead of using only $D_{\text{robot}}$?

`Generalization beyond` $D_{\texttt{robot}}$ One important improvement of Learning from Video (LfV) is the potential to generalize beyond the limited set of tasks contained in the robot dataset $D_{\text{robot}}$. While robot data primarily provides information about low-level robotic skills, such as grasping or locomotion, internet-scale video data contains a much broader variety of tasks and human behaviors. By combining both data sources, models may learn how low-level robot actions relate to higher-level task structures observed in videos. As a result, an LfV system may be capable of solving tasks that are not explicitly present in $D_{\text{robot}}$ but are represented within $D_{\text{video}}$.

`Emergent Capabilities.` In natural language processing and computer vision, the availability of large-scale internet data has led to significant improvements and, in some cases, the emergence of capabilities that were not explicitly trained for. Similar progress is expected in robotics. By combining robot interaction data with internet-scale video data with language annotations, models may learn to connect low-level robotic skills with rich semantic abstractions and higher-level world knowledge obtained from textual data. This combination has the potential to improve generalization, task understanding, and the ability to solve previously unseen tasks.

`Improvements in-distribution of` $D_{\texttt{robot}}$. Furthermore, video data may also improve performance on tasks that are already represented within the robot dataset $D_{\text{robot}}$. Since robot demonstrations are expensive to collect, additional video data can improve data efficiency and help models learn more robust visual and task representations. As a result, Learning from Video (LfV) approaches may achieve higher task success rates and overall better performance compared to approaches trained solely on robot interaction data.

**Information Levels:** Robot data primarily contains low-level and mid-level information, and can be collected from both real-world and simulation, with real-world data being more valuable. In contrast, internet data is typically richer in mid-level and high-level information. The following sections explain each information level in detail.

- `Low-level robot information.` Low-level robot information refers to sensory and control signals that directly describe the robot's physical state, motion, and interaction with its environment. This includes, for instance, end-effector pose, joint positions, joint velocities, joint torques, and gripper state (e.g., open or closed). Additionally, low-level information includes information about the physical forces acting on the robot itself. In simulation environments, they may additionally include physical details of objects in the environment, such as contact forces, object properties or object dynamics. Such low-level information is essential for learning precise motor control tasks, including grasping, locomotion, and manipulation.

  **Proprioceptive information** refers to the robot's internal sense of its own body and movement. It includes data about the robot's end-effector pose which implicity inlcudes joint angles, joint velocities, and gripper configuration. This information is crucial for executing accurate and stable motions, as it allows the robot to understand its current state and adjust its actions accordingly. A robot may visually observe a cup through a camera and wants to grasp it. Proprioceptive information tells the controller how to move the arm to the cup, which includes:

  - what is the current pose/state of the robot
  - how far the arm has moved,
  - whether the wrist is rotated correctly,
  - whether the gripper is aligned with the handle.

  **Tactile data** refers to information obtained through physical contact between the robot and its environment. It is comparable to the human sense of touch. Common tactile signals include contact forces, pressure distributions, slip detection, surface texture information, and vibration signals. These measurements are typically acquired using sensors placed on robot grippers, fingertips, or other contact surfaces. For instance, during grasping, tactile sensors can indicate whether an object has been successfully grasped, whether it is slipping, or whether excessive force is being applied. This feedback is critical for maintaining stable and safe

object manipulation.

- `Mid-level video information.` Mid-level video information refers to visual observations that capture the dynamics of objects, agents, and environments over time without providing explicit low-level control signals. In contrast to robot data, video data does not include direct information about actions or internal robot states. Instead, it provides sequences of RGB observations that encode how the visual scene evolves over time.

  This type of information includes visual dynamics such as object motion, changes in spatial configurations, and interactions between entities in the scene. For example, videos can capture how objects are moved, grasped, or manipulated by humans, as well as how these actions affect the surrounding environment. Although no explicit force or control signals are available, the physical behavior of objects (e.g., sliding, rotating, or deforming) can often be inferred implicitly from the visual changes across frames.

  A key aspect of mid-level video information is that it encodes **physical behavior at a perceptual level**. While it does not provide direct measurements of forces or torques, it still reflects underlying physical principles such as gravity, friction, and object permanence through observable motion patterns. For instance, a video of a person pouring water into a glass implicitly contains information about liquid flow dynamics and object interaction constraints.

  In addition, mid-level video information provides a natural source for **language grounding**. Many video datasets are paired with textual annotations, captions, or narration, which link visual observations to semantic concepts. This allows models to associate language with observed actions and events, such as "opening a door", "placing an object on a table", or "picking up a cup". Through such alignment, video data helps bridge the gap between perception and high-level task understanding, enabling learning of more abstract representations that go beyond purely visual dynamics.

- `High-level language information.` High-level language information refers to abstract semantic descriptions of tasks, concepts, and behaviors expressed in natural language. In contrast to visual or robot-centric signals, language does not encode direct sensory observations or motor commands, but instead provides structured knowledge about goals, constraints, and task structures. This includes descriptions of concepts (e.g., objects and their properties), relational knowledge, and symbolic abstractions of actions and environments.

  Such information is particularly important for representing task intent and enabling generalization across different embodiments and environments. Language can describe tasks at multiple levels of abstraction, ranging from low-level action descriptions (e.g., “pick up the cup”) to high-level procedural or goal-oriented instructions (e.g., “prepare a table for breakfast”). This hierarchical structure allows models to connect concrete behaviors with more abstract task specifications.

  In addition, language plays a central role in **planning and reasoning**. It provides a

medium for expressing sequential structure, subgoals, and dependencies between actions. For example, a task such as "clean the table" can be decomposed into intermediate steps such as removing objects, wiping the surface, and reorganizing items. Such decompositions reflect implicit reasoning about task structure and enable more systematic policy learning.

Furthermore, language serves as a bridge for incorporating prior knowledge into robotic systems. Through textual descriptions, models can access commonsense knowledge about object affordances, physical interactions, and typical human behaviors. This enables improved generalization to unseen tasks by leveraging semantic relationships that are not explicitly present in robot or video data alone.

### 4.2.5 Challenges of Video Data




**Figure 4.3:** Key challenges in Learning from Videos [18].

Although internet-scale video data offers significant potential for robotic learning, it also introduces several fundamental challenges, see Figure 4.3. In contrast to robot interaction datasets, videos are typically high-dimensional, noisy, weakly labeled, highly diverse and lacks on low-level information. Extracting meaningful representations and task-relevant information from such data is therefore a non-trivial problem.

`Missing Action Labels.` One major limitation of raw video data is the absence of explicit action labels required by many imitation learning and offline reinforcement learning approaches. While videos provide rich visual observations of behaviors, they typically do not contain the low-level control commands executed during the task. Retrospectively inferring robot actions from human videos is challenging, since human motions often cannot be directly mapped to the action space of a robotic system.

Furthermore, videos usually lack additional reinforcement learning signals such as reward annotations, goal labels, or start-of- and end-of-episode boundaries.

`Missing Low-level Information.` Internet videos also lack on low-level sensory information. Skillful behaviors often depend on tactile feedback, force measurements, proprioceptive signals, or depth information, which are generally not observable in classical RGB video. Although videos may capture high-level task structure and object interactions, they do not explicitly provide the fine-grained physical information necessary for learning accurate motor control and stable interaction with the environment.

`Distribution Shift.` Another challenge arises from the distribution shift between internet videos and the downstream robotics domain. Differences may occur in camera viewpoints, environments, embodiments, object appearances, and task distributions. The Human demonstrations in videos may contain behaviors that are inefficient, ambiguous, or irrelevant for robotic execution.

In particular, Learning from Video (LfV) must address the embodiment gap between humans and robots. Human operators and robotic systems often differ significantly in their kinematics, morphology, and control capabilities. Furthermore, there exists a visual gap between the human actor performing the task in the video and the robotic embodiment that is expected to execute the task. As a result, transferring observed human motions directly to robot actions is highly non-trivial and requires models to learn embodiment-invariant task representations.

Additionally, some important robotic tasks, such as specialized industrial manipulation tasks, may be difficult to learn because they are underrepresented in publicly available video datasets.

`High-dimensionality, Noise, and Redundancy.` Video data is inherently high-dimensional and often contains substantial amounts of irrelevant or redundant information. Background changes, camera motion, occlusions, and unrelated actions can make it difficult for models to identify task-relevant features, making it challenging to learn robust representations. Furthermore, the sheer volume of video data can lead to computational challenges in processing and learning from such large datasets.

`Controllability, Stochasticity, and Partial Observability.` In unlabeled video data, it can be difficult for models to determine which changes in the environment are caused by the agent's actions and which originate from external factors or environmental noise. This ambiguity makes it challenging to infer action information directly from video observations. Furthermore, real-world environments are frequently stochastic and only partially observable, meaning that important state information may be hidden from the camera viewpoint. As a result, predicting future states or accurately modeling action consequences from video alone becomes a difficult problem.

None of these challenges have yet been fully solved. In the following sections, we will discuss some possible ways to address these issues coming with internet video data. Nevertheless it seems likely that scaling — with the help of internet video data — can provide significant gains in robotic systems within the near-future [18].

### 4.2.6 Other Paths to Generalist Robots.

Goal: reduce the amount of robot videos

- **Video provides foundational information:** - Contains physics and dynamics information - Shows human behaviors, tasks and actions relevant to robots - High quantity and diversity - Relatively untapped resource - —>can be highly informative for general-purpose robots. use of diverse internet data has facilitated a transition from task-specific models to monolithic foundation models with more general capabilities

LfV will solve the data bottleneck by augmenting traditional robot data with large-scale internet video.

# Chapter 5

# Learning from Video Techniques

Videos are a challenging data modality, as you have seen in Section 4.2.5. This section addresses the two key questions for LfV research:

- How to extract relevant knowledge from internet video?
- How to apply video-extracted knowledge to robotics?

We first review different approaches for extracting foundational knowledge from internet video, including video encoders, video prediction models, and video-to-text models. We then discuss methods for transferring video-extracted knowledge to robotics, addressing challenges such as missing action labels and distribution shift. Finally, we explore the intersection of LfV and reinforcement learning, highlighting how video-based learning can enhance RL algorithms and enable more efficient policy learning from visual data.

## 5.1 Extracting Foundational Knowledge from Internet Video

### 5.1.1 Video Encoders

### 5.1.2 Video Prediction Models

### 5.1.3 Video-to-Text Models.

## 5.2 Video-to-Robot Transfer: Addressing Missing Action Labels and Distribution Shift

## 5.3 LfV and Reinforcement Learning

# Bibliography


[1] OpenAI Josh Achiam et al. "GPT-4 Technical Report". In: 2023. URL: https://api.semanticscholar.org/CorpusID:257532815.

[2] Yongjie Bai et al. *Learning to See and Act: Task-Aware View Planning for Robotic Manipulation*. Version 3. Oct. 28, 2025. DOI: 10.48550/arXiv.2508.05186. arXiv: 2508.05186 [cs]. URL: http://arxiv.org/abs/2508.05186 (visited on 05/02/2026). Pre-published.

[3] James Betker et al. "Improving Image Generation with Better Captions". In: ().

[4] *Boosting Robotic Manipulation Generalization with Minimal Costly Data*. URL: https://arxiv.org/html/2503.19516v2 (visited on 05/02/2026).

[5] Anthony Brohan et al. "RT-1: Robotics Transformer for Real-World Control at Scale". In: 2022. arXiv: 2212.06817.

[6] Anthony Brohan et al. "RT-2: Vision-language-action Models Transfer Web Knowledge to Robotic Control". In: 2023. arXiv: 2307.15818.

[7] Tim Brooks et al. "Video Generation Models as World Simulators". In: (2024). URL: https://openai.com/research/video-generation-models-as-world-simulators.

[8] Yiteng Chen et al. *RoboRouter: Training-Free Policy Routing for Robotic Manipulation*. Mar. 12, 2026. DOI: 10.48550/arXiv.2603.07892. arXiv: 2603.07892 [cs]. URL: http://arxiv.org/abs/2603.07892 (visited on 05/02/2026). Pre-published.

[9] Open X-Embodiment Collaboration et al. *Open X-Embodiment: Robotic Learning Datasets and RT-X Models*. 2023. URL: https://arxiv.org/abs/2310.08864.

[10] Rohan Jagtap. *Understanding the Markov Decision Process (MDP)*. Built In. URL: https://builtin.com/machine-learning/markov-decision-process (visited on 04/28/2026).

[11] Stephen James et al. "Sim-to-Real via Sim-to-Sim: Data-efficient Robotic Grasping via Randomized-to-Canonical Adaptation Networks". In: *CoRR* abs/1812.07252 (2018). arXiv: 1812.07252. URL: http://arxiv.org/abs/1812.07252.

[12] Eric Jang et al. *BC-Z: Zero-Shot Task Generalization with Robotic Imitation Learning*. Feb. 4, 2022. DOI: 10.48550/arXiv.2202.02005. arXiv: 2202.02005 [cs]. URL: http://arxiv.org/abs/2202.02005 (visited on 05/02/2026). Pre-published.

[13] Jared Kaplan et al. *Scaling Laws for Neural Language Models*. 2020. arXiv: 2001.08361 [cs.LG]. URL: https://arxiv.org/abs/2001.08361.

[14] Zachary Kingston and Lydia E. Kavraki. "Robowflex: Robot Motion Planning with MoveIt Made Easy". In: *CoRR* abs/2103.12826 (2021). arXiv: 2103.12826. URL: https://arxiv.org/abs/2103.12826.

[15] Fanqi Lin et al. "Data Scaling Laws in Imitation Learning for Robotic Manipulation". 2024. arXiv: 2410.18647.

[16] Zhao Mandi et al. *CACTI: A Framework for Scalable Multi-Task Multi-Scene Visual Imitation Learning*. Feb. 16, 2023. DOI: 10.48550/arXiv.2212.05711. arXiv: 2212.05711 [cs]. URL: http://arxiv.org/abs/2212.05711 (visited on 05/02/2026). Pre-published.

[17] Robert McCarthy et al. "Towards Generalist Robot Learning from Internet Video: A Survey". In: *Journal of Artificial Intelligence Research* 83 (July 21, 2025). ISSN: 1076-9757. DOI: 10.1613/jair.1.17400. arXiv: 2404.19664 [cs]. URL: http://arxiv.org/abs/2404.19664 (visited on 05/04/2026).

[18] Robert McCarthy et al. "Towards Generalist Robot Learning from Internet Video: A Survey". In: *Journal of Artificial Intelligence Research* 83 (July 2025). ISSN: 1076-9757. DOI: 10.1613/jair.1.17400. URL: http://dx.doi.org/10.1613/jair.1.17400.

[19] Tim Miller. *Markov Decision Processes — Mastering Reinforcement Learning*. URL: https://gibberblot.github.io/rl-notes/single-agent/MDPs.html (visited on 04/28/2026).

[20] *Model Predictive Control Introduction and Setup*. Robotics Knowledgebase. May 4, 2022. URL: https://roboticsknowledgebase.com/wiki/actuation/model-predictive-control/ (visited on 05/08/2026).

[21] *MoveIt 2 Documentation — MoveIt Documentation: Rolling Documentation*. URL: https://moveit.picknik.ai/main/index.html# (visited on 05/08/2026).

[22] *Multitask Robot Manipulation Policies*. URL: https://www.emergentmind.com/topics/multitask-robot-manipulation-policies (visited on 05/02/2026).

[23] Fabio Muratore et al. "Robot Learning from Randomized Simulations: A Review". In: *CoRR* abs/2111.00956 (2021). arXiv: 2111.00956. URL: https://arxiv.org/abs/2111.00956.

[24] NVIDIA et al. *GR00T N1: An Open Foundation Model for Generalist Humanoid Robots*. 2025. arXiv: 2503.14734 [cs.RO]. URL: https://arxiv.org/abs/2503.14734.

[25] Deepak Pathak et al. *Zero-Shot Visual Imitation*. Apr. 23, 2018. DOI: 10.48550/arXiv.1804.08606. arXiv: 1804.08606 [cs]. URL: http://arxiv.org/abs/1804.08606 (visited on 05/04/2026). Pre-published.

[26] Xue Bin Peng et al. "Sim-to-Real Transfer of Robotic Control with Dynamics Randomization". In: *CoRR* abs/1710.06537 (2017). arXiv: 1710.06537. URL: http://arxiv.org/abs/1710.06537.

[27] "Predictive Control of a Two-Wheeled Balancing Robot: Lab Practice Control Systems - Experiment Script". In: ().

[28] Antonin Raffin et al. "DECOUPLING FEATURE EXTRACTION FROM POLICY LEARNING: ASSESSING BENEFITS OF STATE REPRESENTA- TION LEARNING IN GOAL BASED ROBOTICS". In: (2019).

[29] Coursera Staff. *What Is a Markov Decision Process?* Coursera. May 15, 2025. URL: https://www.coursera.org/articles/what-is-a-markov-decision-process (visited on 04/28/2026).

[30] Richard S. Sutton and Andrew G. Barto. *Reinforcement learning: an introduction*. Adaptive computation and machine learning. Cambridge, Mass: MIT Press, 1998. 322 pp. ISBN: 978-0-262-19398-6.

[31] Aviv Tamar et al. "IMITATION LEARNING FROM VISUAL DATA WITH MULTIPLE INTENTIONS". In: (2018).

[32] Joshua Tobin et al. "Domain Randomization for Transferring Deep Neural Networks from Simulation to the Real World". In: *CoRR* abs/1703.06907 (2017). arXiv: 1703.06907. URL: http://arxiv.org/abs/1703.06907.

[33] Toshiaki Tsuji et al. "A Survey on Imitation Learning for Contact-Rich Tasks in Robotics". In: *The International Journal of Robotics Research* (Mar. 14, 2026), p. 02783649261417694. ISSN: 0278-3649. DOI: 10.1177/02783649261417694. URL: https://doi.org/10.1177/02783649261417694 (visited on 05/05/2026).

[34] Ashish Vaswani et al. "Attention Is All You Need". In: *Neural Information Processing Systems*. 2017. URL: https://api.semanticscholar.org/CorpusID:13756489.

[35] Walkerastro. *Action Space, State Space, Observation Space demystified*. Medium. Aug. 26, 2024. URL: https://medium.com/@walkerastro41/action-space-state-space-observation-space-demystified-6c9c00a355b4 (visited on 04/28/2026).

[36] Wenshuai Zhao, Jorge Peña Queralta, and Tomi Westerlund. "Sim-to-Real Transfer in Deep Reinforcement Learning for Robotics: A Survey". In: *CoRR* abs/2009.13303 (2020). arXiv: 2009.13303. URL: https://arxiv.org/abs/2009.13303.

# List of Figures

3.1 Base concept of Reinforcement Learning . . . . . 7
3.2 Overview Robotic Learning . . . . . 8
3.3 Training Progress in Deep Learning and Reinforcement Learning . . . . 10
3.4 State-Value Function . . . . . 11
3.5 State-Action Value Function . . . . . 12

4.1 Image-based instructions for task execution [2]. . . . . 18
4.2 Problem: Data Bottleneck in Robotics . . . . . 26
4.3 Key Challenges in Learning from Videos . . . . . 30

# List of Tables