

msaSDK Module

.security

Classes

MSASecurity

Attributes

auth_backend_cookie instance-attribute

```
auth_backend_cookie = AuthenticationBackend(  
    name="jwt_cookie",  
    transport=self.cookie_authentication,  
    get_strategy=get_jwt_strategy,  
)
```

auth_backend_jwt instance-attribute

```
auth_backend_jwt = AuthenticationBackend(  
    name="jwt_bearer",  
    transport=self.bearer_transport,  
    get_strategy=get_jwt_strategy,  
)
```

auth_backends instance-attribute

```
auth_backends = []
```

bearer_transport instance-attribute

```
bearer_transport = BearerTransport(  
    tokenUrl="auth/jwt/login"  
)
```

cookie_authentication instance-attribute

```
cookie_authentication = CookieTransport(  
    cookie_name="sduaiservices-cookie"  
)
```

Functions

`__init__`

```
__init__() -> None
```

Functions

`getMSASecurity` cached

```
getMSASecurity() -> MSASecurity
```

This function returns a cached instance of the MSASecurity object.



Note



Caching is used to prevent re-reading the environment every time the MSASecurity is used.

`getSecretKey`

```
getSecretKey()
```

`get_jwt_strategy`

```
get_jwt_strategy() -> JWTStrategy
```

Last update: September 13, 2022

Created: September 13, 2022