# u2d_msa_sdk Module

## `.admin.admin`

## Attributes

## Classes

### AdminApp

Bases: `PageAdmin`, `AdminGroup`

Management Applications

**Attributes**

__register_lock instance-attribute

```
__register_lock = False
```

db instance-attribute

```
db = AsyncDatabase(self.engine)
```

engine instance-attribute

```
engine = self.engine or self.app.engine
```

msa_app instance-attribute

```
msa_app: MSAApp = msa_app
```

page_path class-attribute

```
page_path = '/'
```

### tabs_mode class-attribute

```
tabs_mode: TabsModeEnum = None
```

**Functions**

#### __init__

```
__init__(app: AdminApp, msa_app: MSAApp)
```

#### get_admin_or_create

```
get_admin_or_create(
    admin_cls: Type[_BaseAdminT], register: bool = True
) -> Optional[_BaseAdminT]
```

#### get_model_admin cached

```
get_model_admin(table_name: str) -> Optional[ModelAdmin]
```

This function returns a cached instance of the ModelAdmin object.

> **Note**
>
> Caching is used to prevent re-reading the environment every time the ModelAdmin object is used.

#### get_page async

```
get_page(request: Request) -> Union[Page, App]
```

#### get_page_schema

```
get_page_schema() -> Optional[PageSchema]
```

#### register_admin

```
register_admin(
    *admin_cls: Type[_BaseAdminT],
) -> Type[_BaseAdminT]
```

#### register_router

```
register_router()
```

#### router_prefix property

```
router_prefix()
```

#### unregister_admin

```
unregister_admin(*admin_cls: Type[BaseAdmin])
```

## AdminGroup

Bases: `PageSchemaAdmin`

Management Applications Group

**Functions**

#### __init__

```
__init__(app: AdminApp) -> None
```

#### __iter__

```
__iter__() -> Iterator[_PageSchemaAdminT]
```

#### append_child

```
append_child(
    child: _PageSchemaAdminT,
    group_schema: PageSchema = None,
) -> None
```

#### get_page_schema_child

```
get_page_schema_child(
    unique_id: str,
) -> Optional[_PageSchemaAdminT]
```

#### get_page_schema_children async

```
get_page_schema_children(
    request: Request,
) -> List[PageSchema]
```

#### unique_id

```
unique_id() -> str
```

## BaseAdmin

### Attributes

app instance-attribute

```
app = app
```

### Functions

#### __init__

```
__init__(app: AdminApp)
```

#### site

```
site() -> BaseAdminSite
```

#### unique_id

```
unique_id() -> str
```

## BaseAdminSite

Bases: `AdminApp`

### Attributes

auth class-attribute

```
auth: Auth = None
```

db_engine instance-attribute

```
db_engine = self.msa_app.db_engine
```

msa_app instance-attribute

```
msa_app = msa_app
```

router instance-attribute

```
router = self.msa_app.router
```

settings instance-attribute

```
settings = msa_app.settings
```

**Functions**

**__init__**

```
__init__(msa_app: MSAApp)
```

**mount_app**

```
mount_app(msa_app: MSAApp, name: str = 'admin') -> None
```

**router_path**

```
router_path() -> str
```

## BaseFormAdmin

Bases: `PageAdmin`

**Attributes**

form class-attribute

```
form: Form = None
```

form_init class-attribute

```
form_init: bool = None
```

### form_path instance-attribute

```
form_path = self.form_path or f'{self.page_path}/api'
```

### route_init class-attribute

```
route_init: Callable = None
```

### route_submit class-attribute

```
route_submit: Callable = None
```

### router_prefix class-attribute

```
router_prefix: str = '/form'
```

### schema class-attribute

```
schema: Type[BaseModel] = None
```

### schema_init_out class-attribute

```
schema_init_out: Type[Any] = Any
```

### schema_submit_out class-attribute

```
schema_submit_out: Type[Any] = Any
```

**Functions**

#### __init__

```
__init__(app: AdminApp)
```

#### get_form async

```
get_form(request: Request) -> Form
```

#### get_form_item async

```
get_form_item(
    request: Request, modelfield: ModelField
) -> Union[FormItem, MSAUISchemaNode]
```

#### get_page async

```
get_page(request: Request) -> Page
```

#### register_router

```
register_router()
```

## BaseModelAction

Base Model Action

**Attributes**

### action class-attribute

```
action: Action = None
```

### admin instance-attribute

```
admin = admin
```

**Functions**

#### __init__

```
__init__(admin: ModelAdmin)
```

#### fetch_item_scalars async

```
fetch_item_scalars(item_id: List[str]) -> List[BaseModel]
```

#### register_router

```
register_router()
```

# BaseModelAdmin

Bases: `MSASQLModelCrud`

**Attributes**

### app `instance-attribute`

```
app = app
```

### bulk_update_fields `class-attribute`

```
bulk_update_fields: List[
    Union[SQLModelListField, FormItem]
] = []
```

> Batch Edit Fields

### engine `instance-attribute`

```
engine = self.engine or self.app.db.engine
```

### fields `instance-attribute`

```
fields = self.fields or [self.model]
```

### link_model_fields `class-attribute`

```
link_model_fields: List[InstrumentedAttribute] = []
```

> Inline Fields

### link_model_forms `class-attribute`

```
link_model_forms: List[LinkModelForm] = []
```

> Inline Forms

### list_display `class-attribute`

```
list_display: List[
    Union[SQLModelListField, TableColumn]
] = []
```

> Fields to be displayed

### list_filter instance-attribute

```
list_filter = self.list_filter or list_display_insfield
```

### list_per_page class-attribute

```
list_per_page: int = 10
```

> Data volume per page

### model instance-attribute

```
model = model
```

### parser instance-attribute

```
parser = MSASQLModelFieldParser(default_model=self.model)
```

### search_fields class-attribute

```
search_fields: List[SQLModelField] = []
```

> Fuzzy search fields

**Functions**

#### __init__

```
__init__(app: AdminApp, model = None)
```

#### get_actions_on_bulk async

```
get_actions_on_bulk(request: Request) -> List[Action]
```

#### get_actions_on_header_toolbar async

```
get_actions_on_header_toolbar(
    request: Request,
) -> List[Action]
```

### get_actions_on_item async

```
get_actions_on_item(request: Request) -> List[Action]
```

### get_create_action async

```
get_create_action(
    request: Request, bulk: bool = False
) -> Optional[Action]
```

### get_create_form async

```
get_create_form(
    request: Request, bulk: bool = False
) -> Form
```

### get_delete_action async

```
get_delete_action(
    request: Request, bulk: bool = False
) -> Optional[Action]
```

### get_form_item async

```
get_form_item(
    request: Request,
    modelfield: ModelField,
    action: MSACRUDEnum,
) -> Union[FormItem, MSAUISchemaNode, None]
```

### get_form_item_on_foreign_key async

```
get_form_item_on_foreign_key(
    request: Request,
    modelfield: ModelField,
    is_filter: bool = False,
) -> Union[Service, MSAUISchemaNode, None]
```

### get_link_model_forms

```
get_link_model_forms() -> List[LinkModelForm]
```

### get_list_column async

```
get_list_column(
    request: Request, modelfield: ModelField
) -> TableColumn
```

### get_list_columns async

```
get_list_columns(request: Request) -> List[TableColumn]
```

### get_list_display async

```
get_list_display(
    request: Request,
) -> List[Union[SQLModelListField, TableColumn]]
```

### get_list_filter async

```
get_list_filter(
    request: Request,
) -> List[Union[SQLModelListField, FormItem]]
```

### get_list_filter_form async

```
get_list_filter_form(request: Request) -> Form
```

### get_list_table async

```
get_list_table(request: Request) -> TableCRUD
```

### get_list_table_api async

```
get_list_table_api(request: Request) -> MSAUIAPI
```

### get_update_action async

```
get_update_action(
    request: Request, bulk: bool = False
) -> Optional[Action]
```

### get_update_form async

```
get_update_form(
    request: Request, bulk: bool = False
```

```
) -> Form
```

#### router_path

```
router_path() -> str
```

## FormAdmin

Bases: `BaseFormAdmin`

Form Management

#### Functions

#### get_init_data async

```
get_init_data(
    request: Request, **kwargs
) -> MSACRUDOut[Any]
```

#### handle async

```
handle(
    request: Request, data: BaseModel, **kwargs
) -> MSACRUDOut[Any]
```

#### route_init property

```
route_init()
```

#### route_submit property

```
route_submit()
```

## IframeAdmin

Bases: `PageSchemaAdmin`

#### Attributes

#### iframe class-attribute

```
iframe: Iframe = None
```

src class-attribute

```
src: str = ''
```

**Functions**

### get_page_schema

```
get_page_schema() -> Optional[PageSchema]
```

## LinkAdmin

Bases: `PageSchemaAdmin`

Management Links

**Attributes**

link class-attribute

```
link: str = ''
```

**Functions**

### get_page_schema

```
get_page_schema() -> Optional[PageSchema]
```

## LinkModelForm

Link Model to Form

**Attributes**

display_admin instance-attribute

```
display_admin = display_admin
```

item_col instance-attribute

```
item_col = item_col
```

### link_col instance-attribute

```
link_col = link_col
```

### link_model instance-attribute

```
link_model = link_model
```

### path instance-attribute

```
path = f'/{self.display_admin.model.__name__.lower()}'
```

### pk_admin instance-attribute

```
pk_admin = pk_admin
```

**Functions**

#### __init__

```
__init__(
    pk_admin: BaseModelAdmin,
    display_admin: ModelAdmin,
    link_model: Union[SQLModel, Table],
    link_col: Column,
    item_col: Column,
)
```

#### bind_model_admin classmethod

```
bind_model_admin(
    pk_admin: BaseModelAdmin,
    insfield: InstrumentedAttribute,
) -> Optional[LinkModelForm]
```

#### get_form_item async

```
get_form_item(request: Request)
```

#### register_router

```
register_router()
```

#### route_create property

```
route_create()
```

#### route_delete property

```
route_delete()
```

## ModelAction

Bases: `BaseFormAdmin`, `BaseModelAction`

Form and Model Actions

**Attributes**

action class-attribute

```
action: ActionType.Dialog = None
```

router instance-attribute

```
router = self.admin.router
```

schema class-attribute

```
schema: Type[BaseModel] = None
```

**Functions**

#### __init__

```
__init__(admin: ModelAdmin)
```

#### get_action async

```
get_action(request: Request, **kwargs) -> Action
```

#### handle async

```
handle(
    request: Request,
    item_id: List[str],
    data: Optional[BaseModel],
    **kwargs
) -> MSACRUDOut[Any]
```

#### route_submit property

```
route_submit()
```

## ModelAdmin

Bases: `BaseModelAdmin`, `PageAdmin`

Model Management

#### Attributes

##### bind_model class-attribute

```
bind_model: bool = True
```

##### page_path class-attribute

```
page_path: str = ''
```

#### Functions

##### __init__

```
__init__(app: AdminApp, model = None)
```

#### get_page async

```
get_page(request: Request) -> Page
```

#### has_create_permission async

```
has_create_permission(
    request: Request, data: BaseModel, **kwargs
) -> bool
```

#### has_delete_permission async

```
has_delete_permission(
    request: Request, item_id: List[str], **kwargs
) -> bool
```

#### has_list_permission async

```
has_list_permission(
    request: Request,
    paginator: MSACRUDPaginator,
    filters: BaseModel = None,
    **kwargs
) -> bool
```

#### has_read_permission async

```
has_read_permission(
    request: Request, item_id: List[str], **kwargs
) -> bool
```

#### has_update_permission async

```
has_update_permission(
    request: Request,
    item_id: List[str],
    data: BaseModel,
    **kwargs
) -> bool
```

#### register_router

```
register_router()
```

#### router_prefix property

```
router_prefix()
```

## ModelFormAdmin

Bases: `FormAdmin`, `MSASQLModelSelector`, `ABC`

todo Read and update a model resource

**Functions**

#### __init__

```
__init__(app: AdminApp)
```

## PageAdmin

Bases: `PageSchemaAdmin`, `RouterAdmin`

msa_ui page management

**Attributes**

page `class-attribute`

```
page: Page = None
```

page_parser_mode `class-attribute`

```
page_parser_mode: Literal[json, html] = 'json'
```

page_path `class-attribute`

```
page_path: Optional[str] = None
```

page_route_kwargs `class-attribute`

```
page_route_kwargs: Dict[str, Any] = {}
```

router_prefix `class-attribute`

```
router_prefix = '/page'
```

template_name `class-attribute`

```
template_name: str = ''
```

**Functions**

#### __init__

```
__init__(app: AdminApp)
```

#### error_no_page_permission

```
error_no_page_permission(request: Request)
```

#### get_page async

```
get_page(request: Request) -> Page
```

#### get_page_schema

```
get_page_schema() -> Optional[PageSchema]
```

#### page_parser async

```
page_parser(request: Request, page: Page) -> Response
```

#### page_permission_depend async

```
page_permission_depend(request: Request) -> bool
```

#### register_router

```
register_router()
```

#### route_page property

```
route_page() -> Callable
```

## PageSchemaAdmin

Bases: `BaseAdmin`

**Attributes**

group_schema instance-attribute

```
group_schema = self.get_group_schema()
```

page_schema instance-attribute

```
page_schema = self.get_page_schema()
```

**Functions**

### __init__

```
__init__(app: AdminApp)
```

### get_group_schema

```
get_group_schema() -> Optional[PageSchema]
```

| RAISES | DESCRIPTION |
| --- | --- |
| `TypeError` | TypeError(_StandardError) |

### get_page_schema

```
get_page_schema() -> Optional[PageSchema]
```

| RAISES | DESCRIPTION |
| --- | --- |
| `TypeError` | TypeError(_StandardError) |

### has_page_permission async

```
has_page_permission(request: Request) -> bool
```

## RouterAdmin

Bases: `BaseAdmin`, `MSARouterMixin`

Management Router

**Functions**

### __init__

```
__init__(app: AdminApp)
```

#### register_router

```
register_router()
```

#### router_path

```
router_path() -> str
```

## TemplateAdmin

Bases: `PageAdmin`

Jinja2-Rendering Template Management

**Attributes**

page `class-attribute`

```
page: Dict[str, Any] = {}
```

page_parser_mode `class-attribute`

```
page_parser_mode = 'html'
```

page_path `instance-attribute`

```
page_path = self.page_path or f'/{self.template_name}'
```

templates `class-attribute`

```
templates: Jinja2Templates = None
```

**Functions**

#### __init__

```
__init__(app: AdminApp)
```

#### get_page `async`

```
get_page(request: Request) -> Dict[str, Any]
```

### page_parser async

```
page_parser(
    request: Request, page: Dict[str, Any]
) -> Response
```

---

Last update: September 13, 2022

Created: September 13, 2022