

# Auth Admin Site

## msaSDK Auth

*msaSDK Auth.*

*Auth Site that extends the Admin Site Web UI with Login/Auth for the API's.*

## Simple Example

Just define in the Service Definition (Settings)

```
site_auth: bool = False
```

```
# -*- encoding: utf-8 -*-
"""
Copyright (c) 2022 - U2D.ai / S.Welcker
"""
__version__ = "0.0.1"

from msaSDK.models.service import get_msa_app_settings
from msaSDK.service import MSAAApp

# get the MSA app setting, clear the cache, set some settings
get_msa_app_settings.cache_clear()
settings = get_msa_app_settings()
settings.title = "SPK.ai - MSA/SDK MVP"
settings.version = "SPK.0.0.1"
settings.debug = True
settings.site_auth = True

# Create the main app instance, like FastAPI but provide a Setting Definition Instance
# Define if the optional Admin Site gets mounted automatically, if False you need to
Mount in your own Startup MSAUIEvent Handler
app = MSAAApp(settings=settings, auto_mount_site=True,
              contact={"name": "msaSDK", "url": "http://u2d.ai", "email":
"stefan@u2d.ai"},
              license_info={"name": "MIT", "url": "https://opensource.org/licenses/MIT",
})

# use the internal logger of app
app.logger.info("Initialized " + settings.title + " " + settings.version)

# Optional use startup event
```

```

@app.on_event("startup")
async def startup():
    app.logger.info("msaSDK Own Startup MSAUIEvent")

# Optional use shutdown event
@app.on_event("shutdown")
async def shutdown():
    app.logger.info("msaSDK Own Shutdown MSAUIEvent")

```

## Validation Method

### Decorator

- Recommended scenario: Single route. Supports synchronous/asynchronous routing.

```

@app.get("/auth/user")
@app.auth.requires()
def user(request: Request):
    return request.user

@app.get("/auth/admin_roles")
@app.auth.requires('admin')
def admin_roles(request: Request):
    return request.user

@app.get("/auth/vip_roles")
@app.auth.requires(['vip'])
async def vip_roles(request: Request):
    return request.user

@app.get("/auth/admin_or_vip_roles")
@app.auth.requires(roles = ['admin', 'vip'])
def admin_or_vip_roles(request: Request):
    return request.user

@app.get("/auth/admin_groups")
@app.auth.requires(groups = ['admin'])
def admin_groups(request: Request):
    return request.user

@app.get("/auth/admin_roles_and_admin_groups")
@app.auth.requires(roles = ['admin'], groups = ['admin'])
def admin_roles_and_admin_groups(request: Request):
    return request.user

@app.get("/auth/vip_roles_and_article_update")
@app.auth.requires(roles = ['vip'], permissions = ['article:update'])

```

```
def vip_roles_and_article_update(request: Request):
    return request.user
```

## Dependencies (Recommended)

- Recommended scenarios: single routes, route collections, MSAApp applications.

```
from fastapi import Depends
from typing import Tuple
from msaSDK.auth import Auth
from msaSDK.auth.models import User

app = MSAApp...

@app.get("/auth/admin_roles_depend_1")
def admin_roles(user: User = Depends(app.auth.get_current_user)):
    return user # or request.user

@app.get("/auth/admin_roles_depend_2", dependencies=[Depends(app.auth.requires('admin'))])
def admin_roles(request: Request):
    return request.user

app = MSAApp(dependencies=[Depends(app.auth.requires('admin'))])

@app.get("/auth/admin_roles_depend_3")
def admin_roles(request: Request):
    return request.user
```

## Middleware

- Recommended Scenario: MSAApp Application

```
app = MSAApp()

auth.backend.attach_middleware(app)
```

## Direct call

- Recommended scenarios: Non-routed methods

```
from msaSDK.auth.models import User

async def get_request_user(request: Request) -> Optional[User]:
    # user= await auth.get_current_user(request)
```

```

if await auth.requires('admin', response=False)(request):
    return request.user
else:
    return None

```

## Token Storage Backend

NSA auth supports multiple token storage methods. Default is: `DbTokenStore`, suggest to customize it to: `JwtTokenStore`.

### JwtTokenStore

```

from msaSDK.auth.backends.jwt import JwtTokenStore
from sqlalchemy.ext.asyncio import create_async_engine
from sqlalchemy_database import AsyncDatabase

engine = create_async_engine(url='sqlite+aiosqlite:///amisadmin.sqlite_db', future=True)

auth = Auth(
    db=AsyncDatabase(engine),

    token_store=JwtTokenStore(secret_key='09d25e094faa6ca2556c818166b7a9563b93f7099f6f0f4caa6c1
)

# Auth Admin Site
site = AuthAdminSite(
    settings=Settings(database_url_async='sqlite+aiosqlite:///amisadmin.sqlite_db'),
    auth=auth
)

```

### DbTokenStore

```

from msaSDK.auth.backends.db import DbTokenStore

auth = Auth(
    db=AsyncDatabase(engine),
    token_store=DbTokenStore(db=AsyncDatabase(engine))
)

```

### RedisTokenStore

```

# Creating auth objects with `RedisTokenStore`
from msaSDK.auth.backends.redis import RedisTokenStore
from aioredis import Redis

auth = Auth(
    db=AsyncDatabase(engine),


```

```
token_store=RedisTokenStore(redis=Redis.from_url('redis://localhost?sqlite_db=0'))
)
```

## RBAC Model

The `RBAC` model used in this system is as follows, you can also expand it according to your needs.

- Reference: [Design of permission system](#)



## Advanced Expansion

### Expanding the `User` model

```
from datetime import date

from msaSDK.admin.models.fields import Field
from msaSDK.auth.models import BaseUser

# Customize the `User` model, inherit from `BaseUser`.
class MyUser(BaseUser, table=True):
    birthday: date = Field(None, title="Date of Birth")
    location: str = Field(None, title="Location")

# Create auth objects using a custom `User` model
auth = Auth(db=AsyncDatabase(engine), user_model=MyUser)
```

### Extending the `Role`, `Group`, `Permission` model

```
# Customize `Group` model, inherit from `BaseRBAC`;
# override `Role`, `Permission` model is similar, the difference is the table name.
class MyGroup(BaseRBAC, table = True):
    __tablename__ = 'auth_group' # Database table name, must be this to override the
    default model
    icon: str = Field(None, title = 'Icons')
    is_active: bool = Field(default = True, title = "Activate or not")
```

### Customize `UserAuthApp` default management class

The default management classes can be replaced by inheritance overrides. For example:

`UserLoginFormAdmin`, `UserRegFormAdmin`, `UserInfoFormAdmin`,  
`UserAdmin`, `GroupAdmin`, `RoleAdmin`, `PermissionAdmin`

```
# Custom model management class, inheritance rewrites the corresponding default
management class
class MyGroupAdmin(admin.ModelAdmin):
    group_schema = None
    page_schema = PageSchema(label = 'User Group Management', icon = 'fa fa-group')
    model = MyGroup
    link_model_fields = [Group.roles]
    readonly_fields = ['key']

# Customize the user authentication application, inherit and rewrite the default user
authentication application
class MyUserAuthApp(UserAuthApp):
    GroupAdmin = MyGroupAdmin

# Customize user management site, inherit rewrite the default user management site
class MyAuthAdminSite(AuthAdminSite):
    UserAuthApp = MyUserAuthApp

# Use the custom `AuthAdminSite` class to create the site object
site = MyAuthAdminSite(settings, auth = auth)
```

## Interface Preview

### Login Screen

- Open `http://127.0.0.1:8090/admin/auth/form/login` in your browser:

User Login

---



## Login

MSA SDK Admin - Login

\* Password

\* Username

Sign up

Sign in

### Home Screen with System Info

- Open `http://127.0.0.1:8090/admin/` in your browser:

The screenshot shows the msaSDK Admin interface. The left sidebar contains links for Home, TestArticle, TestCategory, API Docs, and Profiler. The main content area displays three sections:

### Service Info

Title	Version	Language	Debug
SPK.ai - MSA/SDK MVP	SPK.0.0.1		True

### MSA SDK

System	Python	Version	License
Linux	3.9.14	0.0.1	MIT

### System

Property	Value	Property	Value
Booted	2022-09-07 09:30:50	IP	127.0.1.1
CPU Physical	8	MAC Address	45:af:c9:4d:95:67
Mem Total	65.6 GB	CPU Logical	16
OS Name	Linux	CPU in Use	0
		CPU Affinity	16
		Mem Usage	24.8%
		Mem Free	49.35 GB
		PID	165749
		OS Release	5.15.0-47-generic
		Status	running

Copyright © 2022 by u2d.ai [msa-sdk-admin v0.0.1](#)

## CRUD of SQLModels Screen

The screenshot shows the msaSDK Admin interface for the 'TestCategory' screen. The left sidebar contains links for Home, TestArticle, TestCategory, API Docs, and Profiler. The main content area displays a filter section and a table of results.

### Filter

id  ArticleTitle  ArticleDescription  status ☐ ArticleContent

SHOWING 2 OF 2 RESULT(S)

id	ArticleTitle	ArticleDescription	status	ArticleContent
1	cat 11	cat 11	<input checked="" type="checkbox"/>	cat content 11
2	cat 2	cat 2	<input checked="" type="checkbox"/>	cat content 2



## OpenAPI Interactive Documentation (Swagger) Screen

- Open `http://127.0.0.1:8090/admin/docs` in your browser:

The screenshot displays the OpenAPI Interactive Documentation (Swagger) screen for the msaSDK Admin interface. The interface features a dark blue sidebar on the left with navigation links: Home, TestArticle, TestCategory, API Docs (expanded), OpenAPI, Redocs, and Profiler. The main content area shows the 'auth' API section with a list of endpoints. Each endpoint is represented by a colored bar indicating the HTTP method (GET, POST, DELETE) and the endpoint path. The endpoints are as follows:

Method	Endpoint	Description	Access
GET	/auth/userinfo	Userinfo	Public
GET	/auth/logout	User Logout	Public
POST	/auth/gettoken	OAuth Token	Protected
POST	/auth/	Route	Protected
POST	/auth/form/login/api	Route	Protected
POST	/auth/form/reg/api	Route	Protected
POST	/auth/form/userinfo	Userinfo	Protected
GET	/auth/form/userinfo/api	Route	Protected
POST	/auth/form/userinfo/api	Route	Protected
POST	/auth/useradmin/role/{item_id}	Auth User Roles Create	Protected
DELETE	/auth/useradmin/role/{item_id}	Auth User Roles Delete	Protected
POST	/auth/useradmin/group/{item_id}	Auth User Groups Create	Protected
DELETE	/auth/useradmin/group/{item_id}	Auth User Groups Delete	Protected

At the bottom of the screen, the copyright information is displayed: Copyright © 2022 by u2d.ai msa-sdk-admin v0.0.1

## License Agreement

- msaSDK Based on MIT open source and free to use, it is free for commercial use, but please clearly show the copyright information about msaSDK - Auth Admin in the display interface.

Last update: September 14, 2022

Created: September 9, 2022