u2d_msa_sdk Module

.utils.scheduler

Attributes

```
__version__ (module-attribute)
```

```
__version__ = '0.0.3'
```

Classes

MSAScheduler

Attributes

debug instance-attribute

```
debug = debug
```

Debug mode True/False

enabled instance-attribute

```
enabled: bool = False
```

is_running (instance-attribute)

```
is_running: bool = False
```

jobs instance-attribute

jobs = jobs

dictionary MSATimers instances

 $local_time_zone({\scriptstyle {\tt instance-attribute}})$

```
local_time_zone = local_time_zone
```

logger instance-attribute

```
logger = parent_logger if parent_logger else logger
```

Functions

__init__

```
__init__(
    jobs: dict,
    local_time_zone: str = "UTC",
    poll_millis: float = 1000,
    debug: bool = False,
    parent_logger: Logger = None,
)
```

MSAScheduler object runs timers

Standard Polling is 1 second

PARAMETER	DESCRIPTION	
jobs	timer_jobs: dict[MSATimerEnum, list] = { TYPE: dict	
local_time_zone	str = 'UTC' TYPE: str	DEFAULT: 'UTC'
poll_millis	float = 1000 TYPE: float	DEFAULT: 1000
debug	bool = False TYPE: bool	DEFAULT: False
parent_logger	logger instance to use, if empty it creates a local loguru logger TYPE: Logger DEFAULT: None	

```
run_timers(poll_adjuster = 0.99, debug = False)

runs timers as follows:

• Step 1: run every poll jobs

• Step 2: load timer queues for next poll

• Step 3: delay function which runs previous poll queues

poll_adjustor allows time for other timing

stop_timers

stop_timers()
```

MSATimerEnum

Stop all timers

```
Enum for the different timer Types

Attributes

every_hour __class-attribute

every_minute __lass-attribute

every_minute = 'every minute'

every_poll __class-attribute

every_poll = 'every poll'

every_second __lass-attribute
```

```
on_the_15_minute class-attribute
  on_the_15_minute = 'on the 15 minute'
on_the_15_second _{\text{class-attribute}}
  on_{the_{15}_{second}} = 'on the 15 second'
on_the_30_minute class-attribute
  on_the_30_minute = 'on the 30 minute'
on_the_30_second class-attribute
  on_the_30_second = 'on the 30 second'
on_the_5_minute class-attribute
  on_the_5_minute = 'on the 5 minute'
on_the_5_second _{class-attribute}
  on_{the_{5}}=cond = 'on the 5 second'
schedule class-attribute
  schedule = 'schedule'
```

MSATimers

Class to create dictionary of timers for use in MSAScheduler.

Attributes

```
timer_jobs [instance-attribute]
```

```
timer_jobs = {
    MSATimerEnum.every_poll: [],
    MSATimerEnum.every_second: [],
    MSATimerEnum.on_the_5_second: [],
    MSATimerEnum.on_the_15_second: [],
    MSATimerEnum.on_the_30_second: [],
```

```
MSATimerEnum.every_minute: [],
   MSATimerEnum.on_the_5_minute: [],
   MSATimerEnum.on_the_15_minute: [],
   MSATimerEnum.on_the_30_minute: [],
   MSATimerEnum.every_hour: [],
   MSATimerEnum.schedule: [],
}
```

Functions

__init__

```
__init__()
```

self.timer_jobs is the primary resource in MSATimers This is filled by MSATimers It is then accessed by the source and served to MSAScheduler

create_timer

```
create_timer(
   T_mode: MSATimerEnum,
   func: typing.Callable,
   mark_HH_MM: str = None,
)
```

Create a Timer

PARAMETER	DESCRIPTION	
T_mode	MSATimerEnum TYPE: MSATimerEnum	
func	the call handler for this timer TYPE: typing.Callable	
mark_HH_MM	If scheduler type then this is the time for execution. TYPE: str	DEFAULT: None

Functions

get_time

```
get_time(local_time_zone = 'UTC')
```

get_time_stamp

```
get_time_stamp(
    local_time_zone="UTC", time_format="HMS"
)
```

Last update: September 13, 2022 Created: September 13, 2022