# msaSDK Module

.utils.scheduler

### Classes

### **MSAScheduler**

Bases: Rocketry

Scheduling application



If enabled, it creates a memory log as this info is neede for some conditions. So ensure the memory doesnt run full Define a task that clears the log

```
repo: MemoryRepo = self.scheduler.session.get_repo()
repo.collection.clear()
```

**Execution conditions** 

Execution on fixed time interval Syntax

```
[hourly | daily | weekly | monthly]
[hourly | daily | weekly | monthly] between <start> and <end>
[hourly | daily | weekly | monthly] [before | after | starting] <time>
```

Fixed time interval Syntax

```
time of [hour | day | week | month] between <start> and <end> time of [hour | day | week | month] [after | before] <time>
```

Timedelta Syntax

```
every <timedelta>
```

Task Status Syntax

```
has [succeeded | failed | finished | started | terminated] [this hour | today | this week | this month] between <start> and <end> has [succeeded | failed | finished | started | terminated] [this hour | today | this week | this month] [before | after] <time> has [succeeded | failed | finished | started | terminated] past <timedelta>
```

#### Task Dependence Syntax

```
after task '<task>'
after task '<task>' [succeeded | failed | finished | terminated]
after tasks '<task 1>', '<task 2>' ...
after tasks '<task 1>', '<task 2>' ... [succeeded | failed | finished]
after any tasks '<task 1>', '<task 2>' ... [succeeded | failed | finished]
```

#### **Examples:**

```
# Execution on fixed time interval
app.scheduler.task("hourly")
app.scheduler.task("daily between 22:00 and 23:00")
app.scheduler.task("weekly before Friday")
app.scheduler.task("monthly starting 3rd")
# Fixed time interval
app.scheduler.task("time of hour before 45:00")
app.scheduler.task("time of day between 10:00 and 16:00")
app.scheduler.task("time of week after Monday")
app.scheduler.task("time of month after 5th")
# Time delta
app.scheduler.task("every 1 hour")
app.scheduler.task("every 30 sec")
app.scheduler.task("every 2 hours, 30 minutes")
app.scheduler.task("every 1 day, 12 hour, 30 min, 20 sec")
# Task Status
app.scheduler.task("has succeeded this hour")
app.scheduler.task("has failed today between 08:00 and 16:00")
app.scheduler.task("has started this week before Friday")
app.scheduler.task("has terminated this month after 6th")
app.scheduler.task("has succeeded past 2 hours, 30 minutes")
# Task Dependence
app.scheduler.task("after task 'a_task'")
app.scheduler.task("after task 'a_task' succeeded")
app.scheduler.task("after task 'a_task' failed")
app.scheduler.task("after task 'a_task' finished")
app.scheduler.task("after tasks 'a_task', 'another_task' finished")
```

#### **Functions**

\_\_init\_\_

```
__init__(
    session: Session = None,
    logger_repo: Optional[BaseRepo] = None,
    execution=None,
    **kwargs
)
```

## **Functions**

## get\_time

```
get_time(local_time_zone = 'UTC')
```

## get\_time\_stamp

```
get_time_stamp(
    local_time_zone="UTC", time_format="HMS"
)
```

Last update: September 14, 2022 Created: September 14, 2022