

msaSDK Module

`.utils.sysinfo`

Provides System Information about devices, OS etc.

Attributes

`__version__` module-attribute

```
__version__ = '0.1.1'
```

str: Module Version

Classes

MSACPUFrequency

Bases: `SQLModel`

Pydantic CPU Frequency Info Model.

Attributes

`current` class-attribute

```
current: Optional[float]
```

`max` class-attribute

```
max: Optional[int]
```

`min` class-attribute

```
min: Optional[int]
```

MSACPUStats

Bases: `SQLModel`

Pydantic CPU Stats Info Model.

Attributes

`ctx_switches` class-attribute

```
ctx_switches: Optional[int]
```

number of context switches (voluntary + involuntary) since boot.

`interrupts` class-attribute

```
interrupts: Optional[int]
```

number of interrupts since boot.

`soft_interrupts` class-attribute

```
soft_interrupts: Optional[int]
```

number of software interrupts since boot. Always set to 0 on Windows and SunOS.

`syscalls` class-attribute

```
syscalls: Optional[int]
```

number of system calls since boot. Always set to 0 on Linux.

MSACPUTimes

Bases: `SQLModel`

Pydantic CPU Timings Info Model.

Attributes

`guest` class-attribute

```
guest: Optional[float]
```

(Linux 2.6.24+): time spent running a virtual CPU for guest operating systems under the control of the Linux kernel

guest_nice class-attribute

```
guest_nice: Optional[int]
```

(Linux 3.2.0+): time spent running a niced guest (virtual CPU for guest operating systems under the control of the Linux kernel)

idle class-attribute

```
idle: Optional[float]
```

time spent doing nothing

iowait class-attribute

```
iowait: Optional[float]
```

(Linux): time spent waiting for I/O to complete. This is not accounted in idle time counter.

irq class-attribute

```
irq: Optional[int]
```

(Linux, BSD): time spent for servicing hardware interrupts

nice class-attribute

```
nice: Optional[int]
```

(UNIX): time spent by niced (prioritized) processes executing in user mode; on Linux this also includes guest_nice time

softirq class-attribute

```
softirq: Optional[float]
```

(Linux): time spent for servicing software interrupts

steal class-attribute

steal: Optional[int]

(Linux 2.6.11+): time spent by other operating systems running in a virtualized environment

system class-attribute

system: Optional[float]

time spent by processes executing in kernel mode

user class-attribute

user: Optional[float]

time spent by normal processes executing in user mode; on Linux this also includes guest time

MSADiskIO

Bases: SQLModel

Pydantic Disk IO Info Model.

ATTRIBUTE	DESCRIPTION
<small>read_count</small>	number of reads TYPE: <small>Optional[int]</small>
<small>write_count</small>	number of writes TYPE: <small>Optional[int]</small>
<small>read_bytes</small>	number of bytes read TYPE: <small>Optional[int]</small>
<small>write_bytes</small>	number of bytes written TYPE: <small>Optional[int]</small>
<small>read_time</small>	(all except NetBSD and OpenBSD) time spent reading from disk (in milliseconds) TYPE: <small>Optional[int]</small>

ATTRIBUTE	DESCRIPTION
<code>write_time</code>	(all except NetBSD and OpenBSD) time spent writing to disk (in milliseconds) TYPE: <code>Optional[int]</code>
<code>busy_time</code>	(Linux, FreeBSD) time spent doing actual I/Os (in milliseconds) TYPE: <code>Optional[int]</code>
<code>read_merged_count</code>	number of merged reads (see iostats doc) TYPE: <code>Linux</code>
<code>write_merged_count</code>	number of merged writes (see iostats doc) TYPE: <code>Linux</code>

Attributes

`busy_time` class-attribute

```
busy_time: Optional[int]
```

`read_bytes` class-attribute

```
read_bytes: Optional[int]
```

`read_count` class-attribute

```
read_count: Optional[int]
```

`read_merged_count` class-attribute

```
read_merged_count: Optional[int]
```

`read_time` class-attribute

```
read_time: Optional[int]
```

`write_bytes` class-attribute

```
write_bytes: Optional[int]
```

write_count class-attribute

```
write_count: Optional[int]
```

write_merged_count class-attribute

```
write_merged_count: Optional[int]
```

write_time class-attribute

```
write_time: Optional[int]
```

MSAGPUInfo

Bases: SQLModel

Pydantic GPU Info Model.

Attributes

free_memory class-attribute

```
free_memory: Optional[str]
```

id class-attribute

```
id: Optional[int]
```

load class-attribute

```
load: Optional[str]
```

name class-attribute

```
name: Optional[str]
```

temperature class-attribute

```
temperature: Optional[str]
```

total_memory class-attribute

```
total_memory: Optional[str]
```

used_memory class-attribute

```
used_memory: Optional[str]
```

uuid class-attribute

```
uuid: Optional[str]
```

MSAMemoryUsage

Bases: SQLModel

Pydantic Memory Usage Info Model.

Attributes

active class-attribute

```
active: Optional[float]
```

(UNIX): memory currently in use or very recently used, and so it is in RAM.

available class-attribute

```
available: Optional[float]
```

the memory that can be given instantly to processes without the system going into swap. This is calculated by summing different memory values depending on the platform and it is supposed to be used to monitor actual memory usage in a cross platform fashion.

buffers class-attribute

```
buffers: Optional[float]
```

(Linux, BSD): cache for things like file system metadata.

cached class-attribute

```
cached: Optional[float]
```

(Linux, BSD): cache for various things.

free class-attribute

```
free: Optional[float]
```

memory not being used at all (zeroed) that is readily available; note that this doesn't reflect the actual memory available (use available instead). total - used does not necessarily match free.

inactive class-attribute

```
inactive: Optional[float]
```

(UNIX): memory that is marked as not used.

percent class-attribute

```
percent: Optional[float]
```

the percentage usage calculated as $(\text{total} - \text{available}) / \text{total} * 100$

total class-attribute

```
total: Optional[float]
```

total physical memory (exclusive swap).

used class-attribute

```
used: Optional[float]
```

memory used, calculated differently depending on the platform and designed for informational purposes only. total - free does not necessarily match used.

MSANetworkAdapter

Bases: SQLModel

Pydantic Network Adapter Info Model.

Attributes

address class-attribute

```
address: Optional[str]
```

the primary NIC address (always set).

broadcast class-attribute

```
broadcast: Optional[str]
```

the broadcast address (may be None).

family class-attribute

```
family: Optional[int]
```

the address family, either AF_INET or AF_INET6 or psutil.AF_LINK, which refers to a MAC address.

netmask class-attribute

```
netmask: Optional[str]
```

the netmask address (may be None).

ptp class-attribute

```
ptp: Optional[int]
```

stands for "point to point"; it's the destination address on a point to point interface (typically a VPN). broadcast and ptp are mutually exclusive. May be None.

MSANetworkAdapters

Bases: SQLModel

Pydantic Network Adapters List Model.

Attributes

adapters class-attribute

```
adapters: List[MSANetworkAdapter] = []
```

name class-attribute

```
name: str = ''
```

MSANetworkConnection

Bases: SQLModel

Pydantic Network Connection Info Model.

Attributes

family class-attribute

```
family: Optional[int]
```

the address family, either AF_INET, AF_INET6 or AF_UNIX.

file_descriptor class-attribute

```
file_descriptor: Optional[int]
```

the socket file descriptor. If the connection refers to the current process this may be passed to socket.fromfd to obtain a usable socket object. On Windows and SunOS this is always set to -1.

index class-attribute

```
index: Optional[int]
```

local_addr class-attribute

```
local_addr: Optional[str]
```

the local address as a (ip, port) named tuple or a path in case of AF_UNIX sockets. For UNIX sockets see notes below.

pid class-attribute

```
pid: Optional[int]
```

the PID of the process which opened the socket, if retrievable, else None. On some platforms (e.g. Linux) the availability of this field changes depending on process privileges (root is needed).

remote_addr class-attribute`remote_addr: Optional[str]`

the remote address as a `(ip, port)` named tuple or an absolute `path` in case of UNIX sockets. When the remote endpoint is not connected you'll get an empty tuple (`AF_INET*`) or `""` (`AF_UNIX`). For UNIX sockets see notes below.

status class-attribute`status: str = ''`

represents the status of a TCP connection. The return value is one of the `psutil.CONN_*` constants (a string). For UDP and UNIX sockets this is always going to be `psutil.CONN_NONE`.

type class-attribute`type: Optional[int]`

the address type, either `SOCK_STREAM`, `SOCK_DGRAM` or `SOCK_SEQPACKET`.

MSANetworkIO

Bases: `SQLModel`

Pydantic Network IO Info Model.

ATTRIBUTE	DESCRIPTION
<code>bytes_sent</code>	number of bytes sent TYPE: <code>Optional[int]</code>
<code>bytes_recv</code>	number of bytes received TYPE: <code>Optional[int]</code>
<code>packets_sent</code>	number of packets sent TYPE: <code>Optional[int]</code>
<code>packets_recv</code>	number of packets received TYPE: <code>Optional[int]</code>

ATTRIBUTE	DESCRIPTION
<code>errin</code>	total number of errors while receiving TYPE: <code>Optional[int]</code>
<code>errout</code>	total number of errors while sending TYPE: <code>Optional[int]</code>
<code>dropin</code>	total number of incoming packets which were dropped TYPE: <code>Optional[int]</code>
<code>dropout</code>	total number of outgoing packets which were dropped (always 0 on macOS and BSD) TYPE: <code>Optional[int]</code>

Attributes

`bytes_recv` class-attribute

```
bytes_recv: Optional[int]
```

`bytes_sent` class-attribute

```
bytes_sent: Optional[int]
```

`dropin` class-attribute

```
dropin: Optional[int]
```

`dropout` class-attribute

```
dropout: Optional[int]
```

`errin` class-attribute

```
errin: Optional[int]
```

`errout` class-attribute

```
errout: Optional[int]
```

packets_recv class-attribute

```
packets_recv: Optional[int]
```

packets_sent class-attribute

```
packets_sent: Optional[int]
```

MSANetworkStat

Bases: SQLModel

Pydantic Network Stats Info Model.

Attributes

duplex class-attribute

```
duplex: Optional[int]
```

the duplex communication type; it can be either NIC_DUPLEX_FULL, NIC_DUPLEX_HALF or NIC_DUPLEX_UNKNOWN.

isup class-attribute

```
isup: Optional[bool]
```

a bool indicating whether the NIC is up and running (meaning ethernet cable or Wi-Fi is connected).

mtu class-attribute

```
mtu: Optional[int]
```

NIC's maximum transmission unit expressed in bytes.

speed class-attribute

```
speed: Optional[int]
```

the NIC speed expressed in mega bits (MB), if it can't be determined (e.g. 'localhost') it will be set to 0.

MSANetworkStats

Bases: `SQLModel`

Pydantic Network Stats List Info Model.

Attributes

adapters `class-attribute`

```
adapters: List[MSANetworkStat] = []
```

name `class-attribute`

```
name: str = ''
```

MSASwap

Bases: `SQLModel`

Pydantic Swapfile Info Model.

Attributes

free `class-attribute`

```
free: Optional[float]
```

percent `class-attribute`

```
percent: Optional[float]
```

the percentage usage calculated as (total - available) / total * 100

total `class-attribute`

```
total: Optional[float]
```

used `class-attribute`

```
used: Optional[float]
```

MSASystemGPUInfo

Bases: `SQLModel`

Pydantic System GPU Info Model.

Attributes

CPU_Logical `class-attribute`

```
CPU_Logical: Optional[int]
```

CPU_Physical `class-attribute`

```
CPU_Physical: Optional[int]
```

GPUs `class-attribute`

```
GPUs: Optional[List[MSAGPUInfo]]
```

HW_Identifier `class-attribute`

```
HW_Identifier: str = ''
```

Host_Name `class-attribute`

```
Host_Name: str = ''
```

IP_Address `class-attribute`

```
IP_Address: str = ''
```

MAC_Address `class-attribute`

```
MAC_Address: str = ''
```

Memory_Available `class-attribute`

```
Memory_Available: str = ''
```

Memory_Physical `class-attribute`

```
Memory_Physical: str = ''
```

Node_Name class-attribute

```
Node_Name: str = ''
```

OS_Name class-attribute

```
OS_Name: str = ''
```

OS_Release class-attribute

```
OS_Release: str = ''
```

OS_Version class-attribute

```
OS_Version: str = ''
```

PID class-attribute

```
PID: Optional[int]
```

Runtime_Cmd class-attribute

```
Runtime_Cmd: List[str] = []
```

Runtime_Exe class-attribute

```
Runtime_Exe: str = ''
```

Runtime_Status class-attribute

```
Runtime_Status: str = ''
```

Service_Start class-attribute

```
Service_Start: str = ''
```

System_Boot class-attribute


```
System_Boot: str = ''
```

MSASystemInfo

Bases: `SQLModel`

Pydantic System Info Model.

Attributes

CPU_Affinity class-attribute

```
CPU_Affinity: Optional[int]
```

CPU_Current class-attribute

```
CPU_Current: Optional[int]
```

CPU_Frequency class-attribute

```
CPU_Frequency: Optional[MSACPUFrequency]
```

CPU_LoadAvg class-attribute

```
CPU_LoadAvg: Optional[List[float]]
```

CPU_Logical class-attribute

```
CPU_Logical: Optional[int]
```

Amount of logical (each physical core doing 2 or more threads, hyperthreading) CPU's

CPU_Physical class-attribute

```
CPU_Physical: Optional[int]
```

Amount of physical CPU's

CPU_Stats class-attribute

```
CPU_Stats: Optional[MSACPUStats]
```

CPU_Times class-attribute

```
CPU_Times: Optional[MSACPUTimes]
```

CPU_Usage_Name class-attribute

```
CPU_Usage_Name: str = ''
```

CPU_Usage_Process class-attribute

```
CPU_Usage_Process: Optional[float]
```

CPU_Usage_Total class-attribute

```
CPU_Usage_Total: Optional[float]
```

Disk_IO class-attribute

```
Disk_IO: Optional[MSADiskIO]
```

HW_Identifier class-attribute

```
HW_Identifier: str = ''
```

Host_Name class-attribute

```
Host_Name: str = ''
```

IP_Address class-attribute

```
IP_Address: str = ''
```

MAC_Address class-attribute

```
MAC_Address: str = ''
```

Memory_Available class-attribute

```
Memory_Available: str = ''
```

Memory_Physical class-attribute

```
Memory_Physical: str = ''
```

Memory_Usage class-attribute

```
Memory_Usage: Optional[MSAMemoryUsage]
```

Network_Adapters class-attribute

```
Network_Adapters: Optional[List[MSANetworkAdapters]]
```

Network_Connections class-attribute

```
Network_Connections: Optional[List[MSANetworkConnection]]
```

Network_IO class-attribute

```
Network_IO: Optional[MSANetworkIO]
```

Network_Stats class-attribute

```
Network_Stats: Optional[List[MSANetworkStats]]
```

Node_Name class-attribute

```
Node_Name: str = ''
```

OS_Name class-attribute

```
OS_Name: str = ''
```

OS_Release class-attribute

```
OS_Release: str = ''
```

OS_Version class-attribute

```
OS_Version: str = ''
```

PID class-attribute

```
PID: Optional[int]
```

Runtime_Cmd class-attribute

```
Runtime_Cmd: List[str] = []
```

Runtime_Exe class-attribute

```
Runtime_Exe: str = ''
```

Runtime_Status class-attribute

```
Runtime_Status: str = ''
```

Service Status, running or stopped

Service_Start class-attribute

```
Service_Start: str = ''
```

Swap class-attribute

```
Swap: Optional[MSASwap]
```

System_Boot class-attribute

```
System_Boot: str = ''
```

Temperatures class-attribute

```
Temperatures: Optional[List[MSATemperatures]]
```

MSATemperature

Bases: `SQLModel`

Pydantic Temperature Info Model.

Attributes

critical class-attribute`critical: Optional[float]`**current** class-attribute`current: Optional[float]`**high** class-attribute`high: Optional[float]`**label** class-attribute`label: Optional[str]`

MSATemperatures

Bases: `SQLModel`

Pydantic Temperatures List Model.

Attributes

device class-attribute`device: str = ''`**temps** class-attribute`temps: List[MSATemperature] = []`

Functions

get_cpu_freq

`get_cpu_freq() -> MSACPUFrequency`

Get psutil.cpu_freq()

RETURNS	DESCRIPTION
<code>cpf</code>	MSACPUFrequency TYPE: <code>MSACPUFrequency</code>

get_cpu_stats

```
get_cpu_stats() -> MSACPUStats
```

Get psutil.cpu_times()

RETURNS	DESCRIPTION
<code>cst</code>	MSACPUStats TYPE: <code>MSACPUStats</code>

get_cpu_times

```
get_cpu_times() -> MSACPUTimes
```

Get psutil.cpu_times()

RETURNS	DESCRIPTION
<code>cti</code>	MSACPUTimes TYPE: <code>MSACPUTimes</code>

get_cpu_usage

```
get_cpu_usage(  
    user: str = None, ignore_self: bool = False  
) -> tuple[int, int, str]
```

Returns the total CPU usage for all available cores.

PARAMETER	DESCRIPTION

PARAMETER	DESCRIPTION
<code>user</code>	If given, returns only the total CPU usage of all processes for the given user. TYPE: <code>str</code> DEFAULT: <code>None</code>
<code>ignore_self</code>	If <code>True</code> the process that runs this script will be ignored. TYPE: <code>bool</code> DEFAULT: <code>False</code>

RETURNS	DESCRIPTION
<code>total</code>	total usage TYPE: <code>int</code>
<code>largest_process</code>	largest process usage TYPE: <code>int</code>
<code>largest_process_name</code>	name of the largest process TYPE: <code>str</code>

get_disk_io

```
get_disk_io() -> MSADiskIO
```

Get psutil.disk_io_counters()

RETURNS	DESCRIPTION
<code>dio</code>	MSADiskIO TYPE: <code>MSADiskIO</code>

get_gpus

```
get_gpus() -> List[MSAGPUInfo]
```

Get GPUUtil.getGPUs()

RETURNS	DESCRIPTION
---------	-------------

RETURNS	DESCRIPTION
<code>list_gpus</code>	List[MSAGPUInfo] = [] TYPE: List[MSAGPUInfo]

get_hostname

```
get_hostname() -> str
```

Get socket.gethostname()

RETURNS	DESCRIPTION
<code>hostname</code>	str TYPE: str

get_list_partitions

```
get_list_partitions() -> List
```

Get psutil.disk_partitions()

RETURNS	DESCRIPTION
<code>partitions_list</code>	List = [] TYPE: List

get_load_average

```
get_load_average() -> tuple[float, float, float]
```

Returns the CPU load average in tuple[1min, 5min, 15min].

RETURNS	DESCRIPTION
<code>1min</code>	total usage TYPE: float

RETURNS	DESCRIPTION
<code>5min</code>	largest process usage TYPE: <code>float</code>
<code>15min</code>	name of the largest process TYPE: <code>float</code>

get_map_disk_usage

```
get_map_disk_usage() -> Dict
```

Get get_partition_usage(get_list_partitions())

RETURNS	DESCRIPTION
<code>rdict</code>	Dict TYPE: <code>Dict</code>

get_memory_usage

```
get_memory_usage() -> MSAMemoryUsage
```

Get psutil.virtual_memory()

RETURNS	DESCRIPTION
<code>mu</code>	MSAMemoryUsage TYPE: <code>MSAMemoryUsage</code>

get_network_adapters

```
get_network_adapters() -> List[MSANetworkAdapters]
```

Get psutil.net_if_addrs()

RETURNS	DESCRIPTION
---------	-------------

RETURNS	DESCRIPTION
<code>ret</code>	List[MSANetworkAdapters] = [] TYPE: List[MSANetworkAdapters]

get_network_connections

```
get_network_connections() -> List[MSANetworkConnection]
```

Get psutil.net_connections()

RETURNS	DESCRIPTION
<code>rlist</code>	List[MSANetworkConnection] = [] TYPE: List[MSANetworkConnection]

get_network_io

```
get_network_io() -> MSANetworkIO
```

Get psutil.net_io_counters()

RETURNS	DESCRIPTION
<code>nio</code>	MSANetworkIO TYPE: MSANetworkIO

get_network_stats

```
get_network_stats() -> List[MSANetworkStats]
```

Get psutil.net_if_stats()

RETURNS	DESCRIPTION
<code>ret</code>	List[MSANetworkStats] = [] TYPE: List[MSANetworkStats]

get_partition_usage

```
get_partition_usage(partitions) -> Dict
```

Get psutil.disk_usage(partition)

RETURNS	DESCRIPTION
<code>ret</code>	Dict = {"partition": list, "total": list, "used": list, "free": list, "percent": list} TYPE: <code>Dict</code>

get_swap

```
get_swap() -> MSASwap
```

Get psutil.swap_memory()

RETURNS	DESCRIPTION
<code>sw</code>	MSASwap TYPE: <code>MSASwap</code>

get_sysgpuinfo

```
get_sysgpuinfo() -> MSASystemGPUInfo
```

Get MSASystemGPUInfo

RETURNS	DESCRIPTION
<code>system_gpu_info</code>	Pydantic System GPU Info Model. TYPE: <code>MSASystemGPUInfo</code>

get_sysinfo

```
get_sysinfo() -> MSASystemInfo
```

Get MSASystemInfo

RETURNS	DESCRIPTION
<code>system_info</code>	Pydantic System Info Model. TYPE: <code>MSASystemInfo</code>

get_temperatures

```
get_temperatures() -> List[MSATemperatures]
```

Get psutil.sensors_temperatures()

RETURNS	DESCRIPTION
<code>ret</code>	List[MSATemperatures] = [] TYPE: <code>List[MSATemperatures]</code>

Last update: September 13, 2022

Created: September 13, 2022