

PIZZA SALES SQL QUERIES

A. KPI's :-

1. Total Revenue:

```
SELECT SUM(total_price) AS Total_Revenue FROM pizza_sales;
```

Results		Messages	
Total_Revenue			
1	817860.05083847		

2. Average Order Value:

```
SELECT (SUM(total_price) / COUNT(DISTINCT order_id)) AS  
Avg_order_Value FROM pizza_sales
```

Results		Messages	
Avg_order_Value			
1	38.3072623343546		


3. Total Pizzas Sold:

```
SELECT SUM(quantity) AS Total_pizza_sold FROM pizza_sales
```

Results		Messages	
Avg_order_Value			
1	38.3072623343546		

4. Total Orders:

```
SELECT COUNT(DISTINCT order_id) AS Total_Orders FROM pizza_sales
```




The screenshot shows a SQL Server Results window with two tabs: 'Results' and 'Messages'. The 'Results' tab is active, displaying a single row of data. The column header is 'Total_Orders' and the value is '21350'.

	Total_Orders
1	21350

5. Average Pizzas Per Order:

```
SELECT CAST(CAST(SUM(quantity) AS DECIMAL(10,2)) /  
CAST(COUNT(DISTINCT order_id) AS DECIMAL(10,2)) AS DECIMAL(10,2))  
AS Avg_Pizzas_per_order  
FROM pizza_sales
```



The screenshot shows a SQL Server Results window with two tabs: 'Results' and 'Messages'. The 'Results' tab is active, displaying a single row of data. The column header is 'Avg_Pizzas_per_order' and the value is '2.32'.

	Avg_Pizzas_per_order
1	2.32

B. Daily Trend for Total Orders:

```
SELECT DATENAME(DW, order_date) AS order_day, COUNT(DISTINCT  
order_id) AS total_orders  
FROM pizza_sales  
GROUP BY DATENAME(DW, order_date)
```

Output :

	order_day	total_orders
1	Wednesday	3024
2	Saturday	3158
3	Monday	2794
4	Sunday	2624
5	Friday	3538
6	Thursday	3239
7	Tuesday	2973

C. Monthly Trend for Orders:

```
select DATENAME(MONTH, order_date) as Month_Name, COUNT(DISTINCT
order_id) as Total_Orders
from pizza_sales
GROUP BY DATENAME(MONTH, order_date)
```

Output :

	Month_Name	Total_Orders
1	February	1685
2	June	1773
3	August	1841
4	April	1799
5	May	1853
6	December	1680
7	January	1845
8	September	1661
9	October	1646
10	July	1935
11	November	1792
12	March	1840

D. % of Sales by Pizza Category:

```
SELECT pizza_category, CAST(SUM(total_price) AS DECIMAL(10,2)) as  
total_revenue,  
CAST(SUM(total_price) * 100 / (SELECT SUM(total_price) from  
pizza_sales) AS DECIMAL(10,2)) AS PCT  
FROM pizza_sales  
GROUP BY pizza_category
```

Output :

	pizza_category	total_revenue	PCT
1	Classic	220053.10	26.91
2	Chicken	195919.50	23.96
3	Veggie	193690.45	23.68
4	Supreme	208197.00	25.46

E. % of Sales by Pizza Size:

```
SELECT pizza_size, CAST(SUM(total_price) AS DECIMAL(10,2)) as  
total_revenue,  
CAST(SUM(total_price) * 100 / (SELECT SUM(total_price) from  
pizza_sales) AS DECIMAL(10,2)) AS PCT  
  
FROM pizza_sales  
  
GROUP BY pizza_size  
  
ORDER BY pizza_size
```

Output :

	pizza_size	total_revenue	PCT
1	L	375318.70	45.89
2	M	249382.25	30.49
3	S	178076.50	21.77
4	XL	14076.00	1.72
5	XXL	1006.60	0.12

F. Total Pizzas Sold by Pizza Category:

```
SELECT pizza_category, SUM(quantity) as Total_Quantity_Sold
FROM pizza_sales
WHERE MONTH(order_date) = 2
GROUP BY pizza_category
ORDER BY Total_Quantity_Sold DESC
```

Output :

	pizza_category	Total_Quantity_Sold
1	Classic	1178
2	Supreme	964
3	Veggie	944
4	Chicken	875

G. Top 5 Pizzas by Revenue:

```
SELECT Top 5 pizza_name, SUM(total_price) AS Total_Revenue
FROM pizza_sales
GROUP BY pizza_name
ORDER BY Total_Revenue DESC
```

Output :

	pizza_name	Total_Revenue
1	The Thai Chicken Pizza	43434.25
2	The Barbecue Chicken Pizza	42768
3	The California Chicken Pizza	41409.5
4	The Classic Deluxe Pizza	38180.5
5	The Spicy Italian Pizza	34831.25

H. Bottom 5 Pizzas by Revenue:

```
SELECT Top 5 pizza_name, SUM(total_price) AS Total_Revenue
FROM pizza_sales
GROUP BY pizza_name
ORDER BY Total_Revenue ASC
```

Output :

	pizza_name	Total_Revenue
1	The Brie Carre Pizza	11588.4998130798
2	The Green Garden Pizza	13955.75
3	The Spinach Supreme Pizza	15277.75
4	The Mediterranean Pizza	15360.5
5	The Spinach Pesto Pizza	15596

I. Top 5 Pizzas by Quantity:

```
SELECT Top 5 pizza_name, SUM(quantity) AS Total_Pizza_Sold
FROM pizza_sales
GROUP BY pizza_name
ORDER BY Total_Pizza_Sold DESC
```

Output :

	pizza_name	Total_Pizza_Sold
1	The Classic Deluxe Pizza	2453
2	The Barbecue Chicken Pizza	2432
3	The Hawaiian Pizza	2422
4	The Pepperoni Pizza	2418
5	The Thai Chicken Pizza	2371

J. Bottom 5 Pizzas by Quantity:

```
SELECT TOP 5 pizza_name, SUM(quantity) AS Total_Pizza_Sold
FROM pizza_sales
GROUP BY pizza_name
ORDER BY Total_Pizza_Sold ASC
```

Output :

	pizza_name	Total_Pizza_Sold
1	The Brie Carre Pizza	490
2	The Mediterranean Pizza	934
3	The Calabrese Pizza	937
4	The Spinach Supreme Pizza	950
5	The Soppressata Pizza	961

K. Top 5 Pizzas by Total Orders:

```
SELECT Top 5 pizza_name, COUNT(DISTINCT order_id) AS Total_Orders
FROM pizza_sales
GROUP BY pizza_name
ORDER BY Total_Orders DESC
```

Output :

	pizza_name	Total_Orders
1	The Classic Deluxe Pizza	2329
2	The Hawaiian Pizza	2280
3	The Pepperoni Pizza	2278
4	The Barbecue Chicken Pizza	2273
5	The Thai Chicken Pizza	2225

L. Bottom 5 Pizzas by Total Orders:

```
SELECT Top 5 pizza_name, COUNT(DISTINCT order_id) AS Total_Orders
FROM pizza_sales
GROUP BY pizza_name
ORDER BY Total_Orders ASC
```

Output :

	pizza_name	Total_Orders
1	The Brie Carre Pizza	480
2	The Mediterranean Pizza	912
3	The Spinach Supreme Pizza	918
4	The Calabrese Pizza	918
5	The Chicken Pesto Pizza	938