

Ex No: 3

Date:

DEVELOP A LEXICAL ANALYZER TO RECOGNIZE TOKENS USING LEX TOOL

AIM:

To implement the program to identify C keywords, identifiers, operators, and statements like [], {} using LEX tool.

ALGORITHM:

- Define patterns for C keywords, identifiers, operators, and end statements using regular expressions. Use %option noyywrap to disable the default behavior of yywrap.
- Utilize regular expressions to match patterns for C keywords, identifiers, operators, and end statements. Associate each pattern with an action to be executed when matched.
- Define actions to print corresponding token categories for matched patterns. Handle special cases like function declarations, numeric literals, and processor directives separately.
- Open the input file (sample.c in this case) for reading. Start lexical analysis using yylex() to scan the input and apply defined rules.
- Increment a counter (n) each time a newline character is encountered. Print the total number of lines at the end of the program execution.

PROGRAM:

```
%option noyywrap
letter [a-zA-Z]
digit [0-9]
id [_a-zA-Z]
AO [+|-|/|%|*]
RO [<|>|<=|>|=|=]
pp [#]
%{
int n=0;
%}

%%
"void"                printf("%s return type\n",yytext);
{letter}*([()])       printf("%s Function\n",yytext);
"int"|"float"|"if"|"else" printf("%s keywords\n",yytext);
"printf"              printf("%s keywords\n",yytext);
{id}({id}|{digit})*   printf("%s Identifier\n",yytext);
{digit}{digit}*       printf("%d Numbers\n",yytext);
{AO}                  printf("%s Arithmetic Operators\n",yytext);
{RO}                  printf("%s Relational Operators\n",yytext);
{pp}{letter}*(<|{letter}*.{letter}>) printf("%s processor
                                Directive\n",yytext);

[n]                    n++;
```

```
".","|","|"}"{"|";"                printf("%s others\n",yytext);
```

```
% %
```

```
int main()
```

```
{
```

```
    yyin=fopen("sample.c","r");
```

```
    yylex();
```

```
    printf("No of Lines %d\n",n);
```

```
}
```

OUTPUT:

```
[student@fedora swethaادلuru276]$ v3 276exp.2.1
[student@fedora swethaادلuru276]$ lex 276exp2.1
[student@fedora swethaادلuru276]$ cc lex.yy.c
[student@fedora swethaادلuru276]$ ./a.out
#include<stdio.h> void main(){ int a,b; }
#include<stdio.h> processor Directive
void return type
main() Function
{ others
  int keywords
  a Identifier
, others
b Identifier
; others
} others
```

RESULT: