EXP 21: Develop a C program to implement worst fit algorithm of memory management.

```
#include <stdio.h>
#define MAX 25
void worstFit(int blockSize[], int m, int processSize[], int n) {
  int allocation[MAX];
  // Initially no process is allocated
  for (int i = 0; i < n; i++)
    allocation[i] = -1;
 // Pick each process and find the worst fit block
  for (int i = 0; i < n; i++) {
    int worstldx = -1;
    for (int j = 0; j < m; j++) {
      if (blockSize[j] >= processSize[i]) {
        if (worstIdx == -1 || blockSize[j] > blockSize[worstIdx])
          worstldx = j;
      }
    }
    // If a block was found
    if (worstldx != -1) {
      allocation[i] = worstIdx;
      blockSize[worstIdx] -= processSize[i];
    }
```

```
}
  // Display allocation result
  printf("\nProcess No.\tProcess Size\tBlock No.\n");
  for (int i = 0; i < n; i++) {
    printf("%d\t\t%d\t\t", i + 1, processSize[i]);
    if (allocation[i] != -1)
      printf("%d\n", allocation[i] + 1);
    else
      printf("Not Allocated\n");
 }
}
int main() {
  int blockSize[MAX], processSize[MAX];
  int m, n;
  printf("Enter number of memory blocks: ");
  scanf("%d", &m);
  printf("Enter size of each block:\n");
  for (int i = 0; i < m; i++)
    scanf("%d", &blockSize[i]);
  printf("Enter number of processes: ");
  scanf("%d", &n);
  printf("Enter size of each process:\n");
  for (int i = 0; i < n; i++)
    scanf("%d", &processSize[i]);
```

```
worstFit(blockSize, m, processSize, n);
return 0;
}
```

Sample Output

```
Enter number of memory blocks: 3
Enter size of each block:
45 67 87
Enter number of processes: 3
Enter size of each process:
2 34 667

Process No. Process Size Block No.
1 2 3
2 34 3
3 667 Not Allocated
```