

EXP 9: Illustrate the concept of inter-process communication using shared memory with a C program.

For Writing,

```
// Writer Process: writer.c

#include <stdio.h>
#include <sys/ipc.h>
#include <sys/shm.h>
#include <string.h>

int main() {
    key_t key = ftok("shmfile", 65); // Generate unique key
    int shmid = shmget(key, 1024, 0666 | IPC_CREAT); // Create shared memory

    char *str = (char*) shmat(shmid, (void*)0, 0); // Attach
    printf("Write data: ");
    fgets(str, 1024, stdin); // Write input into shared memory

    printf("Data written in shared memory: %s\n", str);
    shmdt(str); // Detach

    return 0;
}
```

For Reading,

```
// Reader Process: reader.c

#include <stdio.h>
#include <sys/ipc.h>
#include <sys/shm.h>

int main() {
    key_t key = ftok("shmfile", 65); // Same key as writer
```

```
int shmid = shmget(key, 1024, 0666); // Locate shared memory

char *str = (char*) shmat(shmid, (void*)0, 0); // Attach
printf("Data read from shared memory: %s\n", str);

shmdt(str);      // Detach
shmctl(shmid, IPC_RMID, NULL); // Remove shared memory

return 0;
}
```

Sample Input (For Writing)

Write data: 2 3 4

Sample Output

Data written in shared memory: 2 3 4