

Write a program to read two integer values and print true if both the numbers end with the same digit, otherwise print false. Example: If 698 and 768 are given, program should print true as they both end with 8. Sample Input 1 25 53 Sample Output 1 false Sample Input 2 27 77 Sample Output 2 true

**Answer:** (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int x,y;
5     scanf("%d%d",&x,&y);
6     if(x%10==y%10)
7     {
8         printf("true");
9     }
10    else
11    {
12        printf("false");
13    }
14
15 }
```

|   | Input | Expected | Got   |   |
|---|-------|----------|-------|---|
| ✓ | 25 53 | false    | false | ✓ |
| ✓ | 27 77 | true     | true  | ✓ |

Passed all tests! ✓

## Objective

In this challenge, we're getting started with conditional statements.

## Task

Given an integer,  $n$ , perform the following conditional actions:

- If  $n$  is odd, print **Weird**
- If  $n$  is even and in the inclusive range of **2** to **5**, print **Not Weird**

```
1 #include<stdio.h>
2 int main()
3 {
4     int n;
5     scanf("%d",&n);
6     if(n%2==0)
7     {
8         if(n>=2&&n<=5)
9         {
10             printf("Not Weird");
11         }
12         if(n>=6&&n<=20){
13             printf("Weird");}
14         if(n>20){
15             printf("Not Weird");
16         }
17     }
```

```
10     printf("Not Weird");
11 }
12 if(n>=6&& n<=20){
13     printf("Weird");}
14     if(n>20){
15         printf("Not Weird");
16     }
17 }
18 }
19 }
20 else{
21     printf("Weird");}
22 }
23
24
```

|   | Input | Expected  | Got       |   |
|---|-------|-----------|-----------|---|
| ✓ | 3     | Weird     | Weird     | ✓ |
| ✓ | 24    | Not Weird | Not Weird | ✓ |

Passed all tests! ✓

Question **3**

Correct

Three numbers form a Pythagorean triple if the sum of squares of two numbers is equal to the square of the third. For example, 3, 5 and 4 form a Pythagorean triple, since  $3^2 + 4^2 = 25 = 5^2$ . You are given three integers, a, b, and c. They need not be given in increasing order. If they form a Pythagorean triple, then print "yes", otherwise, print "no". Please note that the output message is in small letters. Sample Input 1 3 5 4 Sample Output 1 yes Sample Input 2 5 8 2 Sample Output 2 no

**Answer:** (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int a,b,c;
5     scanf("%d %d %d",&a,&b,&c);
6     if((a*a+b*b==c*c) || (b*b+a*a==c*c) || (c*c+a*a==b*b))
```



**Answer:** (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int a,b,c;
5     scanf("%d %d %d",&a,&b,&c);
6     if((a*a+b*c==b*b) || (b*b+a*a==c*c) || (c*c+a*a==b*b))
7         printf("yes");
8     else
9         printf("no");
10    return 0;
11
12 }
```

|   | Input       | Expected | Got |   |
|---|-------------|----------|-----|---|
| ✓ | 3<br>5<br>4 | yes      | yes | ✓ |
| ✓ | 5<br>8<br>2 | no       | no  | ✓ |

Passed all tests! ✓

Finish review