

8:49

Vo 5G 62%



Week-04-02-Practice Session-Coding: Attempt review | REC-CIS
rajalakshmicolleges.org



Flag question

A set of N numbers (separated by one space) is passed as input to the program. The program must identify the count of numbers where the number is odd number.

Input Format:

The first line will contain the N numbers separated by one space.

Answer. (penalty regime: 0 %)

```
1  #include<stdio.h>
2  int main()
3  {
4      int N,x=0;
5      while(scanf("%d",&N)==1)
6      {
7          if(N%2!=0)
8          {
9              x++;
10         }
11     }
12     printf("%d",x);
13     return 0;
14 }
```

	Input	Expected	Got	
✓	5 10 15 20 25 30 35 40 45 50	5	5	✓

Passed all tests! ✓

Question **2**

Correct

Marked out of 5.00

 [Flag question](#)

8:49

Vo 5G 62%



Week-04-02-Practice Session-Coding: Attempt review | REC-CIS
rajalakshmicolleges.org



Given a number N, return true if and only if it is a *confusing number*, which satisfies the following condition:

We can rotate digits by 180 degrees to form new digits. When 0, 1, 6, 8, 9 are rotated 180 degrees, they become 0, 1, 9, 8, 6 respectively. When 2, 3, 4, 5 and 7 are rotated 180 degrees, they become invalid. A *confusing number* is a number that when rotated 180 degrees becomes a **different** number with each digit valid.

Example 1:

8:49

Vo 5G 62%



Week-04-02-Practice Session-Coding: Attempt review | REC-CIS
rajalakshmicolleges.org



```
1 #include<stdio.h>
2 int main()
3 {
4     int n,x,y=1;
5     scanf("%d",&n);
6     while (n!= 0&&y==1)
7     {
8         x=n%10,n=n/10;
9         if(x==2 || x==3 || x==4 || x==5)
10        {
11            y++;
12        }
13    }
14 }
```

8:49

Vo 5G 62%



Week-04-02-Practice Session-Coding: Attempt review | REC-CIS
rajalakshmicolleges.org



```
8      x=n%10,n=n/10;
9      if(x==2 || x==3 || x==4 || x==5)
10     {
11         y++;
12     }
13 }
14 if(y==1)
15 {
16     printf("true");
17 }
18 else
19 {
20     printf("false");
21 }
```

	Input	Expected	Got	
✓	6	true	true	✓
✓	89	true	true	✓
✓	25	false	false	✓

Passed all tests! ✓

A nutritionist is labeling all the best power foods in the market. Every food item arranged in a single line, will have a value beginning from 1 and increasing by 1 for each, until all items have a value associated with them. An item's value is the same as the number of macronutrients it has. For example, food item with value 1 has 1 macronutrient, food item with value 2 has 2 macronutrients, and incrementing in this fashion.

The nutritionist has to recommend the best combination to patients, i.e. maximum total of macronutrients. However, the nutritionist must avoid prescribing a particular sum of macronutrients (an 'unhealthy' number), and this sum is known. The nutritionist chooses food items in the increasing order of their value. Compute the highest total of macronutrients that can be prescribed to a patient, without the sum matching the given 'unhealthy' number.


```
1 #include<stdio.h>
2 int main()
3 {
4     long int n,t,i,nut=0;
5     scanf("%ld%ld",&n,&t);
6     for(i=1;i<=n;i++)
7     {
8         nut=nut+i;
9         if(nut==t)
10        {
11            nut=nut-1;
12        }
13    }
14    printf("%ld",nut%1000000007);
15    return 0;
16 }
```

8:50

Vo 5G 63%



Week-04-02-Practice Session-Coding: Attempt review | REC-CIS
rajalakshmicolleges.org



	Input	Expected	Got	
✓	2 2	3	3	✓
✓	2 1	2	2	✓
✓	3 3	5	5	✓

Marked out of 3.00

[Flag question](#)

Write a program that prints a simple chessboard.

Input format:

The first line contains the number of inputs T.

The lines after that contain a different values for size of the chessboard

Output format:

```
1 #include<stdio.h>
2 int main()
3 {
4     int T,d,i=0,i1,i2,o;
5     char c;
6     scanf("%d",&T);
7     while(i<T)
8     {
9         scanf("%d",&d);
10        i1=0;
11        while(i1<d)
12        {
13            o=1;
14            i2=0;
15            if(i1%2==0)
16            {
17                o=0;
```

```
14         i2=0;
15         if(i1%2==0)
16         {
17             o=0;
18         }
19         while(i2<d)
20         {
21             c='B';
22             if(i2%2==o)
23             {
24                 c='W';
25             }
26             printf("%c",c);
27             i2++;
28         }
29         i1+=1;
30         printf("\n");
```

```
21         c = 'D';
22         if(i2%2==0)
23         {
24             c = 'W';
25         }
26         printf("%c",c);
27         i2++;
28     }
29     i1+=1;
30     printf("\n");
31 }
32 i=i+1;
33 }
34 return 0;
35
36 }
```



	Input	Expected	Got	
✓	2	WBW	WBW	✓
	3	BWB	BWB	
	5	WBW	WBW	
		WBWBW	WBWBW	
		BWBWB	BWBWB	
		WBWBW	WBWBW	
		BWBWB	BWBWB	
		WBWBW	WBWBW	

Passed all tests ✓