

9:12

Vo 5G 79%



Week-05-02-Practice Session-Coding: Attempt review | REC-CIS
rajalakshmicolleges.org



Given a positive integer N, return true if and only if it is an Armstrong number.

Example 1:

Input:

153

```
1 #include<stdio.h>
2 #include<math.h>
3 int main()
4 {
5     int n;
6     scanf("%d",&n);
7     int x=0,n2=n;
8     while(n2!=0)
9     {
10         x++;
11         n2=n2/10;
12     }
13     int sum=0;
14     int n3=n,n4;
15     while(n3!=0)
16     {
17         n4=n3%10;
```



```
13  int sum=0;
14  int n3=n,n4;
15  while(n3!=0)
16  {
17      n4=n3%10;
18      sum=sum+pow(n4,x);
19      n3=n3/10;
20  }
21  if(n==sum)
22  {
23      printf("true");
24  }
25  else
26  {
27      printf("false");
28  }
29  return 0;
```

```
28     }  
29     return 0;  
30 }
```

	Input	Expected	Got	
✓	153	true	true	✓
✓	123	false	false	✓

Passed all tests! ✓

Correct

Marked out of 5.00

[Flag question](#)

Take a number, reverse it and add it to the original number until the obtained number is a palindrome. Constraints $1 \leq \text{num} \leq 999999999$ Sample Input 1 32 Sample Output 1 55 Sample Input 2 789 Sample Output 2 66066

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int rn,n,nt=0,i=0;
```

```
1 #include<stdio.h>
2 int main()
3 {
4     int rn,n,nt=0,i=0;
5     scanf("%d",&n);
6     do{
7         nt=n;rn=0;
8         while(n!=0)
9         {
10             rn=rn*10+n%10;
11             n=n/10;
12         }
13         n=nt+rn;
14         i++;
15     }
16     while(rn !=nt || i==1);
17     printf("%d",rn);
```

```
9 {  
10     rn=rn*10+n%10;  
11     n=n/10;  
12 }  
13 n=nt+rn;  
14 i++;  
15 }  
16 while(rn !=nt || i==1);  
17 printf("%d",rn);  
18 return 0;  
19 }
```

	Input	Expected	Got	
✓	32	55	55	✓
✓	789	66066	66066	✓

Passed all tests! ✓

A number is considered lucky if it contains either 3 or 4 or 3 and 4 both in it. Write a program to print the nth lucky number. Example, 1st lucky number is 3, and 2nd lucky number is 4 and 3rd lucky number is 33 and 4th lucky number is 34 and so on. Note that 13, 40 etc., are not lucky as they have other numbers in it.

The program should accept a number 'n' as input and display the nth lucky number as output.

Sample Input 1:

3

```
1 #include<stdio.h>
2 int main()
3 {
4     int n=1,i=0,nt,co=0,e;
5     scanf("%d",&e);
6     while(i<e)
7     {
8         nt=n;
9         while(nt!=0)
10        {
11            co=0;
12            if(nt%10!=3 && nt%10!=4)
13            {
14                co=1;
15                break;
16            }
17            nt=nt/10;
```

```
9 while(nt!=0)
10 {
11     co=0;
12     if(nt%10!=3 && nt%10!=4)
13     {
14         co=1;
15         break;
16     }
17     nt=nt/10;
18 }
19 if(co==0)
20 {
21     i++;
22 }
23 n++;
24 }
25 printf("%d",--n);
26 return 0;
```

```
14         co--;
15         break;
16     }
17     nt=nt/10;
18 }
19 if(co==0)
20 {
21     i++;
22 }
23 n++;
24 }
25 printf("%d",--n);
26 return 0;
27 }
```

9:14

Vo 5G 80%



Week-05-02-Practice Session-Coding: Attempt review | REC-CIS
rajalakshmicolleges.org



	Input	Expected	Got	
✓	34	33344	33344	✓

Passed all tests! ✓

Finish review