

Marked out of 3.00

 [Flag question](#)

Given an array A of sorted integers and another non negative integer k, find if there exists 2 indices i and j such that $A[i] - A[j] = k$, $i \neq j$.

Input Format

1. First line is number of test cases T. Following T lines contain:
2. N, followed by N integers of the array
3. The non-negative integer k

```
1  #include<stdio.h>
2  int main()
3  {
4      int t;
5      scanf("%d",&t);
6      while(t--){
7          int n;
8          scanf("%d",&n);
9          int a[n];
10         for(int i=0;i<n;i++){
11             scanf("%d",&a[i]);
12         }
13         int k;
14         scanf("%d",&k);
15         int flag=0;
16         for(int i=0;i<n;i++){
17             for(int j=i+1;j<n;j++){
```

```
11         scanf("%d",&a[i]);
12     }
13     int k;
14     scanf("%d",&k);
15     int flag=0;
16     for(int i=0;i<n;i++){
17         for(int j=i+1;j<n;j++){
18             if(a[i]-a[j]==k || a[j]-a[i]==k){flag=1;break;}
19         }
20         if(flag) break;}
21     printf("%d\n",flag);
22 }
23 }
```

9:15

Vo 5G 81%



Week-06-01-Practice Session-Coding: Attempt review | REC-CIS

rajalakshmicolleges.org



	Input	Expected	Got	
✓	1 3 1 3 5 4	1	1	✓
✓	1 3 1 3 5 99	0	0	✓

Passed all tests! ✓

9:15

Vo 5G 81%



Week-06-01-Practice Session-Coding: Attempt review | REC-CIS
rajalakshmicolleges.org



Sam loves chocolates and starts buying them on the 1st day of the year. Each day of the year, x , is numbered from 1 to Y . On days when x is odd, Sam will buy x chocolates; on days when x is even, Sam will not purchase any chocolates.

Complete the code in the editor so that for each day N_i (where $1 \leq x \leq N \leq Y$) in array `arr`, the number of chocolates Sam purchased (during days 1 through N) is printed on a new line. This is a function-only challenge, so input is handled for you by the locked stub code in the editor.

Input Format

```
1  #include<stdio.h>
2  int main()
3  {
4      int t;
5      scanf("%d",&t);
6      while(t--){
7          int n,c=0;
8          scanf("%d",&n);
9          for(int i=0;i<=n;i++){
10             if(i%2!=0) c=c+i;
11         }printf("%d\n",c);
12     }
13 }
```

9:16

Vo 5G 82%



Week-06-01-Practice Session-Coding: Attempt review | REC-CIS

rajalakshmicolleges.org



	Input	Expected	Got	
✓	3 1 2 3	1 1 4	1 1 4	✓
✓	10 71 100 86 54 40 9	1296 2500 1849 729 400 25 1521	1296 2500 1849 729 400 25 1521	✓

Hence, the answer: {2, 3}.

Complete the code in the editor below. The program must return an array of m positive integers, one for each $\text{maxes}[i]$ representing the total number of elements $\text{nums}[j]$ satisfying $\text{nums}[j] \leq \text{maxes}[i]$ where $0 \leq j < n$ and $0 \leq i < m$, in the given order.

It has the following:

$\text{nums}[\text{nums}[0], \dots, \text{nums}[n-1]]$: first array of positive integers

$\text{maxes}[\text{maxes}[0], \dots, \text{maxes}[n-1]]$: second array of positive integers

Answer: (penalty regime: 0 %)

```
1  #include<stdio.h>
2  int main()
3  {
4      int s1,s2,ans;
5      scanf("%d",&s1);
6      int ta[s1];
7      for(int i=0;i<s1;i++)
8          scanf("%d",&ta[i]);
9      scanf("%d",&s2);
10     int tb[s2];
11     for(int i=0;i<s2;i++)
12         scanf("%d",&tb[i]);
13     for(int j=0;j<s2;j++)
14     {
15         ans=0;
16         for(int i=0;i<s1;i++){
```

```
10 int tb[s2];
11 for(int i=0;i<s2;i++)
12 scanf("%d",&tb[i]);
13 for(int j=0;j<s2;j++)
14 {
15     ans=0;
16     for(int i=0;i<s1;i++){
17         if(tb[j]>=ta[i])
18             ans++;
19     }printf("%d\n",ans);
20 }
21 }
```

Input	Expected	Got
-------	----------	-----

	Input	Expected	Got	
✓	4 1 4 2 4 2 3 5	2 4	2 4	✓
✓	5 2 10 5 4 8	1 0 3 4	1 0 3 4	✓