

9:32



Vo 5G 91%



Coding: Attempt review | REC-CIS
rajalakshmicolleges.org



Coders here is a simple task for you, you have given an array of size ***N*** and an integer ***M***.

Your task is to calculate the ***difference between maximum sum and minimum sum of N-M*** elements of the given array.

Constraints:

$1 \leq t \leq 10$

$1 \leq n \leq 1000$

```
2 int main()
3 {
4     int t;
5     scanf("%d",&t);
6     while(t--)
7     {
8         int n,m,d,min,temp;
9         scanf("%d %d",&n,&m);
10        d=n-m;
11        int arr[n];
12        for(int i=0;i<n;i++)
13            scanf("%d",&arr[i]);
14        for(int j=0;j<n;j++)
15        {
16            min=j;
17            for(int k=j;k<n;k++)
18            {
```

```
16     min=j;
17     for(int k=j;k<n;k++)
18     {
19         if(arr[k]<arr[min])
20             min=k;
21     }
22     temp=arr[min];
23     arr[min]=arr[j];
24     arr[j]=temp;
25 }
26 int maxsum=0,minsum=0;
27 for(int a=0;a<d;a++)
28     minsum+=arr[a];
29 for(int b=n-1;b>m-1;b--)
30     maxsum+=arr[b];
31 printf("%d\n",maxsum-minsum);
32
```

9:33

Vo 5G 91%



Coding: Attempt review | REC-CIS
rajalakshmicolleges.org



```
25     }  
26     int maxsum=0,minsum=0;  
27     for(int a=0;a<d;a++)  
28         minsum+=arr[a];  
29     for(int b=n-1;b>m-1;b--)  
30         maxsum+=arr[b];  
31     printf("%d\n",maxsum-minsum);  
32  
33     }  
34 }
```

34 | }

	Input	Expected	Got	
✓	1 5 1 1 2 3 4 5	4	4	✓

Passed all tests! ✓

Flag question

A new deadly virus has infected large population of a planet. A brilliant scientist has discovered a new strain of virus which can cure this disease. Vaccine produced from this virus has various strength depending on midichlorians count. A person is cured only if midichlorians count in vaccine batch is more than midichlorians count of person. A doctor receives a new set of report which contains midichlorians count of each infected patient, Practo stores all vaccine doctor has and their midichlorians count. You need to determine if doctor can save all patients with the vaccines he has. The number of vaccines and patients are equal.

Input Format

```
1  #include<stdio.h>
2  int main()
3  {
4      int n,min1,min2,temp,flag=1;
5      scanf("%d",&n);
6      int vac[n],pat[n];
7      for(int i=0;i<n;i++)
8          scanf("%d",&vac[i]);
9      for(int i=0;i<n;i++)
10         scanf("%d",&pat[i]);
11
12     for(int j=0;j<n-1;j++)
13     {
14         min1=j,min2=j;
15         for(int k=j;k<n;k++)
16         {
17             if(vac[k]<vac[min1])
```

9:33

Vo 5G 92%



Coding: Attempt review | REC-CIS

rajalakshmicolleges.org



```
22     temp=vac[min1];
23     vac[min1]=vac[j];
24     vac[j]=temp;
25
26     temp=pat[min2];
27     pat[min2]=pat[j];
28     pat[j]=temp;
29 }
30 for(int i=0;i<n;i++)
31 {
32     if(vac[i]<=pat[i])
33     {
34         flag=0;
35         break;
```



```
31 {  
32     if(vac[i]<=pat[i])  
33     {  
34         flag=0;  
35         break;  
36     }  
37 }  
38 if(flag==1)  
39 printf("Yes");  
40 else  
41 printf("No");  
42  
43 }
```

```
35         break;
36     }
37 }
38 if(flag==1)
39     printf("Yes");
40 else
41     printf("No");
42
43 }
```

	Input	Expected	Got	
✓	5	No	No	✓

	Input	Expected	Got	
✓	5 123 146 454 542 456 100 328 248 689 200	No	No	✓

Passed all tests! ✓

9:34

Vo 5G 92%



Coding: Attempt review | REC-CIS
rajalakshmicolleges.org



Flag question

You are given an array of n integer numbers $a_1, a_2, \dots, a_n$. Calculate the number of pair of indices (i, j) such that $1 \leq i < j \leq n$ and $a_i \text{ xor } a_j = 0$.

Input format

- First line: n denoting the number of array elements

9:34

Vo 5G 92%



Coding: Attempt review | REC-CIS
rajalakshmicolleges.org



```
1 #include<stdio.h>
2 int main()
3 {
4     int n,count=0;
5     scanf("%d",&n);
6     int arr[n];
7     for(int i=0;i<n;i++)
8         scanf("%d",&arr[i]);
9     for(int i=0;i<n-1;i++)
10    {
11        for(int j=i+1;j<n;j++)
12        {
13            if((arr[i]^arr[j])==0)
14                count++;
```

```
11     for(int j=1+i;j<n;j++)
12     {
13         if((arr[i]^arr[j])==0)
14             count++;
15     }
16 }
17 printf("%d",count);
18 }
```

	Input	Expected	Got	

	Input	Expected	Got	
✓	5 1 3 1 4 3	2	2	✓

Passed all tests! ✓

Question **4**

Correct

Marked out of 1.00

You are given an array **A** of non-negative integers of size **m**. Your task is to sort the array in non-decreasing order and print out the original indices of the new sorted array.

Example:

$A = \{4, 5, 3, 7, 1\}$

After sorting the new array becomes $A = \{1, 3, 4, 5, 7\}$.

The required output should be "4 2 0 1 3"

Answer: (penalty regime: 0 %)

```
1  #include<stdio.h>
2  int main()
3  {
4      int n;
5      scanf("%d",&n);
6      int arr[n];
7      for(int i=0;i<n;i++)
8          scanf("%d",&arr[i]);
9      int max=arr[0];
10     for(int i=1;i<n;i++)
11     {
12         if(arr[i]>max)
13             max=arr[i];
14     }
```

```
12         if(arr[i]<max)
13             max=arr[i];
14     }
15     max++;
16     int min=0;
17     for(int a=0;a<n;a++)
18     {
19         for(int b=0;b<n;b++)
20         {
21             if(arr[b]<arr[min])
22                 min=b;
23         }
24     printf("%d ",min);
25     arr[min]=max;
26 }
27 }
```

	Input	Expected	Got	
✓	5 4 5 3 7 1	4 2 0 1 3	4 2 0 1 3	✓

Passed all tests! ✓

Finish review

Quiz navigation