

9:36

Vo 5G 93%



Coding: Attempt review | REC-CIS
rajalakshmicolleges.org



Input Format

First and only line contains the value of array separated by single space.

A 0 0	A 0 1	A 0 2
4	6	9
A 1 0	A 1 1	A 1 2
2	5	8
A 2 0	A 2 1	A 2 2

9:37

Vo 5G 93%



Coding: Attempt review | REC-CIS

rajalakshmicolleges.org



Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int arr[3][3];
5     for(int i=0;i<3;i++)
6     {
7         for(int j=0;j<3;j++)
8         {
9             scanf("%d",&arr[i][j]);
10        }
11    }
12    int odd=0,even=0;
13    for(int i=0;i<3;i++)
```

```
12 // odd & even  
13 for(int i=0;i<3;i++)  
14 {  
15     for(int j=0;j<3;j++)  
16     {  
17         if((i+j)%2!=0)  
18             odd+=arr[i][j];  
19         else  
20             even+=arr[i][j];  
21     }  
22 }  
23 printf("%d\n%d",even,odd);  
24 }  
25
```

	Input	Expected	Got	
✓	1 2 3 4 5 6 7 8 9	25 20	25 20	✓
✓	21 422 423 443 586 645 657 846 904	2591 2356	2591 2356	✓

Passed all tests! ✓

Marked out of 5.00

 [Flag question](#)

Microsoft has come to hire interns from your college. N students got shortlisted out of which few were males and a few females. All the students have been assigned talent levels. Smaller the talent level, lesser is your chance to be selected. Microsoft wants to create the result list where it wants the candidates sorted according to their talent levels, but there is a catch. This time Microsoft wants to hire female candidates first and then male candidates.

The task is to create a list where first all-female candidates are sorted in a descending order and then male candidates are sorted in a descending order.

9:37

Vo 5G 93%



Coding: Attempt review | REC-CIS
rajalakshmicolleges.org



Answer: (penalty regime: 0 %)

```
1  #include<stdio.h>
2  struct data
3  {
4      int gen;int tal;
5
6  };
7  int main()
8  {
9      int n;
10     scanf("%d",&n);
11     struct data a[n];
12     for(int i=0;i<n;i++)
```

9:38

Vo 5G 94%



Coding: Attempt review | REC-CIS

rajalakshmicolleges.org



```
13 scanf("%d %d",&a[i].gen,&a[i].tal);
14 for(int i=0;i<n-1;i++)
15 {
16     for(int j=0;j<n-i-1;++j)
17     {
18         if(a[j].tal<a[j+1].tal)
19         {
20             struct data temp=a[j];
21             a[j]=a[j+1];
22             a[j+1]=temp;
23         }
24     }
25 }
26 for(int i=0;i<n;i++)
```

```
23     }
24     }
25 }
26 for(int i=0;i<n;i++)
27 {
28     if(a[i].gen==0)
29     printf("%d ",a[i].tal);
30 }
31 for(int i=0;i<n;++i)
32 {
33
34     if(a[i].gen==1)
35     printf("%d ",a[i].tal);
36 }
37 }
38
```


	Input	Expected	Got
✓	5 0 3 1 6 0 2 0 7 1 15	7 3 2 15 6	7 3 2 15 6
✓	6 0 1 0 26 0 39 0 37 0 7 0 13	39 37 26 13 7 1	39 37 26 13 7 1

9:38

Vo 5G 94%

0 26
0 39
0 37
0 7
0 13



12
1 12
1 14
1 18
1 1
1 2
1 3
1 5
1 8
1 9

31 29 18 14 12 10 9 8 5 3 2 1

31 29 18 14 12 10 9 8 5 3 2 1

9:38

Vo 5G 94%



1 8
1 9
1 10
0 29
0 31



12
0 12
1 12
0 12
1 12
0 12
0 12
1 12
0 12
1 12
1 12

12 12 12 12 12 12 12 12 12 12 12 12 12

12 12 12 12 12 12 12 12 12 12 12 12

Shyam Lal, a wealthy landlord from the state of Rajasthan, being an old fellow and tired of doing hard work, decided to sell all his farmland and to live rest of his life with that money. No other farmer is rich enough to buy all his land so he decided to partition the land into rectangular plots of different sizes with different cost per unit area. So, he sold these plots to the farmers but made a mistake. Being illiterate, he made partitions that could be overlapping. When the farmers came to know about it, they ran to him for compensation of extra money they paid to him. So, he decided to return all the money to the farmers of that land which was overlapping with other farmer's land to settle down the conflict. All the portion of conflicted land will be taken back by the landlord.

To decide the total compensation, he has to calculate the total amount of money to return back to farmers with the same cost they had purchased from him. Suppose, Shyam Lal has a total land area of **1000×1000** equal square blocks where each block is equivalent to a unit square area which can be represented on the co-ordinate axis. Now find the total amount of money he has to return to the

```
1 #include<stdio.h>
2 int main()
3 {
4     int i,j,n,x1,x2,y1,y2,t=0;
5     long long total=0;
6     int arr[1001][1001]={0};
7     scanf("%d",&n);
8     while(n--)
9     {
10         scanf("%d %d %d %d %d",&x1,&y1,&x2,&y2,&t);
11         for(i=x1;i<=x2;i++)
12         {
13             for(j=y1;j<=y2;j++)
14             {
15                 if(arr[i][j]==0)
16                     arr[i][j]+=t;
17                 else if(arr[i][j]>0)
```

```
11     for(i=x1;i<=x2;i++)
12     {
13         for(j=y1;j<=y2;j++)
14         {
15             if(arr[i][j]==0)
16                 arr[i][j]+=t;
17             else if(arr[i][j]>0)
18                 arr[i][j]=(-1)*(arr[i][j]+t);
19             else if(arr[i][j]<0)
20                 arr[i][j]-=t;
21         }
22     }
23 }
24 for(i=1;i<1001;i++)
25 {
26     for(j=1;j<1001;j++)
27     {
```

```
24     for(i=1;i<1001;i++)
25     {
26         for(j=1;j<1001;j++)
27         {
28             if(arr[i][j]<0)
29                 total+=arr[i][j];
30         }
31     }
32     printf("%lld\n",(-1)*total);
33     return 0;
34 }
```

Input	Expected	Got
-------	----------	-----

	Input	Expected	Got	
✓	3 1 4 4 6 1 4 3 6 6 2 2 2 5 4 3	35	35	✓
✓	1 48 12 49 27 8	0	0	✓
✓	3 88 34 99 76 44 82 65 94 100 81 58 16 65 66 7	10500	10500	✓

Passed all tests! ✓