Status	Finished
Started	Monday, 19 October 2026, 8:20 AM
Completed	Monday, 19 October 2026, 8:32 AM
Duration	12 mins 19 secs
Grade	**15.00** out of 15.00 (**100**%)

Question **1**

Correct

Mark 1.00 out of 1.00

Which method is used to write a list of strings to a file?

a. write()
b. writelines() ✓
c. write_list()
d. write_all()

The correct answer is: writelines()

Question **2**

Correct

Mark 1.00 out of 1.00

Default EOL character of text file in python is ,

a. \n ✓
b. \t
c. space
d. ,

The correct answer is:
\n

Question **3**

Correct

Mark 1.00 out of 1.00

What does the buffering parameter in the open() function control?

a. The access mode of the file
b. The file's read/write position
c. The buffer size for the file operations ✓
d. The encoding of the file

The correct answer is: The buffer size for the file operations

Question **4**

Correct

Mark 1.00 out of 1.00

Which method is used to sets the position of a file pointer

a. ftell()
b. fseek()
c. tell()
d. seek() ✓

The correct answer is: seek()

Question **5**

Correct

Mark 1.00 out of 1.00

Select the incorrect file access mode

a. wb+
b. r
c. ab+
d. rw+ ✓

The correct answer is: rw+

Question **6**

Correct

Mark 1.00 out of 1.00

What is the use of tell() method in python?

- a. tells you the current position within the file ✓
- b. tells you the end position within the file
- c. tells you the file is opened or not
- d. none of the mentioned

The correct answer is:
tells you the current position within the file

Question **7**

Correct

Mark 1.00 out of 1.00

What does the flush() method do in file handling?

- a. Moves the file cursor to the beginning
- b. Deletes the file content
- c. Closes the file
- d. Flushes the internal buffer to the file ✓

The correct answer is: Flushes the internal buffer to the file

Question **8**

Correct

Mark 1.00 out of 1.00

To open a file c:\scores.txt for appending data, we use _____

- a. outfile = open("c:\\scores.txt", "rw")
- b. outfile = open(file = "c:\scores.txt", "w")
- c. outfile = open(file = "c:\\scores.txt", "w")
- d. outfile = open("c:\\scores.txt", "a") ✓

The correct answer is:
outfile = open("c:\\scores.txt", "a")

Question **9**

Correct

Mark 1.00 out of 1.00

What happens if you try to open a file in read mode ('r') that does not exist?

a. A new file is created
b. An empty file object is returned
c. The operation is ignored
d. An error is raised ✓

The correct answer is: An error is raised

Question **10**

Correct

Mark 1.00 out of 1.00

What happens if you try to open a file in write mode ('w') and the file already exists?

a. It clears the old data and starts fresh ✓
b. It does nothing
c. It appends data to the file
d. It raises an error

The correct answer is: It clears the old data and starts fresh

Question **11**

Correct

Mark 1.00 out of 1.00

To open a file a.txt for reading, we use _____

a. infile = open(file = “a.txt”, “r”)
b. infile = open(file = “a.txt”, “r”)
c. infile = open(“a.txt”, “r”) ✓
d. infile = open(file, “a.txt”, “r”)

The correct answer is:
infile = open(“a.txt”, “r”)

Question **12**

Correct

Mark 1.00 out of 1.00

Which function is used to open a file in Python?

a. open_file()
b. open() ✓
c. openfile()
d. file()

The correct answer is: open()

Question **13**

Correct

Mark 1.00 out of 1.00

Select the correct output of the following code

```
fp.seek(5, 1)
```

a.
- Move file pointer five characters behind from the current position.

b. Move file pointer five characters ahead from the beginning

c.
- Move file pointer five characters behind ahead from the end of a file.

d.
- Move file pointer five characters ahead from the current position. ✓

The correct answer is:

- Move file pointer five characters ahead from the current position.

Question **14**

Correct

Mark 1.00 out of 1.00

What is the output of the following code?

```
f = open("test.txt", "w")
f.write("Hello, world!")
f.close()
f = open("test.txt", "r")
print(f.read())
f.close()
```

a. Hello, world! ✓

b. Hello

c. world

d. An error is raised

The correct answer is: Hello, world!

Question **15**

Correct

Mark 1.00 out of 1.00

file_object.seek(offset [, reference_point])

What is the default, the value of reference_point?

a. null

b. 0 ✓

c. 1

d. 2

e. garbage

The correct answer is:
0