Status	Finished
Started	Friday, 9 October 2026, 2:51 PM
Completed	Friday, 9 October 2026, 2:56 PM
Duration	5 mins 16 secs
Grade	**15.00** out of 15.00 (**100**%)

Question **1**

Correct

Mark 1.00 out of 1.00

Which of the following statement is not true regarding functions?

- a. A function definition begins with "define" ✓
- b. Function header always ends with a colon ( ) .
- c. A function may or may not have parameters.
- d. A function may or may not return value.

Question **2**

Correct

Mark 1.00 out of 1.00

A variable that is defined inside any function or a block is known as a ____.

- a. Global variable
- b. Local variable ✓
- c. inside variable
- d. Function Variable

Question **3**

Correct

Mark 1.00 out of 1.00

What is the output of the following function call?

```
def outer_fun(a, b):
    def inner_fun(c, d):
        return c + d
        return inner_fun(a, b)
    return a
result = outer_fun(5, 10)
print(result)
```

- a. 15
- b. Syntax Error
- c. (15,5)
- d. 5 ✓

Question **4**

Correct

Mark 1.00 out of 1.00

A function may return multiple values using _____.

a. String
b. Tuple ✓
c. Dictionary
d. List

Question **5**

Correct

Mark 1.00 out of 1.00

What will be the output of the following Python code?

```
def sayHello():
    print('Hello World!')
sayHello()
sayHello()
```

a. None of the mentioned
b. Hello World! ✓
Hello World!
c. 'Hello World!'
'Hello World!'
d. Hello
Hello

Question **6**

Correct

Mark 1.00 out of 1.00

The function can be called in the program by writing function name followed by _____.

a. None of the mentioned
b. { }
c. ( ) ✓
d. [ ]

Question **7**

Correct

Mark 1.00 out of 1.00

Which of the following items are present in the function header?

- a. Both A and B ✓
- b. return value
- c. B. parameter list
- d. A. function name

Question **8**

Correct

Mark 1.00 out of 1.00

Python function always returns a value

Select one:

- True ✓
- False

Question **9**

Correct

Mark 1.00 out of 1.00

Which of the following number can never be generated by the following code: random.randrange(0, 100)

- a. 99
- b. 0
- c. 1
- d. 100 ✓

Question **10**

Correct

Mark 1.00 out of 1.00

Which of the following function definition header is wrong?

- a. def scan(p1, p2 = 4, p3 = 5):
- b. def div(p1=4, p2, p3): ✓
- c. def mul(p1, n1, m1):
- d. def sum(n1, n2, n = 3):

Question **11**

Correct

Mark 1.00 out of 1.00

The process of dividing a computer program into separate independent blocks of code with specific functionalities is known as _____.

a. More Programming
b. Step Programming
c. Modular Programming ✓
d. Programming

Question **12**

Correct

Mark 1.00 out of 1.00

The _____ statement returns the values from the function to the calling function.

a. send
b. take
c. return ✓
d. give

Question **13**

Correct

Mark 1.00 out of 1.00

Choose the correct statement

a. We can create function with no argument and with return value(s)
b. We can create function with no argument and no return value.
c. All of the mentioned ✓
d. We can create function with argument(s) and no return value.

Question **14**

Correct

Mark 1.00 out of 1.00

Which of the following is not the type of function argument?

a. Required argument
b. default argument
c. Keyword argument
d. initial argument ✓

Question **15**

Correct

Mark 1.00 out of 1.00

What is the output of the following function call?

```
def fun1(num):
    return num + 25
fun1(5)
print(num)
```

a. NameError ✓

b. 5

c. num

d. 25