
Table of Contents

passivityCtrl	1
Constants and Variables	1
Trajectory Generation	1
Planar Arm Dynamics	2
Passivity-Based Controller	2
Outputs	3

passivityCtrl

Creates the ODE function for a two link planar arm tracking a cubic polynomial trajectory by passivity-based control.

```
function [ dx ] = passivityCtrl( t, x, a1, a2)
```

Constants and Variables

Sets A as the global A variable (the past joint accelerations):

```
global A
```

Set the parameters for the arm:

```
I1=10; I2 = 10; m1=5; r1=.5; m2=5; r2=.5; l1=1; l2=1;  
g=9.8;
```

Calculate the parameters in the dynamic model:

```
a = I1+I2+m1*r1^2+ m2*(l1^2+ r2^2);  
b = m2*l1*r2;  
d = I2+ m2*r2^2;
```

Trajectory Generation

Note x is in the form of $q1, q2, q1_dot, q2_dot$:

Cubic polynomials:

```
vec_t = [1; t; t^2; t^3];  
theta_d = [a1'*vec_t; a2'*vec_t];
```

Calculate the velocity and acceleration in both θ_1 and θ_2 :

```
a1_vel = [a1(2), 2*a1(3), 3*a1(4), 0];  
a1_acc = [2*a1(3), 6*a1(4), 0, 0];  
a2_vel = [a2(2), 2*a2(3), 3*a2(4), 0];  
a2_acc = [2*a2(3), 6*a2(4), 0, 0];
```

Calculate the desired trajectory (assuming 3rd order polynomials for trajectories):

```
dtheta_d =[a1_vel*vec_t; a2_vel* vec_t];
ddtheta_d =[a1_acc*vec_t; a2_acc* vec_t];
```

Set the current joint values:

```
theta = x(1:2,1);
theta_dot = x(3:4,1);
theta_dot_dot = A;
```

Planar Arm Dynamics

Calculate the parameters in the dynamic model:

```
a = I1+I2*t+m1*r1^2+ m2*(l1^2+ r2^2);
b = m2*l1*r2;
d = I2+ m2*r2^2;
```

Calculate the actual dynamic model of the system:

```
Mmat = [a+2*b*cos(x(2)), d+b*cos(x(2)); d+b*cos(x(2)), d];
Cmat = [-b*sin(x(2))*x(4), -b*sin(x(2))*(x(3)+x(4));
        b*sin(x(2))*x(3), 0];
Gmat = [m1*g*r1*cos(x(1))+m2*g*(l1*cos(x(1))+r2*cos(x(1)+x(2)));
        m2*g*r2*cos(x(1)+x(2))];
invM = inv(Mmat);
invMC = invM*Cmat;
```

Passivity-Based Controller

Set the k_v gain constant (positive definite matrix):

```
kv = [25 0; ...
      0 25];
```

Set the $\textit{capital_lambda}$ constant (positive definite square matrices):

```
capital_lambda = [10 0; ...
                  0 10];
```

Calculate the tracking errors, e , e_dot , and e_dot_dot :

```
e = theta - theta_d;
e_dot = theta_dot - dtheta_d;
e_dot_dot = theta_dot_dot - ddtheta_d;
```

Calculate r and r_dot :

```
I = eye(2,2);
r = e_dot + capital_lambda*e;
r_dot = e_dot_dot + capital_lambda*e_dot;
```

Calculate v :

```
% v = q_dot - r
v = theta_dot - r;
```

Calculate a :

```
%a = q_dot_dot - r  
a = theta_dot_dot - r_dot;
```

Calculate the controller, u :

```
u = zeros(2,1);  
u = Mmat*a + Cmat*v + Gmat - kv*r;
```

Calculate the acceleration values:

```
theta_dot_dot = zeros(2,1);  
% theta_dot_dot = sigma_dot - si_dot_dot  
theta_dot_dot = invM*(u - Cmat*theta_dot - Gmat);
```

Update the acceleration values:

```
A = theta_dot_dot;
```

Outputs

Initialize the output of the function, dx :

```
dx = zeros(4,1);
```

Set the final outputs:

```
dx(1) = x(3,1);  
dx(2) = x(4,1);  
dx(3) = theta_dot_dot(1);  
dx(4) = theta_dot_dot(2);
```

```
end
```

Published with MATLAB® R2018a