



## Summary

*I have extensive and broad experience in Physical Design Implementation, Flow Development and Methodology and a long history of successful implementations that went into productized, high volume silicon, sometimes using [flows that I set up](#). I can quickly bring to bear a potent mix of expertise across physical design, EDA, programming and circuits to overcome seemingly intractable roadblocks. I have excellent communication skills, analytical abilities and ... ingenuity. I'm a U.S.Citizen.*

[www.linkedin.com/in/gurmeet](https://www.linkedin.com/in/gurmeet) |

[github.com/swiftgurmeet](https://github.com/swiftgurmeet)

[https://swiftgurmeet.github.io/st/resume\\_gurmeet\\_singh.pdf](https://swiftgurmeet.github.io/st/resume_gurmeet_singh.pdf)

## Experience

### [2026-] IBM Research, Consulting Engineer (through CTG Inc.)

- Design Technology Co-Optimization (DTCO) work on improving multiple libraries with different heights and their PPA benchmarking. PnR flow optimization.
- Develop Continuous Mixed Row (CMR) PnR flow using Synopsys Fusion Compiler.
- Data Analytics and Visualization of PnR metrics

### [2022-2024] Intel, Physical Design Methodology Engineer

- Create an implementation (rtl2gds) flow for Intel 18A node using mostly Tcl code and Cadence Flowtool that supports numerous flow, technology, power/performance/area optimization options. This enabled me and others to run batch jobs with up to thousands of parallel runs with different options, IPs, libraries and metal stacks for regressions or analysis. Started the git repo for the flow and made over 150 commits.
- Worked with Cadence to productize and publish an [Intel18A PPA oriented reference flow](#) usable by customers to jump start their own implementation flows.
- Set up infrastructure for analyzing a large number of Intel18A synthesis/place&route runs on industry standard IPs with Cadence based Genus/Innovus based flow, collect PPA and other QOR metrics and continually document/present them visually using Python-Matplotlib and R-ggplot2.
- Use the above infrastructure to continually improve and benchmark the PPA metrics of industry standard IPs and publish results with different versions of Intel18A libraries and PDKs.
- Worked with Cadence to produce a performance optimized implementation and the associated hierarchical RTL2GDS flow for a high performance ARM core (Cortex-X925 “Blackhawk”) on the Intel18A process.

### [2020-2022] Protingent Corp. ( [Samsung Austin Research Center](#), Physical Design Consultant)

- Physical implementation (rtl2gds) of 3 large GPU blocks to tapeout [Silicon Success] on a 4nm technology using Cadence Innovus, including floorplanning in SNPS, meeting all area/power/timing requirements. Over 75 timing/DRC ECOs. Provide guidance to the CAD team on methodology.
- PnR flow development in SNPS fusion compiler for 3nm (Samsung 3GAP) technology

### [18-20] [Esperanto Technologies](#), Physical Design Methodology and Global Clocking Engineer

- Defined physical design methodology for 7nm process corners including very low voltage operation and timing margins

- Design of global clock distribution network for a very large 7nm SoC, model the reconvergent network, simulate with spice, implement using ICC2 and resimulate with extracted spice netlist. Publish chip level clock specification document.
- Block level place and route implementation of a million gate low voltage design.
- Set up a Synopsys Custom Compiler schematic and netlisting environment with extracted views. Characterize PVT sensitivity of library cells, esp. level shifters and a ring oscillator with spice simulations and publish results.
- Set up and define methodology for an EM/IR flow using Ansys Redhawk/Seascope
- Support and manage PLL, DLL, DDR, PCIE vendors through weekly meetings.

**[15-17] [zGlue Inc](#), Physical Design (Independent Consultant)**

- Physical design methodology and netlist-to-gds flow development in tcl using Cadence toolset. Also developed Assura physical verification and logical equivalence (lec) flows.
- Hierarchical implementation of an instance array design including floorplanning, power grid design, pin placement, place and route, logical equivalence and physical verification. [Silicon success](#).
- Abstract (LEF) generation of analog macros and hierarchical instances to allow for through the block routing.
- Mixed-signal custom CAD support including SKILL programming
- Set up Virtuoso QRC extraction flow for full chip STA, set up and run full chip STA with Tempus, set up and run full chip LEC with Conformal. [Silicon success](#).

**[13-14] Qualcomm Technologies, Senior Staff Engineer**

- Top level floorplan, power grid design with multiple power domains, using CPF/UPF for a mixed signal design, automated floorplan generation with Tcl. Wrote power intent CPF from scratch. Full chip formal (LEC) and low power (CLP) verification using Cadence tools. Apache Redhawk EM/IR analysis, debug and fixes. My leadership enabled a rare ahead of schedule tapeout. [Silicon success](#).

**[12-13] Cadence Design Systems, Staff Applications Engineer**

- Developed complete, automated rtl2gds flow (Globalfoundries 14nm/finFET); optimized for PPA and validated on A9 ARM core with Neon coprocessor (TT Nominal @ 2.5 GHz).
- Helped tapeout a DDR IP for a client by doing the final setup/hold/other fixes.

**[2011-12] Sandforce Inc./LSI Corp., Principal Engineer**

- Developed a complete, and deployed, a 40 nm automated and optimized, tapeout ready, Cadence based netlist to tapeout implementation flow at Sandforce Inc.
- Wrote Tcl scripts for a correct by construction, tunable flow used to implement all blocks in the design.
- Developed automated, tapeout ready, STA setup using Primetime-SI using Tcl/Perl scripts.
- Did studies on standard cell EM limits by frequency and flop metastability characteristics
- Implemented eight large blocks at tapeout quality using the above flow ; the resulting GDSII were timing, LEC, LVS/DRC clean. [Silicon success](#).

**[2010-11] West Valley Technologies (Sandisk, Physical Design Contractor)**

- Developed hierarchical physical implementation flow in 65nm technology using Cadence at Sandisk.
- Set up 40nm Cadence based, automated, tapeout ready, block level netlist to tapeout implementation flow at Sandisk Inc.

**[2008-10] ChipZen Inc., owner (Qualcomm, Physical Design Consultant)**

- 65nm WiFi ASIC: Tapeout implementation of large block using Magma. [Silicon Success](#).
- 65nm WiFi ASIC: Full chip EM/IR signoff using Apache-Redhawk. [Silicon Success](#).

**[2007-08] AMCC, Principal Engineer**

- Telecom ASIC: Tapeout implementation of two large blocks using Magma at AMCC. [Silicon Success](#).

