

Degree-3 spectral refinement: research-draft verification package

Repository source: README.md

Contents

Candidate coefficient	1
What has been checked	1
What remains before public release	2
Typeset PDF versions of the Markdown documentation	2
Build the paper	2
Run the exact Python checks	2
Run the R cross-check	3
Current verification language	3

This is a **private, pre-release verification project** for a candidate refinement of Nishioka's lower bound for the three-dimensional Blaschke–Lebesgue problem. The repository now contains an integrated LaTeX research draft, but it is not yet ready for public release.

Candidate coefficient

The proposed bound is

$$\text{Vol}(K) \geq \frac{\pi}{1914} \left(259 - 27\sqrt{\frac{15183}{17303}} \right) d^3 \approx 0.3836027047 d^3.$$

Nishioka's published coefficient is $4\pi/33 \approx 0.3807991095$. The candidate is numerically weaker than the much newer HYRA claims; its possible contribution is the independent degree-3 spectral mechanism.

What has been checked

- A general degree-3 spherical harmonic is represented by a seven-parameter symmetric trace-free tensor.
- The central norm and determinant identities are integrated exactly over S^2 with SymPy rational arithmetic.
- The crucial constants are derived from polynomial identities rather than inserted as final answers.
- A second exact formulation checks the determinant identity independently.
- Deterministic numerical quadrature and random tensor tests check conventions.
- Independent Python and base-R numerical implementations both pass; see `expected/CROSS_LANGUAGE_COMPARISON.md`.
- The final coefficient is simplified and evaluated exactly.
- The noncomputational bridge from the determinant estimate to the candidate volume bound has a line-by-line draft in `proof/BRIDGE_LEMMAS.md`.
- The degree-3 tensor identity now has a human-readable derivation in `proof/DEGREE3_TENSOR_IDENTITY.md`, including a contraction-graph count for all six quartic moments.
- The contraction-graph table is independently enumerated by exact Python code; a matching base-R script is included for cross-language checking.
- An internal line-by-line audit is recorded in `proof/PROOF_AUDIT.md`.
- The complete proof has been merged into an eight-page LaTeX manuscript in `paper/degree3_spectral_refinement.tex`; the tracked PDF was built and visually inspected in this project environment.

What remains before public release

- Run and preserve the base-R pairing-count and numerical outputs plus R session metadata after applying the current patch.
- Have the named author read and approve the complete manuscript, especially the authorship, responsibility, and AI-assistance language.
- Add automated continuous integration for Python, R, and the LaTeX build.
- Add public-facing repository metadata: `LICENSE`, `CITATION.cff`, and `VERIFICATION_STATUS.md`.
- Perform a fresh-clone reproducibility test.
- Obtain outside mathematical review after the first public research-draft release.

See `proof/PROOF_LEDGER.md`, `proof/CLAIM_DEPENDENCIES.md`, `proof/PROOF_AUDIT.md`, `proof/BRIDGE_LEMMAS.md`, and `proof/DEGREE3_TENSOR_IDENTITY.md`.

Typeset PDF versions of the Markdown documentation

GitHub does not consistently render the repository's single-backslash LaTeX math delimiters. Typeset PDF counterparts are tracked under `rendered/markdown/`, with the source directory structure preserved. The Markdown files remain the editable source of truth.

- [Repository overview PDF](#)
- [Cross-language comparison PDF](#)
- [Paper build notes PDF](#)
- [Bridge lemmas PDF](#)
- [Claim dependencies PDF](#)
- [Degree-3 tensor identity PDF](#)
- [Internal proof audit PDF](#)
- [Proof ledger PDF](#)

Regenerate every Markdown-derived PDF from the repository root with:

```
./build_markdown_pdfs.sh
```

The build requires Pandoc 3 or later, Python 3, and a XeLaTeX installation. The script recognizes the `\(...\)` and `\[...\]` delimiters used in the proof notes, converts the few multi-line tagged displays to valid `amsmath` environments, normalizes the PDF trailer identifiers for reproducible output, and writes a SHA-256 manifest to `rendered/markdown/SHA256SUMS.txt`.

Build the paper

The manuscript source and tracked PDF are in `paper/`. Build from the repository root with:

```
./build_paper.sh
```

The build requires `latexmk` and a standard LaTeX installation. See `paper/README.md`.

Run the exact Python checks

From the repository root:

```
python -m pip install -r requirements.txt
./run_python_checks.sh
```

The exact symbolic scripts are:

- `python/verify_degree3_identity.py`
- `python/verify_degree3_identity_alt.py`
- `python/verify_bound_arithmetic.py`
- `python/verify_pairing_counts.py`

The numerical stress test is:

- `python/numerical_stress_tests.py`

Run the R cross-check

The R scripts use base R only:

```
Rscript R/verify_pairing_counts.R  
Rscript R/numerical_stress_tests.R
```

The first script independently checks the finite pairing-count table; the second is an independent numerical tensor cross-check. The general exact symbolic integration is performed by the Python/SymPy scripts.

Current verification language

Use:

AI-assisted, non-peer-reviewed research draft seeking independent mathematical verification.

Do not use:

Peer-reviewed, certified, or independently verified theorem.