

## Sécurité informatique de l'infrastructure de confiance

Travail de Master

Réunion participative, 10.07.2025 Fabrice Egger



## Écosystème ouvert



## Modèle de menace

- Modèle STRIDE
  - Spoofing (dissimulation d'identité)
  - Tampering (manipulation)
  - Repudiation (déni)
  - Information Disclosure (violation de la vie privée)
  - Denial of Service (refus de service)
  - Elevation of Privilege (augmentation des droits)

## Modèle de menaces

lssuer					
ID STRIDE Name		Name	me Description		
TIS-S01	S	Issue restricted schema	An issuer can issue a VC without authorization to do so.	Allow issuing in Trust Registry (CRT01)	
TIS-S02	S	Acquire issuing private key	If an attacker gets access to the private key of the issuer signing VCs, they can issue arbitrary credentials in his name.	HSM (CGN01), Key Rotation (CGN02)	
TIS-S03	ST	Acquire DID update key	If an attacker gets access to the DID update key of the issuer, it can change the DID log and therefore (1) invalidate all credentials from this issuer, and (2) insert your key to sign VCs in the name of the issuer.	HSM (CGN01), Key Rotation (CGN02), DID Prerotation (CRB01), Access token protected writes (CRG01)	
TIS-S04	S	Man in the middle	An attacker can perform a man-in-the-middle attack to get access to the VC's content.		
TIS-S05	S	Get physical access to issuer cooperation	An attacker can get access to the issuer's machine to issue malicious credentials.	Issue revocable credentials (CIS01), Status Requests (CRS01)	
TIS-S06	S	Issue their trust statement	An attacker can issue trust statements, which makes them eligible to issue other VCs.  Countermeasures	Issue revocable credentials	


An attacker can act as another issuer by resubmi General

178 Menaces56 Contre-mesures


Replay VC.

ID	Name	Description
CGN01	HSM	We use a Hardware Security Module (HSM) / secure key storage on mobile that makes it impossible to extract keys. They can, therefore, not be leaked.
CGN02	Key rotation	To reduce the "blast radius" when a key gets compromised (e.g., we use a new key every 100'000 issues for important VCs).
CGN03	Whitelisted cryptography	We enforce and use a small list of supported algorithms for encryption, signing, and hashing.
CGN04	Secure standards	We implement the latest version of did:webvh, OID4VCI, OID4VP, DIF Presentation, OCA, etc, standard according to the docs.
CGN05	JWT singatures	We use JWT signatures to prove the integrity and issuer of the JWT.
CGN06	HTTPS	We use HTTPS for all our communication between components.
CGN07	Random UUID	We use secure randomness to create unique UUIDs.
CGN08	Secure libraries	We use widely used and well-tested libraries to parse content (JSON, JWT, Requests).


TIS-S07 S




## Arbres d'attaque: Preuve d'obtention



## Arbres d'attaque






## Analyse de la sécurité

- 95 points faibles / risques
- 58 risques faibles, 29 risques moyens, 8 risques élevés et 0 risque critique
- 49 déjà traités pour la bêta publique
- Liste de toutes les vulnérabilités encore ouvertes publiée

<b>Probabilité \ Impact</b>	Bas	Moyen	Haut	Critique
Bas	31	21	4	5
Moyen	6	16	6	2
Haut	1	2	1	0
Critique	0	0	0	0

## Attaque par canal latéral sur la présentation





## Contourner la vérification




#### Avant la vérification

```
"header" : {
    "kid" : "did:tdw:12345:swiyu.admin.ch#key-1",
    "typ" : "vc+sd-jwt",
    "alg" : "ES256"
},
"payload" : {
    "vct" : 'betaid sdjwt",
    "iss" : "did:tdw:12345:swiyu.admin.ch",
    "_sd" :
    ["DCV4b0z4RESo0FX8SDV93TG4t2Gnk7zCGXB90wytIcM",
    "goXpzZhlBxzUhcg36gcK3fPDo9fUpxBrKwNgOX3P5lA"],
    "..."
},
"signature" :
"F6blSghb9oHg-vp1kUEe_CUV1CxFKMZFGP7gBej-apalidkvd
sJNq0ujzbwLiq70iUS0otPcc8ejVmDsBb67zw"
}
```

## Après la vérification Echanger "vct": eid sdjwt",

```
"vct" : eid sdjwt",
"iss" : "did:tdw:12345:swiyu.admin.ch",
"family_name": "Egger",
"..."
}
```

## Absence de validation du registre de confiance



## Résumé

- Première ébauche d'un modèle de menaces pour 2026
- Arbres d'attaque
- Analyse de la sécurité
- Assistance à la correction des vulnérabilités (49 / 95 déjà corrigées)

#### À emporter

- Bon de commencer avec la bêta publique
- La sécurité est un processus
- Programme de bug bounty

#### **Travaux futurs**

- Étendre le contrôle de la sécurité
- Analyse de la sécurité des standards implémentés

# Diapositives supplémentaires

## Vérification Contourner



```
"header" : {
  "kid": "did:tdw:12345:swiyu.admin.ch#key-1",
  "typ" : "vc+sd-jwt",
                                                      O64zqAxe412a108iroA", "family name", "Egger"
 "alg" : "ES256"
                                                 ["2GLC42sz7dRBA49WSXAad", "vct", "eid-sdjwt"]
"payload" : {
  "vct" : betaid sdjwt",
  "iss" : "did:tdw:12345:swiyu.admin.ch", 1
  " sd" :
  ["DCV4bQz4RESo0FX8SDV93TG4t2Gnk7zCGXB90wytIcM"
  "goXpzZhlBxzUhcg36gcK3fPDo9fUpxBrKwNg0X3P5lA"
                                                                              "vct" : 'eid sdjwt",
                                                                               "iss" : "did:tdw:12345:swiyu.admin.ch",
"signature" :
                                                                               "family name": "Egger",
"F6blSghb9oHg-vp1kUEe CUV1CxFKMZFGP7gBej-apalidkvd
sJNq0ujzbwLiq70iUS0otPcc8ejVmDsBb67zw"
```

## Demandes de réseau local

Risque	Impact	Probabilité	
Moyen	Moyen	Moyen	

