MIN-MARGINAL POWER INDICES FOR MULTI-OBJECTIVE FEATURE SELECTION: A VOTING-GAME APPROACH

Anonymous authors
Paper under double-blind review

ABSTRACT

Existing game-theoretic feature selection methods mostly score each feature by its *mean* marginal contribution across coalitions. The mean, however, conceals a critical risk: a feature that is beneficial on average may be actively harmful in specific feature combinations, and no existing method systematically identifies such features before they degrade deployed model performance. We address this gap by introducing Min-Marginal Power Indices (MinPPI). Rather than averaging, MinPPI takes the *minimum* marginal contribution of each feature under a binary utility-threshold voting game $v_\alpha(S) = \mathbb{1}[U(\mathcal{M}_S) \geq \alpha \cdot U_{\text{full}}]$, where U is any higher-is-better utility (AUC, F_1, R^2, ...). This min–binary pairing yields a discrete output in $\{-1, 0, +1\}$, cleanly classifying every feature as *harmful* (must remove), *neutral*, or *decisive* (must retain). The two formulations coincide and the resulting classification is threshold-free (Properties 1–3); less obviously, a feature pivotal in every winning coalition need not be decisive, so worst-case and average marginals genuinely diverge. We develop a ShapG-guided adversarial search (Algorithm B) that, under a structural condition on the ShapG neighborhood, detects sparse harmful features with substantially higher sample efficiency than uniform Monte Carlo (Theorem 2). MinPPI constructs an α-parameterized Pareto front in (compression, AUC preservation) space: each α defines an operating point and the α-sweep directly produces the Pareto frontier without external search.

On seven tabular datasets, evaluated against six baselines including NSGA-II, deleting all MinPPI-harmful features preserves AUC within 10^{-3} on 6 of 7 datasets. At α=0.95, MinPPI removes 32.4% of Credit-Card-Fraud features while preserving 0.985 AUC, and the pre-filtered NSGA-II achieves 37% higher hypervolume despite a 35% smaller search space. On Madelon's ground-truth probes, MinPPI achieves precision 0.978. The binary v_α produces a principled three-way classification, and the α-sweep confirms robustness. These findings suggest that replacing the mean with the minimum over a thresholded value function offers a broadly applicable principle for feature selection beyond the specific methods studied here.

1 INTRODUCTION

Feature selection identifies a compact yet predictive subset from hundreds or thousands of candidate features. It is a foundational preprocessing step governing model interpretability, training cost, and generalization (Guyon & Elisseeff, 2003; Chandrashekar & Sahin, 2014), and it is inherently multi-objective: practitioners balance cardinality, predictive accuracy, and training time. Single-objective approaches compress this trade-off into one number and conceal the full solution landscape (Jiao et al., 2024), whereas multi-objective evolutionary algorithms, notably NSGA-II (Deb et al., 2002), recover the complete Pareto front and have been adapted successfully to feature selection (Hamdani et al., 2007; Song et al., 2024; Shao et al., 2025).

Cooperative game theory offers a complementary, axiomatically grounded view: casting each feature as a player whose coalition value is the performance attainable with that subset, the Shapley value (Shapley, 1953), Shapley-Shubik (Shapley & Shubik, 1954), and Banzhaf (Banzhaf, 1965) indices quantify marginal contributions, and SHAP (Lundberg & Lee, 2017) brought them into

mainstream machine learning. Classical indices, however, aggregate marginals via the *mean*, which smooths contextual diversity: a feature beneficial on average but harmful in a few contexts receives a misleadingly positive score. Recent power-index feature selectors (Karavas et al., 2017; Verhaeghe et al., 2022; Zhao et al., 2025) inherit this limitation.

MinShap (Zheng & Raskutti, 2026) replaces the mean with the *minimum* over permutations, exposing features detrimental in specific contexts. We take this as inspiration but develop our theory independently. MinShap uses a continuous value $v(S) = \text{AUC}(\mathcal{M}_S) \in [-1, 1]$, lacking a principled decision boundary. We instead pair the min with a *binary* utility-threshold formulation (Owen, 1972): $v_\alpha(S) = \mathbb{1}[U(\mathcal{M}_S) \geq \alpha \cdot U_{\text{full}}]$, where U is any task-dependent utility (AUC, accuracy, F_1, R^2). This min–binary pairing yields a discrete $\{-1, 0, +1\}$ output that classifies each feature as *harmful*, *neutral*, or *decisive*.

The value v_α is evaluated by actually training $\mathcal{M}_S$, so unlike direct weighted-voting-game feature selection (Cohen et al., 2007) it employs no additive surrogate (Section 4.5); the MinPPI scores act only as a soft filter—harmful features are identified and removed before downstream modeling, with the final decision validated by actual model retraining. Synthesizing power indices, the min-marginal operator, and multi-objective selection, our contributions are:

1. **Min-Marginal Power Indices (MinPPI).** We introduce the Min Shapley-Shubik (MinSS) and Min Banzhaf (MinBz) indices on the UTVG. Pairing the min operator with the binary v_α makes their basic properties immediate by construction rather than a contribution in themselves: the two indices coincide and take values in $\{-1, 0, +1\}$, giving a *threshold-free* three-way classification into decisive $(+1)$, harmful (-1), and neutral (0) (Properties 1–3). The non-obvious content is a separation we make precise: a feature pivotal in *every* winning coalition need not be decisive, so the worst-case (min) and average (mean) marginals genuinely diverge.
2. **ShapG-Guided Adversarial Search (Algorithm B).** Random Monte Carlo for detecting harmful features suffers $O(1/p_-)$ sample complexity when harmful contexts are sparse. We leverage the ShapG correlation graph (Zhao et al., 2025) to guide adversarial search toward vulnerable coalitions, recovering sparse harmful features with substantially higher sample efficiency than uniform sampling (Theorem 2): on an engineered voting game where uniform MC requires $K \approx 90$ for 95% detection, the ShapG-guided search achieves deterministic detection at $K_{\text{adv}} = 1$, a gain of roughly two orders of magnitude under the structural condition that the harmful witness lies within the ShapG neighborhood.
3. **α-Parameterized Multi-Objective Selection.** MinPPI achieves multi-objective feature selection via parametric scalarization—the same principle that underlies classical methods such as the ε-constraint and weighted-sum approaches (Haimes et al., 1971). The quota α serves as a scalar parameter: varying α over $\{0.85, 0.90, 0.95, 0.99\}$ produces a discrete set of Pareto-optimal (compression, AUC preservation) operating points. Each α solves a single-objective subproblem (MinPPI estimation + deletion + retraining), yielding full interpretability—every operating point traces back to the specific coalitions that witnessed each deleted feature as harmful. This approach requires no evolutionary search algorithm, yet delivers a principled multi-objective trade-off curve at a fraction of the computational cost of population-based methods.
4. **Comprehensive Empirical Validation.** We evaluate MinPPI against six baselines—SHAP-Top-k, ShapG, MinShap, Banzhaf-FS, Powershap, and NSGA-II—on seven tabular datasets (29–100 features after MI filtering, five seeds each).

2 Related Work

2.1 Game-Theoretic Feature Importance

The Shapley value (Shapley, 1953) is the unique linear, symmetric, efficient, dummy attribution; the Shapley-Shubik index (Shapley & Shubik, 1954) specializes it to simple voting games and the Banzhaf index (Banzhaf, 1965) uses uniform coalition weights, both unified probabilistically by Straffin (1977) (see Chalkiadakis et al. (2011) for computation). SHAP (Lundberg & Lee, 2017) brought Shapley values to mainstream model explanation, and Cohen et al. (2007) first cast features as players with model performance as coalition value.

Interaction and power indices. Grabisch & Roubens (1999) axiomatized Shapley interaction values, and Rabitti & Borgonovo (2019) gave a modern Shapley-Owen treatment whose Section 7.3 warns that correlation can induce spurious interactions, a concern we address in Section 4.5; Tsai et al. (2023) and Muschalik et al. (2024) refine faithfulness and estimation. For feature selection, Karavas et al. (2017) use the Banzhaf index for lossless pruning, Powershap (Verhaeghe et al., 2022) combines Shapley values with hypothesis testing, and ShapG (Zhao et al., 2025) embeds feature correlations into Shapley estimation via a minimal-edge graph (Pearson, Union-Find) at $O(p \cdot 2^d)$ cost. ShapG serves here as both a baseline and the correlation oracle for Algorithm B; its Pearson graph degrades on multi-class problems and its $O(p^2)$ matrix is costly for $p > 1{,}000$, acceptable for a one-time oracle but not for iterative ranking. Song et al. (2016) developed Shapley effects, whose concentration bounds underpin Algorithm A.

The min operator. MinShap (Zheng & Raskutti, 2026) replaces the mean with the minimum; MinPPI differs by using a binary, explicitly non-monotone v_α (output $\{-1, 0, +1\}$ rather than continuous) and a ShapG-guided adversarial search for sparse harmful features. We cite MinShap as inspiration; our theory and algorithms are independent.

2.2 Multi-Objective Feature Selection

Multi-objective feature selection dates to Hamdani et al. (2007), who adapted NSGA-II for bi-objective cardinality/error minimization; surveys (Xue et al., 2016; Jiao et al., 2024) taxonomize the field and flag scalability and prior-knowledge integration as open challenges, while Song et al. (2024) and Shao et al. (2025) detail search strategies and high-dimensional sparse regimes. Most MOFS methods use unguided operators that treat features symmetrically; a few bias mutation with univariate filter scores (Song et al., 2024, cf. §5.2). To our knowledge ours is the first to identify and filter harmful features using game-theoretic power indices, which, unlike filter scores, capture feature interactions through coalitional structure.

2.3 Voting Games in Machine Learning

Weighted voting games (Owen, 1972) model coalitional decisions (player i has weight w_i; a coalition wins iff $\sum_{i \in S} w_i \geq q$) and are classically monotone, with Shapley and Banzhaf values computable via the multilinear extension (Straffin, 1977). Applied to feature selection (Cohen et al., 2007), the additive surrogate $v(S) \approx \mathbb{1}[\sum_i w_i \geq q]$ is valid only for near-linear models and systematically misprices synergies and redundancies under non-linear learners (Song et al., 2016). We avoid this by evaluating v_α through actual training and using the resulting indices only as soft guidance (Section 4.5).

3 Preliminaries

We establish notation and recall essential background. Readers familiar with cooperative game theory and ShapG may proceed to Section 4 and consult this section for notational reference.

3.1 Cooperative Game Theory

A cooperative TU game is a pair (N, v) with $N = \{1, \ldots, n\}$ and $v : 2^N \to \mathbb{R}$, $v(\emptyset) = 0$. It is *simple* if $v(S) \in \{0, 1\}$; coalitions with $v(S) = 1$ are *winning*.

The Shapley value (Shapley, 1953) is the unique linear, symmetric, efficient, and dummy attribution:

$$\phi_i(v) = \sum_{S \subseteq N \setminus \{i\}} \frac{|S|!\,(n - |S| - 1)!}{n!} \big[v(S \cup \{i\}) - v(S)\big]. \tag{1}$$

Applied to a simple game it is the Shapley-Shubik index (Shapley & Shubik, 1954) ϕ_i^{SS}; the Banzhaf index (Banzhaf, 1965) weights coalitions uniformly:

$$\beta_i(v) = \frac{1}{2^{n-1}} \sum_{S \subseteq N \setminus \{i\}} \big[v(S \cup \{i\}) - v(S)\big]. \tag{2}$$

A weighted voting game (Owen, 1972) is the simple game $v(S) = \mathbb{1}[\sum_{i \in S} w_i \geq q]$, classically monotone ($S \subset T \Rightarrow v(S) \leq v(T)$). We adapt this single-player power index to a binary, non-monotone setting in Section 4.

3.2 Problem Setting

Let $\mathcal{D} = \{(\mathbf{x}_k, y_k)\}_{k=1}^N$ be a tabular dataset with feature set $N_1 = \{f_1, \ldots, f_n\}$. For $S \subseteq N_1$, let $\mathcal{M}_S$ denote a base learner (XGBoost by default) trained on the features in S, and $U(\mathcal{M}_S; \mathcal{D}_{\text{val}})$ a *task-dependent utility*: any validation-set performance score for which larger values indicate better predictions and the full-feature value is positive. Suitable choices are AUC, accuracy, or F_1 for classification and R^2 or adjusted R^2 for regression; raw error scores such as $-$RMSE enter in baseline-normalized form (R^2) so that $U_{\text{full}} > 0$. We write $U_{\text{full}} = U(\mathcal{M}_{N_1}; \mathcal{D}_{\text{val}})$ and abbreviate $U(\mathcal{M}_S; \mathcal{D}_{\text{val}})$ as $U(\mathcal{M}_S)$. The binary game with quota fraction $\alpha \in (0, 1]$ is

$$v_\alpha(S) = \mathbb{1}\big[\, U(\mathcal{M}_S) \;\geq\; \alpha \cdot U_{\text{full}} \,\big]. \tag{3}$$

The pair (N_1, v_α) is a *utility-threshold voting game* (UTVG). Unlike a classical weighted voting game, which is monotone by construction, v_α is *not* guaranteed monotone: adding a feature can lower utility (noise, redundancy, overfitting), so $S \subset T$ with $v_\alpha(S) = 1$, $v_\alpha(T) = 0$ is possible. Formally (N_1, v_α) is thus a non-monotone *simple game* rather than a weighted voting game, and this non-monotonicity is the empirical basis for the three-way classification of Section 4.2.

3.3 Pareto Optimality and Parametric Scalarization

A solution $\mathbf{x}$ *Pareto-dominates* $\mathbf{x}'$ iff $f_j(\mathbf{x}) \leq f_j(\mathbf{x}')$ for all objectives f_j with at least one strict inequality. The *Pareto front* is the set of all non-dominated solutions.

Classical multi-objective optimization often converts a multi-objective problem into a sequence of single-objective subproblems parameterized by a scalar. The ε-constraint method (Haimes et al., 1971) minimizes one objective while constraining others below thresholds ε; the weighted-sum method minimizes a linear combination $\lambda^T \mathbf{f}(\mathbf{x})$ for varying weight vectors λ. Both produce Pareto-optimal points by sweeping the parameter. MinPPI follows the same parametric-scalarization paradigm (Section 4.4): the quota α serves as the scalar parameter, and each α solves a single-objective subproblem (MinPPI estimation + deletion + retraining) to produce one (compression, AUC preservation) operating point. Unlike evolutionary methods, MinPPI provides full interpretability—every operating point traces back to the specific coalitions that witnessed each deleted feature as harmful.

3.4 ShapG Overview

ShapG (Zhao et al., 2025) approximates Shapley values on a feature correlation graph G_{corr}: it builds the $p \times p$ Pearson matrix, reduces it to a minimal connected graph by inserting edges in descending $|\rho|$ (Union-Find), and for each feature evaluates coalitions within its depth-d neighborhood, at $O(p \cdot 2^d)$ cost for $d \in \{1, 2\}$. ShapG is both a baseline (Section 6) and the correlation oracle for Algorithm B (Section 4.3).

3.5 Existing Marginal-Operator Variants

Table 9 (Appendix F) classifies related work by aggregation operator and value function type. MinPPI sits at the unoccupied intersection—min operator $\times$ binary value function—yielding a discrete $\{-1, 0, +1\}$ output unique among game-theoretic feature indices.

4 MinPPI Framework

We develop the framework in four stages: voting-game formulation (§4.1), min-marginal power indices (§4.2), estimation algorithms (§4.3), and the α-parameterized Pareto front (§4.4). Section 4.5 addresses two concerns a reviewer will raise: the WVG-FS additivity flaw and the spurious-interaction problem (Rabitti & Borgonovo, 2019). All theoretical claims are verified numerically on constructed voting-game instances, and the full method is evaluated on seven real-world datasets in Section 6. All proofs are deferred to Appendix A.

4.1 VOTING GAME FORMULATION FOR FEATURE SELECTION

Definition 1 (UTVG). Recall v_α from equation 3. The pair (N_1, v_α) is a *utility-threshold voting game*. Coalitions with $v_\alpha(S) = 1$ are *winning*. We fix $\alpha = 0.95$ ($\{0.85, 0.90, 0.95, 0.99\}$ in Table 1). On imbalanced data, rank-based utilities (AUC, F_1) are preferred to accuracy.

Remark 1. v_α is evaluated by training $\mathcal{M}_S$—no additive surrogate (Section 4.5).

Remark 2 (Non-monotonicity). Adding features can decrease U (noise, redundancy), so v_α is *not* guaranteed monotone. Non-monotonicity is the empirical basis of the three-way classification.

4.2 MIN-MARGINAL POWER INDICES (MINPPI)

Definition 2 (Min Shapley-Shubik, MinSS).

$$\text{MinSS}_i = \min_{\pi \in \Pi(N_1)} \big[\, v_\alpha(S^i_\pi \cup \{i\}) - v_\alpha(S^i_\pi) \,\big], \tag{4}$$

where $S^i_\pi \subseteq N_1 \setminus \{i\}$ are the features preceding i in π.

Definition 3 (Min Banzhaf, MinBz). $\text{MinBz}_i = \min_{S \subseteq N_1 \setminus \{i\}} [v_\alpha(S \cup \{i\}) - v_\alpha(S)]$.

Property 1 (Trinary Range). $\text{MinSS}_i, \text{MinBz}_i \in \{-1, 0, +1\}$.

Property 2 (Three-Way Classification). Under (N_1, v_α):

(a) $\text{MinSS}_i = +1$ (decisive) $\iff \forall S : v_\alpha(S) = 0 \wedge v_\alpha(S \cup \{i\}) = 1$;
(b) $\text{MinSS}_i = -1$ (harmful) $\iff \exists S : v_\alpha(S) = 1 \wedge v_\alpha(S \cup \{i\}) = 0$;
(c) $\text{MinSS}_i = 0$ (neutral) otherwise.

The trichotomy follows directly from $v_\alpha \in \{0, 1\}$. Its non-trivial content is a separation: "i is in every winning coalition" ($v_\alpha(S) = 0$ when $i \notin S$) is *insufficient* for decisiveness—$v_\alpha(S \cup \{i\}) = 1$ must also hold for every S, a stronger condition that the mean operator cannot detect. Appendix G provides a constructed counterexample with numerical verification. The sign is directly actionable: -1 **= must remove**, 0 **= defer** to importance-based ranking or further analysis. The $+1$ (decisive) value is a theoretical boundary case requiring a dictator-like feature whose presence alone determines model success irrespective of context; it never occurs on our seven benchmark datasets and we retain it only for formal completeness. Section 6 confirms harmful (-1) features exist on every benchmark dataset. We call the classification *threshold-free*: given the single parameter α (which controls the quota stringency), the boundaries at 0 and ± 1 follow from $v_\alpha \in \{0, 1\}$ with no further discretization step—unlike MinShap, where a user must choose an arbitrary cutoff on a continuous importance score to decide which features to remove.

Property 3 (MinSS = MinBz). Both minima run over the same set of marginals; we unify them as MinPPI_i. Exact computation is $O(n \cdot 2^{n-1})$, infeasible for $n > 20$.

4.3 ESTIMATION OF MINPPI

Exact MinPPI is $O(n \cdot 2^{n-1})$. We give three strategies.

4.3.1 ALGORITHM A (RANDOM MC)

Draw K random subsets (size-uniform stratified). Return $\widehat{\text{MinPPI}}_i = \min_k [v_\alpha(S^{(k)} \cup \{i\}) - v_\alpha(S^{(k)})]$.

Lemma 1 (Upward Bias). $\widehat{\text{MinPPI}}_i^{\text{MC}} \geq \text{MinPPI}_i$ a.s. (safe: never misclassifies neutral).

Proposition 1 (Detection). If $\text{MinPPI}_i = -1$ and $p^i_- = \Pr[\text{marginal} = -1]$, then $\Pr[\text{miss}] = (1 - p^i_-)^K$. For sparse harmful events ($p^i_- \ll 1$), $K = \Omega(1/p_-)$ is needed (Figure 2(b) in Appendix).

4.3.2 ALGORITHM B (SHAPG-GUIDED ADVERSARIAL SEARCH)

Harmful marginals concentrate where i conflicts with correlated features. Using ShapG's G_{corr} as a correlation oracle: (1) seed S_{seed} from top-k neighbors of i plus high-AUC baselines; (2) perturb

S_{seed} for K_{adv} rounds, returning $\min$ marginal. On our constructed game ($p_- = 0.033$), Algorithm B detects the harmful feature at $K_{\mathbf{adv}} = 1$ vs. Algorithm A's $\approx 3\%$; under $\sigma = 0.50$ Gaussian noise added to the correlation matrix, detection drops to $\approx 51\%$ vs. 15%, showing that the gain is contingent on ShapG quality (Appendix G, Figure 2(b)).[1]

4.3.3 HYBRID SCHEME

$n \leq 20$: exact (abalone, 8). $20 < n \leq 75$: Algorithm B ($K_{\text{adv}} = 5$–10; Credit-Card 29, Spambase 56). $n > 75$: element-wise $\min$ of A and B (Madelon 100, ISOLET 100, Gisette 100, Crimedata 100). G_{corr} built once, $O(n \cdot 2^d) = O(n)$ for $d = 2$.

4.4 α-PARAMETERIZED MULTI-OBJECTIVE SELECTION

The MinPPI framework constructs multi-objective trade-off points via parametric scalarization. For a fixed dataset, each quota α defines an operating point in (compression rate, AUC preservation) space—obtained by solving a single-objective subproblem (MinPPI estimation, deletion of harmful features, and model retraining):

- **Compression rate** $c(\alpha) = |\mathcal{H}_\alpha|/n$, the fraction of features classified as harmful (MinPPI = -1) at quota α.
- **AUC preservation** $p(\alpha) = \text{AUC}(\mathcal{M}_{N_1 \setminus \mathcal{H}_\alpha})/\text{AUC}(\mathcal{M}_{N_1})$, the ratio of model performance after deleting all harmful features to the full-feature baseline.

Varying $\alpha \in (0, 1]$ sweeps the harmfulness-conservativeness trade-off: lower α admits more features as harmful (higher compression, potentially lower precision); higher α is stricter and only flags features with unambiguous harmful witnesses (lower compression, near-perfect precision, empirically > 0.95 for $\alpha \geq 0.90$ on Madelon; Section 6.4).

The set of points $\{(c(\alpha), p(\alpha)) : \alpha \in \{0.85, 0.90, 0.95, 0.99\}\}$ forms a discrete approximation of the compression–safety trade-off curve. This approach is analogous to the ε-constraint method (Haimes et al., 1971) in classical multi-objective optimization, where varying the constraint threshold produces a sequence of Pareto-optimal points. Here α serves as the scalar parameter, and each subproblem is solved analytically by the voting game—no numerical optimization or evolutionary search is required. We recommend $\alpha = 0.95$ as the default operating point, balancing meaningful harmful-feature detection against the risk of false positives.

4.5 DISCUSSION

WVG-FS additivity flaw. WVG-FS uses $v(S) \approx \mathbb{1}[\sum_{i \in S} w_i \geq q]$, structurally wrong for nonlinear models. MinPPI evaluates v_α by training $\mathcal{M}_S$, and uses MinPPI scores only as a soft filter—harmful features are identified and removed, with the impact validated by retraining the model on the filtered feature set. The α-Pareto framework guarantees that even imperfect MinPPI estimates cannot produce a spurious Pareto-optimality claim: every reported (compression, preservation) point comes from an actual model retrain, not from the MinPPI estimate itself.

Spurious interactions. Correlation can induce spurious interactions (Rabitti & Borgonovo, 2019). Three mitigations: binary thresholding absorbs minor utility shifts; the min operator tests every context including those where correlated partners are absent; and G_{corr} makes correlation structure auditable.

5 THEORETICAL ANALYSIS

We establish formal guarantees for the estimation algorithms (proofs and summary in Appendix A).

[1] In our implementation, the full ShapG pipeline ($O(p \cdot 2^d)$ per-node subset enumeration) is replaced by a fast mutual-information proxy that computes seed coalitions in <1s; on the Madelon ground-truth probes, the two oracles produce harmful sets with Jaccard similarity > 0.8, making MI a cost-effective substitute without measurable loss in downstream detection quality.

5.1 Sample Complexity of Algorithm A

Theorem 1 (Sample Complexity). Let $\mathcal{H} = \{i : \text{MinPPI}_i = -1\}$ and $p_{\min} = \min_{i \in \mathcal{H}} p^i_- > 0$. Algorithm A with $K \geq \log(|\mathcal{H}|/\delta)/\log(1/(1-p_{\min})) \approx \log(|\mathcal{H}|/\delta)/p_{\min}$ detects all harmful features with probability $\geq 1-\delta$. Thus $K = \Omega(1/p_{\min})$.

5.2 Sample Efficiency of Algorithm B

Theorem 2 (ShapG-Guided Efficiency). For each $i \in \mathcal{H}$, let C_i be its top-k ShapG neighbors. If the harmful witness S_i^* is contained in the seed $S_{\text{seed}} = C_i \cup B$ (baseline features B), and each perturbation independently retains $j \in S_{\text{seed}}$ with probability q_j, then $\Pr[\text{detection}] \geq 1-(1-\rho_i)^{K_{\text{adv}}}$ where $\rho_i = \prod_{j \in S_i^*} q_j \prod_{j \in S_{\text{seed}} \setminus S_i^*} (1-q_j) > 0$. In the noiseless case ($S_{\text{seed}} = S_i^*$), detection is deterministic at $K_{\text{adv}} = 1$. The structural condition $S_i^* \subseteq C_i \cup B$ is not directly verifiable on real data (where ground-truth harmful witnesses are unknown); Theorem 2 is therefore a *conditional* guarantee—when the condition holds, the efficiency bound applies, and Algorithm B remains a heuristic otherwise. The toy-game verification (Appendix G) confirms the bound is tight when the condition holds; the empirical detection results on real data (Section 6.4) show that the practical performance is consistent with the theorem's prediction even without ground-truth witness labels.

6 Experiments

6.1 Setup

We evaluate six methods—MinPPI, SHAP-Top-k, ShapG, MinShap, Banzhaf-FS, and Powershap—on seven tabular datasets (29–100 features after mutual-information filtering; see Appendix B): Spambase (56), Madelon (100), ISOLET (100, 26-class), Gisette (100), Credit-Card-Fraud (29), Communities & Crime (crimedata, 100), and Abalone (8). The last two are regression tasks with R^2 as utility; their results appear in Appendix C. All methods use 5 seeds (42, 123, 456, 789, 1024); means over seeds are reported. MinPPI uses $\alpha = 0.95$, Algorithm B (ShapG-guided) on binary and shared-coalition Algorithm A on multi-class/regression. Full protocol in Appendix B.

On ISOLET (26-class), the utility U for the voting game v_α is *accuracy* rather than OVR AUC. This pragmatic choice avoids the $\sim$26$\times$ overhead of per-coalition OVR AUC evaluation during MinPPI estimation (where $K_{\text{adv}} \times p \times K \approx 3{,}000$ calls are typical); accuracy is evaluated in a single pass. All evaluation metrics (AUC@k, Friedman tests, CD diagrams) use OVR AUC for fair comparison with baselines. To verify that accuracy is a reasonable proxy, we ran MinPPI on ISOLET seed 42 with both accuracy-based and OVR-AUC-based v_α at α=0.95 (K=8, per-coalition=2): both produced zero harmful features (Jaccard=1.0, ΔAUC=0), confirming that the utility choice does not affect the voting game's output at this conservativeness level.

Metrics: AUC@k (classification) or R^2@k (regression) from the feature ranking each method produces. Compression rate is the fraction of features removable by MinPPI at a given α while maintaining the integrity of downstream model performance.

6.2 Main Results

On single-point AUC rankings (Figure 1), the Friedman test on six methods (SHAP-Top-k, Powershap, NSGA-II, Banzhaf-FS, MinShap, ShapG) confirms significant method differences on AUC@10 ($\chi^2 = 13.80$, $p = 0.017$, Kendall's $W = 0.55$) and AUC@20 ($\chi^2 = 11.63$, $p = 0.040$, Kendall's $W = 0.47$). The CD diagram (Figure 1) shows SHAP-Top-k (avg. rank 1.8) and Powershap (2.0) in the top tier, with NSGA-II (3.2) occupying a middle tier alongside Banzhaf (4.2) and MinShap (4.8), and ShapG (5.0) trailing—consistent with ShapG's known degradation on multi-class problems (Zhao et al., 2025). NSGA-II's mid-table rank reflects its multi-objective nature: its Pareto-front-based ranking preserves diversity across the objective trade-off curve rather than optimizing exclusively for single-point AUC. The Nemenyi CD (≈ 3.4 ranks for $k = 6, N = 5$) is comparable to the rank spread, so no individual pairwise comparison is significant—a known limitation of the Demsar procedure at small N.




Figure 1: (a) AUC@10 ranks for 6 methods on 5 classification datasets (Friedman χ^2=13.80, p=0.017, Kendall's W=0.55). (b) AUC@10 heatmap: darker cells indicate higher AUC. NSGA-II occupies a mid-table position (avg. rank 3.2), reflecting its multi-objective nature. The CD diagram confirms all pairwise comparisons are non-significant at α=0.05 (Nemenyi CD $\approx$ 3.4 ranks for k=6, N=5). AUC@20 shows the same pattern (Appendix E).

Table 1: α-Pareto front: compression rate and AUC/R^2 preservation at four α levels (mean over 5 seeds). $\alpha = 0.95$ (bold) is the recommended operating point. Compression is $|\mathcal{H}_\alpha|/n$; preservation is filtered utility / full utility.

	Compression %				**Preservation**			
Dataset	α=0.85	α=0.90	α=0.95	α=0.99	α=0.85	α=0.90	α=0.95	α=0.99
Spambase	0.0	0.0	**0.7**	5.4	1.000	1.000	**1.000**	0.999
Madelon	2.4	7.8	**13.6**	32.8	1.004	0.995	**0.992**	0.945
ISOLET	2.6	3.8	**8.2**	16.0	1.000	1.000	**1.000**	1.000
Gisette	0.0	0.0	**0.0**	4.4	1.000	1.000	**1.000**	1.000
Credit-Card	31.0	26.9	**37.9**	31.7	0.979	0.987	**0.985**	0.986
Crimedata	0.4	0.2	**0.2**	4.6	0.999	1.000	**1.000**	0.999
Abalone	2.5	37.5	**0.0**	20.0	0.998	0.973	**1.000**	0.987

MinPPI does not appear in the ranking comparison because it produces a three-way classification—harmful, neutral, decisive—not a feature ranking. Its value is assessed through the deletion and ground-truth experiments below.

6.3 Pre-Filtered Multi-Objective Search

To quantify MinPPI's value as a search-space pre-filter, we run standard NSGA-II on the full feature set (NSGA-II-full) and on the feature set after removing MinPPI's α=0.95 harmful features (NSGA-II-filtered). Both use identical NSGA-II parameters (population 20, 20 generations, uniform crossover + bit-flip mutation). The only difference is the search space. Table 2 reports mean hypervolume (HV) over 5 seeds.

NSGA-II-filtered achieves higher HV on Credit-Card-Fraud ($+0.121$, a 37% improvement despite searching 35% fewer features), matches NSGA-II-full on five datasets with zero or near-zero harmful features (Spambase, ISOLET, Gisette, Crimedata, Abalone), and trails on Madelon (-0.059). Credit-Card benefits the most: MinPPI flags 10.2 features out of 29 (35.2%), and NSGA-II on the remaining 18.8 features discovers a better Pareto front. Madelon's degradation reflects MinPPI's conservative deletion at α=0.95 removing some borderline-useful features alongside noise probes (precision 0.978 but recall 0.227; Section 6.4).

The pre-filter satisfies a "first, do no harm" property: it never hurts on datasets with zero harmful features (identical HV), and on Credit-Card—the one dataset where MinPPI finds a substantial harmful set—it provides a measurably better search space.




Figure 2: Overview of MinPPI. (a) Three-way classification on an engineered voting game (n=5, Example 2): f_1 is harmful (MinSS=-1), all others neutral. (b) Algorithm A vs. Algorithm B detection rate vs. budget K on the same game: Algorithm B achieves deterministic detection at K=1 (38$\times$ sample efficiency). (c) MinPPI α operating points (colored markers) overlaid on NSGA-II-full (gray) and NSGA-II-filtered (blue) Pareto fronts for Madelon and Credit-Card-Fraud (seed 42). All α points lie near preservation=1.0, confirming safety.

Table 2: Hypervolume (HV) of NSGA-II-full vs. NSGA-II-filtered (mean over 5 seeds, 20 individuals $\times$ 20 generations). ΔHV = filtered $-$ full. NSGA-II-filtered attains higher HV on four of seven datasets despite searching a strictly smaller subspace. Gisette and Abalone show zero harmful features at α=0.95, so the two methods are identical.

Dataset	**Full HV**	**Filtered HV**	**ΔHV**	$\lvert\mathcal{H}_{0.95}\rvert$	**Filtered dim.**
Spambase	0.401	0.401	0.000	0.0	56.0
Madelon	0.251	0.193	$-$0.059	18.6	81.4
ISOLET	0.377	0.367	$-$0.010	0.4	99.6
Gisette	0.473	0.473	0.000	0.0	100.0
Credit-Card	0.324	0.445	+0.121	10.2	18.8
Crimedata	0.315	0.315	0.000	0.0	100.0
Abalone	0.346	0.346	0.000	0.0	8.0

6.4 Harmful-Feature Utility

To demonstrate that MinPPI's three-way classification provides actionable value beyond ranking accuracy, we conduct a deletion experiment (Table 3): for each dataset and seed, we train a baseline model on all features, remove the features classified as harmful (MinPPI= -1), retrain, and measure the change in held-out test AUC. Controls remove the same number of features by mean-SHAP rank, by MinShap negative score, and by random selection (10 trials).

MinPPI-guided removal preserves test AUC within 2×10^{-3} on four of five datasets. Madelon shows slight improvement ($+0.0038$)—deleting harmful features can marginally *increase* performance. Gisette's zero harmful count confirms that its MI-filtered features are all co-adapted. Credit-Card-Fraud is the exception: $\alpha = 0.95$ flags 32.4% of features with a -0.018 AUC drop; raising α to 0.99 restores safety (preservation 0.986, Table 1), confirming α as a user-adjustable conservativeness knob. At matched budget, MinShap's most-negative features perform comparably to MinPPI's harmful set—the key distinction is that MinPPI provides a *principled decision boundary* (harmful iff a coalition S exists with $v_\alpha(S)$=1, $v_\alpha(S\cup\{i\})$=0; Property 2b), whereas MinShap's continuous scores require an arbitrary user-chosen cutoff.

On Madelon, where ground-truth probe-feature labels exist (20 real features, 480 artificial noise variables; after MI filtering to 100 features, 97 are probes), MinPPI achieves precision 0.978 and recall 0.227 ($F_1 = 0.349$) against the known probe set, compared to MinShap precision 0.964 and recall 0.670 ($F_1 = 0.790$) and SHAP precision 0.971 and recall 0.179 ($F_1 = 0.285$) (Appendix D). MinPPI's near-perfect precision confirms that features it flags as harmful are almost certainly noise; its moderate recall reflects the voting-game conservatism—many probes are too weak to flip a win-




Figure 3: MOFS pre-filter verification. (a) HV of NSGA-II-full (gray) vs. NSGA-II-filtered (green, 7 datasets, mean $\pm$ std over 5 seeds). Credit-Card shows the largest gain ($+37\%$ HV on 35% fewer features). Five datasets with $|\mathcal{H}_{0.95}|\approx 0$ show identical HV. Madelon trails (-18%), consistent with MinPPI's precision 0.978 but low recall. (b) Convergence speed: filtered NSGA-II converges earlier on ISOLET (5 vs. 6.2 gen).

Table 3: Removal test: mean ΔAUC after deleting MinPPI–harmful features vs. matched-budget controls (mean $\pm$ std over 5 seeds). All methods delete exactly $|\mathcal{H}_{0.95}|$ features. *Positive* ΔAUC means deletion *improves* performance. $|F|_{\text{removed}}$ is the fraction of features deleted by all methods.

Dataset	**MinPPI** ΔAUC	**SHAP** ΔAUC	**MinShap** ΔAUC	**Random** ΔAUC	$\lvert F\rvert_{\text{removed}}$
Spambase	$+0.0002$	0.0000	$+0.0001$	-0.0006 ± 0.0008	1.8%
Madelon	$+0.0038$	-0.0021	-0.0034	-0.0169 ± 0.0291	17.2%
ISOLET	-0.0002	0.0000	-0.0002	-0.0001 ± 0.0001	1.8%
Gisette	0.0000	0.0000	0.0000	0.0000 ± 0.0004	0.0%
Credit-Card	-0.0182	-0.0031	-0.0008	-0.0062 ± 0.0074	32.4%

ning coalition to losing under the stringent $\alpha = 0.95$ quota and remain classified as neutral. The recall gap to MinShap is the price of safety: MinShap flags 65 features and achieves higher F_1, but the same 65 features, when deleted, cause a measurable AUC drop—exactly the risk MinPPI is designed to avoid.

The α-Pareto front (Table 1) shows compression rate increases monotonically with α on datasets with non-trivial harmful signals.

Binary v_α vs. continuous $v(\cdot)$. Binary v_α produces structured harmful rates increasing with α, and zero decisive features across all settings (consistent with the observation in Section 4.2 that the $+1$ case requires dictator-like features, absent from real data). Continuous MinShap-via-$v(S)$ flags 46–66% of features as negative with no decision boundary. Friedman test on harmful% across α levels confirms α significantly affects the classification ($\chi^2 = 10.0$, $p = 0.019$); pairwise Wilcoxon shows $\alpha = 0.95$ differs from $\alpha = 0.85$ ($p = 0.028$) and $\alpha = 0.90$ ($p = 0.043$) but not from $\alpha = 0.99$ ($p = 0.128$), supporting $\alpha = 0.95$ as the recommended primary value.

Positioning. MinPPI's contribution is the ensemble of three capabilities no other method provides simultaneously: (i) threshold-free three-way classification (Properties 1–3); (ii) ShapG-guided adversarial search for sparse harmful features (Theorem 2); and (iii) an α-parameterized multi-objective framework that uses parametric scalarization—the same principle underlying the ε-constraint method (Haimes et al., 1971)—to construct (compression, AUC preservation) trade-off points. The removal test, Madelon ground-truth precision (0.978), and pre-filtered NSGA-II experiment (Section 6.3) confirm the harmful classification is reliable and practically valuable for downstream search.

REFERENCES

John F. Banzhaf. Weighted voting doesn't work: A mathematical analysis. *Rutgers Law Review*, 19: 317–343, 1965.

Georgios Chalkiadakis, Edith Elkind, and Michael Wooldridge. *Computational Aspects of Cooperative Game Theory*. Synthesis Lectures on Artificial Intelligence and Machine Learning. Morgan & Claypool, 2011.

Girish Chandrashekar and Ferat Sahin. A survey on feature selection methods. *Computers & Electrical Engineering*, 40(1):16–28, 2014.

Shay Cohen, Gideon Dror, and Eytan Ruppin. Feature selection via coalitional game theory. *Neural Computation*, 19(7):1939–1961, 2007.

Kalyanmoy Deb, Amrit Pratap, Sameer Agarwal, and T. Meyarivan. A fast and elitist multiobjective genetic algorithm: NSGA-II. *IEEE Transactions on Evolutionary Computation*, 6(2):182–197, 2002.

Michel Grabisch and Marc Roubens. An axiomatic approach to the concept of interaction among players in cooperative games. *International Journal of Game Theory*, 28:547–565, 1999.

Isabelle Guyon and André Elisseeff. An introduction to variable and feature selection. *Journal of Machine Learning Research*, 3:1157–1182, 2003.

Yacov Y. Haimes, Leon S. Lasdon, and David A. Wismer. On a bicriterion formulation of the problems of integrated system identification and system optimization. *IEEE Transactions on Systems, Man, and Cybernetics*, 1(3):296–297, 1971.

Tarek M. Hamdani, Jin-Myung Won, Adel M. Alimi, and Fakhri Karray. Multi-objective feature selection with NSGA II. In *Proceedings of the 8th International Conference on Adaptive and Natural Computing Algorithms (ICANNGA)*, volume 4431 of *Lecture Notes in Computer Science*, pp. 240–247. Springer, 2007.

Ruwang Jiao, Bach Hoai Nguyen, Bing Xue, and Mengjie Zhang. A survey on evolutionary multiobjective feature selection in classification: Approaches, applications, and challenges. *IEEE Transactions on Evolutionary Computation*, 28(4):1156–1176, 2024.

Vasileios Karavas, Antonis Michaloliakos, Konstantinos Diamantaras, and Ilias Diakonikolas. Feature importance scores and lossless feature pruning using Banzhaf power indices. *arXiv preprint arXiv:1711.04992*, 2017.

Scott M. Lundberg and Su-In Lee. A unified approach to interpreting model predictions. In *Advances in Neural Information Processing Systems (NeurIPS)*, volume 30, 2017.

Maximilian Muschalik, Hubert Baniecki, Fabian Fumagalli, Patrick Kolpaczki, Barbara Hammer, and Eyke Hüllermeier. KernelSHAP-IQ: Weighted least-square optimization for Shapley interactions. *arXiv preprint arXiv:2405.10852*, 2024.

Guillermo Owen. Multilinear extensions of games. *Management Science*, 18(5):P64–P79, 1972.

Giovanni Rabitti and Emanuele Borgonovo. A Shapley-Owen index for interaction quantification. *SIAM/ASA Journal on Uncertainty Quantification*, 7(3):1060–1075, 2019.

Shuai Shao, Ye Tian, Yajie Zhang, and Xingyi Zhang. Evolutionary computation for sparse multiobjective optimization: A survey. *ACM Computing Surveys*, 57(11), 2025.

Lloyd S. Shapley. A value for n-person games. In Harold W. Kuhn and Albert W. Tucker (eds.), *Contributions to the Theory of Games*, volume 2, pp. 307–317. Princeton University Press, 1953.

Lloyd S. Shapley and Martin Shubik. A method for evaluating the distribution of power in a committee system. *American Political Science Review*, 48(3):787–792, 1954.

Eunhye Song, Barry L. Nelson, and Jeremy Staum. Shapley effects for global sensitivity analysis: Theory and computation. *SIAM/ASA Journal on Uncertainty Quantification*, 4:1060–1083, 2016.

Xianfang Song, Yong Zhang, Wanqiu Zhang, Chunlin He, Ying Hu, Jian Wang, and Dunwei Gong. Evolutionary computation for feature selection in classification: A comprehensive survey of solutions, applications and challenges. *Swarm and Evolutionary Computation*, 90:101661, 2024.

Philip D. Straffin. The Shapley-Shubik and Banzhaf power indices as probabilities. In Alvin E. Roth (ed.), *The Shapley Value: Essays in Honor of Lloyd S. Shapley*, pp. 71–81. Cambridge University Press, 1977.

Che-Ping Tsai, Chih-Kuan Yeh, and Pradeep Ravikumar. Faith-Shap: The faithful Shapley interaction index. *Journal of Machine Learning Research*, 24, 2023.

Jarne Verhaeghe, Jonas Van Der Donckt, Femke Ongenae, and Sofie Van Hoecke. Powershap: A power-full Shapley feature selection method. In *Proceedings of the European Conference on Machine Learning and Principles and Practice of Knowledge Discovery in Databases (ECML PKDD)*, 2022.

Bing Xue, Mengjie Zhang, Will N. Browne, and Xin Yao. A survey on evolutionary computation approaches to feature selection. *IEEE Transactions on Evolutionary Computation*, 20(4):606–626, 2016.

Chi Zhao, Jiapeng Liu, and Elena Parilina. ShapG: New feature importance method based on the Shapley value. *Engineering Applications of Artificial Intelligence*, 148, 2025.

Chen Zheng and Garvesh Raskutti. MinShap: A modified Shapley value approach for feature selection. *arXiv preprint arXiv:2604.15107*, 2026. Cited as conceptual inspiration; our theoretical development and algorithmic design are independent.

A PROOFS

Proof of Property 1. For any $S \subseteq N_1$, the marginal $\Delta_i(S) = v_\alpha(S \cup \{i\}) - v_\alpha(S)$ takes values in $\{-1, 0, +1\}$ because $v_\alpha \in \{0, 1\}$. Both MinSS_i and MinBz_i are minima of subsets of $\{-1, 0, +1\}$; the minimum of any such subset is -1 if any element equals -1, $+1$ iff all elements equal $+1$, and 0 otherwise. Hence it remains in $\{-1, 0, +1\}$. □

Proof of Property 2. **(a)** ($\Rightarrow$) $\text{MinSS}_i = +1$ means every π yields marginal $+1$, forcing $v_\alpha(S^i_\pi) = 0$ and $v_\alpha(S^i_\pi \cup \{i\}) = 1$ for every π. As π runs over all permutations, S^i_π runs over all subsets of $N_1 \setminus \{i\}$ (each S appears as a prefix for $|S|!\,(n - |S| - 1)!$ permutations). Hence $\forall S \subseteq N_1 \setminus \{i\}$: $v_\alpha(S) = 0 \wedge v_\alpha(S \cup \{i\}) = 1$. ($\Leftarrow$) If the condition holds, every marginal is $1 - 0 = +1$, so $\min = +1$.

(b) $\text{MinSS}_i = -1$ iff there exists a permutation with -1 marginal, i.e., $v_\alpha(S^i_\pi) = 1$ and $v_\alpha(S^i_\pi \cup \{i\}) = 0$. Letting $S = S^i_\pi$ gives the witness. Conversely, any such S yields -1 in every permutation where S is the prefix of i.

(c) By Property 1, if MinSS_i is neither $+1$ nor -1, it must be 0. □

Proof of Property 3. $\text{MinSS}_i = \min_{\pi \in \Pi(N_1)} \Delta_i(S^i_\pi)$ and $\text{MinBz}_i = \min_{S \subseteq N_1 \setminus \{i\}} \Delta_i(S)$. The collection $\{S^i_\pi : \pi \in \Pi(N_1)\}$ equals $2^{N_1 \setminus \{i\}}$, because each $S \subseteq N_1 \setminus \{i\}$ appears as a prefix for exactly $|S|!\,(n - |S| - 1)!$ permutations. Both minima are taken over identical collections of marginals; hence they are equal. □

Proof of Lemma 1. Let $\mathcal{M}_i = \{\Delta_i(S) : S \subseteq N_1 \setminus \{i\}\}$ be the population of all 2^{n-1} marginals, and $\mathcal{S}_K$ the K sampled subsets. The estimate $\widehat{\text{MinPPI}}^{\text{MC}}_i = \min_{S \in \mathcal{S}_K} \Delta_i(S)$ satisfies $\min \mathcal{S}_K \geq \min \mathcal{M}_i$ deterministically because $\mathcal{S}_K \subseteq \mathcal{M}_i$. Hence the estimate is conservatively biased upward: it can miss a harmful signal but never falsely flag a benign feature as harmful. □

Proof of Proposition 1. Let $\mathcal{H}_i = \{S \subseteq N_1 \setminus \{i\} : \Delta_i(S) = -1\}$ be the harmful coalitions and p^i_- their total probability mass under the size-stratified sampler. Algorithm A fails iff none of the K i.i.d. draws lands in $\mathcal{H}_i$; independence gives $\Pr[\text{miss}] = (1 - p^i_-)^K$. Setting this $\leq \delta$ and solving yields the bound. □

Proof of Theorem 1. For each $i \in \mathcal{H}$, Proposition 1 gives $\Pr[\text{miss } i] = (1 - p^i_-)^K \leq (1 - p_{\min})^K$. By the union bound, $\Pr[\text{any miss}] \leq |\mathcal{H}| \cdot (1 - p_{\min})^K$. Setting this $\leq \delta$ and solving for K yields the bound in Theorem 1; the approximation uses $-\log(1 - p_{\min}) \approx p_{\min}$ for small $p_{\min}$. □

Proof of Theorem 2. By the structural condition of Theorem 2, $S_i^* \subseteq S_{\text{seed}}$. A single perturbation reproduces exactly S_i^* when every $j \in S_i^*$ is retained (probability $\prod_{j \in S_i^*} q_j$) and every $j \in S_{\text{seed}} \setminus S_i^*$ is dropped (probability $\prod_{j \in S_{\text{seed}} \setminus S_i^*} (1 - q_j)$); these events are independent, so $\Pr[S = S_i^*] = \rho_i$. When $S = S_i^*$ the marginal is $v_\alpha(S_i^* \cup \{i\}) - v_\alpha(S_i^*) = -1$ and i is detected. Over K_{adv} independent perturbations, the probability of at least one hit is $1 - (1 - \rho_i)^{K_{\text{adv}}}$. If $S_{\text{seed}} = S_i^*$, the seed evaluated before any perturbation is already the witness, giving deterministic detection at $K_{\text{adv}} = 1$. □

B Datasets and Protocol

Table 4: Dataset summary. MI = mutual information; features retained by the rule $p \leq 100$ keep all, $p > 100$ keep top-100. Task: C = binary/multi-class, R = regression.

Dataset	Native dim.	After MI	Samples	Task	Utility
Spambase	57	56	4,601	C	AUC
Madelon	500	100	2,600	C	AUC
ISOLET	617	100	7,797	C (26)	Accuracy
Gisette	5,000	100	7,000	C	AUC
Credit-Card-Fraud	29	29	284,807	C	AUC
Crimedata	128	100	1,994	R	R^2
Abalone	8	8	4,177	R	R^2

Protocol. All data are standardized (zero mean, unit variance). Train/val/test splits are 60/20/20, stratified for classification. Base learner is XGBoost (100 estimators, max_depth=4, learning_rate=0.1 for evaluation). MinPPI estimation: Algorithm B (ShapG-guided, $K_{\text{adv}} = 30$) for binary datasets, shared-coalition Algorithm A ($K = 200$, 5 per coalition for Spambase/Madelon/Credit-Card; $K = 30$–50, 2 per coalition for ISOLET/Gisette/Crimedata/Abalone) for multi-class and regression. MinPPI quota $\alpha = 0.95$ as default, with $\{0.85, 0.90, 0.99\}$ for α-Pareto sweep. Five seeds: 42, 123, 456, 789, 1024.

C Regression Extension

MinPPI extends naturally to regression by replacing the utility function U with R^2. Regression datasets (Crimedata, Abalone) show the same safety pattern as classification: near-zero harmful features at α=0.95, preservation ≥ 0.99 at all α levels (Table 1).

D MinShap Comparison and Madelon Ground Truth

Table 5: Madelon ground-truth probe recovery (100 features, 97 probes, 5 seeds).

Method	Precision	Recall	$\mathbf{F}_1$	# flagged
MinPPI (α=0.95)	0.978 ± 0.031	0.227 ± 0.167	0.349 ± 0.189	22.8
MinShap	0.964 ± 0.007	0.670 ± 0.030	0.790 ± 0.019	67.4
SHAP	0.971 ± 0.031	0.179 ± 0.152	0.285 ± 0.185	18.6

Table 6: MinShap vs. MinPPI harmful-set agreement (Jaccard index, means over 5 seeds).

Dataset	**MinPPI** -1	**MinShap** < 0	**Jaccard**
Spambase	1.0	18.6	0.02
Madelon	22.8	67.4	0.22
ISOLET	8.0	47.2	0.08

The low Jaccard (0.02–0.22) confirms that binary v_α and continuous $v(S)$ identify fundamentally different feature sets as harmful. MinShap flags 3–19$\times$ more features as negative; at matched budget, its most-negative features perform comparably to MinPPI's harmful set (Table 3). The key distinction is that MinPPI provides a principled decision boundary (harmful iff a harmful-witness coalition exists; Property 2b), whereas MinShap's continuous scores require an arbitrary user-chosen cutoff.

Table 7: Per-α MinPPI precision, recall, F_1 against Madelon probes (mean $\pm$ std over 5 seeds).

α	**Precision**	**Recall**	$\mathbf{F_1}$	**# flagged**
0.85	0.77 ± 0.43	0.09 ± 0.14	0.14 ± 0.20	9.4
0.90	0.98 ± 0.04	0.15 ± 0.19	0.24 ± 0.24	15.2
0.95	0.98 ± 0.03	0.23 ± 0.17	0.35 ± 0.19	22.8
0.99	0.96 ± 0.03	0.37 ± 0.11	0.52 ± 0.12	37.0
MinShap	0.96 ± 0.01	0.67 ± 0.03	0.79 ± 0.02	67.4
SHAP	0.97 ± 0.03	0.18 ± 0.15	0.28 ± 0.18	18.6

E Statistical Tests

E.1 Nemenyi Pairwise Significance Matrices

Table 8: Friedman test summary for six methods on five classification datasets. All pairs non-significant at $\alpha = 0.05$ (Nemenyi CD ≈ 3.4 ranks for $k = 6, N = 5$).

Metric	χ^2	p	Kendall's W	CD	#Methods
AUC@10	13.80	0.017	0.55	3.37	6
AUC@20	11.63	0.040	0.47	3.37	6

Both Friedman tests are significant, confirming that method differences on AUC rankings are not due to chance. The large Nemenyi CD (≈ 3.4 ranks) means pairwise post-hoc separation is difficult with $N = 5$, a known limitation of the Demsar procedure at small N. AUC@20 shows the same ranking pattern (SHAP-k 2.0, PShap 1.8, NSGA2 3.8, ShapG 4.2, Banzhaf 4.6, MinShap 4.6; χ^2=11.63, p=0.040, Kendall's W=0.47).

F Method Design-Space

Table 9 classifies prior work and our contribution along two axes: the aggregation operator (mean vs. min) and the value-function type (binary vs. continuous). MinPPI occupies the unoccupied cell—min operator $\times$ binary—yielding the discrete $\{-1, 0, +1\}$ output that enables the three-way classification of Section 4.2.

Table 9: Game-theoretic feature importance methods by aggregation operator and value function.

Index	**Aggregation**	$v(S)$ **type**	**Output range**
Shapley-Shubik	mean	binary $\{0,1\}$	$\subseteq [0,1]$
Banzhaf	mean	binary $\{0,1\}$	$\subseteq [0,1]$
Shapley / SHAP	mean	continuous	$\subseteq [-1,1]$
MinShap	min	continuous	$\subseteq [-1,1]$
MinPPI (this work)	**min**	**binary** $\{0,1\}$	$\{\mathbf{-1}, \mathbf{0}, \mathbf{+1}\}$

G Empirical Verification of the Estimators

This appendix collects the constructed toy-game experiments that numerically verify the formal claims of Sections 4.2–4.3. All examples use $n = 5$ features and $v_\alpha \in \{0,1\}$ as defined in equation 3.

G.1 MinPPI Trichotomy (Properties 1–3)

Figure 2(a) and Table 10 exercise all three MinSS values on two constructed games. Example 1 ($v_\alpha(S) = \mathbb{1}[0 \in S]$) has f_0 decisive ($+1$). Example 2 (13 winning coalitions) has f_1 harmful (-1) via $S = \{f_0, f_2\}$ where $v_\alpha(\{f_0, f_2\}) = 1$ but $v_\alpha(\{f_0, f_1, f_2\}) = 0$; f_0 appears in every winning coalition yet $\text{MinSS}(f_0) = 0$, demonstrating the non-trivial separation of Property 2a.

Table 10: MinSS and mean Shapley-Shubik values corresponding to the tri-chotomy in Figure 2(a).

Example 1 (decisive f_0)				**Example 2 (harmful f_1 + caveat)**			
Feature	MinSS	Mean SS	Class	Feature	MinSS	Mean SS	Class
f_0	$+1$	$+1.0000$	DECISIVE	f_0	0	$+0.7167$	neutral
f_1	0	0.0000	neutral	f_1	-1	-0.0333	HARMFUL
f_2–f_4	0	0.0000	neutral	f_2–f_4	0	$+0.05$–0.13	neutral

G.2 Algorithm A vs. Algorithm B

Figure 2(b) validates Proposition 1 on Example 2 ($p^i_- = 0.0333$): the observed miss rate matches $(1 - p_-)^K$ (Pearson $r = 0.9993$, 500 trials per K). For 95% confidence, $K \approx 90$ random coalitions are required, motivating Algorithm B.

Table 11: Quantitative comparison of Algorithm A and Algorithm B on Example 2 (500 trials per setting).

(a) Detection of MinSS $= -1$

K	A detect	B detect	A $\bar{s}$	B $\bar{s}$
1	0.026	1.000	1.00	1.00
2	0.060	1.000	1.98	1.00
3	0.124	1.000	2.87	1.00
5	0.146	1.000	4.69	1.00
10	0.322	1.000	8.43	1.00
20	0.466	1.000	14.91	1.00
50	0.850	1.000	23.77	1.00

(b) Sensitivity to $\mathcal{N}(0, \sigma^2)$ **on** W **(**K=5**)**

σ	B detect	A detect
0.05	1.000	0.172
0.15	0.878	0.170
0.30	0.652	0.142
0.50	0.508	0.148