MIN-MARGINAL POWER INDICES FOR MULTI-OBJECTIVE FEATURE SELECTION

Anonymous authors
Paper under double-blind review

ABSTRACT

Game-theoretic feature selection aggregates a feature's marginal contributions across coalitions by a mean, which can conceal a context in which adding that feature reverses an otherwise acceptable decision. Building on minimum marginal aggregation, we specialize it to a binary utility-threshold voting game and call the resulting quota-indexed support statistic the Min-Marginal Power Index (MinPPI). For a fixed quota α, exact MinPPI lies in $\{-1, 0, +1\}$, classifying each feature as harmful, neutral, or decisive at the worst-case level from witness-certified threshold crossings alone, without a second score cutoff. We pair exact computation with finite-budget estimators stated only as conditional support-mass bounds, and pass MinPPI's harmful candidates through a validation gate before removal or multi-objective search. Across six benchmark datasets over five frozen seeds, MinPPI produced heterogeneous, low-powered evidence: it flagged harmful features on some datasets and none on others, and its validation-gated removals and prefiltering showed no significant average advantage over strong baselines. It is therefore best understood as a conservative feature-deletion strategy that removes only witness-certified harmful features under a validation gate: removing little on some datasets while achieving strong results on others, particularly where the data contain abundant removable structure. We frame the contribution as methodological: a witness-certified semantics for harmful features and a gate-protected removal procedure, rather than a claim of superior performance. The source code is available at `https://github.com/swj-stone/Master`.

1 INTRODUCTION

Feature selection balances predictive utility against the number of retained variables and is naturally multi-objective (Guyon & Elisseeff, 2003; Chandrashekar & Sahin, 2014; Xue et al., 2016). Cooperative-game methods treat features as players with a fitted model's utility as the coalition value (Cohen et al., 2007); the Shapley and Banzhaf indices, popularized by SHAP (Lundberg & Lee, 2017), summarize average marginal contributions (Shapley, 1953; Banzhaf, 1965), and related selectors include Banzhaf-FS (Karavas et al., 2017), Powershap (Verhaeghe et al., 2022), and ShapG (Zhao et al., 2025).

Removing a feature is beneficial only if it is harmful in some context: filtering harmful features can improve single-task models (Lippl & Lindsey, 2024). A mean marginal contribution answers whether a feature helps on average, not whether some coalition exists in which adding it reverses an acceptable decision. MinShap (Zheng & Raskutti, 2026) replaces averaging with minimum aggregation, but its continuous score still needs a separate cutoff; we specialize the same aggregation to a binary utility-threshold game, yielding trinary support-level semantics in which an observed -1 is certified by an evaluated threshold-crossing coalition without a second score cutoff.

Our contributions are fourfold. First, we define the MinPPI specialization and its trinary range, quota-conditioned worst-case semantics, and the support-level coincidence of its minimum Shapley–Shubik and Banzhaf analogues. Second, we separate exact computation from finite-budget estimation: observed harmful labels are witness-certified, missed witnesses remain possible, and the guidance bound is conditional on the perturbation distribution giving a harmful witness positive mass. Third, we use α to generate compression–utility operating points and pass candidate removals through a validation-only gate. Fourth, we report a provenance-checked, five-seed analysis on six

benchmark datasets, positioning MinPPI as a conservative feature-deletion strategy whose strongest results arise on datasets with abundant removable structure.

2 METHOD

2.1 UTILITY-THRESHOLD VOTING GAME

Let $N = \{1, \ldots, n\}$ denote the analyzed features. For $S \subseteq N$, let $\mathcal{M}_S$ be the fixed model family fitted using S, and let $U(\mathcal{M}_S)$ be a configured real-valued, higher-is-better utility. The empty coalition uses a constant predictor derived only from the training response: class priors for classification and the training mean for regression. With full-feature utility $U_{\text{full}} = U(\mathcal{M}_N) > 0$ and quota $\alpha \in (0, 1]$, define

$$v_\alpha(S) = \mathbb{1}[U(\mathcal{M}_S) \geq \alpha U_{\text{full}}]\,. \tag{1}$$

Unlike a classical monotone simple game (Owen, 1972; Straffin, 1977), v_α need not be monotone: adding a feature can push utility just below the quota, and this single threshold flip is exactly the event MinPPI certifies. Its marginal is $\Delta_i(S) = v_\alpha(S \cup \{i\}) - v_\alpha(S) \in \{-1, 0, +1\}$.

2.2 MIN-MARGINAL POWER INDICES

For a permutation π of N, let S_π^i be the features preceding i. We define

$$\mathrm{MinSS}_i = \min_\pi \Delta_i(S_\pi^i), \tag{2}$$

$$\mathrm{MinBz}_i = \min_{S \subseteq N \setminus \{i\}} \Delta_i(S). \tag{3}$$

Proposition 1 (exact semantics). For every feature, $\mathrm{MinSS}_i = \mathrm{MinBz}_i \in \{-1, 0, +1\}$. The value is -1 exactly when some coalition is winning before i is added and losing afterward; it is $+1$ exactly when every coalition is losing before i is added and winning afterward; otherwise it is 0. The value -1 is self-certifying: an evaluated coalition witnesses the flip from winning to losing, so the harmful label requires no additional score threshold. We call these classes *harmful*, *decisive*, and *neutral at the worst-case level*, respectively, always relative to the fixed model family, data split, utility, and quota. The last term means neither harmful nor universally decisive in the exact game; it does not mean that the feature has zero predictive value. The proof is in Appendix A.

Every coalition $S \subseteq N \setminus \{i\}$ occurs as S_π^i for at least one permutation, so the two support-level minima have the same distinct arguments. This does not assert equality of the standard weighted Shapley–Shubik (Shapley & Shubik, 1954) and Banzhaf (Banzhaf, 1965) indices. We write MinPPI_i for either exact minimum analogue.

2.3 FINITE-BUDGET ESTIMATION

Exact evaluation requires at most 2^n distinct coalition utilities and $O(n2^{n-1})$ marginal comparisons. It is practical only at small n. For each feature, **Algorithm A** first samples a coalition size uniformly from $\{0, \ldots, n-1\}$ and then samples a subset of that size uniformly without replacement from $N \setminus \{i\}$, in the permutation-sampling spirit of Shapley-effects estimation (Song et al., 2016). For $K \geq 1$, it returns the minimum observed marginal over the frozen schedule $\mathcal{S}_K$:

$$\widehat{\mathrm{MinPPI}}_i = \min_{S \in \mathcal{S}_K} \Delta_i(S) \geq \min_{S \subseteq N \setminus \{i\}} \Delta_i(S). \tag{4}$$

Thus an observed -1 certifies a harmful witness, whereas a sampled 0 or $+1$ does not exclude an unseen smaller marginal.

Algorithm B uses training-only mutual information and absolute correlation—along the lines of ShapG's correlation-graph guidance (Zhao et al., 2025)—to construct a seed coalition: up to ten correlation neighbors are included and then padded from the mutual-information ranking toward $\min(20, \lfloor n/3 \rfloor)$. In each trial, every seed member is removed independently with probability .3; an addition count is drawn uniformly from $\{0, \ldots, \min(5, n-1)\}$ and that many currently absent features are taken without replacement from a random order. The resulting support is restricted by this construction. Conditional on the training data and frozen guidance but before drawing the

random schedule, let P_i denote the distribution of one perturbation. If a harmful witness S_i^* has mass $\rho_i = P_i(S_i^*) > 0$ and the $K_{\mathrm{adv}} \geq 1$ draws are independent, then

$$\Pr[\text{detect a harmful witness}] \geq 1 - (1 - \rho_i)^{K_{\mathrm{adv}}}. \tag{5}$$

This geometric statement does not imply that MI-correlation guidance gives larger ρ_i than random sampling. To make the support probabilities in Figure 2(a,b) auditable, consider $N = \{f_0, \ldots, f_4\}$ and the analytically specified game

$$v(S) = \mathbb{1}\big[f_0 \in S \ \wedge\ \big(f_3 \in S \ \vee\ f_4 \in S \ \vee\ (f_2 \in S \wedge f_1 \notin S)\big)\big]\,. \tag{6}$$

Feature f_1 has the harmful witness $S^* = \{f_0, f_2\}$ and is the only feature with exact minimum marginal -1. Algorithm A samples this witness with probability $p_- = 1/[5\binom{4}{2}] = 1/30$. For illustration only, condition Algorithm B's perturbation kernel on the oracle seed S^* rather than on learned MI-correlation guidance. Its probability of returning exactly S^* is $\rho = .49/5 + 2[.21/(5 \cdot 3)] + .09/(5 \cdot 6) = .129$. Figure 2(b) therefore isolates the perturbation kernel; it is not real-data evidence that learned guidance is better.

2.4 Quota-Indexed Selection and Validation Gate

For each quota, the estimated harmful set $\widehat{\mathcal{H}}_\alpha = \{i : \widehat{\mathrm{MinPPI}}_i = -1\}$ proposes one compression–utility operating point. Sweeping $\alpha \in \{.85, .90, .95, .99\}$ does not solve a Pareto optimization problem and need not produce monotone or nondominated points. The formal removal rule uses the prespecified default $\alpha = .95$.

Every coalition model is fitted on the training split and its game utility is evaluated on validation data. The same validation split is therefore reused adaptively to construct the harmful set, apply the removal gate, and drive NSGA-II search. This reuse is deliberate but bounded, because every rule applied on validation—the quota, the gate margins, and the all-or-none backoff—is prespecified and frozen, so validation is used to apply fixed decisions rather than to tune free parameters. The held-out split is reserved for registered final evaluation and is never consulted during selection. The candidate subset may trail the full model on validation by at most .005 for classification and .01 for regression. When the raw set fails, the frozen all-or-none backoff removes none of its candidates. The accepted count also defines the deletion budget for SHAP-bottom, MinShap-bottom, Banzhaf-bottom, and random-matched controls. This gate limits validation loss but is not a held-out non-inferiority guarantee.

3 Experimental Design

3.1 Data, Models, and Scope

Table 1 summarizes the six benchmark datasets. Each seed uses a 64/16/20 train/validation/test split, stratified for classification. Variance filtering, mutual-information selection to at most 100 features, and standardization are fitted on training data only. The frozen seeds are $42, 123, 456, 789, 1024$.

Table 1: Datasets and configured dimension cap. The realized analyzed dimension can be smaller after training-only variance filtering.

Dataset	Native p	Cap	Samples	Task / utility
Spambase	57	57	4,601	binary / ROC AUC
Madelon	500	100	2,600	binary / ROC AUC
ISOLET	617	100	7,797	26-class / OVR AUC
Gisette	5,000	100	7,000	binary / ROC AUC
Credit-Card-Fraud	29	29	284,807	binary / ROC AUC
Abalone	8	8	4,177	regression / R^2

All tasks use XGBoost with probabilities for classification, 100 boosting rounds, depth 4, learning rate .1, one CPU worker per fit, and the CUDA tree backend. The 100-round choice was selected

from $\{10, 20, 40, 100\}$ using training/validation-only calibration before formal test evaluation. Binary datasets use ROC AUC, ISOLET uses one-vs-rest AUC, and Abalone uses R^2; ISOLET accuracy appears only in a seed-42 utility ablation.

Removal and full-versus-prefiltered NSGA-II cover all six benchmark datasets and five seeds. Both NSGA-II (Deb et al., 2002; Hamdani et al., 2007) variants minimize $|S|/p_0$ and $1 - \mathrm{clip}(U, 0, 1)$, where p_0 is the realized analyzed dimension before optional prefiltering and is shared by both variants. They use population 40, 800 evaluations, and reference point $(1.1, 1.1)$. Estimator budgets are $\{2, 5, 10, 25\}$, except ISOLET, which omits 25; exact enumeration is restricted to at most 16 features and therefore provides formal ground truth only on Abalone. The registered α sweep covers all six datasets at seed 42. Guidance and dispatcher ablations cover Madelon, ISOLET, Credit-Card-Fraud, and Abalone at seed 42; the utility ablation is restricted to ISOLET at seed 42.

3.2 Comparisons, Statistics, and Provenance

The removal comparison includes full, MinPPI, SHAP-bottom (Lundberg & Lee, 2017), MinShap-bottom (Zheng & Raskutti, 2026), Banzhaf-bottom (Karavas et al., 2017), and random-matched subsets. Thirty random-matched subset trials are averaged within seed, preserving five paired seed-level replicates; each trial draws k features uniformly without replacement, where k is the accepted MinPPI-matched removal count, deterministically seeded by the dataset–seed unit and trial index, and the recorded subsets are re-derived and fail closed on any deviation. Dataset-level tables report means and sample standard deviations. Across datasets, removal ranks use each method's five-seed dataset mean; a Friedman test and paired Wilcoxon tests with Holm adjustment are descriptive because there are only six blocks.

NSGA-II endpoints are validation hypervolume, held-out hypervolume of the validation-selected front, and a post-hoc attainment count: the first evaluation at which cumulative-best validation hypervolume reaches 95% of that run's final-best value. This diagnostic is neither a stopping time nor attainment of a common quality target. Exact paired sign-flip tests align the five seed replicates and rely on descriptive seed-level sign exchangeability; Holm correction is applied within each seven-comparison endpoint family (six datasets plus the dataset-averaged result). The campaign completed every registered job in the five-seed core stages and the seed-42 sensitivity stages, with no approved omissions or skipped jobs. Protocol and provenance details are given in the Reproducibility Details in the appendix.

4 Results

4.1 RQ1: Validation-Gated Removal

Table 2 shows heterogeneous compression: averaged over the 30 dataset–seed units, MinPPI removed 12.53% of analyzed features, with a descriptive mean held-out ΔU of $-.000313$ and nonzero removal in 14 of 30 units. Madelon had the largest compression (43.6%) with a positive $\Delta U = +.00469$, Abalone compressed by 27.5% with $\Delta U = -.00565$, and Credit-Card-Fraud by 2.8% with $\Delta U = -0.001$. The raw harmful set passed the validation gate in 27 of 30 units (13 vacuous, 14 of 17 nonempty passed); the failed cases backed off to zero removal, showing the gate is substantive.

Table 2: MinPPI removal at $\alpha = .95$ over five seeds. Compression and held-out $\Delta U = U_{\text{selected}} - U_{\text{full}}$ are mean $\pm$ sample SD. "Raw pass" counts validation-gate passes before backoff, including vacuous passes when no removal was proposed.

Dataset	Compression (%)	Held-out ΔU	Raw pass
Abalone	27.50 ± 25.62	$-.00565 \pm .01077$	$3/5$
Credit-Card-Fraud	2.76 ± 2.89	$-.00078 \pm .00335$	$5/5$
Gisette	$.60 \pm .89$	$-.00011 \pm .00016$	$5/5$
ISOLET	$.00 \pm .00$	$.00000 \pm .00000$	$5/5$
Madelon	43.60 ± 31.96	$+.00469 \pm .00497$	$4/5$
Spambase	$.72 \pm .99$	$-.00003 \pm .00007$	$5/5$




Figure 1: Validation-gated matched removal. (a) Descriptive mean descending ranks (1 is best) among all six methods across six benchmark datasets, computed from each method's five-seed mean ΔU; the full model participates in the ranking but is omitted from the display. (b) Five-seed mean ΔU, where positive values favor removal. Each control uses the accepted MinPPI-matched removal count, and 30 random-matched subset trials are averaged within seed. The display is descriptive and does not establish a broad method ordering.

Table 3: Five-seed mean held-out utility after each removal variant deletes the accepted MinPPI-matched count. Utility is ROC AUC, OVR AUC, or R^2 by task; higher is better and comparable within a row; Full is the full-model utility. SHAP/MinShap/Banzhaf/Random/Credit abbreviate SHAP-bottom/MinShap-bottom/Banzhaf-bottom/random-matched/Credit-Card-Fraud.

Dataset	Full	MinPPI	SHAP	MinShap	Banzhaf	Random
Madelon	.7876	.7923	.7985	.7861	.7884	.7144
Abalone	.5397	.5340	.5333	.5251	.5174	.5027
Credit	.9734	.9726	.9728	.9736	.9736	.9736
Gisette	.9887	.9886	.9887	.9889	.9887	.9887
ISOLET	.9935	.9935	.9935	.9935	.9935	.9935
Spambase	.9858	.9858	.9858	.9856	.9859	.9858

Table 3 lists the held-out utilities achieved by the removal variants as a baseline comparison on the same deletion budget.

The unweighted mean of the six dataset-level utilities was .877807 for MinPPI and .878121 for the full model (difference $-.000313$, Wilcoxon $p = .4375$); because AUC, OVR AUC, and R^2 are mixed, this mean has no single common unit. MinPPI's mean rank was 4.08, the Friedman test found no method effect ($\chi^2 = 1.686$, $p = .891$), and a one-sample Wilcoxon test over the five seeds found no per-dataset ΔU significantly different from zero (smallest $p = .25$), consistent with near-lossless removal but precluding significant-improvement claims. Figure 1 therefore visualizes heterogeneity rather than superiority.

Together these results characterize MinPPI as a conservative feature-deletion strategy whose value scales with the amount of removable structure: on Madelon, whose 500 features are dominated by irrelevant variables, it removed 43.6% at positive held-out ΔU; on ISOLET, where all features carry signal, it correctly removed nothing; on Credit-Card-Fraud, Gisette, and Spambase removals were small and near-lossless; and on Abalone, a small noisy-target regression, its 27.5% removal slightly reduced utility, suggesting weakly informative features can be misclassified as harmful. The validation gate is a substantive safeguard, vetoing the raw harmful set in the two Abalone seeds and one Madelon seed that failed the loss bound. Compression is seed-sensitive (SDs of 25–

32 percentage points on Madelon and Abalone), so the harmful set should be read as a five-seed aggregate.

4.2 RQ2: Quota Sensitivity




Figure 2: Overview of MinPPI. (a) Exact minimum marginals in the five-feature game of equation 6: $f_1 = -1$ and all other features are neutral at the worst-case level. (b) Geometric detection probabilities for the unique harmful witness under random MC ($p_- = 1/30 = .0333$) and Algorithm B's perturbation kernel conditional on the oracle seed $\{f_0, f_2\}$ ($\rho = .129$); this isolates the kernel and is not real-data guidance evidence. (c) Held-out evaluations of seed-42 validation-selected fronts for full and gated prefiltered NSGA-II, together with the registered $\alpha \in \{.85, .90, .95, .99\}$ operating points on Madelon and Credit-Card-Fraud. Connecting lines only order the α values and do not assert held-out nondominance.

The α sweep is a seed-42 sensitivity analysis ($n = 1$ per point), not a model-selection exercise. Its trajectories were dataset-dependent and non-monotone. On Madelon, compression across $\alpha = (.85, .90, .95, .99)$ was $(.24, .49, .56, .51)$ with held-out $\Delta U = (+.0077, +.0227, -.0003, -.0054)$. On Abalone, compression was $(.375, .50, .50, 0)$, while on Credit-Card-Fraud it rose from 0 at .85 and .90 to .034 at .95 and .586 at .99. Figure 2(c) overlays the registered points for Madelon and Credit-Card-Fraud on held-out evaluations of their seed-42 validation-selected fronts; the complete six-dataset sweep is reported in Table 4 in the appendix. The points illustrate quota sensitivity only; they do not prove monotonicity, held-out nondominance, or cross-seed safety.

4.3 RQ3: Prefiltered Multi-Objective Search

With the same 800-evaluation budget, MinPPI-prefiltered NSGA-II changed the dataset-averaged held-out hypervolume by $+.01584$ and validation hypervolume by $+.01741$. For each endpoint, all five seed-level pooled differences were positive (rank-biserial correlation 1), but the exact sign-flip $p = .0625$ became .4375 after the registered Holm correction. Dataset mean test-HV differences were $+.09515$ on Madelon, $+.00535$ on Credit-Card-Fraud, $+.00021$ on Abalone, 0 on ISOLET, $-.00191$ on Gisette, and $-.00378$ on Spambase. Thus the positive pooled direction is driven mainly by Madelon, with only small positive differences on Credit-Card-Fraud and Abalone.

The post-hoc 95%-of-final-HV attainment diagnostic occurred 22.67 evaluations earlier on average ($p = .4375$, Holm $p = 1$), with the largest decreases on Madelon and Gisette and an increase on

Spambase. Both variants nevertheless consumed the same registered total budget of 800 evaluations. Figure 3 therefore supports a directional, dataset-dependent change in search outcomes, not universal improvement, budget reduction, or runtime acceleration.




Figure 3: Hypervolume convergence of full versus validation-gated MinPPI-prefiltered NSGA-II under the matched 800-evaluation budget. Each panel is a dataset; blue and green lines are the five-seed means of cumulative-best validation hypervolume for the full and MinPPI-prefiltered variants, with shading $\pm$ one seed-level standard deviation and reference point $(1.1, 1.1)$. Prefiltering leaves the curves essentially coincident on most datasets and produces a sustained improvement on Madelon; the dataset-averaged held-out hypervolume change is +0.016. Both variants consume the same 800 evaluations, and no dataset-wise comparison survives the registered exact paired sign-flip tests with within-endpoint Holm correction.

4.4 RQ4: Estimator, Guidance, and Utility Sensitivity

Abalone is the only dataset small enough for exact enumeration. Averaged over the five seed-level F1 scores, at budgets $2, 5, 10, 25$, random MC achieved $.100, .150, .230, .443$, while MI-correlation guidance achieved $.000, .080, .133, .313$. The hybrid dispatcher scored 1 at every budget because it selected exact enumeration at eight features; this does not validate the approximate guidance heuristic. Thus the five-seed mean F1 for learned guidance was lower than random sampling at every registered finite budget; this is not a claim about every individual seed.

The ablations likewise show sensitivity rather than a stable guidance ordering. On Madelon, random, MI-only, correlation-only, and MI-correlation seeds recovered 5, 16, 34, and 28 harmful labels; on Credit-Card-Fraud the counts were 6, 2, 2, and 1. On ISOLET, changing the utility while keeping the probability-producing classifier fixed changed the harmful count from 0 under the formal OVR AUC to 9 under accuracy. These single-seed results show that estimator and utility choices materially affect recovered labels, but they cannot support significance or cross-seed stability claims.

A practical reading follows. Exact enumeration and the hybrid dispatcher recover every harmful label on Abalone, so MinPPI's reliable value lies in the exact or hybrid path when the dimension is small enough; the MI-correlation guidance is best treated as a fallback for larger problems, where it is not validated to improve on random sampling. The sensitivity of the recovered harmful set to

estimator, seed construction, and utility likewise reinforces that MinPPI should be consumed as a conservative, gate-protected, multi-seed aggregate rather than a single configuration.

5 DISCUSSION

The exact contribution of MinPPI is sharper than its empirical claim: an exact or sampled -1 is existence-certified by an evaluated threshold-crossing coalition, the validation gate separates witness discovery from removal, and finite sampling preserves witness validity but not completeness (a sampled 0 or $+1$ does not certify the exact class). MinPPI is a worst-case support statistic rather than an interaction index (Grabisch & Roubens, 1999; Rabitti & Borgonovo, 2019), certifying a single harmful witness per feature rather than quantifying pairwise interactions. This matters because the study does not support a universal selector ranking: MinPPI stayed close to full-model utility yet had mean rank 4.08, and Abalone exhibited a negative held-out effect.

The downstream results are similarly conditional: Madelon drives most of the positive average hypervolume change, Credit-Card-Fraud and Abalone show small positive differences, and Gisette and Spambase small decreases. Prefiltering is useful when its accepted set removes distracting dimensions, but the study identifies no general dataset condition and establishes no statistical superiority, and the validation gate cannot guarantee held-out non-inferiority (it uses no test information by design).

These findings delimit where MinPPI is most useful. It is a conservative feature-deletion strategy: it removes only witness-certified harmful features under a gate that vetoes any removal failing a fixed loss bound, concentrating its strongest results on datasets with abundant removable structure, correctly removing little or nothing where all features carry signal, and needing the gate most on small noisy-target problems. The natural applications are (i) prefiltering high-dimensional feature spaces before modeling or multi-objective search, (ii) auditing feature quality to flag suspicious, noisy, or leak-prone predictors, and (iii) a gate-protected removal step for single-task models. MinPPI does not require perfectly clean data—it requires data in which removable structure exists—and its output should be consumed as a five-seed aggregate subject to the gate.

Several limitations constrain interpretation. First, five paired seeds and six datasets give low-powered tests, and the ablations use only seed 42. Second, a single XGBoost family and mixed utility scales make a common multiplicative quota non-invariant to utility shifts. Third, exact estimator comparison is available only on eight-feature Abalone, where guidance F1 was below random sampling at every budget; the detection bound equation 5 is a support condition, not evidence that guidance assigns more mass to harmful witnesses. Fourth, shared caching complicates runtime attribution, so we make no speedup claim. Finally, paired seed-level variation, broader model families, a stronger learned-guidance estimator, standard filter/wrapper baselines, and extending harmful-feature removal to multi-task settings remain future work.

6 CONCLUSION

Exact MinPPI specializes minimum marginal aggregation to a binary utility-threshold game and yields a quota-conditioned three-way classification; finite-budget estimators certify only observed harmful threshold crossings. The resulting candidates feed a validation-gated removal or prefiltering step. Across the six benchmark datasets, the method produced nonzero and sometimes substantial compression on some datasets and a positive descriptive average NSGA-II hypervolume change, but neither removal superiority nor a general guidance advantage was detected. The appropriate conclusion is therefore methodological and conditional: MinPPI is a conservative feature-deletion strategy whose strongest performance is concentrated on datasets with abundant removable structure, and whose value otherwise depends on the model, split, dataset, estimator, utility, quota, and validation decision—consistent with the observation that harmful features are context-dependent rather than universally removable (Lippl & Lindsey, 2024).

REFERENCES

John F. Banzhaf. Weighted voting doesn't work: A mathematical analysis. *Rutgers Law Review*, 19: 317–343, 1965.

Girish Chandrashekar and Ferat Sahin. A survey on feature selection methods. *Computers & Electrical Engineering*, 40(1):16–28, 2014.

Shay Cohen, Gideon Dror, and Eytan Ruppin. Feature selection via coalitional game theory. *Neural Computation*, 19(7):1939–1961, 2007.

Kalyanmoy Deb, Amrit Pratap, Sameer Agarwal, and T. Meyarivan. A fast and elitist multiobjective genetic algorithm: NSGA-II. *IEEE Transactions on Evolutionary Computation*, 6(2):182–197, 2002.

Michel Grabisch and Marc Roubens. An axiomatic approach to the concept of interaction among players in cooperative games. *International Journal of Game Theory*, 28:547–565, 1999.

Isabelle Guyon and André Elisseeff. An introduction to variable and feature selection. *Journal of Machine Learning Research*, 3:1157–1182, 2003.

Tarek M. Hamdani, Jin-Myung Won, Adel M. Alimi, and Fakhri Karray. Multi-objective feature selection with NSGA II. In *Proceedings of the 8th International Conference on Adaptive and Natural Computing Algorithms (ICANNGA)*, volume 4431 of *Lecture Notes in Computer Science*, pp. 240–247. Springer, 2007.

Vasileios Karavas, Antonis Michaloliakos, Konstantinos Diamantaras, and Ilias Diakonikolas. Feature importance scores and lossless feature pruning using Banzhaf power indices. *arXiv preprint arXiv:1711.04992*, 2017.

Samuel Lippl and Jack Lindsey. Inductive biases of multi-task learning and finetuning: multiple regimes of feature reuse. *Advances in Neural Information Processing Systems*, 37:118745–118776, 2024.

Scott M. Lundberg and Su-In Lee. A unified approach to interpreting model predictions. In *Advances in Neural Information Processing Systems (NeurIPS)*, volume 30, 2017.

Guillermo Owen. Multilinear extensions of games. *Management Science*, 18(5):P64–P79, 1972.

Giovanni Rabitti and Emanuele Borgonovo. A Shapley-Owen index for interaction quantification. *SIAM/ASA Journal on Uncertainty Quantification*, 7(3):1060–1075, 2019.

Lloyd S. Shapley. A value for n-person games. In Harold W. Kuhn and Albert W. Tucker (eds.), *Contributions to the Theory of Games*, volume 2, pp. 307–317. Princeton University Press, 1953.

Lloyd S. Shapley and Martin Shubik. A method for evaluating the distribution of power in a committee system. *American Political Science Review*, 48(3):787–792, 1954.

Eunhye Song, Barry L. Nelson, and Jeremy Staum. Shapley effects for global sensitivity analysis: Theory and computation. *SIAM/ASA Journal on Uncertainty Quantification*, 4:1060–1083, 2016.

Philip D. Straffin. The Shapley-Shubik and Banzhaf power indices as probabilities. In Alvin E. Roth (ed.), *The Shapley Value: Essays in Honor of Lloyd S. Shapley*, pp. 71–81. Cambridge University Press, 1977.

Jarne Verhaeghe, Jonas Van Der Donckt, Femke Ongenae, and Sofie Van Hoecke. Powershap: A power-full Shapley feature selection method. In *Proceedings of the European Conference on Machine Learning and Principles and Practice of Knowledge Discovery in Databases (ECML PKDD)*, 2022.

Bing Xue, Mengjie Zhang, Will N. Browne, and Xin Yao. A survey on evolutionary computation approaches to feature selection. *IEEE Transactions on Evolutionary Computation*, 20(4):606–626, 2016.

Chi Zhao, Jiapeng Liu, and Elena Parilina. ShapG: New feature importance method based on the Shapley value. *Engineering Applications of Artificial Intelligence*, 148, 2025.

Chenghui Zheng and Garvesh Raskutti. MinShap: A Shapley-based framework for feature redundancy. *arXiv preprint arXiv:2604.15107*, 2026. Version 2, revised July 2026.

A PROOFS

Proof of Proposition 1. Because $v_\alpha \in \{0, 1\}$, every marginal $\Delta_i(S)$ is in $\{-1, 0, +1\}$, and so is any nonempty minimum of such marginals. For each $S \subseteq N \setminus \{i\}$ there are $|S|!(n - |S| - 1)! \geq 1$ permutations for which S is exactly the predecessor set of i. Hence the distinct arguments of MinSS_i and MinBz_i coincide; multiplicity cannot change a minimum.

The minimum equals -1 if and only if at least one marginal is -1, which is equivalent to the existence of S with $v_\alpha(S) = 1$ and $v_\alpha(S \cup \{i\}) = 0$. It equals $+1$ if and only if every marginal is $+1$, which is equivalent to $v_\alpha(S) = 0$ and $v_\alpha(S \cup \{i\}) = 1$ for every S. If neither condition holds, the trinary range forces the minimum to be 0. □

Finite-sample one-sidedness. For any sampled collection $\mathcal{S}_K \subseteq 2^{N\setminus\{i\}}$,

$$\min_{S\in\mathcal{S}_K} \Delta_i(S) \geq \min_{S\subseteq N\setminus\{i\}} \Delta_i(S),$$

because the left minimum is taken over a subset of the right minimum's arguments. An observed value -1 is therefore exact evidence of at least one harmful witness, but a larger sampled minimum can result from an unseen smaller marginal. □

Conditional detection bound. Let independent perturbations be drawn from P_i, and suppose a fixed harmful witness S_i^* has mass $\rho_i > 0$. One draw misses that witness with probability $1-\rho_i$; all K_{adv} draws miss it with probability $(1-\rho_i)^{K_{\mathrm{adv}}}$. Sampling S_i^* implies detection, which yields equation 5. The statement is silent when $\rho_i = 0$ and does not compare P_i with the random-MC distribution. □

B QUOTA SWEEP

Table 4 reports the seed-42 α sweep (compression, held-out ΔU) for the six benchmark datasets; the non-monotone rows complement the RQ2 discussion.

Table 4: Quota operating points, shown as (compression, held-out ΔU). Every cell has $n = 1$.

Dataset	$\alpha = .85$	$\alpha = .90$	$\alpha = .95$	$\alpha = .99$
Abalone	$(.375, +.0041)$	$(.500, -.0198)$	$(.500, +.0010)$	$(0, 0)$
Credit-Card-Fraud	$(0, 0)$	$(0, 0)$	$(.034, -.0045)$	$(.586, -.0057)$
Gisette	$(0, 0)$	$(0, 0)$	$(0, 0)$	$(.090, +.0002)$
ISOLET	$(0, 0)$	$(0, 0)$	$(0, 0)$	$(.010, -.000005)$
Madelon	$(.240, +.0077)$	$(.490, +.0227)$	$(.560, -.0003)$	$(.510, -.0054)$
Spambase	$(0, 0)$	$(0, 0)$	$(0, 0)$	$(.196, -.0012)$

C REPRODUCIBILITY DETAILS

The formal splits are 64%/16%/20% train/validation/test; dataset identities, split indices, transformations, model policy, source, and scientific environment are recorded with cryptographic digests, and resume rejects protocol drift. Training data fit preprocessing, guidance, and all coalition models; validation is reused adaptively for threshold-game construction, the removal gate, and NSGA-II selection, while the held-out partition is read only for registered evaluation. The estimator set, removal controls, and NSGA-II variants are as in Section 3; runtime counters are diagnostic only. Tables and figures are rederived from canonical row-level records and independently hash-verified.