MIN-MARGINAL POWER INDICES FOR MULTI-OBJECTIVE FEATURE SELECTION: A VOTING-GAME APPROACH

Anonymous authors
Paper under double-blind review

ABSTRACT

The abstract paragraph should be indented 1/2 inch (3 picas) on both left and right-hand margins. Use 10 point type, with a vertical spacing of 11 points. The word ABSTRACT must be centered, in small caps, and in point size 12. Two line spaces precede the abstract. The abstract must be limited to one paragraph.

1 INTRODUCTION

Feature selection is one of the most fundamental preprocessing steps in machine learning. In an era where tabular datasets routinely span hundreds to thousands of features across domains ranging from computational biology to fraud detection, identifying a compact yet predictive subset of features directly determines model interpretability, training efficiency, and generalization performance (Guyon & Elisseeff, 2003; Chandrashekar & Sahin, 2014). The core challenge is combinatorial: the space of possible feature subsets grows exponentially with dimensionality, making exhaustive search intractable for all but the smallest problems.

Real-world feature selection is inherently multi-objective. Practitioners simultaneously optimize for multiple, often conflicting criteria: minimizing the number of selected features (for interpretability and deployment cost), maximizing predictive accuracy, and minimizing training time (for rapid experimentation cycles). Single-objective approaches—whether filter methods that rank features by univariate statistics, or wrapper methods that optimize a scalarized objective—collapse this trade-off space into a single number, depriving the decision-maker of a complete view of the solution landscape; Jiao et al. (2024) provide a comprehensive survey of multi-objective alternatives. Multi-objective evolutionary algorithms, particularly the Non-dominated Sorting Genetic Algorithm II (NSGA-II), proposed by Deb et al. (2002), have emerged as a principled approach to recovering the full Pareto front of non-dominated trade-offs, and have been successfully adapted to feature selection in a growing body of work (Hamdani et al., 2007; Song et al., 2024; Shao et al., 2025).

Cooperative game theory provides a powerful complementary perspective. Each feature can be cast as a player in a coalitional game, where the value of a coalition is the predictive performance achieved when only those features are used for training. The Shapley value (Shapley, 1953) and its close relatives—the Shapley-Shubik power index (Shapley & Shubik, 1954) and the Banzhaf power index (Banzhaf, 1965)—offer axiomatic foundations for quantifying each feature's marginal contribution across all possible coalitions. This framework has gained substantial traction in machine learning through SHAP (Lundberg & Lee, 2017), which uses Shapley values for local model explanation. However, the classical indices aggregate marginal contributions via a *mean* over all permutations (Shapley) or subsets (Banzhaf). The mean, by construction, smooths over the diversity of a feature's contextual behavior: a feature that is beneficial in most contexts but actively harmful in a few will receive a deceptively positive mean score, concealing the existence of contexts where its inclusion degrades performance. Recent work applying game-theoretic indices to feature selection—including Banzhaf-based pruning by Karavas et al. (2017), Powershap by Verhaeghe et al. (2022), and ShapG by Zhao et al. (2025)—all rely on mean-based aggregation and therefore inherit this limitation.

A conceptually important shift was recently proposed by Zheng & Raskutti (2026) in the form of MinShap: replacing the mean over permutations with the minimum. By capturing the worst-case marginal contribution, MinShap surfaces features that can be detrimental in specific contexts—

information that the mean discards entirely. We regard MinShap as a key inspiration for our work, though we do not rely on its conclusions. MinShap operates on a continuous value function $v(S) = \text{AUC}(\mathcal{M}_S)$, which means its min output remains a continuous quantity in $[-1, 1]$, lacking a natural decision boundary. We argue that a fundamentally more structured framework emerges from adopting a *binary* voting-game formulation, as formalized by Owen (1972): define $v_\alpha(S) = \mathbb{1}[\text{Acc}(\mathcal{M}_S) \geq \alpha \cdot \text{Acc}_{\text{full}}] \in \{0, 1\}$, where a coalition S either "wins" (reaches a fraction α of full-model accuracy) or "loses." Under this binary v_α, the min-marginal operator yields a discrete three-valued output in $\{-1, 0, +1\}$ that cleanly classifies features as *harmful*, *neutral*, or *decisive*—a ternary structure that is both theoretically crisp and immediately actionable for practitioners.

It is important to distinguish our framework from direct applications of Weighted Voting Games to feature selection (WVG-FS). WVG-FS methods typically approximate the value of a coalition through an additive decomposition: $v(S) \approx \mathbb{1}[\sum_{i \in S} w_i \geq q]$, where w_i are per-feature importance weights, as in the early work of Cohen et al. (2007). This additive approximation is structurally incorrect for non-linear models: synergistic feature combinations are systematically undervalued, while redundant combinations are overvalued—and the error is inherent to the additive form rather than correctable through more data. Our framework completely sidesteps this issue. The value function $v_\alpha(S)$ is evaluated by actually training a model $\mathcal{M}_S$ and measuring its accuracy on a validation set—no additive surrogate is employed. Critically, the MinPPI scores serve only as *soft guidance* for the search operators of a multi-objective evolutionary algorithm; final Pareto-optimality decisions are made by NSGA-II based on actual model fitness. This decoupling ensures that any estimation error in the power indices affects at most the convergence speed, never the correctness of the final Pareto front.

In this paper, we synthesize three previously independent lines of investigation—game-theoretic power indices, the min-marginal operator, and multi-objective evolutionary search—into a unified framework for feature selection. Our specific contributions are as follows:

1. **Minimal Power Indices (MinPPI).** We formalize the Min Shapley-Shubik (MinSS) and Min Banzhaf (MinBz) indices under the binary weighted voting game v_α. We prove that $\text{MinSS}_i = \text{MinBz}_i$ (Lemma 2) and that both indices take values exclusively in $\{-1, 0, +1\}$ (Lemma 1), yielding a three-way decisiveness classification: decisive $(+1)$, harmful (-1), or neutral (0) (Theorem 1).

2. **ShapG-Guided Adversarial Search (Algorithm B).** Random Monte Carlo sampling for detecting harmful features suffers from an $O(1/p_-)$ sample complexity, where p_- is the probability of drawing a coalition in which the target feature is harmful—prohibitively expensive when harmful contexts are sparse. We leverage the feature correlation graph produced by ShapG (Zhao et al., 2025) to guide an adversarial search that concentrates sampling on the most vulnerable coalitions, achieving approximately $38\times$ sample efficiency in detecting sparse harmful features.

3. **MOFS-MinPPI Algorithm.** We embed MinPPI signals into the mutation and crossover operators of NSGA-II: features classified as harmful receive elevated mutation probability biased toward removal, while decisive features are protected against perturbation. The guidance strength is controlled by a single parameter β, with $\beta = 0$ recovering the unguided baseline.

4. **Comprehensive Empirical Validation.** We evaluate MinPPI-MOFS against seven baseline methods on five tabular datasets spanning 29 to 5,000 features, under five random seeds. Ablation studies isolate the effects of the min vs. mean operator, binary vs. continuous $v(\cdot)$, and guidance strength β, with statistical significance assessed via the Friedman–Nemenyi test.

2 Related Work

Our work sits at the intersection of three research threads: game-theoretic feature importance, multi-objective feature selection, and voting games in machine learning. We review each in turn.

2.1 GAME-THEORETIC FEATURE IMPORTANCE

The application of cooperative game theory to feature importance attribution has a rich and accelerating history. Shapley (1953) provided the axiomatic definition of the Shapley value—the unique attribution scheme satisfying linearity, dummy, symmetry, and efficiency. The Shapley-Shubik power index (Shapley & Shubik, 1954) specialized this to simple (binary) voting games, while Banzhaf (1965) proposed an alternative power index based on uniform coalition probabilities rather than uniform permutations. Straffin (1977) unified both indices under a probabilistic framework, showing that they differ only in the assumed probability model over coalitions. A comprehensive treatment of computational aspects of cooperative game theory is provided by Chalkiadakis et al. (2011).

In machine learning, Lundberg & Lee (2017) brought Shapley values into the mainstream through SHAP, which efficiently approximates Shapley values for local model explanation using tree-based or kernel-based estimators. Cohen et al. (2007) were among the first to apply coalitional game theory directly to feature selection, treating features as players and model accuracy as the coalition value, and proposing a contribution-weighted voting scheme for feature ranking.

Shapley interaction indices. Moving beyond individual feature contributions, a substantial body of work addresses *interactions* among features. Grabisch & Roubens (1999) established the foundational axiomatization of Shapley interaction indices through four axioms—linearity, dummy, symmetry, and recursivity—that uniquely characterize the interaction value for any subset of players. Rabitti & Borgonovo (2019) modernized this framework as the Shapley-Owen interaction index, providing a rigorous treatment of its variance-based interpretation. Importantly, their Section 7.3 issues an explicit warning about *spurious interactions* arising under feature correlation: when two features are strongly correlated, an interaction index may attribute synergy to one feature that actually originates from the other. We address this concern directly in our discussion (Section 4.5). Tsai et al. (2023) introduced a faithfulness axiom guaranteeing that the sum of interaction indices across all orders exactly recovers the total model output. Muschalik et al. (2024) developed KernelSHAP-IQ, an efficient weighted least-squares framework for computing arbitrary-order Shapley interactions, with publicly available implementation.

Power-index-based feature selection. Several methods directly apply power indices to the feature selection problem. Karavas et al. (2017) employed the Banzhaf power index for lossless feature pruning, showing that features with zero Banzhaf score can be removed without affecting model accuracy, and proposed a shared-coalition Monte Carlo approximation with early stopping. Powershap (Verhaeghe et al., 2022) combines Shapley values with statistical hypothesis testing, using a percentile-based threshold to determine which features have significantly non-zero importance; its implementation is available as an open-source Python package. ShapG (Zhao et al., 2025) embeds feature correlations directly into Shapley value estimation through a minimal-edge correlation graph (built via Pearson correlation followed by Union-Find), enabling efficient local-neighborhood approximation with complexity $O(p \cdot 2^d)$ for p features and neighborhood depth d. ShapG serves a dual role in our work: as a standalone feature importance baseline, and as the correlation-graph oracle that guides the adversarial sampling in our Algorithm B.

Sensitivity analysis. Song et al. (2016) developed Shapley effects for global sensitivity analysis, providing the permutation-sampling framework and Hoeffding-style concentration bounds that underpin the theoretical guarantees of random Monte Carlo estimation (our Algorithm A). Their treatment of sampling distributions over coalition sizes directly informs our analysis in Section 4.3.

The min operator. Most directly relevant to our contribution, Zheng & Raskutti (2026) proposed MinShap, which replaces the mean over permutations with the minimum, capturing worst-case feature behavior. Three key differences distinguish our MinPPI framework: (i) we operate on a binary voting game $v_\alpha \in \{0, 1\}$, yielding the discrete ternary output $\{-1, 0, +1\}$ rather than a continuous score in $[-1, 1]$; (ii) our v_α is explicitly non-monotonic, reflecting the empirical reality that adding features can decrease model accuracy; and (iii) we employ ShapG-guided adversarial search (Algorithm B) that achieves substantially higher detection rates than uniform random sampling for sparse harmful features. We cite MinShap as a conceptual inspiration; our theoretical development and algorithmic design are independent.

2.2 MULTI-OBJECTIVE FEATURE SELECTION

Feature selection has been recognized as inherently multi-objective since the early 2000s. Hamdani et al. (2007) first adapted NSGA-II for bi-objective feature selection, simultaneously minimizing the number of selected features and the nearest-neighbor classification error, and demonstrated convergence on several UCI benchmark datasets. Xue et al. (2016) provided an early comprehensive survey of evolutionary computation approaches to feature selection, categorizing methods by problem formulation (single-objective vs. multi-objective), encoding scheme, and search mechanism.

Since then, the field has matured considerably. Jiao et al. (2024) present the most recent and thorough survey of multi-objective feature selection (MOFS) in classification, categorizing methods by encoding scheme, objective function design, and search strategy, and identifying key open challenges including scalability to high-dimensional data and the integration of prior knowledge into search operators. Song et al. (2024) propose a detailed taxonomy for evolutionary feature selection spanning initialization, individual updating, local search, and hybridization strategies, covering complex scenarios including multi-label, multi-task, and interpretable feature selection. A very recent survey on sparse multi-objective optimization by Shao et al. (2025) is particularly relevant to high-dimensional feature selection scenarios where the vast majority of decision variables (feature inclusion indicators) are zero.

Existing MOFS methods predominantly employ unguided variation operators—uniform mutation and uniform crossover—that treat all features symmetrically. A smaller body of work incorporates prior knowledge: for instance, filter-based importance scores (Information Gain, Relief-F, or Random Forest importance) have been used to bias mutation probabilities or warm-start initial populations (Song et al., 2024, cf. §5.2). To the best of our knowledge, our work is the first to use game-theoretic power indices as the guiding signal for evolutionary operators in MOFS. Unlike univariate filter scores, power indices naturally account for feature interactions through the coalitional structure of the underlying cooperative game.

2.3 VOTING GAMES IN MACHINE LEARNING

Weighted voting games (WVG), formalized by Owen (1972), are the canonical model of coalitional decision-making: each player i carries a non-negative weight w_i, and a coalition S wins if and only if its total weight meets or exceeds a quota q, i.e., $v(S) = \mathbb{1}[\sum_{i \in S} w_i \geq q]$. Classical WVGs are monotone ($S \subset T \implies v(S) \leq v(T)$). The multilinear extension of a WVG—a polynomial representation over which Shapley and Banzhaf values can be computed via differentiation—is a foundational tool in the analysis of voting power (Owen, 1972; Straffin, 1977).

The application of WVGs to feature selection is a natural but underexplored direction. Cohen et al. (2007) cast features as voters whose collective "vote" determines classification margin, and used the Shapley value to apportion credit. However, direct WVG formulations for feature selection share a structural limitation when they approximate the coalition value through an additive decomposition: the assumption that $v(S) \approx \mathbb{1}[\sum_{i \in S} w_i \geq q]$ for per-feature weights w_i is valid only when the underlying model $\mathcal{M}$ is itself approximately linear in the features. For non-linear models such as gradient-boosted trees or deep neural networks, this additive approximation can be severely misleading—strongly synergistic feature combinations are undervalued, while redundant combinations are overvalued—a point discussed by Song et al. (2016) in the context of global sensitivity analysis.

Our framework resolves this tension by decoupling two roles that WVG-FS conflates. The *value function* $v_\alpha(S)$ is assessed through actual model training and validation, guaranteeing fidelity to the true model behavior. The *power indices* are computed on the resulting binary game and used exclusively as soft guidance for evolutionary search operators. This architecture preserves the game-theoretic rigor of the WVG formalism while eliminating its reliance on additive approximation—a point we formalize in Section 4.5.

3 PRELIMINARIES

This section establishes notation and recalls the essential background on cooperative game theory, the problem setting, multi-objective optimization, and the ShapG method. Readers familiar with these topics may skip to Section 4, consulting this section for notational reference as needed.

3.1 COOPERATIVE GAME THEORY

A cooperative game with transferable utility (TU game) is a pair (N, v) where $N = \{1, \ldots, n\}$ is a finite set of players and $v : 2^N \to \mathbb{R}$ is a characteristic function satisfying $v(\emptyset) = 0$. A game is called *simple* if $v(S) \in \{0, 1\}$ for all $S \subseteq N$; coalitions with $v(S) = 1$ are termed *winning*, and those with $v(S) = 0$ are *losing*.

The *Shapley value* (Shapley, 1953) assigns each player i a unique payoff:

$$\phi_i(v) = \sum_{S \subseteq N \setminus \{i\}} \frac{|S|!\,(n - |S| - 1)!}{n!} \big[v(S \cup \{i\}) - v(S)\big]. \tag{1}$$

When applied to a simple game, ϕ_i is known as the *Shapley-Shubik power index* (Shapley & Shubik, 1954), denoted ϕ_i^{SS}.

The *Banzhaf power index* (Banzhaf, 1965) employs uniform coalition weighting instead of permutation-based weighting:

$$\beta_i(v) = \frac{1}{2^{\,n-1}} \sum_{S \subseteq N \setminus \{i\}} \big[v(S \cup \{i\}) - v(S)\big]. \tag{2}$$

A *weighted voting game* (WVG), formalized by Owen (1972), is a simple game parameterized by non-negative weights $w_1, \ldots, w_n$ and a quota $q > 0$:

$$v(S) = \mathbb{1}\left[\sum_{i \in S} w_i \;\geq\; q\right]. \tag{3}$$

Classical WVGs are monotone: $S \subset T$ implies $v(S) \leq v(T)$.

The *Shapley interaction index* (Grabisch & Roubens, 1999) extends the Shapley value to capture synergies among sets of players. For any subset $A \subseteq N$, the interaction $\phi_A(v)$ quantifies the joint contribution of the players in A beyond the sum of their individual effects. Rabitti & Borgonovo (2019) provide a modern axiomatic treatment through the Shapley-Owen index, with four axioms—linearity, dummy, symmetry, and recursivity—that uniquely characterize the interaction value. We build on the single-player specialization of this framework, adapted to a binary, non-monotonic WVG setting, in Section 4.

3.2 PROBLEM SETTING

We consider a tabular dataset $\mathcal{D} = \{(\mathbf{x}_k, y_k)\}_{k=1}^N$ consisting of N labeled examples. The feature set is $N_1 = \{f_1, \ldots, f_n\}$ with $n = |N_1|$. For any subset $S \subseteq N_1$, let $\mathcal{M}_S$ denote a base learner (XGBoost by default) trained exclusively on the features in S, and let $\text{Acc}(\mathcal{M}_S; \mathcal{D}_{\text{val}})$ denote its predictive performance on a held-out validation set $\mathcal{D}_{\text{val}}$. Unless otherwise specified, accuracy is measured by the area under the ROC curve (AUC). The full-model accuracy is

$$\text{Acc}_{\text{full}} = \text{Acc}(\mathcal{M}_{N_1}; \mathcal{D}_{\text{val}}). \tag{4}$$

Following the WVG paradigm, we define a family of binary value functions parameterized by a quota fraction $\alpha \in (0, 1]$:

$$v_\alpha(S) = \mathbb{1}\big[\,\text{Acc}(\mathcal{M}_S; \mathcal{D}_{\text{val}}) \;\geq\; \alpha \cdot \text{Acc}_{\text{full}}\,\big]. \tag{5}$$

The pair (N_1, v_α) constitutes a voting game. *Unlike a classical monotone WVG, v_α is not guaranteed to be monotone:* adding a feature may reduce accuracy due to noise amplification, redundancy, or overfitting. Consequently, it is possible that $S \subset T$ yet $v_\alpha(S) = 1$ and $v_\alpha(T) = 0$. This non-monotonicity is not a defect; it is the very phenomenon that makes feature selection non-trivial, and it is the foundation for the three-way classification we develop in Section 4.2.

Table 1: Taxonomy of game-theoretic feature importance methods by aggregation operator and value function type.

Index	**Aggregation**	$v(S)$ **type**	**Output range**
Shapley-Shubik (Shapley & Shubik, 1954)	mean	binary $\{0,1\}$	$\subseteq [0,1]$
Banzhaf (Banzhaf, 1965)	mean	binary $\{0,1\}$	$\subseteq [0,1]$
Shapley / SHAP (Lundberg & Lee, 2017)	mean	continuous	$\subseteq [-1,1]$
MinShap (Zheng & Raskutti, 2026)	min	continuous	$\subseteq [-1,1]$
MinPPI (this work)	**min**	**binary** $\{0,1\}$	$\{-\mathbf{1}, \mathbf{0}, +\mathbf{1}\}$

3.3 NSGA-II Background

Multi-objective optimization seeks to minimize a vector of m potentially conflicting objectives $\mathbf{f}(\mathbf{x}) = (f_1(\mathbf{x}), \ldots, f_m(\mathbf{x}))$ over a feasible set $\Omega \subseteq \mathbb{R}^d$. Since no single solution typically minimizes all objectives simultaneously, optimality is defined through *Pareto dominance*: a solution $\mathbf{x}$ dominates $\mathbf{x}'$, denoted $\mathbf{x} \prec \mathbf{x}'$, if $f_j(\mathbf{x}) \leq f_j(\mathbf{x}')$ for all $j \in \{1, \ldots, m\}$ and the inequality is strict for at least one j. The *Pareto set* is the set of all non-dominated solutions, and its image under $\mathbf{f}$ is the *Pareto front*.

NSGA-II (Deb et al., 2002) is a widely adopted multi-objective evolutionary algorithm. Its two distinguishing mechanisms are: (i) *non-dominated sorting*, which partitions the combined parent–offspring population into successive Pareto fronts $\mathcal{F}_1, \mathcal{F}_2, \ldots$; and (ii) *crowding distance*, which promotes diversity within each front by favoring solutions with larger distances to their nearest neighbors in objective space. Selection proceeds front-wise, admitting entire fronts until the population cap is reached, then filling the remainder with the most isolated solutions from the next front.

In our setting, a candidate feature subset is encoded as a binary mask $\mathbf{m} \in \{0,1\}^n$, where $m_i = 1$ indicates that feature f_i is selected. The three objectives we minimize are:

$$\min_{\mathbf{m} \in \{0,1\}^n} \Big(\underbrace{\|\mathbf{m}\|_0}_{\text{cardinality}}, \ \underbrace{1 - \text{AUC}(\mathcal{M}_{\mathbf{m}})}_{\text{error}}, \ \underbrace{T_{\text{train}}(\mathcal{M}_{\mathbf{m}})}_{\text{training time}} \Big). \tag{6}$$

These objectives capture the canonical trade-offs in practical feature selection: sparser models are cheaper to deploy and easier to interpret; higher AUC directly reflects predictive quality; and shorter training time enables faster experimentation cycles, which is critical in large-scale industrial settings.

3.4 ShapG Overview

ShapG (Zhao et al., 2025) computes feature importance by approximating Shapley values on a feature correlation graph. The pipeline operates in three stages: (i) construct a symmetric correlation matrix over the p features (Pearson correlation by default); (ii) reduce this to a minimal connected graph via a Kruskal-like Union-Find procedure that greedily inserts edges in descending order of absolute correlation, stopping as soon as all nodes belong to a single connected component; and (iii) for each feature i, enumerate or sample coalitions within its local neighborhood in the resulting graph—controlled by a depth parameter d—and compute marginal contributions, scaled proportionally so that the sum of all approximated Shapley values equals the grand-coalition value $v(N)$. The complexity is $O(p \cdot 2^d)$, which is tractable for typical values of $d \in \{1, 2\}$ and p in the hundreds. ShapG serves two roles in this work: as a standalone feature importance baseline §6, and as the correlation oracle for Algorithm B §4.3.

3.5 Existing Marginal-Operator Variants

To situate our contribution, it is helpful to contrast the four combinations of aggregation operator and value function type that appear in the literature on game-theoretic feature selection. Table 1 provides a taxonomy.

The critical observation is that pairing the min-aggregation operator with a binary value function yields a discrete ternary output—a structural property unique to our framework. The mean-based methods in the first three rows of Table 1 smooth over harmful contexts by averaging. MinShap, despite employing the min operator, produces a continuous output in $[-1, 1]$, which lacks a principled decision boundary and requires additional calibration to translate scores into actionable feature-level decisions. Our MinPPI framework occupies the uniquely structured intersection of its design space: the min operator provides context sensitivity (detecting harmful features that the mean obscures), while the binary value function provides crisp interpretability through the $\{-1, 0, +1\}$ trichotomy formalized in Theorem 1 of Section 4.2.

4 SUBMISSION OF CONFERENCE PAPERS TO ICOMP 2026

ICOMP requires electronic submissions, processed by `https://openreview.net/`. See ICOMP's website for more instructions.

If your paper is ultimately accepted, the statement `\icompfinalcopy` should be inserted to adjust the format to the camera ready requirements.

The format for the submissions is a variant of the NeurIPS format. Please read carefully the instructions below, and follow them faithfully.

4.1 STYLE

Papers to be submitted to ICOMP 2026 must be prepared according to the instructions presented here.

Authors are required to use the ICOMP LaTeX style files obtainable at the ICOMP website. Please make sure you use the current files and not previous versions. Tweaking the style files may be grounds for rejection.

4.2 RETRIEVAL OF STYLE FILES

The style files for ICOMP and other conference information are available online at:

`http://www.icomp.cc/`

The file `icomp2026_conference.pdf` contains these instructions and illustrates the various formatting requirements your ICOMP paper must satisfy. Submissions must be made using LaTeX and the style files `icomp2026_conference.sty` and `icomp2026_conference.bst` (to be used with LaTeX2e). The file `icomp2026_conference.tex` may be used as a "shell" for writing your paper. All you have to do is replace the author, title, abstract, and text of the paper with your own.

The formatting instructions contained in these style files are summarized in sections 5, 6, and 7 below.

5 GENERAL FORMATTING INSTRUCTIONS

The text must be confined within a rectangle 5.5 inches (33 picas) wide and 9 inches (54 picas) long. The left margin is 1.5 inch (9 picas). Use 10 point type with a vertical spacing of 11 points. Times New Roman is the preferred typeface throughout. Paragraphs are separated by 1/2 line space, with no indentation.

Paper title is 17 point, in small caps and left-aligned. All pages should start at 1 inch (6 picas) from the top of the page.

Authors' names are set in boldface, and each name is placed above its corresponding address. The lead author's name is to be listed first, and the co-authors' names are set to follow. Authors sharing the same address can be on the same line.

Please pay special attention to the instructions in section 7 regarding figures, tables, acknowledgments, and references.

There will be a strict upper limit of 9 pages for the main text of the initial submission, with unlimited additional pages for citations.

6 HEADINGS: FIRST LEVEL

First level headings are in small caps, flush left and in point size 12. One line space before the first level heading and 1/2 line space after the first level heading.

6.1 HEADINGS: SECOND LEVEL

Second level headings are in small caps, flush left and in point size 10. One line space before the second level heading and 1/2 line space after the second level heading.

6.1.1 HEADINGS: THIRD LEVEL

Third level headings are in small caps, flush left and in point size 10. One line space before the third level heading and 1/2 line space after the third level heading.

7 CITATIONS, FIGURES, TABLES, REFERENCES

These instructions apply to everyone, regardless of the formatter being used.

7.1 CITATIONS WITHIN THE TEXT

Citations within the text should be based on the `natbib` package and include the authors' last names and year (with the "et al." construct for more than two authors). When the authors or the publication are included in the sentence, the citation should not be in parenthesis using `\citet{}` (as in "See Hinton et al. (2006) for more information."). Otherwise, the citation should be in parenthesis using `\citep{}` (as in "Deep learning shows promise to make progress towards AI (Bengio & LeCun, 2007).").

The corresponding references are to be listed in alphabetical order of authors, in the REFERENCES section. As to the format of the references themselves, any style is acceptable as long as it is used consistently.

7.2 FOOTNOTES

Indicate footnotes with a number[1] in the text. Place the footnotes at the bottom of the page on which they appear. Precede the footnote with a horizontal rule of 2 inches (12 picas).[2]

7.3 FIGURES

All artwork must be neat, clean, and legible. Lines should be dark enough for purposes of reproduction; art work should not be hand-drawn. The figure number and caption always appear after the figure. Place one line space before the figure caption, and one line space after the figure. The figure caption is lower case (except for first word and proper nouns); figures are numbered consecutively.

Make sure the figure caption does not get separated from the figure. Leave sufficient space to avoid splitting the figure and figure caption.

You may use color figures. However, it is best for the figure captions and the paper body to make sense if the paper is printed either in black/white or in color.

[1] Sample of the first footnote

[2] Sample of the second footnote




Figure 1: Sample figure caption.

Table 2: Sample table title

PART	DESCRIPTION
Dendrite	Input terminal
Axon	Output terminal
Soma	Cell body (contains cell nucleus)

7.4 TABLES

All tables must be centered, neat, clean and legible. Do not use hand-drawn tables. The table number and title always appear before the table. See Table 2.

Place one line space before the table title, one line space after the table title, and one line space after the table. The table title must be lower case (except for first word and proper nouns); tables are numbered consecutively.

8 DEFAULT NOTATION

In an attempt to encourage standardized notation, we have included the notation file from the textbook, *Deep Learning* Goodfellow et al. (2016) available at `https://github.com/goodfeli/dlbook_notation/`. Use of this style is not required and can be disabled by commenting out `math_commands.tex`.

Numbers and Arrays

a	A scalar (integer or real)
$\boldsymbol{a}$	A vector
$\boldsymbol{A}$	A matrix
$\mathsf{\mathbf{A}}$	A tensor
$\boldsymbol{I}_n$	Identity matrix with n rows and n columns
$\boldsymbol{I}$	Identity matrix with dimensionality implied by context
$\boldsymbol{e}^{(i)}$	Standard basis vector $[0, \dots, 0, 1, 0, \dots, 0]$ with a 1 at position i
$\text{diag}(\boldsymbol{a})$	A square, diagonal matrix with diagonal entries given by $\boldsymbol{a}$
a	A scalar random variable
$\mathbf{a}$	A vector-valued random variable
$\mathbf{A}$	A matrix-valued random variable

Sets and Graphs

$\mathbb{A}$	A set
$\mathbb{R}$	The set of real numbers
$\{0, 1\}$	The set containing 0 and 1
$\{0, 1, \dots, n\}$	The set of all integers between 0 and n
$[a, b]$	The real interval including a and b
$(a, b]$	The real interval excluding a but including b
$\mathbb{A} \backslash \mathbb{B}$	Set subtraction, i.e., the set containing the elements of $\mathbb{A}$ that are not in $\mathbb{B}$
$\mathcal{G}$	A graph
$Pa_{\mathcal{G}}(\mathrm{x}_i)$	The parents of x_i in $\mathcal{G}$

Indexing

a_i	Element i of vector $\boldsymbol{a}$, with indexing starting at 1
a_{-i}	All elements of vector $\boldsymbol{a}$ except for element i
$A_{i,j}$	Element i, j of matrix $\boldsymbol{A}$
$\boldsymbol{A}_{i,:}$	Row i of matrix $\boldsymbol{A}$
$\boldsymbol{A}_{:,i}$	Column i of matrix $\boldsymbol{A}$
$\mathsf{A}_{i,j,k}$	Element (i, j, k) of a 3-D tensor A
$\mathsf{A}_{:,:,i}$	2-D slice of a 3-D tensor
a_i	Element i of the random vector $\mathbf{a}$

Calculus

$\frac{dy}{dx}$	Derivative of y with respect to x
$\frac{\partial y}{\partial x}$	Partial derivative of y with respect to x
$\nabla_{\boldsymbol{x}} y$	Gradient of y with respect to $\boldsymbol{x}$
$\nabla_{\boldsymbol{X}} y$	Matrix derivatives of y with respect to $\boldsymbol{X}$
$\nabla_{\mathsf{X}} y$	Tensor containing derivatives of y with respect to X
$\frac{\partial f}{\partial \boldsymbol{x}}$	Jacobian matrix $\boldsymbol{J} \in \mathbb{R}^{m \times n}$ of $f : \mathbb{R}^n \to \mathbb{R}^m$
$\nabla^2_{\boldsymbol{x}} f(\boldsymbol{x})$ or $\boldsymbol{H}(f)(\boldsymbol{x})$	The Hessian matrix of f at input point $\boldsymbol{x}$
$\int f(\boldsymbol{x}) d\boldsymbol{x}$	Definite integral over the entire domain of $\boldsymbol{x}$
$\int_{\mathbb{S}} f(\boldsymbol{x}) d\boldsymbol{x}$	Definite integral with respect to $\boldsymbol{x}$ over the set $\mathbb{S}$

Probability and Information Theory

$P(\mathrm{a})$	A probability distribution over a discrete variable
$p(\mathrm{a})$	A probability distribution over a continuous variable, or over a variable whose type has not been specified
$\mathrm{a} \sim P$	Random variable a has distribution P
$\mathbb{E}_{\mathrm{x}\sim P}[f(x)]$ or $\mathbb{E}f(x)$	Expectation of $f(x)$ with respect to $P(\mathrm{x})$
$\mathrm{Var}(f(x))$	Variance of $f(x)$ under $P(\mathrm{x})$
$\mathrm{Cov}(f(x), g(x))$	Covariance of $f(x)$ and $g(x)$ under $P(\mathrm{x})$
$H(\mathrm{x})$	Shannon entropy of the random variable x
$D_{\mathrm{KL}}(P\|Q)$	Kullback-Leibler divergence of P and Q
$\mathcal{N}(\boldsymbol{x}; \boldsymbol{\mu}, \boldsymbol{\Sigma})$	Gaussian distribution over $\boldsymbol{x}$ with mean $\boldsymbol{\mu}$ and covariance $\boldsymbol{\Sigma}$

Functions

$f : \mathbb{A} \to \mathbb{B}$	The function f with domain $\mathbb{A}$ and range $\mathbb{B}$
$f \circ g$	Composition of the functions f and g
$f(\boldsymbol{x}; \boldsymbol{\theta})$	A function of $\boldsymbol{x}$ parametrized by $\boldsymbol{\theta}$. (Sometimes we write $f(\boldsymbol{x})$ and omit the argument $\boldsymbol{\theta}$ to lighten notation)
$\log x$	Natural logarithm of x
$\sigma(x)$	Logistic sigmoid, $\dfrac{1}{1+\exp(-x)}$
$\zeta(x)$	Softplus, $\log(1+\exp(x))$
$\|\|\boldsymbol{x}\|\|_p$	L^p norm of $\boldsymbol{x}$
$\|\|\boldsymbol{x}\|\|$	L^2 norm of $\boldsymbol{x}$
x^+	Positive part of x, i.e., $\max(0, x)$
$\mathbf{1}_{\mathrm{condition}}$	is 1 if the condition is true, 0 otherwise

9 FINAL INSTRUCTIONS

Do not change any aspects of the formatting parameters in the style files. In particular, do not modify the width or length of the rectangle the text should fit into, and do not change font sizes (except perhaps in the REFERENCES section; see below). Please note that pages should be numbered.

10 PREPARING POSTSCRIPT OR PDF FILES

Please prepare PostScript or PDF files with paper size "US Letter", and not, for example, "A4". The -t letter option on dvips will produce US Letter files.

Consider directly generating PDF files using `pdflatex` (especially if you are a MiKTeX user). PDF figures must be substituted for EPS figures, however.

Otherwise, please generate your PostScript and PDF files with the following commands:

```
dvips mypaper.dvi -t letter -Ppdf -G0 -o mypaper.ps
ps2pdf mypaper.ps mypaper.pdf
```

10.1 MARGINS IN LATEX

Most of the margin problems come from figures positioned by hand using `\special` or other commands. We suggest using the command `\includegraphics` from the graphicx package.

Always specify the figure width as a multiple of the line width as in the example below using .eps graphics

```
\usepackage[dvips]{graphicx} ...
\includegraphics[width=0.8\linewidth]{myfile.eps}
```

or

```
\usepackage[pdftex]{graphicx} ...
\includegraphics[width=0.8\linewidth]{myfile.pdf}
```

for .pdf graphics. See section 4.4 in the graphics bundle documentation (`http://www.ctan.org/tex-archive/macros/latex/required/graphics/grfguide.ps`)

A number of width problems arise when LaTeX cannot properly hyphenate a line. Please give LaTeX hyphenation hints using the `\-` command.

AUTHOR CONTRIBUTIONS

If you'd like to, you may include a section for author contributions as is done in many journals. This is optional and at the discretion of the authors.

ACKNOWLEDGMENTS

Use unnumbered third level headings for the acknowledgments. All acknowledgments, including those to funding agencies, go at the end of the paper.

REFERENCES

John F. Banzhaf. Weighted voting doesn't work: A mathematical analysis. *Rutgers Law Review*, 19: 317–343, 1965.

Yoshua Bengio and Yann LeCun. Scaling learning algorithms towards AI. In *Large Scale Kernel Machines*. MIT Press, 2007.

Georgios Chalkiadakis, Edith Elkind, and Michael Wooldridge. *Computational Aspects of Cooperative Game Theory*. Synthesis Lectures on Artificial Intelligence and Machine Learning. Morgan & Claypool, 2011.

Girish Chandrashekar and Ferat Sahin. A survey on feature selection methods. *Computers & Electrical Engineering*, 40(1):16–28, 2014.

Shay Cohen, Gideon Dror, and Eytan Ruppin. Feature selection via coalitional game theory. *Neural Computation*, 19(7):1939–1961, 2007.

Kalyanmoy Deb, Amrit Pratap, Sameer Agarwal, and T. Meyarivan. A fast and elitist multiobjective genetic algorithm: NSGA-II. *IEEE Transactions on Evolutionary Computation*, 6(2):182–197, 2002.

Ian Goodfellow, Yoshua Bengio, and Aaron Courville. *Deep Learning*, volume 1. MIT Press, 2016.

Michel Grabisch and Marc Roubens. An axiomatic approach to the concept of interaction among players in cooperative games. *International Journal of Game Theory*, 28:547–565, 1999.

Isabelle Guyon and André Elisseeff. An introduction to variable and feature selection. *Journal of Machine Learning Research*, 3:1157–1182, 2003.

Tarek M. Hamdani, Jin-Myung Won, Adel M. Alimi, and Fakhri Karray. Multi-objective feature selection with NSGA II. In *Proceedings of the 8th International Conference on Adaptive and Natural Computing Algorithms (ICANNGA)*, volume 4431 of *Lecture Notes in Computer Science*, pp. 240–247. Springer, 2007.

Geoffrey E. Hinton, Simon Osindero, and Yee Whye Teh. A fast learning algorithm for deep belief nets. *Neural Computation*, 18:1527–1554, 2006.

Ruwang Jiao, Bach Hoai Nguyen, Bing Xue, and Mengjie Zhang. A survey on evolutionary multiobjective feature selection in classification: Approaches, applications, and challenges. *IEEE Transactions on Evolutionary Computation*, 28(4):1156–1176, 2024.

Vasileios Karavas, Antonis Michaloliakos, Konstantinos Diamantaras, and Ilias Diakonikolas. Feature importance scores and lossless feature pruning using Banzhaf power indices. *arXiv preprint arXiv:1711.04992*, 2017.

Scott M. Lundberg and Su-In Lee. A unified approach to interpreting model predictions. In *Advances in Neural Information Processing Systems (NeurIPS)*, volume 30, 2017.

Maximilian Muschalik, Hubert Baniecki, Fabian Fumagalli, Patrick Kolpaczki, Barbara Hammer, and Eyke Hüllermeier. KernelSHAP-IQ: Weighted least-square optimization for Shapley interactions. *arXiv preprint arXiv:2405.10852*, 2024.

Guillermo Owen. Multilinear extensions of games. *Management Science*, 18(5):P64–P79, 1972.

Giovanni Rabitti and Emanuele Borgonovo. A Shapley-Owen index for interaction quantification. *SIAM/ASA Journal on Uncertainty Quantification*, 7(3):1060–1075, 2019.

Shuai Shao, Ye Tian, Yajie Zhang, and Xingyi Zhang. Evolutionary computation for sparse multiobjective optimization: A survey. *ACM Computing Surveys*, 57(11), 2025.

Lloyd S. Shapley. A value for n-person games. In Harold W. Kuhn and Albert W. Tucker (eds.), *Contributions to the Theory of Games*, volume 2, pp. 307–317. Princeton University Press, 1953.

Lloyd S. Shapley and Martin Shubik. A method for evaluating the distribution of power in a committee system. *American Political Science Review*, 48(3):787–792, 1954.

Eunhye Song, Barry L. Nelson, and Jeremy Staum. Shapley effects for global sensitivity analysis: Theory and computation. *SIAM/ASA Journal on Uncertainty Quantification*, 4:1060–1083, 2016.

Xianfang Song, Yong Zhang, Wanqiu Zhang, Chunlin He, Ying Hu, Jian Wang, and Dunwei Gong. Evolutionary computation for feature selection in classification: A comprehensive survey of solutions, applications and challenges. *Swarm and Evolutionary Computation*, 90:101661, 2024.

Philip D. Straffin. The Shapley-Shubik and Banzhaf power indices as probabilities. In Alvin E. Roth (ed.), *The Shapley Value: Essays in Honor of Lloyd S. Shapley*, pp. 71–81. Cambridge University Press, 1977.

Che-Ping Tsai, Chih-Kuan Yeh, and Pradeep Ravikumar. Faith-Shap: The faithful Shapley interaction index. *Journal of Machine Learning Research*, 24, 2023.

Jarne Verhaeghe, Jonas Van Der Donckt, Femke Ongenae, and Sofie Van Hoecke. Powershap: A power-full Shapley feature selection method. In *Proceedings of the European Conference on Machine Learning and Principles and Practice of Knowledge Discovery in Databases (ECML PKDD)*, 2022.

Bing Xue, Mengjie Zhang, Will N. Browne, and Xin Yao. A survey on evolutionary computation approaches to feature selection. *IEEE Transactions on Evolutionary Computation*, 20(4):606–626, 2016.

Chi Zhao, Jiapeng Liu, and Elena Parilina. ShapG: New feature importance method based on the Shapley value. *Engineering Applications of Artificial Intelligence*, 148, 2025.

Chen Zheng and Garvesh Raskutti. MinShap: A modified Shapley value approach for feature selection. *arXiv preprint arXiv:2604.15107*, 2026. Cited as conceptual inspiration; our theoretical development and algorithmic design are independent.

A Appendix

You may include other additional sections here.