



Messages

- (0.1) GET <Webservice>
- (0.2) returns <Webservice> (with Button "Login with eID")
- Click on "Login with eID" triggers:
- (1) OpenID: Authorization Request
- (2.1) OpenID: Authorization Grant
- (2.2) GET <redirect_uri>
- (2.3) returns <redirect_uri> (with "Please start AusweisApp")
- (3) GET <uri that returns tcTokenURI>
- (4) BSI: returns tcTokenURI
- (5) BSI: forward tcTokenURI to AusweisApp
- (6) BSI: GET tcTokenURI
- (7) BSI: eID-Interface: useID Request
- (8) BSI: eID-Interface: useID Response
- (9) BSI: Transmit tcToken
- latest possible moment for User PIN input
- (10) BSI: Initialize trusted channel via tcToken
- (11) BSI: Call RefreshAddress
- (12) BSI: eID-Interface: getResult Request
- (13) BSI: eID-Interface: getResult Response
- (14) BSI: Response from eService
- (15) BSI: Forward Browser to RefreshAddress
- (16) BSI: Surf to RefreshAddress
- (17) Returns page that triggers POST
- (18) OpenID: Authorization Grant
- (19) OpenID: Access Token
- (20) Forward Access Token
- (21) OpenID: GET /userinfo, send Access Token
- (22) OpenID: Send User Data