


EE 610 Image Processing

Project 1: Restoring the brain image

Name: Swrangsar Basumatary Roll: 09d07040

The original image that is to be filtered is:



The fnlCg code:

```
function x = fnlCg(x0,sampler,data, param)
%-----
%-----
%-----
-----
x = x0;

% line search parameters - Dont touch..leave alone
```

```

maxlsiter = 150;
gradToll = 1.0000e-030;
alpha = 0.0100;
beta = 0.6000;
t0 = 1;
Itlim = 16;

k = 0;

% compute g0 = grad(Phi(x))
g0 = wGradient(x,sampler,data, param);

dx = -g0;

% iterations
while(1)

% backtracking line-search

    % pre-calculate values, such that it would be cheap to
    compute the objective
    % many times for efficient line-search
    f0 = objective(x,dx, 0, sampler,data, param);
    t = t0;

    [f1] = objective(x,dx, t,sampler,data, param);

    lsiter = 0;

    while (f1 > f0 - alpha*t*abs(g0(:)'*dx(:)))^2 &
    (lsiter<maxlsiter)
        lsiter = lsiter + 1;
        t = t * beta;
        [f1] = objective(x,dx, t,sampler,data, param);
    end

    if lsiter == maxlsiter
        disp('Reached max line search,.... not so good... might
have a bug in operators. exiting... ');
        return;
    end

    % control the number of line searches by adapting the
    initial step search
    if lsiter > 2
        t0 = t0 * beta;

```

```

end

if lsiter<1
    t0 = t0 / beta;
end

x = (x + t*dx);

%----- uncomment for debug purposes
-----
disp(sprintf('%d    , obj: %f ', k,f1));

%-----

%conjugate gradient calculation- Dont touch

g1 = wGradient(x,sampler,data, param);
bk = g1(:)'*g1(:)/(g0(:)'*g0(:)+eps);
g0 = g1;
dx = - g1 + bk* dx;
k = k + 1;

%TODO: need to "think" of a "better" stopping criteria ;- )
if (k > Itnlim) | (norm(dx(:)) < gradToll)
    break;
end

end

return;

function [res] = objective(x,dx,t,sampler,data, param)
%DEFINE obj
x = x + (t * dx);
b = data;
Ax = sampler .* fftshift(fft2(fftshift(x)));
obj = (Ax - b);
res=(obj(:)'*obj(:)) + (param.TVWeight * TV(x));

function grad = wGradient(x,sampler,data, param)
%Define this function
gradObj=gOBJ(x,sampler,data);
grad = (gradObj) + (param.TVWeight * gTV(x));

```

```

function gradObj = gOBJ(x,sampler,data)
% computes the gradient of the data consistency
%DEFINE gradObj
b = data;
Ax = sampler .* fftshift(fft2(fftshift(x)));
AhAx = ifftshift(ifft2(ifftshift(Ax)));
Ahb = ifftshift(ifft2(ifftshift(b)));
gradObj = 2 * (AhAx - Ahb);

function gradTV = gTV(x)
% compute gradient of TV operator
gradTV=filter2([0 -1 1],filter2([1 -1 0], x))
+filter2([0;-1;1],filter2([1;
-1; 0], x));

%YOU MAY WANT TO ADD MORE FUNCTIONS AND GRADIENTS
function totalvariation = TV(x)
ux = filter2([1 -1 0], x);
uy = filter2([1; -1; 0], x);
ux2 = ux .* (conj(ux));
uy2 = uy .* (conj(uy));
mag = sqrt(ux2 + uy2);
totalvariation = sum(mag(:)) ;

```

The brain demo code:

```

close all; clear all;

load brain512

sampler=mask./pdf;

%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
% Reconstruction Parameters
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%

N = size(data);      % image Size
DN = size(data);     % Fourier data Size
param.TVWeight = .77; % Weight for TV penalty

```

```

% scale data
im_dc = ifftshift(ifft2(ifftshift(data.*sampler))); % matrix E
has been defined here
data = data/max(abs(im_dc(:)));

im_dc = im_dc/max(abs(im_dc(:)));

res = im_dc; %Initial degraded image supplied to fnlcg function

% do iterations
tic
for n=1:5
    res = fnlCg(res,sampler,data, param); %initialize fnlcg
    im_res = res;
    figure(100), imshow(abs(im_res),[]), drawnow
end
toc

```

The output image is:


```

%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%

N = size(data);      % image Size
DN = size(data);     % Fourier data Size
param.TVWeight = .77; % Weight for TV penalty

% scale data
im_dc = ifftshift(ifft2(ifftshift(data.*sampler))); % matrix E
has been defined here
data = data/max(abs(im_dc(:)));

im_dc = im_dc/max(abs(im_dc(:)));

res = im_dc; %Initial degraded image supplied to fnlcg function

% do iterations
tic
for n=1:5
    res = fnlCg(res,sampler,data, param); %initialize fnlcg
    im_res = res;
    figure(100), imshow(abs(im_res),[]), drawnow
end
toc

```

The output of sampled phantom image is:

