

ForgeSlicer

Comprehensive Manual QA Test Plan

Version 1.2 · June 27, 2026

Environment: <https://orca-cad-slice.preview.emergentagent.com>

ForgeSlicer is a browser-based 3D CAD + Slicer that fuses a TinkerCAD-style primitive editor, Shapr3D-style reverse engineering, and an OrcaSlicer-style slicing handoff into a single workflow. This document is the comprehensive manual QA test plan that walks a tester through every user-facing surface — primitives, Boolean operations, importers, RANSAC reverse engineering, AI / voice workflows, the community gallery, Learn lessons, Trust pages, account and email flows, and slicer handoff.

Each test case has a stable ID (so regressions can be referenced across releases), the click-by-click steps a tester should follow, the expected result, and a priority. Run P0 cases on every release, P1 cases weekly, and P2 cases when a related area changes.

Test environment: <https://orca-cad-slice.preview.emergentagent.com>. Recommended browsers: latest Chrome, Firefox, and Safari. Use Chromium-based browsers for WebGPU-dependent paths.

P0 Run every release

P1 Run weekly

P2 Run on related changes

Contents

1. Onboarding & First-Run	Landing tab bar (iter-108), Beginner Starters, Auth (email + Google)
2. Primitive Editor & Boolean Operations	Primitives, Boolean Operations (Manifold-3D WASM)
3. Importers (STL / OBJ / 3MF / SVG / ZIP)	Mesh imports
4. Reverse Engineering (RANSAC)	Dialog & detection (Phase 1–3 shipped)
5. AI & Voice Workflows	Conversational AI, Text on Surface
6. Measurement, Snapping & Grid	Measurement
7. Community Gallery (v2)	Browse & filter
8. Learn Section	Lessons
9. Trust, Privacy & Changelog	Trust pages
10. Slicer Handoff	Multi-object 3MF export → OrcaSlicer
11. SEO & Marketing Surfaces	SEO landings
12. Cross-Cutting Quality Bars	Performance & accessibility

1. Onboarding & First-Run

Landing tab bar (iter-108)

ID	Test Case	Steps	Expected Result	Pri
LAND-01	Landing tab bar shows 5 tabs in fixed order below the hero	1. Open / in a private window. 2. Locate the row of tabs directly below the hero block and above the marketing sections.	Exactly 5 tabs in this order: Start · Templates · Gallery · Learn · Trust. Each has an icon + label and a data-testid 'landing-tab-{id}'. The container has data-testid 'landing-tabbar'. The header and footer remain visible above and below.	P0
LAND-02	Start is the default tab on every fresh load	1. Open / in a private window. 2. Observe which tab is active before clicking anything.	Start tab is selected (orange underline + orange text); active panel data-testid is 'landing-tabpanel-start'. The AI/voice, audience, feature grid, 5-step, and Beginner Starters sections all render.	P0
LAND-03	Each tab swaps the body content; hero stays pinned above	1. Click Templates → Gallery → Learn → Trust → Start in turn.	Each click swaps the tabpanel content within ~50 ms; only the content area below the tab bar changes. The hero (logo, headline, CTAs, anvil image) remains visible above the tab bar across all 5 tabs.	P0
LAND-04	Tab state is session-only — refresh resets to Start	1. Click Trust tab. 2. Hard refresh the page (Cmd-R / F5).	After refresh, the URL stays '/', Start tab is selected again. No ?tab= query string is added or required.	P1
LAND-05	Trust tab links route to the full Trust hub, Privacy, and Changelog	1. Switch to Trust tab. 2. Click each of the 3 CTAs.	'Read the full Trust hub' → /trust. 'Privacy details' → /privacy. 'Changelog' → /changelog. Each destination renders correctly.	P1

Beginner Starters

ID	Test Case	Steps	Expected Result	Pri
ONB-01	12 Beginner Starter cards render in a responsive grid inside the Start tab	1. Open / in a private window. 2. Ensure the Start tab is active (it is by default). 3. Scroll down past the marketing sections (AI/voice, Audience, Feature grid, 5-step) until you reach the 'Beginner Starter Projects' grid. 4. Count the cards.	12 starter cards render in a responsive grid (2 cols on small, 3 on lg, 4 on xl). Each card shows an icon, title, difficulty pill, estimated print time, and skill tags. data-testid 'landing-beginner-starters' is present inside 'landing-tabpanel-start' and 'landing-starters-grid' contains 12 children.	P0
ONB-02	Opening a starter populates the workspace with that starter's geometry	1. From the Beginner Starters grid, click any card (e.g. 'Keychain'). 2. Wait for /workspace?template=<id> to mount.	URL is /workspace?template=<id>; sessionStorage.forgeslicer.launchTemplate contains the payload; the starter mesh appears in the scene; the outliner shows the starter's nodes.	P0
ONB-03	Skip onboarding banner is dismissible & non-blocking	1. Land on /. 2. Locate the dismissible announcement banner in the bottom-right corner on product routes. 3. Click the X.	Banner closes, never reappears in the same session, no fullscreen modal interrupts work.	P1

ID	Test Case	Steps	Expected Result	Pri
ONB-04	Workspace tips toast cycles one tip at a time on entry	1. Sign in. 2. Navigate to /workspace from the landing CTA. 3. Wait for the small bottom-right toast.	A small dismissible 'tip of the day'-style toast appears (NOT a fullscreen popup) with the next unseen tip. Closing it advances the queue; reopening /workspace later shows the next tip. After all tips are seen, a 'That's all the tips for now.' toast fires once.	P1
ONB-05	After creating an account, the user lands on the landing page (not the workspace)	1. Go to /signin?mode=register. 2. Fill display name, email, password. 3. Click 'Create account'.	After success, URL becomes '/' and the landing page renders with the user signed in (avatar visible in header). It MUST NOT auto-redirect to /workspace. Same expectation for Google sign-in and magic-link completion when no explicit ?return= was specified.	P0

Auth (email + Google)

ID	Test Case	Steps	Expected Result	Pri
AUTH-01	Email + password signup → email verification	1. /signup. 2. Use a fresh address. 3. Submit. 4. Check inbox.	Account row created, verification email arrives via Resend, link sets `verified=true`.	P0
AUTH-02	Magic link sign-in	1. /signin. 2. Click 'Send magic link'. 3. Click link in email.	Single-use link signs the user in within 15 minutes; reusing it returns an expired error.	P0
AUTH-03	Password reset	1. /signin → 'Forgot password'. 2. Submit email. 3. Open link. 4. Set new password.	Reset link valid 60 min, signs user out of all sessions on success.	P0
AUTH-04	Emergent-managed Google sign-in	1. /signin → 'Continue with Google'. 2. Approve the consent screen.	User is created or matched on email, profile photo + name populate.	P0

2. Primitive Editor & Boolean Operations

Primitives

ID	Test Case	Steps	Expected Result	Pri
PRIM-0 1	Insert cube / sphere / cylinder / cone / torus / triangle	1. Editor → Primitives palette. 2. Click each shape in turn.	Each primitive spawns at origin with sensible defaults; scene tree updates; gizmo attaches.	P0
PRIM-0 2	Edit a primitive's dimensions via the right-side Inspector (numeric fields)	1. Select a cylinder by clicking it. 2. Open the right-side Inspector panel (RightPanel). 3. Edit Width / Depth / Height numeric inputs, then radius and segment count if exposed.	Mesh regenerates live as you type (debounced), without flicker or selection loss. Each commit creates one undo step. The dimensions reflect back into the gizmo's bounding box.	P0
PRIM-0 2b	Edit a primitive by dragging its TinkerCAD-style face handles directly	1. Select a cube. 2. Grab one of the small colored squares on a face (cyan / magenta / yellow / etc). 3. Drag outward and release.	The face moves along its normal in real time; opposite face stays put; final dimensions match the drag delta (± 0.1 mm with snapping on). One undo step recorded for the whole drag.	P0
PRIM-0 3	Triangle primitive — equilateral default	1. Insert triangle. 2. Inspect dimensions panel.	Equilateral by default; PRD note: configurable base/height/angles is upcoming P1.	P1
PRIM-0 4	Transform: move / rotate / scale via gizmo	1. Select primitive. 2. Press G / R / S (or click toolbar). 3. Drag axes.	Snapping to 1 mm / 15° works with Shift; numeric panel reflects gizmo state.	P0

Boolean Operations (Manifold-3D WASM)

ID	Test Case	Steps	Expected Result	Pri
BOOL-0 1	Union two overlapping cubes	1. Insert 2 cubes overlapping. 2. Multi-select. 3. Toolbar → Union.	Result is a single watertight mesh; volume $\approx$ sum minus overlap; history step recorded.	P0
BOOL-0 2	Subtract cylinder from cube (hole)	1. Insert cube and cylinder passing through it. 2. Select cube then cylinder. 3. Subtract.	Hole punched cleanly; resulting mesh is manifold; no inverted normals.	P0
BOOL-0 3	Intersect cube $\cap$ sphere	1. Place a sphere overlapping a cube. 2. Intersect.	Yields the cube-corner-cut-by-sphere lens; mesh is closed; saves to project.	P0
BOOL-0 4	Boolean on non-manifold input shows healing toast	1. Import a known non-manifold STL. 2. Attempt Boolean.	Healing pass runs; if unrecoverable, user sees clear error toast instead of a crash.	P1

3. Importers (STL / OBJ / 3MF / SVG / ZIP)

Mesh imports

ID	Test Case	Steps	Expected Result	Pri
IMP-01	STL drag-drop	1. Drag any STL onto the canvas.	Mesh appears centered, axis-aligned bbox shown; units default mm.	P0
IMP-02	OBJ with material groups	1. Import an OBJ that has multiple groups.	Groups become separate scene-tree nodes preserving names.	P0
IMP-03	3MF multi-object project	1. Import a 3MF authored in PrusaSlicer or Bambu Studio.	All objects retained with their original transforms; print-settings warning if present.	P0
IMP-04	SVG extrude	1. Drop an SVG. 2. Set extrude depth in the modal.	2D paths become a solid mesh; bezier curves sampled smoothly.	P1
IMP-05	ZIP archive (mixed assets)	1. Drop a ZIP containing STL + 3MF + SVG.	Importer enumerates contents, asks the user to choose, imports the selection.	P1

4. Reverse Engineering (RANSAC)

Dialog & detection (Phase 1–3 shipped)

ID	Test Case	Steps	Expected Result	Pri
RE-01	Open Reverse Engineer dialog from a selected mesh	1. Select an imported mesh. 2. Toolbar → 'Reverse engineer'.	Modal opens, sensitivity controls visible, detection runs and lists primitives.	P0
RE-02	RANSAC detects a box+cylinder composite	1. Import the 'bracket.stl' sample. 2. Run detection.	Result lists at least 1 box and 1 cylinder with sane dimensions ($\pm 5\%$).	P0
RE-03	Sensitivity slider (Phase 4, upcoming)	1. Drag the sensitivity slider. 2. Re-run detection.	Higher sensitivity yields more primitives, lower yields fewer; no infinite spinner.	P1
RE-04	Replace with primitives button (Phase 5, upcoming)	1. Click 'Replace with primitives'.	Original mesh hidden, parametric Three.js primitives spawned at detected transforms; undo restores mesh.	P0

5. AI & Voice Workflows

Conversational AI

ID	Test Case	Steps	Expected Result	Pri
AI-01	Voice command: 'make a 20 mm cube'	1. Click mic. 2. Speak the command.	Whisper transcribes; GPT-5.2 returns JSON intent; cube of side 20 mm appears.	P0
AI-02	Meshy AI: text → 3D	1. AI panel → 'Text to 3D'. 2. 'low-poly rocket'. 3. Submit.	Job polls Meshy; result mesh imports into the scene when ready; failure surfaces friendly toast.	P0
AI-03	Meshy AI: image → 3D	1. Upload an image to the AI panel. 2. Generate.	Returns watertight mesh; preview thumbnail accurate.	P1
AI-04	Meshy attribution copy	1. Open AI panel.	Footer explicitly states 'Powered by Meshy.ai — third-party service'.	P1

Text on Surface

ID	Test Case	Steps	Expected Result	Pri
TXT-01	Text-on-surface MVP	1. Select a flat face. 2. Tools → Text on surface. 3. Type 'Hi'. 4. Apply.	Helvetica text mesh extrudes onto the face; aligned to face normal; Boolean-union onto host.	P0

6. Measurement, Snapping & Grid

Measurement

ID	Test Case	Steps	Expected Result	Pri
MEAS-01	Linear measurement between two vertices	1. Tool → Measure. 2. Click 2 vertices.	Distance label shown in mm; persists until cleared; respects unit toggle.	P1
MEAS-02	Grid + snapping toggles	1. View menu → Toggle grid / Toggle snapping.	Grid renders at 10 mm; snapping locks transforms to 1 mm; toggles persist across reloads.	P1

7. Community Gallery (v2)

Browse & filter

ID	Test Case	Steps	Expected Result	Pri
GAL-01	Public gallery loads with taxonomy	1. Open /gallery.	Categories sidebar visible (Functional, Decorative, Educational...), pagination works, featured creators row populated.	P0
GAL-02	Filter by tag + category	1. Select category 'Functional' + tag 'organizer'.	Result set narrows; URL reflects state; deep link reproducible.	P0
GAL-03	Visibility: private item hidden in public gallery	1. As user A publish private item. 2. Sign out. 3. Browse gallery.	Private item NOT listed publicly but still appears in A's profile.	P0
GAL-04	Contributor Lifetime celebration email	1. As an account, cross 100 components + 20 designs.	Resend dispatches the celebration email; badge appears on profile.	P1

8. Learn Section

Lessons

ID	Test Case	Steps	Expected Result	Pri
LRN-01	/learn lists 8 lessons	1. Open /learn.	8 lesson cards render with duration + difficulty tags.	P1
LRN-02	Lesson detail page deep-links	1. Click a lesson. 2. Copy URL. 3. Open in incognito.	Lesson loads directly, meta tags + structured data correct.	P1

9. Trust, Privacy & Changelog

Trust pages

ID	Test Case	Steps	Expected Result	Pri
TRUST-01	/trust renders policy summary	1. Open /trust.	Sections: data handling, third-party services (Meshy, OpenAI, Resend), security posture.	P1
TRUST-02	/privacy + /changelog accessible from footer	1. Scroll to footer on any page.	Both links present and resolve to readable pages.	P1

10. Slicer Handoff

Multi-object 3MF export → OrcaSlicer

ID	Test Case	Steps	Expected Result	Pri
SLI-01	Send to OrcaSlicer (desktop)	1. Build a scene with 3 objects. 2. Toolbar → 'Send to slicer' → Orca.	3MF downloads with all objects, transforms, and modifier volumes; opens in Orca without warnings.	P0
SLI-02	PrusaSlicer / Bambu Studio variants	1. Repeat with Prusa and Bambu targets.	Each slicer opens the 3MF cleanly; vendor-specific profile metadata respected when set.	P1
SLI-03	Watertight check before export	1. Force a non-manifold mesh. 2. Attempt export.	Modal warns and offers auto-heal; export blocked until user accepts or cancels.	P0

11. SEO & Marketing Surfaces

SEO landings

ID	Test Case	Steps	Expected Result	Pri
SEO-01	Targeted landings render unique meta	1. Visit each of the 8 SEO pages from /seo (or sitemap).	Each page has unique <title>, <meta description>, OG tags, JSON-LD.	P2
SEO-02	sitemap.xml + robots.txt valid	1. curl /sitemap.xml and /robots.txt.	XML validates, robots references the sitemap, no 5xx.	P2

12. Cross-Cutting Quality Bars

Performance & accessibility

ID	Test Case	Steps	Expected Result	Pri
QA-01	Cold load TTI < 4 s on cable	1. Lighthouse on /editor.	Performance score $\geq$ 80, no render-blocking JS warnings.	P1
QA-02	Keyboard navigation across modals	1. Tab through Reverse Engineer dialog.	Focus trap honored, ESC closes, no focus-loss bugs.	P1
QA-03	Mobile responsive sanity	1. Open / on a 390 px-wide viewport.	Hero, gallery, learn render without horizontal scroll; editor shows a gentle 'desktop recommended' note.	P2

Sign-off

When all P0 cases pass and no P1 regressions are open, this build is ready to ship. Record the tester, date, browser, and any deviations below before archiving.

Tester	
Date	
Browser / OS	
Build / commit	
Notes	