

Quze — Player Setup Guide

How to open the game and connect to the server

Two URLs — you need both

Quze uses two separate addresses. Players often need both on first launch.

Purpose	What it is
App URL	Flutter web PWA — open the game in the browser
API URL	FastAPI backend — set once in Database Info on login

1. App URL (open the game in the browser)

This is the **Flutter web PWA**, not the API.

Local network (your PC hosts the game)

After building and serving `build/web` :

Setup	URL to give players
HTTP (e.g. <code>python -m http.server 8080 --bind 0.0.0.0</code>)	<code>http://YOUR_PC_IP:8080/</code>
HTTPS (recommended on phones)	<code>https://YOUR_PC_IP:8080/</code>

Replace **YOUR_PC_IP** with the PC's LAN address from `ipconfig` (e.g. `192.168.2.10`).

Important: Do not send `localhost` or `127.0.0.1` — that only works on the PC itself.

Install on phone: open that URL → **Add to Home screen** / **Install app** (not browser "Download").

Production / cloud

Use your hosted PWA URL, for example:

`https://quze.yourdomain.com/`

(Firebase, Netlify, Nginx, etc. — see `CLOUD_DEPLOYMENT.md` in the project.)

2. API URL (Database Info on login)

The app talks to FastAPI separately. Default is `http://localhost:8000/api`, which **does not work on a phone**.

On the login screen → **Database Info**, set:

Setup	API URL
Local LAN	<code>http://YOUR_PC_IP:8000/api</code>
HTTPS backend	<code>https://YOUR_PC_IP:8000/api</code>
Production (same domain)	<code>https://yourdomain.com/api</code>

Backend must run on `0.0.0.0:8000` and port **8000** must be reachable (firewall).

What to send users (typical LAN setup)

Message example:

Open: `http://192.168.2.10:8080/` (or `https://...` if using HTTPS)

On first launch → Database Info → Server URL:
`http://192.168.2.10:8000/api` → Save

Log in and play.

Optional: QR code for the app URL (`:8080`).

Single URL (production, optional)

If Nginx/Caddy serves the PWA at `/` and proxies `/api` to FastAPI on the same domain, you can send only:

`https://yourdomain.com/`

API may still need to be set in Database Info unless the app is configured to use the same origin automatically (default is still `localhost:8000` until the user saves a custom URL).

Summary

- Send players the **:8080** app link.
- They must set the **:8000/api** server in Database Info on first use.

- Exception: both deployed under one HTTPS domain with proper config.

Host setup (organizer)

1. **Backend:** `python backend_fastapi/start_server.py` (port 8000)
2. **Web app:** serve `build/web` on port 8080:

```
cd team_results_notification/build/web
python -m http.server 8080 --bind 0.0.0.0
```

3. Share `http://YOUR_PC_IP:8080/` and `http://YOUR_PC_IP:8000/api`