

Object Oriented Programming in Java

12: Stream API

Licence

You are free to

- **Share** — copy and redistribute the material in any medium or format
- **Adapt** — remix, transform, and build upon the material




under the following terms

- **Attribution** — You must give appropriate credit, provide a link to the license, and indicate if changes were made. You may do so in any reasonable manner, but not in any way that suggests the licensor endorses you or your use.
 - **NonCommercial** — You may not use the material for commercial purposes.
 - **ShareAlike** — If you remix, transform, or build upon the material, you must distribute your contributions under the same license as the original.
-
- The samples and slides are inspired by the [Object Oriented Programming course](#) at the University of Zagreb, Faculty of Electrical Engineering and Computing, Zagreb, Croatia.
 - Original materials in Croatian were created by (in alphabetical order): Ivica Botički, Marko Čupić, Mario Kušek, Boris Milašinović, and Krešimir Pripužić under CC-BY-NC-SA licence.
 - Adapted for this course by Boris Milašinović and shared under the same licence
 - <https://creativecommons.org/licenses/by-nc-sa/4.0/>



Data classes used in examples

- Student has first name, last name, id, and number of points
 - read only attributes, values set in constructor
- Can be used in various collections as it
 - overrides *equals* and *hashCode*
 - implements Comparable
 - natural comparator (compares by id)
 - 4 additional comparators (one for each attribute)
 - Comparing strings in specific language using appropriate comparator (see next slide)
- Hard coded list of students in *StudentData*



Language specific comparators

- Natural comparator for *String* compares strings by their encoding value but each language has own way to compare

12_.../swu/oopj/streams/CompareTest.java

```
Comparator<Object> compHR = Collator.getInstance(  
    Locale.forLanguageTag("hr")); //Croatian  
Comparator<Object> compChina = Collator.getInstance(Locale.CHINA);  
String s1 = "王"; //Wáng should be before Zhōu  
String s2 = "周"; //Zhōu  
System.out.println(s1.compareTo(s2)); // 7971  
System.out.println(compChina.compare(s1, s2)); // -1  
System.out.println(compHR.compare(s1, s2)); // 1  
  
s1 = "č"; //in Croatian č (like Ch in Chongqing) should be before ć  
s2 = "ć"; //ć (like q in Chongqing)  
System.out.println(s1.compareTo(s2)); // 6  
System.out.println(compChina.compare(s1, s2)); // 1  
System.out.println(compHR.compare(s1, s2)); // -1
```

Java streams and Java Stream API

- The Java Stream API provides a functional approach to processing collections of objects
 - Not to be confused with input/output streams (of bytes)
- A stream pipeline consists of
 - a **source** (an array, a collection, an I/O channel, ...)
 - zero or more **intermediate operations** which transform a stream into another stream (e.g. filtering, sorting, mapping to another type)
 - a **terminal operation** which produces a result (e.g. count, average, new collection) or side-effect (e.g. printing elements)
- Streams are lazy
 - computation on the source data is only performed when the terminal operation is initiated, and source elements are consumed only as needed.
 - Creating new stream does not create a copy of a source

Creating a stream from a collection

- Interface *Collections* offers default methods *stream* and *parallelStream* that creates a stream
 - Interface *Stream* extends *BaseStream* and offers many intermediate and terminal methods
 - Some of frequently used methods are shown later in examples
 - There also exists more specific streams like *IntStream*, *LongStream* and *DoubleStream* with additional methods

<<Java Interface>>	
BaseStream<T,S>	
java.util.stream	
iterator():Iterator<T>	
spliterator():Spliterator<T>	
isParallel():boolean	
sequential():S	
parallel():S	
unordered():S	
onClose(Runnable):S	
close():void	

<<Java Interface>>	
Stream<T>	
java.util.stream	
filter(Predicate<? super T>):Stream<T>	
map(Function<? super T,? extends R>):Stream<R>	
mapToInt(ToIntFunction<? super T>):IntStream	
mapToLong(ToLongFunction<? super T>):LongStream	
mapToDouble(ToDoubleFunction<? super T>):DoubleStream	
flatMap(Function<? super T,Stream<? extends R>>):Stream<R>	
flatMapToInt(Function<? super T,IntStream>):IntStream	
flatMapToLong(Function<? super T,LongStream>):LongStream	
flatMapToDouble(Function<? super T,DoubleStream>):DoubleStream	
distinct():Stream<T>	
sorted():Stream<T>	
sorted(Comparator<? super T>):Stream<T>	
peek(Consumer<? super T>):Stream<T>	
limit(long):Stream<T>	
skip(long):Stream<T>	
forEach(Consumer<? super T>):void	
forEachOrdered(Consumer<? super T>):void	
toArray():Object[]	
toArray(IntFunction<A[]>):A[]	
reduce(T,BinaryOperator<T>):T	
reduce(BinaryOperator<T>):Optional<T>	
reduce(U,BiFunction<U,? super T,U>,BinaryOperator<U>):U	
collect(Supplier<R>,BiConsumer<R,? super T>,BiConsumer<R,R>):R	
collect(Collector<? super T,A,R>):R	
min(Comparator<? super T>):Optional<T>	
max(Comparator<? super T>):Optional<T>	
count():long	
anyMatch(Predicate<? super T>):boolean	
allMatch(Predicate<? super T>):boolean	
noneMatch(Predicate<? super T>):boolean	
findFirst():Optional<T>	
findAny():Optional<T>	
<u>builder():Builder<T></u>	
<u>empty():Stream<T></u>	
<u>of(T):Stream<T></u>	
<u>of(T[]):Stream<T></u>	
<u>iterate(T,UnaryOperator<T>):Stream<T></u>	
<u>generate(Supplier<T>):Stream<T></u>	
<u>concat(Stream<? extends T>,Stream<? extends T>):Stream<T></u>	

Printing collection content using Stream API

- Print all students from a list using streams and terminal method *forEach*
 - `forEach` consumes source elements and do action defined with argument of type *Consumer<? super T>*
 - Note: interface *List* also has *forEach*, but it is not the same method

```
List<Student> students = StudentData.load();  
// using anonymous class  
students.stream().forEach(new Consumer<Student>() {  
    @Override  
    public void accept(Student t) {  
        System.out.println(t);  
    }  
});
```

```
// using lambda  
students.stream().forEach(t -> System.out.println(t));  
// students.stream().forEach(System.out::println);
```

12_.../swu/oopj/streams/Example1.java

Filtering a stream

- Filter is an intermediate method that creates new stream based on a predicate

Stream<T> filter(Predicate<? super T> predicate);

- Note: it just create a new stream, it does not consume data, nor it copy source content
- Can be chained with another filter method or another intermediate method
- An example: print students that have 40 points or more
 - A variant with lambda example is shown on the slide, a variant with anonymous classes is available in examples source code

[12_.../swu/oopj/streams/Example2.java](#)

```
students.stream()  
    .filter(s -> s.getPoints() >= 40)  
    .forEach(t -> System.out.println(t));
```


Note on terminal method(s)

- On a stream only one terminal method can be applied
 - Applying another terminal method on a stream that has been consumed causes exception → new stream should be created

12_.../swu/oopj/streams/Example3.java

```
List<Student> students = StudentData.load();
Stream<Student> st = students.stream();
st.forEach(t -> System.out.println(t)); //OK

//st.forEach(t -> System.out.println(t));
//causes exception: java.lang.IllegalStateException
// because stream has already been operated upon or closed

students.stream().forEach(t -> System.out.println(t)); //OK
//.stream() creates new stream
```

Sorting streams

- Sorted streams can be sorted using
 - `sorted()` using natural
 - `sorted(Comparator<? super T>)` with custom comparator
- To compare by multiple criteria composite comparator should be used as an argument
- `sorted` is intermediate method and it does not change the source
[12_.../swu/oopj/streams/Example4.java](#)

```
List<Student> students = StudentData.load();  
//print all students with 40 or more points, sorted by last name  
students.stream()  
    .filter(s -> s.getPoints() > 40)  
    .sorted(Student.BY_LAST_NAME)  
    .forEach(t -> System.out.println(t));  
  
//notice that source has not been changed  
students.stream().forEach(t -> System.out.println(t));
```

Stateless and stateful intermediate operations

- Intermediate operations are divided into stateless and stateful operations.
- Stateless operations (e.g. filter), retain no state from previously seen element when processing a new element. Each element can be processed independently of operations on other elements.
- Stateful operations may need to process the entire input before producing a result.
 - For example, one cannot produce any results from sorting a stream until one has seen all elements of the stream.
 - As a result, under parallel computation, some pipelines containing stateful intermediate operations may require multiple passes on the data or may need to buffer significant data.

Stream mapping

- A stream can be transformed to a new stream by mapping each object to another using provided function
<R> Stream<R> map(Function<? super T, ? extends R> mapper);
 - Each *t* of type *T* from *Stream<T>* on input is mapped to *R* by *calling mapper.apply(t)* thus forming a *Stream<R>*
 - An example: Stream of students (with more than 30 points) is transformed (mapped to) stream of students' surnames
 - Later those names are stored to a new list (shown later)

12_.../swu/oopj/streams/Example5.java

```
lastNames = students.stream()  
    .filter(s -> s.getPoints() > 30)  
    .map(s -> s.getLastName())  
    ...
```

Collecting streams elements (1)

- *collect* is terminal methods which in combination with custom implementation of *Collector* interface or using built-in collectors(from class *Collectors*) copy stream elements to map, list, set, ...

12_.../swu/oopj/streams/Example5.java

```
List<String> lastNames = students
    .stream()
    .filter(s -> s.getPoints() > 30)
    .map(s -> s.getLastName())
    .sorted(comp)
    .collect(Collectors.toList());

//print new collection
lastNames.stream()
    .forEach(t -> System.out.println(t));
```

Collecting streams elements (2)

- The result of collecting depends on collector
- When working with `Stream<String>` an useful collector that joins all elements (strings) into new string separated by desired delimiter can be used

12_.../swu/oopj/streams/Example5b.java

```
List<Student> students = StudentData.load();
Comparator<Object> comp = Collator.getInstance(Locale.CHINA);
String lastNames = students.stream()
    .filter(s -> s.getPoints() > 30)
    .map(s -> s.getLastName())
    .sorted(comp)
    .collect(Collectors.joining(", "));

System.out.println(lastNames);
```

Mapping to stream of “primitive” types (1)

- Due to nature of Java Generics `Stream<T>` can contain only classes and not primitive types (i.e. `Stream<Integer>` vs *`Stream<int>`*)
 - However, when mapping function should produce Integer, Double or Long, instead of *map* method, the following methods can be used *mapToInt*, *mapToLong*, *mapToDouble* returning *IntStream*, *LongStream*, *DoubleStream*

12_.../swu/oopj/streams/Example6.java

```
students.stream()  
    .filter(s -> s.getPoints() > threshold)  
    .mapToInt(s -> s.getPoints()) //returns IntStream
```

Mapping to stream of “primitive” types (2)

- *IntStream*, *DoubleStream*, and *LongStream* offers additional methods, e.g. calculate min value, max value, average value, ...
- *average()* is a **reduction** method (terminal method that reduce only one value) - returns an *OptionalDouble*
- *OptionalDouble* can contain *double* value (method *isPresent()*) which can be get with *getAsDouble()* that returns double or throws *NoSuchElementException* if not present
 - A better approach is to use methods *ifPresent* or *ifPresentOrElse* from *OptionalDouble*

12_.../swu/oopj/streams/Example6*.java

```
double avgGrade = students.stream()
    .filter(s -> s.getPoints() > threshold)
    .mapToInt(s -> s.getPoints()) // IntStream
    .average() //OptionalDouble
    .getAsDouble(); // double or exception throws
```


Zip file as a source stream

- Stream are not necessarily related to collection
- Streams can be created from various sources
- zip file can be a source for a stream and each element in the stream is subclass of *ZipEntry*
 - Example: Print first three lines from each txt file in zip file

```
try(ZipFile zip = new ZipFile(filename)){
    zip.stream()
        .filter(entry ->
            entry.getName().toLowerCase().endsWith(".txt"))
        .forEach(entry -> write3LinesWithScanner(zip, entry));
} ...

private static void write3LinesWithScanner(
    ZipFile zip, ZipEntry entry){
    try (Scanner sc = new Scanner(zip.getInputStream(entry), "UTF-8")) {
        ...
    }
}
```

12_.../swu/oopj/streams/ZipExample.java